STANDARD DEPARTURE CHART-INSTRUMENT

RJFZ / TSUIKI

SID and TRANSITION

MISHIMA THREE DEPARTURE

RWY 07: Turn right....

RWY 25: Turn left within 3NM....

....Climb via TQT R-150 to TQT 15DME, then turn left via TQT 15DME counter clockwise ARC to TQT R-091, then via MIT R-177 to MIT TACAN.

Maintain FL150 between MIT R-177/60DME and MINNE. Cross MIT R-177/14DME at assigned or specified altitude.

Note: Minimum rate of climb

JET....400ft/NM until passing 2,800ft(RWY25) PROP....340ft/NM until passing 2,800ft(RWY25)

HIMESHIMA THREE DEPARTURE

RWY 07: Turn right....

RWY 25: Turn left within 3NM....

....Climb via TQT R-091 until HIMEH(TQT R-091/29.1DME), then proceed as directed by ATC.

Cross HIMEH at assigned or specified altitude.

Note: Minimum rate of climb

JET....400ft/NM until passing 2,800ft(RWY25) PROP....340ft/NM until passing 2,800ft(RWY25)

MUSASHI TRANSITION

After HIMEH, via TFE R-346 to TFE VOR/DME.

KUGA SIX DEPARTURE

RWY 07: Turn right....

RWY 25: Turn left within 3NM....

....Climb via TQT R-150 until TQT R-150/15DME, turn left to intercept and proceed via IWT R-240 (MRA5,000ft) to IWT TACAN.

Cross HIMEH(IWT R-240/34DME) at assigned or specified altitude.

Note: Minimum rate of climb

JET....400ft/NM until passing 2,800ft(RWY25) PROP....340ft/NM until passing 2,800ft(RWY25)

HIMESHIMA REVERSAL TWO DEPARTURE

RWY 07: Turn right....

RWY 25: Turn left within 3NM....

....Climb via TQT R-091 within 20NM of TQT TACAN, turn right reverse course to TQT TACAN, then proceed as directed by ATC.

Cross TQT TACAN at assigned or specified altitude.

Note: Minimum rate of climb

JET....400ft/NM until passing 2,800ft(RWY25) PROP....340ft/NM until passing 2,800ft(RWY25)

STANDARD DEPARTURE CHART-INSTRUMENT

RJFZ / TSUIKI

SID and TRANSITION

NAKATSU REVERSAL TWO DEPARTURE

RWY 07: Turn right....

RWY 25: Turn left within 3NM....

....Climb via TQT R-150 within 20NM of TQT TACAN, turn(direction specified by ATC), reverse course to TQT TACAN, then proceed as directed by ATC.

Cross TQT TACAN at assigned or specified altitude. (MCA at TQT TACAN 6,000ft)

Note: Minimum rate of climb

JET....400ft/NM until passing 2,800ft(RWY25) PROP....340ft/NM until passing 2,800ft(RWY25)

KANMO TRANSITION

After TQT TACAN, proceed via TQT R-350 to KANMO(TQT R-350/8.6DME), then proceed as directed by ATC.

MINNE TRANSITION


After TQT TACAN, proceed via TQT R-026 to MINNE, then via MIT R-177 to MIT TACAN.

OGORI TRANSITION

After TQT TACAN, proceed via TQT R-239 to OGORI(TQT R-239/39.1DME), then proceed as directed by ATC.

Cross TQT 15DME at or above 7,000ft.

STANDARD DEPARTURE CHART-INSTRUMENT



STANDARD ARRIVAL CHART - INSTRUMENT

RJFZ / TSUIKI STAR

HIMEH ARRIVAL

From over HIMEH (IWT R-240/34DME), proceed via IWT R-240, then turn left, proceed via TQT 24DME clockwise ARC to TQT R-130, then turn right proceed via TQT R-130 to SANKO (TQT R-130/14.1DME).

TACAN Z RWY07 : Cross SANKO at or above 6,000ft. TACAN Z RWY25 : Cross SANKO at or above 4,000ft.

