AD 2 AERODROMES

RJNW AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJNW - NOTO

RJNW AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	*371736N/1365744E* 067°/1.0km FM RWY 07 THR
2	Direction and distance from (city)	6.4NM SSE of WAJIMA city
3	Elevation/ Reference temperature	718ft / 28°C (2003-2005)
4	Geoid undulation at AD ELEV PSN	123ft
5	MAG VAR/ Annual change	9°W(2022)/ 4.2'W
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	Noto Airport Management Office 10-11-1, Sue, Mii-machi, Wajima-City, Ishikawa Pref. 929-2392, JAPAN Tel: 0768-26-2100 Fax: 0768-26-2102
7	Types of traffic permitted (IFR/ VFR)	IFR/VFR
8	Remarks	Nil

RJNW AD 2.3 OPERATIONAL HOURS

1	AD Administration	2300 - 1030
2	Customs and immigration	On request Customs: 0767-52-0689 Immigration: 076-222-2450
3	Health and sanitation	Quarantine(human): On request(0761-21-3767) Quarantine(animal, plant): Nil
4	AIS Briefing Office	Nil
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	H24 (TOKYO)
7	ATS	2300 - 1030 Remarks: AFIS provided by Osaka Airport Office.
8	Fuelling	2330 - 0830
9	Handling	0000 - 0800
10	Security	0130 - 0700
11	De-icing	Nil
12	Remarks	Nil

RJNW AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	All the modern instisutions that deal with the weight thing to Boeing 737 type and Airbus A320 type.
2	Fuel/ oil types	Fuel grades : JET A1
3	Fuelling facilities/ capacity	Fuel Truck Refuelling/100KL
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

RJNW AD 2.5 PASSENGER FACILITIES

1	Hotels	Nil
2	Restaurants	At airport
3	Transportation	Busses, Taxi
4	Medical facilities	Hospital in Wajima city 12km
5	Bank and Post Office	Nil
6	Tourist Office	At airport
7	Remarks	Nil

RJNW AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT 7
2	Rescue equipment	Chemical fire fighting truck X 2
3	Capability for removal of disabled aircraft	Ask AD administration
4	Remarks	Nil

RJNW AD 2.7 SEASONAL AVAILABILITY-CLEARING

1	Types of clearing equipment	Snow remove equipments: 5 motor graders
2	Clearance priorities	(1)RWY (2)TWY (3)Apron
3	Remarks	Seasonal availability: all seasons Snow removed will be commenced, if RWY and TWY are covered with a depth of 3cm snow or more.

RJNW AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Apron surface and strength	Surface : concrete, Strength: PCR 830/R/B/W/T
2	Taxiway width, surface and strength	Width : 23m, Surface : Asphalt, Strength: PCR 593/F/C/X/T
3	ACL and elevation	Not available
4	VOR checkpoints	Not available
5	INS checkpoints	Spot NR 1 *371740.11N, 1365723.55E* 2 *371740.72N, 1365725.32E* 3 *371741.39N, 1365727.28E* 4 *371742.00N, 1365729.05E*
6	Remarks	Nil

RJNW AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	Nil
2	RWY and TWY markings and LGT	RWY:RWY07/25 (Marking) RWY designation, RWY CL, RWY THR, RWY middle point, Aiming point, TDZ, RWY side stripe, RWY turn pad CL, RWY turn pad edge (LGT) RCLL, REDL, RTHL, RENL, RTZL(RWY25), WBAR(RWY), Turning point indicator LGT, RWY DIST marker LGT TWY: (Marking) TWY CL, TWY side stripe, RWY HLDG PSN (LGT) TWY edge LGT, TWY CL LGT
3	Stop bars	Nil
4	Remarks	(Marking) Overrun area edge (LGT) APN flood LGT

RJNW / NOTO

180° Turn on RWY

滑走路180°転回要領

１．滑走路中心線からターニングパッド中心線標識に従って進行する。

２．転回灯１が一直線に見えるように進行し、転回灯２が一直線に見えた時転回を開始する。
転回時はMAX STEERING ANGLEを使用する。

180°turn on runway

１． Proceed along the RWY Turn Pad Center Line Marking.

２． Proceed along the RWY Turn Pad Center Line Marking to see the Turning Point Indicator Light 1 on a straight line, then commence turn at the spot where you(pilot) can see the Turning Point Indicator Light 2 on a straight line at an angle of 9 o'clock.
When turning, take MAX STEERING ANGLE.





RJNW AD 2.10 AERODROME OBSTACLES

In Area2 See Obstacle data

Other obstacles

OBST ID/ designation	Obstacle type	Coordinates	Elevation	Markings/ LGT	Remarks
RJNW1	Building	*371735N/1365711E*	775ft	-/LIL	Under transition SFC

In Area3 To be developed

RJNW AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	TOKYO
2	Hours of service MET Office outside hours	H24 (TOKYO)
3	Office responsible for TAF preparation Periods of validity	Nil
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Briefing is available upon inquiry at TOKYO
6	Flight documentation Language(s) used	C En
7	Charts and other information available for briefing or consultation	S_6, U_{85}, U_7, U_5, U_3, U_{25}, U_2/T_r, P_s, P_5, P_3, P_{25}, P_{SWE}, P_{SWF}, P_{SWG}, P_{SWI}, P_{SWM}, P_{SW}(domestic), E, C, W_E, W_F, W_G, W_I, W, N
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	RADIO
10	Additional information (limitation of service, etc.)	Nil

RJNW AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCR) and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
07	066.77°	2000×45	PCR 593/F/C/X/T Asphalt-Concrete	*371722.92N* *1365706.38E* 123ft	THR ELEV: 710ft
25	246.77°	2000×45	PCR 593/F/C/X/T Asphalt-Concrete	*371748.52N* *1365821.00E* 123ft	THR ELEV: 702ft TDZ ELEV: 716.6ft

Slope of RWY	Strip Dimensions (M)	RESA (Overrun) Dimensions (M)	Remarks
7	10	11	14
See AD2.24 AD chart	2120×300	40×(MNM:251 MAX:300)*	RWY Grooving: 2000m×30m
	2120×300	190×(MNM:180 MAX:300)* *For detail, ask airport administrator	

RJNW AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
07	2000	2000	2000	2000	Nil
25	2000	2000	2000	2000	Nil

RJNW AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
07	SALS (*1) 420m LIH	Green -	PAPI 3.0° /LEFT 334.8m 61ft	Nil	2000m 30m Coded color (White/Red) LIH	2000m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)
25	PALS (CAT I) 900m LIH	Green Green	PAPI 3.0° /LEFT 340.3m 61ft	900m	2000m 30m Coded color (White/Red) LIH	2000m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)

Remarks
10
SALS with APCH LGT beacon(590m and 860m FM RWY 07 THR)(*1) Overrun area edge LGT(LEN:60m, Color:Red)(*2)

RJNW AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	ABN: *371744N/1365718E*, White/Green EV4.3sec, HO
2	LDI location and LGT Anemometer location and LGT	LDI:Nil Anemometor: RWY 07 : 376m FM RWY 07 THR, LGTD RWY 25 : 295m FM RWY 25 THR, LGTD
3	TWY edge and center line lighting	TWY edge and center line lights installed, see AD2.9
4	Secondary power supply/ switch-over time	Within 1sec: REDL, RTHL, WBAR, RENL, RCLL, Overrun area edge LGT, Turning point indicator LGT. Within 15sec: Other LGT
5	Remarks	WDI LGT

RJNW AD 2.16 HELICOPTER LANDING AREA

Nil

RJNW AD 2.17 ATS AIRSPACE

Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
Noto Information Zone	Area within a radius of 5NM(9km) of Noto ARP	4,000 or below	E	NOTO RADIO En	

RJNW AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
AFIS	NOTO RADIO	118.05MHz	2300 - 1030	Operated by Osaka Airport Office.

RJNW AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid (VOR declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
VOR (8W°/2017)	NTE	111.45MHz	H24	*371723.86N/ 1365746.48E*		
DME	NTE	1138MHz (CH-51Y)	H24	*371723.86N/ 1365746.48E*	793ft	DME unusable: 000°-010° beyond 30nm BLW 4,000ft. 010°-030° beyond 35nm BLW 4,000ft. 350°-360° beyond 35nm BLW 4,000ft.
ILS-LOC 25	INT	108.95MHz	2300 - 1030	*371720.07N/ 1365658.08E*		LOC: 223m(732ft) away FM RWY 07 THR, BRG(MAG)255°
ILS-GP 25	-	329.15MHz	2300 - 1030	*371741.30N/ 1365812.31E*		GP: 287m(942ft) inside FM RWY 25 THR, 120m(394ft) S of RCL GP angle 3.0° HGT of ILS REF datum 16.5m (54ft).
ILS-DME 25	INT	1113MHz (CH-26Y)	2300 - 1030	*371740.89N/ 1365812.03E*	715ft	DME: 299m(981ft)inside FM RWY 25 THR, 130m(427ft) S of RCL
MSAS		1575.42MHz	H24			Transmitting antennas are satellite based.



REMARKS :

1. ILS-LOC beam BRG(MAG) 255˚
2. HGT of ILS REF datum 16.5m(54ft)
3. GP Angle 3.0˚
4. ELVE of ILS-DME 217.7m(715ft)

RJNW AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

Nil

2. Taxiing to and from stands

Nil

3. Parking area for small aircraft(General aviation)

Nil

4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

Nil

7. School and training flights - technical test flights - use of runways

Nil

8. Helicopter traffic - limitation

Nil

9. Removal of disabled aircraft from runways

Nil

RJNW AD 2.21 NOISE ABATEMENT PROCEDURES

Nil

RJNW AD 2.22 FLIGHT PROCEDURES

TAKE OFF MINIMA

	RWY	ACFT CAT	REDL & RCLL		REDL or RCLL or RCL Marking		NIL (DAYTIME ONLY)	
			RVR	VIS	RVR	VIS	RVR	VIS
Multi-Engine ACFT with TKOF ALTN AP FILED	07	A,B,C,D	-	400m	-	400m	-	500m
	25	A,B,C,D	400m	400m	400m	400m	-	500m
OTHER	07	A,B,C,D	AVBL LDG MINIMA					
	25	A,B,C,D						

RJNW AD 2.23 ADDITIONAL INFORMATION

Nil

RJNW AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome/Heliport Chart
Standard Departure Chart - Instrument (HISUI)
Standard Departure Chart - Instrument (URUSI)
Standard Departure Chart - Instrument (HOUSU)
Standard Departure Chart - Instrument (KAIOH)
Standard Arrival Chart - Instrument (GORYU, HAPPO, KILCO-RNAV)

Instrument Approach Chart (ILS Z or LOC Z RWY25)
Instrument Approach Chart (ILS Y or LOC Y RWY25)
Instrument Approach Chart (VOR RWY25)
Instrument Approach Chart (VOR RWY07)
Instrument Approach Chart (RNP RWY25)
Instrument Approach Chart (RNP Z RWY07(AR))
Instrument Approach Chart (RNP Y RWY07(AR))
Instrument Approach Chart (RNP X RWY07)
Other Chart (Visual REP)
Other Chart (MVA CHART)

RJNW / NOTO

AD CHART

CHANGE : WIND SPEED METER, CEILOMETER added.



STANDARD DEPARTURE CHART -INSTRUMENT

RJNW / NOTO SID

HISUI FOUR DEPARTURE

RWY07 : Climb RWY HDG to 1300FT, turn right...
RWY25 : Climb RWY HDG to 1200FT, turn left HDG 032˚...
...to intercept and proceed via NTE R077 to HISUI.

Note RWY07 : 5.0% climb gradient required up to 1300FT.
OBST ALT 772FT located at 0.3NM 046° FM end of RWY07.



CHANGE : PROC renamed. Note added. OBST figure deleted.

STANDARD DEPARTURE CHART -INSTRUMENT

RJNW / NOTO SID

URUSI TWO DEPARTURE

RWY07 : Climb RWY HDG to 1300FT, turn right HDG217˚...
RWY25 : Climb RWY HDG to 1200FT, turn left HDG127˚...
...to intercept and proceed via NTE R172 to URUSI.

Cross URUSI at or above 8000FT.

Note RWY07 : 5.0% climb gradient required up to 1300FT.
OBST ALT 772FT located at 0.3NM 046˚ FM end of RWY07.



CHANGE : PROC renamed. Note added. OBST figure deleted.

STANDARD DEPARTURE CHART -INSTRUMENT

RJNW / NOTO

RNAV SID

HOUSU ONE DEPARTURE	RNP1

Note GNSS required.



RWY07 : Climb on HDG075° at or above 1300FT, direct to HISUI.
RWY25 : Climb on HDG255° at or above 1200FT, turn left direct to HISUI.

Note RWY07 : 5.0% climb gradient required up to 1300FT.
OBST ALT 772FT located at 0.3NM 046° FM end of RWY07.

RWY07

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	075 (066.7)	-8.8	-	-	+1300	-	-	RNP1
002	DF	HISUI	-	-	-8.8	-	-	-	-	-	RNP1

RWY25

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	255 (246.7)	-8.8	-	-	+1200	-	-	RNP1
002	DF	HISUI	-	-	-8.8	-	L	-	-	-	RNP1

Waypoint Coordinates

Waypoint Identifier	Coordinates
HISUI	*373534.5N / 1375553.1E*

CHANGE : New PROC.

STANDARD DEPARTURE CHART -INSTRUMENT

RJNW / NOTO

RNAV SID

KAIOH ONE DEPARTURE	RNP1

Note GNSS required.



RWY07 : Climb on HDG075° at or above 1300FT, turn right direct to URUSI at or above 8000FT.
RWY25 : Climb on HDG255° at or above 1200FT, turn left direct to URUSI at or above 8000FT.

Note RWY07 : 5.0% climb gradient required up to 1300FT.
OBST ALT 772FT located at 0.3NM 046° FM end of RWY07.

RWY07

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	075 (066.7)	-8.8	-	-	+1300	-	-	RNP1
002	DF	URUSI	-	-	-8.8	-	R	+8000	-	-	RNP1

RWY25

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	255 (246.7)	-8.8	-	-	+1200	-	-	RNP1
002	DF	URUSI	-	-	-8.8	-	L	+8000	-	-	RNP1

Waypoint Coordinates

Waypoint Identifier	Coordinates
URUSI	*364909.2N / 1370753.5E*

CHANGE : New PROC.

STANDARD ARRIVAL CHART -INSTRUMENT

CHANGE : Specification changed to RNP1(GORYU ARRIVAL). HAPPO ARRIVAL established. VAR. PROC course(KILCO ARRIVAL). Waypoint Coordinates added.

RJNW / NOTO RNAV STAR

GORYU ARRIVAL / HAPPO ARRIVAL / KILCO ARRIVAL	RNP1
Note GNSS required.	



GORYU ARRIVAL

From GORYU, to NOPPY at or above 3000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GORYU	-	-	-8.8	-	-	-	-	-	RNP1
002	TF	NOPPY	-	299 (290.6)	-8.8	29.6	-	+3000	-	-	RNP1

HAPPO ARRIVAL

From HAPPO, to NOPPY at or above 3000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	HAPPO	-	-	-8.8	-	-	-	-	-	RNP1
002	TF	NOPPY	-	305 (296.0)	-8.8	37.2	-	+3000	-	-	RNP1

KILCO ARRIVAL

From HAPPO, to KILCO at or above 6000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	HAPPO	-	-	-8.8	-	-	-	-	-	RNP1
002	TF	KILCO	-	286 (276.9)	-8.8	22.5	-	+6000	-	-	RNP1

Waypoint Coordinates

Waypoint Identifier	Coordinates
GORYU	*371154.6N / 1374610.4E*
HAPPO	*370604.9N / 1375320.7E*
NOPPY	*372214.7N / 1371120.0E*
KILCO	*370843.1N / 1372519.8E*

INSTRUMENT APPROACH CHART

RJNW / NOTO

ILS Z or LOC Z RWY25

KOBE CONTROL	ILS – LOC / INT / ILS–GP / ILS–DME		NOTO RADIO	
132.45 – 125.6 304.4 – 317.1	ILS – LOC INT ILS–GP ILS–DME	108.95 329.15 CH-26Y	118.05 AFIS provided by Osaka Airport Office	NO RADAR



NM to INT	MAPt	2	3	4	5	6	FAF
ALT (3.0˚ APCH Path)	–	1336	1655	1974	2292	2611	2663

MISSED APPROACH

Climb to 2000FT on HDG255˚,
turn left, direct to NTE VOR/DME
and hold at 3000FT.
Contact NOTO RADIO.

Timing not authorized for defining the MAPt.



DME to INT	0.2	0.6	1.6	3.0	6.2	11.4
NM to THR	0	0.5	1.4	2.8	6.0	11.3

Missed APCH climb gradient MNM 5.0%

MINIMA THR elev. 702 AD elev. 718

CAT	CAT Ⅰ DA(H)	CAT Ⅰ RVR/CMV	LOC MDA(H)	LOC RVR/CMV	CIRCLING MDA(H)	CIRCLING VIS
A	902 (200)	550	1170 (468)	1000	1260 (542)	1600
B	902 (200)	550	1170 (468)	1200	1260 (542)	1600
C	902 (200)	550	1170 (468)	1200	1280 (562)	2400
D	902 (200)	550	1170 (468)	1600	1420 (702)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : VAR.

INSTRUMENT APPROACH CHART

RJNW / NOTO

ILS Y or LOC Y RWY25

KOBE CONTROL	ILS – LOC 108.95	NOTO RADIO	NO RADAR
132.45 – 125.6 304.4 – 317.1	INT ILS–GP 329.15 ILS–DME CH-26Y	118.05 AFIS provided by Osaka Airport Office	



NM to INT	MAPt	2	3	4	5	6	FAF
ALT (3.0˚ APCH Path)	–	1336	1655	1974	2292	2611	2663

MISSED APPROACH

Climb to 2000FT on HDG255˚,
turn left, direct to NTE VOR/DME
and hold at 3000FT.
Contact NOTO RADIO.

Timing not authorized for defining the MAPt.



DME to INT	0.2	0.6	1.6	3.0	6.2
NM to THR	0	0.5	1.4	2.8	6.0

Missed APCH climb gradient MNM 5.0%

MINIMA THR elev. 702 AD elev. 718

CAT	CAT I DA(H)	CAT I RVR/CMV	LOC MDA(H)	LOC RVR/CMV	CIRCLING MDA(H)	CIRCLING VIS
A	902 (200)	550	1170 (468)	1000	1260 (542)	1600
B	902 (200)	550	1170 (468)	1200	1260 (542)	1600
C	902 (200)	550	1170 (468)	1200	1280 (562)	2400
D	902 (200)	550	1170 (468)	1600	1420 (702)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : VAR.

INSTRUMENT APPROACH CHART

RJNW / NOTO

VOR RWY25

KOBE CONTROL	NOTO VOR/DME	NOTO RADIO	NO RADAR
132.45 – 125.6 304.4 – 317.1	111.45 NTE CH-51Y 37°17´24˝N/136°57´46˝E	118.05 AFIS provided by Osaka Airport Office	



NM to NTE	MAPt	3	4	FAF
ALT (3.0° APCH Path)	–	1515	1834	1898

MISSED APPROACH

Climb to 2000FT via NTE R250,
turn left, direct to NTE VOR/DME
and hold at 3000FT.
Contact NOTO RADIO.



Timing not authorized for defining the MAPt.

DME to NTE	0.6	2.2	4.2	8.0
NM to THR	0	1.6	3.6	7.4

MINIMA THR elev. 702 AD elev. 718

<table>
<tr><th rowspan="2">CAT</th><th colspan="2"></th><th colspan="2">CIRCLING</th></tr>
<tr><th>MDA(H)</th><th>RVR/CMV</th><th>MDA(H)</th><th>VIS</th></tr>
<tr><td>A</td><td rowspan="4">1240 (538)</td><td>1000</td><td rowspan="2">1260 (542)</td><td rowspan="2">1600</td></tr>
<tr><td>B</td><td rowspan="2">1200</td></tr>
<tr><td>C</td><td>1280 (562)</td><td>2400</td></tr>
<tr><td>D</td><td>1600</td><td>1420 (702)</td><td>3200</td></tr>
</table>

CHANGE : VAR.

INSTRUMENT APPROACH CHART

RJNW / NOTO

VOR RWY07

KOBE CONTROL	NOTO VOR/DME	NOTO RADIO	NO RADAR
132.45 – 125.6 304.4 – 317.1	111.45 NTE CH-51Y 37°17´24˝N/136°57´46˝E	118.05 AFIS provided by Osaka Airport Office	



NM to NTE	FAF	4	3	2	MAPt
ALT (3.0° APCH Path)	2188	1870	1552	1233	–



MISSED APPROACH

Climb to 3000FT via NTE R084, turn right, direct to NTE VOR/DME and hold.
Contact NOTO RADIO.

DME to NTE	5.0	1.7	0.5
NM to THR	4.5	1.2	0

MINIMA THR elev. 710 AD elev. 718

CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	1140 (430)	1200	1260 (542)	1600
B	1140 (430)	1300	1260 (542)	1600
C	1140 (430)	1400	1280 (562)	2400
D	1140 (430)	1600	1420 (702)	3200

CHANGE : VAR.

INSTRUMENT APPROACH CHART

RJNW / NOTO — RNP RWY25

KOBE CONTROL 132.45 - 125.6 304.4 - 317.1	RNP APCH	NOTO RADIO 118.05 AFIS provided by Osaka Airport Office	NO RADAR

Baro-VNAV not authorized below -10°C



NOPPY (IF/MAHF)	372214.69N 1371120.01E
NW550 (FAF)	372012.97N 1370523.03E
RW25 (MAPt)	371748.52N 1365821.00E
NW551 (MATF)	371637.37N 1365453.75E

NM to Next Fix	MAPt	2	3	4	5	6	FAF
ALT(3.0°APCH Path)	-	1393	1711	2030	2348	2667	2700

MISSED APPROACH

Direct to NW551, turn left direct to NOPPY and hold at 3000FT. Contact NOTO RADIO.



MINIMA THR elev. 702 AD elev. 718

CAT	LNAV/VNAV DA(H)	LNAV/VNAV RVR/CMV	LNAV MDA(H)	LNAV RVR/CMV	CIRCLING MDA(H)	CIRCLING VIS
A	1093 (391)	900	1220 (518)	1000	1260 (542)	1600
B	1103 (401)	1000		1200		
C	1117 (415)				1280 (562)	2400
D	1126 (424)	1400		1600	1420 (702)	3200

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJNW / NOTO

RNP Z RWY07(AR)

KOBE CONTROL 132.45 - 125.6 304.4 - 317.1	RNP AR RF required.	NOTO RADIO 118.05 AFIS provided by Osaka Airport Office	NO RADAR

For uncompensated Baro-VNAV systems, procedure not authorized below -10°C / above 45°C





MISSED APPROACH

Climb to 3000FT, to NOPPY and hold.
Contact NOTO RADIO.

Missed APCH climb gradient MNM 3.2%

MINIMA	THR elev. 710	AD elev. 718
CAT	RNP 0.30	
	DA(H)	CMV
A	-	-
B	-	-
C	1010(300)	1400
D	1010(300)	1600

Authorization Required

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : VAR. HLDG pattern for KILCO, NOPPY.

RJNW / NOTO

RNP Z RWY07(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	KILCO	-	-	-8.8	-	-	+6000	-	-	-
002	TF	TABNO	-	285 (276.6)	-8.8	13.9	-	+6000	-	-	1.0
003	TF	ENDOH	-	285 (276.4)	-8.8	7.7	-	4200	-	-	1.0
004	TF	NW750	-	285 (276.3)	-8.8	1.8	-	3639	-165	-3.00	0.3
005	RF Center: NWRF1 r=2.82NM	NW751	-	-	-8.8	7.4	R	1284	-	-3.00	0.3
006	TF	RW07	Y	075 (066.6)	-8.8	1.6	-	760	-	-3.00/50	0.3
007	TF	NOPPY	-	075 (066.7)	-8.8	12.3	-	3000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	KILCO	285 (276.7)	-8.8	1.0 (-14000)	R	6000	FL140	-230 (-14000)	1.0
Hold	NOPPY	256 (246.9)	-8.8	1.0 (-14000)	L	3000	FL140	-230 (-14000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
KILCO	*370843.05N / 1372519.77E*	NWRF1	*371408.38N / 1365636.03E*
TABNO	*371017.61N / 1370758.59E*		
ENDOH	*371108.66N / 1365824.25E*		
NW750	*371120.22N / 1365612.92E*		
NW751	*371643.80N / 1365512.45E*		
RW07	*371722.92N / 1365706.38E*		
NOPPY	*372214.69N / 1371120.01E*		

CHANGE : VAR. HLDG pattern for KILCO, NOPPY.

INSTRUMENT APPROACH CHART

RJNW / NOTO — RNP Y RWY07(AR)

KOBE CONTROL 132.45 - 125.6 304.4 - 317.1	RNP AR RF required.	NOTO RADIO 118.05 AFIS provided by Osaka Airport Office	NO RADAR

For uncompensated Baro-VNAV systems, procedure not authorized below -10°C / above 45°C





MISSED APPROACH

Climb to 3000FT, to NOPPY and hold.
Contact NOTO RADIO.

Missed APCH climb gradient MNM 3.2%

MINIMA	THR elev. 710	AD elev. 718
CAT	RNP 0.30	
	DA(H)	CMV
A	-	-
B		
C	1010(300)	1400
D		1600

MINIMA with Missed APCH climb gradient of 2.5% are not established.

Authorization Required

CHANGE : VAR. PROC course. HLDG pattern for NOPPY.

INSTRUMENT APPROACH CHART

RJNW / NOTO

RNP Y RWY07(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	NOPPY	-	-	-8.8	-	-	+4200	-	-	-
002	TF	BENKO	-	273 (264.0)	-8.8	4.2	-	+4200	-	-	1.0
003	TF	KONOS	-	273 (264.0)	-8.8	7.6	-	4200	-	-	1.0
004	TF	NW760	-	273 (263.9)	-8.8	2.0	-	3555	-165	-3.00	0.3
005	RF Center: NWRF2 r=2.10NM	NW761	-	-	-8.8	7.2	L	1257	-	-3.00	0.3
006	TF	RW07	Y	075 (066.6)	-8.8	1.6	-	760	-	-3.00/50	0.3
007	TF	NOPPY	-	075 (066.7)	-8.8	12.3	-	3000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	NOPPY	256 (246.9)	-8.8	1.0 (-14000)	L	3000	FL140	-230 (-14000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
NOPPY	*372214.69N / 1371120.01E*	NWRF2	*371841.62N / 1365416.12E*
BENKO	*372148.26N / 1370603.41E*		
KONOS	*372059.84N / 1365630.70E*		
NW760	*372046.91N / 1365359.30E*		
NW761	*371645.85N / 1365518.43E*		
RW07	*371722.92N / 1365706.38E*		
NOPPY	*372214.69N / 1371120.01E*		

CHANGE : VAR. PROC course. HLDG pattern for NOPPY.

INSTRUMENT APPROACH CHART

RJNW / NOTO — RNP X RWY07

KOBE CONTROL 132.45 - 125.6 304.4 - 317.1	RNP APCH	NOTO RADIO 118.05 AFIS provided by Osaka Airport Office	NO RADAR

Baro-VNAV not authorized below -10°C



NM to Next Fix	FAF	4	3	2	MAPt
ALT(3.0°APCH Path)	2200	2033	1714	1396	-



MISSED APPROACH

Direct to NOPPY and hold at 3000FT.
Contact NOTO RADIO.

Missed APCH climb gradient MNM 3.0%

MINIMA — THR elev. 710 — AD elev. 718

CAT	LNAV/VNAV		LNAV		CIRCLING	
	DA(H)	CMV	MDA(H)	CMV	MDA(H)	VIS
A	962 (252)	1000	1060 (350)	1200	1260 (542)	1600
B	962 (252)	1100	1060 (350)	1300	1260 (542)	1600
C	972 (262)	1200	1070 (360)	1400	1280 (562)	2400
D	1001 (291)	1400	1080 (370)	1600	1420 (702)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : New PROC.

RJNW / NOTO Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

Call sign	BRG / DIST from ARP	Remarks
見附島 Mitsukejima	066°T / 14.9NM	島 Island
宇出津 Ushitsu	085°T / 9.1NM	港 Harbor
観音崎 Kannonzaki	158°T / 12.0NM	岬 Cape
ツインブリッジ TwinBridge	197°T / 9.8NM	橋 Bridge
穴水 Anamizu	210°T / 4.6NM	港 Harbor
海士崎 Amazaki	238°T / 16.5NM	岬 Cape
猿山 Saruyama	278°T / 11.7NM	岬 Cape
輪島 Wajima	335°T / 7.0NM	港 Harbor

CHANGE : VAR.

RJNW / NOTO

Minimum Vectoring Altitude CHART