

AD CHART

★ ABN

IWAMI AP

TRUE NORTH

APRON FLOOD LGT

WIND SPEED METER

WDI

CGL

165m

110m

1

2

3

WIND SPEED METER

WDI

CEILOMETER

TURNING POINT INDICATOR LGT

402.2m

RVR

RTHL

WDI

2000m

PAPI Angle 3.0°
MEHT 18.5m(61ft)

IWAMI

362.0m

PAPI Angle 3.0°
MEHT 18.5m(61ft)

OVERRUN AREA EDGE LGT

REMARKS : 1. RWY GROOVING 2000 x 30m
2. WIDTH OF TWY 30m
3. STRENGTH OF RWY 42 / F / A / X / T

ALS

SEQUENCED FLASHING LGT (SFL-V)

11

29

SALS

APCH LGT BCN

900m

300m

420m

165m

267m

852m

LONGITUDINAL PROFILE OF RWY

RWY11
56.0m
(184 ft)

RWY29
52.0m
(171 ft)

0.2%

0m

2000m

STANDARD DEPARTURE CHART-INSTRUMENT

RJOW / IWAMI

SID and TRANSITION

SAMBA THREE DEPARTURE


RWY11 : Climb RWY HDG to 800FT, turn left HDG352° ,...
RWY29 : Climb RWY HDG to 700FT, turn right HDG082° ,...
...to intercept and proceed via IME R037 to SAMBA.
Cross SAMBA at or above 7000FT.

Note RWY11 : 5.7% climb gradient required up to 1700FT.
OBST ALT 1322FT located at 4.8NM 094° FM end of RWY11.

IZUMO TRANSITION

From over SAMBA, via XZE R252 to XZE VOR/DME.
Cross CARNY at or below 13000FT, cross BAARU at or below FL230.

CHANGE : PROC renamed(SAMBA THREE DEPARTURE), PROC course. Note RWY11(OBST).



STANDARD DEPARTURE CHART-INSTRUMENT

RJOW / IWAMI

RNAV TRANSITION




From SAMBA at or above 7000FT, to OSPEL at or below 13000FT, to VIBEL at or below FL230.

Critical DME	STD : SAMBA – VIBEL
DME GAP	-
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1.

CHANGE : FIX symbol(SAMBA).

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SAMBA	-	-	-7.8	-	-	+7000	-	-	RNAV1
002	TF	OSPEL	-	077 (069.7)	-7.8	10.5	-	-13000	-	-	RNAV1
003	TF	VIBEL	-	078 (069.8)	-7.8	10.2	-	-FL230	-	-	RNAV1

STANDARD DEPARTURE CHART-INSTRUMENT




CHANGE : New PROC.

INTENTIONALLY LEFT BLANK

STANDARD ARRIVAL CHART-INSTRUMENT

RJOW / IWAMI


RNAV STAR




CHANGE : New PROC.

INTENTIONALLY LEFT BLANK

INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART




CHANGE: VAR. PROC course. TELOB established. Missed APCH course. HLDG course. MSA(BTN 270° and 360°).

VOR A

[illegible]

Turn right, climb to 4000FT via IME
R037 to BLUES and hold.
Contact IWAMI RADIO.




Circling to NORTH side of RWY only


INSTRUMENT APPROACH CHART

RJOW / IWAMI

RNP RWY11(AR)



CHANGE : HLDG course for using NAVAID.

**Authorization Required**

INSTRUMENT APPROACH CHART

RJOW / IWAMI

RNP RWY11(AR)

Coding Table											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	BLUES	-	-	-8.2	-	-	+4000	-	-	1.0
002	TF	OW150	-	238 (229.3)	-8.2	9.8	-	2600	-	-	1.0
003	TF	OW151	-	237 (229.2)	-8.2	1.4	-	2139	-165	-3.00	0.3
004	RF Center: OWRF1 r=2.03NM	OW152	-	-	-8.2	4.4	L	736	-	-3.00	0.3
005	TF	RW11	Y	113 (104.8)	-8.2	1.6	-	238	-	-3.00/54	0.3
006	FA	-	-	113 (104.8)	-8.2	-	-	+600	-	-	1.0
007	DF	BLUES	-	-	-8.2	-	L	4000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	BLUES	217 (208.7)	-8.2	1.0 (-13000)	R	4000	13000	-220 (-13000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
BLUES	345159.02N / 1315423.09E	OWRF1	344304.90N / 1314534.53E
OW150	344533.91N / 1314518.52E		
OW151	344437.18N / 1314358.51E		
OW152	344107.26N / 1314456.99E		
RW11	344043.28N / 1314647.11E		

CHANGE : VAR. Course FM BLUES to OW150. RNAV HLDG established.

INSTRUMENT APPROACH CHART

RJOW / IWAMI

RNP RWY29(AR)



CHANGE : HLDG course for using NAVAID.

INSTRUMENT APPROACH CHART

RJOW / IWAMI

RNP RWY29(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	BLUES	-	-	-8.2	-	-	+4000	-	-	1.0
002	TF	OW950	-	200 (191.5)	-8.2	6.0	-	3100	-	-	1.0
003	TF	OW951	-	200 (191.5)	-8.2	5.3	-	1374	-150	-3.10	0.16 0.30
004	RF Center: OWRF2 r=1.20NM	OW952	-	-	-8.2	2.0	R	731	-	-3.10	0.16 0.30
005	TF	RW29	Y	293 (284.9)	-8.2	1.5	-	221	-	-3.10/50	0.16 0.30
006	FA	-	-	293 (284.9)	-8.2	-	-	+600	-	-	1.0
007	DF	BLUES	-	-	-8.2	-	R	4000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	BLUES	217 (208.7)	-8.2	1.0 (-13000)	R	4000	13000	-220 (-13000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
BLUES	345159.02N / 1315423.09E	OWRF2	344112.62N / 1315014.52E
OW950	344606.97N / 1315256.13E		
OW951	344058.27N / 1315140.08E		
OW952	344002.90N / 1314952.21E		
RW29	344026.72N / 1314803.07E		

CHANGE : VAR. PROC course. RNAV HLDG established.





RJOW / IWAMI

Minimum Vectoring Altitude CHART



CENTER : 344035N/1314725E (ARP)