

## AD 2 AERODROMES

## RJOE AD 2.1 AERODROME LOCATION INDICATOR AND NAME

## RJOE - AKENO

## RJOE AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	343200N/1364020E
2	Direction and distance from (city)	3.2nm NW ISE
3	Elevation/ Reference temperature	20ft / -
4	Geoid undulation at AD ELEV PSN	Nil
5	MAG VAR/ Annual change	Nil
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	JSDF-G
7	Types of traffic permitted(IFR/ VFR)	IFR/VFR
8	Remarks	Nil

## RJOE AD 2.3 OPERATIONAL HOURS

1	AD Administration	2330-0800 MON-FRI,EXC HOL and 29 DEC - 3 JAN Other time 1HR PN
2	Customs and immigration	Nil
3	Health and sanitation	Nil
4	AIS Briefing Office	2330-0800 MON-FRI,EXC HOL and 29 DEC - 3 JAN Other time 1HR PN
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	2200-0800 MON-FRI,EXC HOL and 29 DEC - 3 JAN
7	ATS	2330-0800 MON-FRI,EXC HOL and 29 DEC - 3 JAN Other time 1HR PN
8	Fuelling	Nil
9	Handling	Nil
10	Security	Nil
11	De-icing	Nil
12	Remarks	Nil

**RJOE AD 2.4 HANDLING SERVICES AND FACILITIES**

1	Cargo-handling facilities	Nil
2	Fuel/ oil types	JET A-1
3	Fuelling facilities/ capacity	To be issued later
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

**RJOE AD 2.5 PASSENGER FACILITIES**

1	Hotels	Nil
2	Restaurants	Nil
3	Transportation	Nil
4	Medical facilities	Nil
5	Bank and Post Office	Nil
6	Tourist Office	Nil
7	Remarks	Nil

**RJOE AD 2.6 RESCUE AND FIRE FIGHTING SERVICES**

1	AD category for fire fighting	Nil
2	Rescue equipment	Nil
3	Capability for removal of disabled aircraft	Nil
4	Remarks	Nil

**RJOE AD 2.7 SEASONAL AVAILABILITY-CLEARING**

1	Types of clearing equipment	Nil
2	Clearance priorities	Nil
3	Remarks	Nil

**RJOE AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA**

1	Apron surface and strength	To be issued later
2	Taxiway width, surface and strength	To be issued later
3	ACL and elevation	Not available
4	VOR checkpoints	Nil
5	INS checkpoints	Nil
6	Remarks	Nil

**RJOE AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS**

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	Nil
2	RWY and TWY markings and LGT	RWY: RWY13/31 (LGT) RTHL, REDL RWY: RWY 04/22 Nil  TWY: (LGT) TWY edge LGT
3	Stop bars	Nil
4	Remarks	Nil

**RJOE AD 2.10 AERODROME OBSTACLES**

RWY/Area affected	Obstacle type	Coordinates	Elevation	Markings/ LGT	Remarks
Nil					

## RJOE AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	AKENO
2	Hours of service MET Office outside hours	2200 - 0800 MON-FRI, EXC HOL and 29 DEC - 3 JAN Other time on request
3	Office responsible for TAF preparation Periods of validity	Nil
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Nil
6	Flight documentation Language(s) used	Ja, En
7	Charts and other information available for briefing or consultation	S, U
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	Nil
10	Additional information(limitation of service, etc.)	Nil

## RJOE AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN) and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
13	To be	500x30	SW5000kg (11000lbs)	Nil	Nil
31	issued	500x30	Asphalt	Nil	Nil
	later				
04		500x30	Roll	Nil	Nil
22		500x30		Nil	Nil
Slope of RWY		Strip Dimensions(M)	Remarks		
7		10	12		
to be developed		700 x 300			
		700 x 300			
		700 x 75			
		700 x 75			

**RJOE AD 2.13 DECLARED DISTANCES**

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6

**RJOE AD 2.14 APPROACH AND RUNWAY LIGHTING**

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
13								
31								
04								
22								
Remarks								
10								

**RJOE AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY**

1	ABN/IBN location, characteristics and hours of operation	ABN: 343156N/1363957E, White/Green EV10sec, HO
2	LDI location and LGT Anemometer location and LGT	Nil
3	TWY edge and center line lighting	TWY edge LGT : AVBL
4	Secondary power supply/ switch-over time	Nil
5	Remarks	WDI LGT

**RJOE AD 2.16 HELICOPTER LANDING AREA**

Nil
-----

## RJOE AD 2.17 ATS AIRSPACE

Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
AKENO CTR	Area within a radius of 5nm of AKENO ARP (34°32'N/136°40'E)	2500 or below	D	AKENO Tower	
AKENO ACA	SEE RJOE attached chart				

明野進入管制区  
Akeno Approach Control Area



## RJOE AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
APP	Akeno Approach Control or Radar	140.5MHz(1) 362.3MHz(1) 120.1MHz(1) 139.45MHz(2) 141.95MHz(2) 121.5MHz(E) 243.0MHz(E)	2330-0800(3) MON-FRI Other time 1HR PN	(1)Primary (2)Secondary (3)EXC HOL and 12/29 - 1/3
TWR	Akeno Tower	236.8MHz 126.2MHz 139.8MHz 138.05MHz 140.3MHz 121.5MHz(E) 243.0MHz(E)	2330-0800(3) MON-FRI Other time 1HR PN	
GCA-ASR -PAR	Akeno GCA	335.6MHz 270.8MHz 134.1MHz 141.7MHz 138.3MHz 122.0MHz 243.0MHz(E) 121.5MHz(E)	2330-0800(3) MON-FRI Other time 1HR PN	GP 3.0°. ASR for RWY 31 JSDF-G HEL only. ASR,PAR RWY13

## RJOE AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
TACAN	AKT	1144MHz (CH-57Y)	2330 - 0800(1) MON-FRI Other time 1HR PN	343142.7N/1364030.6E		TACAN Unusable: R100-110 beyond 37NM BLW 3000ft. R110-120 beyond 35NM BLW 3000ft. R120-130 beyond 22NM BLW 4000ft. R130-140 beyond 17NM BLW 4000ft. R140-150 beyond 20NM BLW 4000ft. R150-160 beyond 22NM BLW 4000ft. R160-170 beyond 17NM BLW 4000ft. R170-180 beyond 13NM BLW 4000ft. R180-190 beyond 17NM BLW 4000ft. R190-200 beyond 23NM BLW 5000ft. R200-210 beyond 25NM BLW 5000ft. R210-220 beyond 28NM BLW 6000ft. R220-230 beyond 35NM BLW 8000ft. R270-290 beyond 35NM BLW 7000ft. R300-320 beyond 37NM BLW 5000ft.

## RJOE AD 2.20 LOCAL TRAFFIC REGULATIONS

## 1. Airport regulations

Nil

## 2. Taxiing to and from stands

Nil

## 3. Parking area for small aircraft(General aviation)

Nil



4. Parking area for helicopters

Nil
-----

5. Apron - taxiing during winter conditions

Nil
-----

6. Taxiing - limitations

Nil
-----

7. School and training flights - technical test flights - use of runways

Nil
-----

8. Helicopter traffic - limitation

Nil
-----

9. Removal of disabled aircraft from runways

Nil
-----

**RJOE AD 2.21 NOISE ABATEMENT PROCEDURES**

Nil
-----

**RJOE AD 2.22 FLIGHT PROCEDURES**

**1. TAKE OFF MINIMA**

	RWY	REDL AVBL	REDL OUT
		CEIL-VIS	CEIL-VIS
TKOF ALTN AP FILED	13	200'-800m	200'-800m
	31	200'-800m	200'-800m
OTHER	13	AVBL LDG MINIMA	
	31		

**2. WX MINIMA CONCERNING PAR/ASR APCH PROCEDURE**

ASR RWY 13					ASR RWY 31				
MINIMA		THR ELEV:17	AD ELEV: 20		MINIMA		THR ELEV:15	AD ELEV: 20	
CAT			CIRCLING		CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS		MDA(H)	CMV	MDA(H)	VIS
A	500(480)	1500	600(580)	1600	A	500(480)	1500	600(580)	1600
B					B				
C	-	-	-	-	C	-	-	-	-
D					D				

PAR RWY 13				
MINIMA		THR ELEV:17	AD ELEV: 20	
CAT			CIRCLING	
	DA(H)	CMV	MDA(H)	VIS
A	270(253)	1200	600(580)	1600
B				
C	-	-	-	-
D				

**3. Lost communication procedures for arrival aircraft under radar navigational guidance**

If radio communications with Akeno Approach/Radar are lost for 1 minute, 15 seconds on surveillance final approach, or 5 seconds on PAR final approach, squawk Mode A/3 Code 7600 and;

- (I) 1. Contact Akeno Radar /Tower.  
 2. If unable, proceed in accordance with Visual Flight Rules.  
 3. If unable, execute TACAN NR.1 or NR.2 approach.

**4. Automated Radar Terminal System (ARTS)**

When instructed by ATC, aircraft flying in and out of Akeno approach control area in principle will reply on 4096 Code (Mode A/3) with automatic altitude reporting capability (Mode C) ; Aircraft not equipped with the said transponder shall report ATC to that effect.

明野進入管制区を航行する航空機は、管制機関の指示があった場合、原則として自動高度通報機能を有する 4096 コードによる応答装置を作動させること。上記指示を受けた当該応答装置を有しない航空機は、管制機関に対しその旨を通報すること。

**RJOE AD 2.23 ADDITIONAL INFORMATION**

Nil

**RJOE AD 2.24 CHARTS RELATED TO AN AERODROME**

Standard Departure Chart-Instrument (KOWA, AKENO REVERSAL, ASAMA, HISAI)  
 Standard Arrival Chart-Instrument

Instrument Approach Chart (TACAN NR.1)  
 Instrument Approach Chart (TACAN NR.2)

STANDARD DEPARTURE CHART -INSTRUMENT

RJOE / AKENO

SID

KOWA SIX DEPARTURE

RWY13 : Turn left,...

RWY31 : Turn right,...

.... climb via AKT R060 to XMT TACAN.

Cross XMT TACAN at assigned altitude.

AKENO REVERSAL FOUR DEPARTURE

RWY13 : Turn left,...

RWY31 : Turn right,...

.... climb via AKT R320 until passing 2500FT, then turn right within

AKT TACAN 10DME to intercept and proceed via AKT R320 to AKT.

TRIKE TRANSITION

From over AKT TACAN, via AKT R068 to TRIKE.

Cross AKT 14DME at or above 4000FT.

Cross TRIKE at assigned altitude.

ASAMA ONE DEPARTURE

RWY13 : Turn left,....

RWY31 : Turn right,....

....climb via AKT R105 to ASAMA.

Cross ASAMA at or above 2500FT.

Note : Following climb gradient should be maintained until 2500FT.

Speed (Knots)	60	90	120	150	180	210
Rate (Feet/Min)	300	450	600	750	900	1050

HISAI ONE DEPARTURE

RWY13 : Turn left,....

RWY31 : ....

....climb via AKT R320 to HISAI.

Cross HISAI at or above 2500FT.

Note : Following climb gradient should be maintained until 2500FT.

Speed (Knots)	60	90	120	150	180	210
Rate (Feet/Min)	300	450	600	750	900	1050


CHANGE : PROC renamed(KOWA SIX DEPARTURE, AKENO REVERSAL FOUR DEPARTURE). NDB(AK) abolished.

STANDARD DEPARTURE CHART -INSTRUMENT

RJOE / AKENO

SID

CHANGE : PROC renamed(KOWA SIX DEPARTURE, AKENO REVERSAL FOUR DEPARTURE). NDB(AK) abolished.



STANDARD ARRIVAL CHART-INSTRUMENT

RJOE / AKENO

STAR


AKENO ARRIVAL

From over TRIKE, via AKT R068 to AKT TACAN.

Cross AKT 14DME at or above 4000FT.

Cross AKT TACAN at or above 2500FT.

CHANGE : NDB(AK) abolished.




**INTENTIONALLY LEFT BLANK**

INSTRUMENT APPROACH CHART

RJOE / AKENO


TACAN NR.1



## INSTRUMENT APPROACH CHART


RJOE / AKENO

TACAN NR.2



## MISSED APPROACH

At 0.7DME prior to AKT TACAN,  
climb via AKT R-320 to 2DME,  
turn right to intercept and proceed  
via AKT R-105 to 8DME fix  
and hold at 2500'.



MINIMA		THR elev. 15	AD elev. 20	
CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	680 (660)	1500	680 (660)	1600
B				
C	—	—	—	—
D	—	—	—	—