

AD 2 AERODROMES

RJCT AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJCT - TOKACHI

RJCT AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	425325N/1430930E
2	Direction and distance from (city)	
3	Elevation/ Reference temperature	281ft / -
4	Geoid undulation at AD ELEV PSN	Nil
5	MAG VAR/ Annual change	Nil
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	JSDF-G
7	Types of traffic permitted(IFR/VFR)	IFR/VFR
8	Remarks	Nil

RJCT AD 2.3 OPERATIONAL HOURS

1	AD Administration	2300 - 0800 MON-FRI EXC HOL and 12/29 -1/3 Other time 1HR PN
2	Customs and immigration	Nil
3	Health and sanitation	Nil
4	AIS Briefing Office	2300 - 0800 MON-FRI EXC HOL and 12/29 -1/3 Other time 1HR PN
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	2200 - 0800 MON-FRI Other time on request
7	ATS	2300 - 0800 MON-FRI EXC HOL and 12/29 -1/3 Other time 1HR PN
8	Fuelling	Nil
9	Handling	Nil
10	Security	Nil
11	De-icing	Nil
12	Remarks	Nil

RJCT AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Nil
2	Fuel/ oil types	JP-4
3	Fuelling facilities/ capacity	To be issued later
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

RJCT AD 2.5 PASSENGER FACILITIES

1	Hotels	Nil
2	Restaurants	Nil
3	Transportation	Nil
4	Medical facilities	Nil
5	Bank and Post Office	Nil
6	Tourist Office	Nil
7	Remarks	Nil

RJCT AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	Nil
2	Rescue equipment	Nil
3	Capability for removal of disabled aircraft	Nil
4	Remarks	Nil

RJCT AD 2.7 SEASONAL AVAILABILITY-CLEARING

1	Types of clearing equipment	Nil
2	Clearance priorities	Nil
3	Remarks	Nil

RJCT AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Apron surface and strength	To be issued later
2	Taxiway width, surface and strength	To be issued later
3	ACL and elevation	Not available
4	VOR checkpoints	Nil
5	INS checkpoints	Nil
6	Remarks	Nil

RJCT AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	Nil
2	RWY and TWY markings and LGT	RWY:RWY13/31 (Marking) RWY designation, RWY CL, RWY THR, RWY middle point, RWY side stripe (LGT) REDL, RTHL(RWY31) TWY: (LGT) TWY edge LGT
3	Stop bars	Nil
4	Remarks	Nil

RJCT AD 2.10 AERODROME OBSTACLES

RWY/Area affected	Obstacle type	Coordinates	Elevation	Markings/ LGT	Remarks
RWY13	Trees	425346N/1430852E	325ft	-/-	Above approach SFC
RWY31	Buildings	425305N/1431014E	283ft	-/-	Above approach SFC

RJCT AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	TOKACHI
2	Hours of service MET Office outside hours	Nil
3	Office responsible for TAF preparation Periods of validity	Nil
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Nil
6	Flight documentation Language(s) used	Nil
7	Charts and other information available for briefing or consultation	Nil
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	Nil
10	Additional information(limitation of service, etc.)	Nil

RJCT AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN)and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
13	To be	1500×45	SIWL 8500kg	Nil	
31	issued Later	1500×45	(18740lbs) Asphalt-Concrete	Nil	
Slope of RWY		Strip Dimensions(M)	Remarks		
7		10	12		
See below figure		1620×150 1620×150			
<div><div>RWY13</div><div>RWY31</div><p>The figure shows a profile view of Runway 13/31. The horizontal axis represents distance in feet, with markers at -60, 0, 480, 860, 1060, 1500, and -60. The vertical axis represents elevation in feet. The profile starts at 281ft at -60ft, drops to 278ft at 0ft, rises to 278ft at 480ft, drops to 270ft at 860ft, rises to 265ft at 1060ft, drops to 256ft at 1500ft, and ends at 255ft at -60ft. The slopes between these points are 1.5%, 0.2%, 0.58%, 0.891%, 0.66%, and 0.2% respectively. The runways are labeled RWY13 on the left and RWY31 on the right.</p></div>					

RJCT AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6

RJCT AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
13								
31	AVBL							
Remarks								
10								

RJCT AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	ABN: 425324N/1430910E, White/Green EV6sec, HO
2	LDI location and LGT Anemometer location and LGT	Nil
3	TWY edge and centerline lighting	Nil
4	Secondary power supply/ switch-over time	Nil
5	Remarks	WDI LGT

RJCT AD 2.16 HELICOPTER LANDING AREA

NII

RJCT AD 2.17 ATS AIRSPACE

Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
TOKACHI CTR	Area within a radius of 5nm of TOKACHI ARP (42°53'N143°10'E) exclude OBIHIRO control zone	1500 or below	D	TOKACHI TOWER	
Hidaka ACA	See RJEC attached chart		E	Hidaka APP En	

RJCT AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
APP	Hidaka Approach	128.325MHz 246.1MHz 134.55MHz 121.5MHz(E) 243.0MHz(E)	2230 - 1200	
TWR	Tokachi Tower	122.2MHz 126.2MHz 140.5MHz 139.8MHz 138.05MHz 121.5MHz(E)	2300-0800 MON - FRI(1) Other time 1HR PN	(1) Exc Hol and 12/29 - 1/3 (2) Primary (3) Secondary
GCA-PAR -ASR	Tokachi GCA	133.0MHz(2) 270.8MHz(2) 125.3MHz(3) 303.2MHz(3) 134.1MHz 335.6MHz 138.3MHz 141.95MHz 121.5MHz(E) 243.0MHz(E)	2300-0800 MON - FRI(1) Other time 1HR PN	ASR RWY 13/31 PAR RWY 13/31 GP 3.0°

RJCT AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
TACAN	TKT	1016MHz (CH-55X)	2300 - 0800 MON - FRI EXC HOL and 12/29-1/3. Other time 1HR PN.	425336N/ 1430957E	336.3ft	Unusable: R210-220 beyond 38NM BLW 9000ft R220-230 beyond 35NM BLW 9000ft R230-240 beyond 25NM BLW 9000ft R240-260 beyond 27NM BLW 9000ft R260-270 beyond 29NM BLW 9000ft R270-280 beyond 25NM BLW 9000ft R280-290 beyond 25NM BLW 8000ft R290-300 beyond 31NM BLW 8000ft R300-310 beyond 36NM BLW 8000ft

RJCT AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

Nil

2. Taxiing to and from stands

Nil

3. Parking area for small aircraft(General aviation)

Nil

4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

Nil

7. School and training flights - technical test flights - use of runways

Nil

8. Helicopter traffic - limitation

Nil

9. Removal of disabled aircraft from runways

Nil

RJCT AD 2.21 NOISE ABATEMENT PROCEDURES

Nil

RJCT AD 2.22 FLIGHT PROCEDURES

1. TAKE OFF MINIMA

	RWY	CEIL-VIS
TKOF ALTN AP FILED	13	200'-1600m
	31	
OTHER	13	AVBL LDG MINIMA*
	31	

* Not below MINIMA of TKOF ALTN AP FILED

2. WX MINIMA CONCERNING PAR/ASR APCH PROCEDURE

PAR RWY 13

MINIMA		THR ELEV: 280	AD ELEV: 281	
CAT			CIRCLING	
	DA(H)	CMV	MDA(H)	VIS
A	480(200)	1000	720(439)	1600
B			740(459)	
C				2400
D	-	-	-	-

Note: RWY 13 threshold of PAR RWY 13 is 190m inside from original RWY 13 threshold.

PAR RWY 31

MINIMA		THR ELEV:258	AD ELEV: 281	
CAT			CIRCLING	
	DA(H)	CMV	MDA(H)	VIS
A	478(220)	1000	720(439)	1600
B			740(459)	
C				2400
D	-	-	-	-

Note: RWY 31 threshold of PAR RWY 31 is 125m inside from original RWY 31 threshold.

ASR RWY 13

MINIMA		THR ELEV: 280		AD ELEV: 281	
CAT			CIRCLING		
	MDA(H)	RVR/ CMV	MDA(H)	VIS	
A	720(439)	1500	720(439)	1600	
B			740(459)		
C		1800			2400
D	-	-	-	-	

Note: RWY 13 threshold of ASR RWY 13 is 190m inside from original RWY 13 threshold.

ASR RWY 31

MINIMA		THR ELEV:258	AD ELEV: 281	
CAT			CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	700(442)	1500	720(439)	1600
B			740(459)	
C			1800	
D	-	-	-	-

Note: RWY 31 threshold of ASR RWY 31 is 125m inside from original RWY 31 threshold.

3. Lost communication procedures for arrival aircraft under radar navigational guidance

If radio communications with Hidaka Approach or Tokachi GCA are lost for 1 minute, or 5 seconds(PAR)/15 seconds(ASR) on final approach, squawk Mode A/3 Code 7600 and;

- (I)
 1. Contact Tokachi Tower.
 2. If unable, proceed in accordance with visual flight rules.
 3. If unable, proceed to IBOSA at last assigned altitude or 3,300 feet whichever is higher, and execute instrument approach.
- (II) Procedures other than above will be issued when situation requires.

RJCT AD 2.23 ADDITIONAL INFORMATION

Nil


RJCT AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome/Heliport Chart Standard Departure Chart-Instrument (OTOFUKE REVERSAL, HONBETSU) Standard Arrival Chart-Instrument (TOKACHI) Instrument Approach Chart (TACAN RWY 13)

INTENTIONALLY LEFT BLANK

RJCT / TOKACHI

AD CHART



INTENTIONALLY LEFT BLANK

STANDARD DEPARTURE CHART - INSTRUMENT

RJCT/TOKACHI

SID and TRANSITION

OTOFUKE REVERSAL ONE DEPARTURE

RWY13 : Climb RWY HDG to 500FT, turn left,...

RWY31 : Climb RWY HDG to 500FT, turn right,...

...to intercept and proceed via TKT R040 to 2000FT, turn left

within TKT 10.0DME to intercept and proceed via TKT R040 to TKT TACAN.

Cross TKT TACAN at or above 4000FT.


Note RWY13 : 5.3% climb gradient required up to 500FT.

OBST ALT 340FT located at 0.3NM 157°FM end of RWY13.

NODUK TRANSITION

From over TKT TACAN, climb via TKT R339 to NODUK.

Cross NODUK at or above 6000FT.

HONBETSU TWO DEPARTURE

RWY13 : Climb RWY HDG to 500FT, turn left,...


RWY31 : Climb RWY HDG to 500FT, turn right,...

...via TKT R062 to RUGMO.

Cross RUGMO at or above 5000FT.

Note RWY13 : 5.3% climb gradient required up to 500FT.

OBST ALT 340FT located at 0.3NM 157°FM end of RWY13.

CHANGE : PROC renamed(HONBETSU TWO DEPARTURE, NODUK TRANSITION). PROC course. NOTAK and EATAK abolished.
NODUK and RUGMO established.

INTENTIONALLY LEFT BLANK

STANDARD ARRIVAL CHART - INSTRUMENT

RJCT / TOKACHI

STAR

TOKACHI ARRIVAL

From over TKT TACAN at or above 4000FT, via TKT R040 to IBOSA.
Cross IBOSA at or above 3300FT.



CHANGE : IBOSA established. OSABU abolished.


INTENTIONALLY LEFT BLANK

INSTRUMENT APPROACH CHART


RJCT / TOKACHI

TACAN RWY 13

HIDAKA APP 128.325 — 246.1 — 134.55	TOKACHI TACAN 1016 TKT CH-55X 42°53'36"N/143°09'57"E	TOKACHI TOWER 122.2	GCA AVAILABLE
--	---	----------------------------	---------------



CHANGE : ATC call sign and FREQ. Missed APCH PROC.



MINIMA		THR elev. 281		AD elev. 281	
CAT			CIRCLING		
	MDA(H)	CMV	MDA(H)	VIS	
A	640 (359)	1500	720 (439)	1600	
B			740 (459)		
C		1800			2400
D	—	—	—	—	

INTENTIONALLY LEFT BLANK