

STANDARD DEPARTURE CHART-INSTRUMENT

RJFC / YAKUSHIMA

SID

NAKATANE FOUR DEPARTURE


RWY14 : Climb RWY HDG to 560FT, turn left HDG014°...

RWY32 : Climb RWY HDG to 520FT, turn right HDG104°...


... to intercept and proceed via YKE R058/TGE R239 to TGE VOR/DME.
Cross TGE VOR/DME at or above 6000FT.

Note RWY14 : In case of climbing with 8.8% gradient up to 560FT,
another TKOF WX MINIMA is applicable.
OBST ALT 206FT located at 0.2NM 180° FM end of RWY14.

CHANGE : PROC renamed. KAGOSHIMA SEVEN DEPARTURE abolished. PROC course. Note. OBST chart added.



STANDARD DEPARTURE CHART -INSTRUMENT



STANDARD DEPARTURE CHART -INSTRUMENT

RJFC / YAKUSHIMA

RNAV SID

AMMON FOUR DEPARTURE

RWY14 : Climb on HDG 141° at or above 560FT, turn left direct to KOUKI at or above 6000FT, to AMMON.

RWY32 : Climb on HDG 321° at or above 520FT, turn right direct to KOUKI at or above 6000FT, to AMMON.

Note RWY14 : In case of climbing with 8.8% gradient up to 560FT,
another TKOF WX MINIMA is applicable.
OBST ALT 206FT located at 0.2NM 180° FM end of RWY14.

RWY14


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	141 (134.0)	-6.9	-	-	+560	-	-	RNP1
002	DF	KOUKI	-	-	-6.9	-	L	+6000	-	-	RNP1
003	TF	AMMON	-	004 (357.0)	-6.9	27.0	-	-	-	-	RNP1

RWY32

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	321 (314.0)	-6.9	-	-	+520	-	-	RNP1
002	DF	KOUKI	-	-	-6.9	-	R	+6000	-	-	RNP1
003	TF	AMMON	-	004 (357.0)	-6.9	27.0	-	-	-	-	RNP1

CHANGE : Navigation Specification(Basic RNP1 → RNP1).

STANDARD DEPARTURE CHART -INSTRUMENT



RJFC / YAKUSHIMA

SURF TWO DEPARTURE

Note RWY14 : In case of climbing with 8.8% gradient up to 560FT,
another TKOF WX MINIMA is applicable.
OBST ALT 206FT located at 0.2NM 180° FM end of RWY14.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	141 (134.0)	-6.9	-	-	+560	-	-	RNP1
002	DF	TGE	-	-	-6.9	-	L	-	-	-	RNP1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	321 (314.0)	-6.9	-	-	+520	-	-	RNP1
002	DF	TGE	-	-	-6.9	-	R	-	-	-	RNP1

18/4/24

STANDARD ARRIVAL CHART-INSTRUMENT

RJFC / YAKUSHIMA

STAR

CEDAR ARRIVAL

From over TGE VOR/DME, via TGE R217 to CEDAR.
Cross CEDAR at or above 2200 FT.



CHANGE : JOMON ARRIVAL abolished.

STANDARD ARRIVAL CHART-INSTRUMENT

RJFC / YAKUSHIMA

STAR

TOLOT ARRIVAL

From over TGE VOR/DME, via TGE R266 to TOLOT.

Cross TGE VOR/DME at or above 4000FT, cross TOLOT at or above 3000FT.



CHANGE : New PROC.

RJFC / YAKUSHIMA

VOR RWY 32

KOBE CONTROL
133.85 - 315.3
134.6 - 225.65


YAKUSHIMA VOR/DME
117.0 YKE
CH-117 三三三
30°22'16"N/130°39'16"E

YAKUSHIMA RADIO
118.65
AFIS provided
by Kagoshima Airport Office

NO RADAR




MSA 25NM



EQPT REQUIRED
DME



At 2.5 DME prior to YKE VOR/DME,
turn right and climb to 2200FT via YKE
R127 to CEDAR and hold.
Contact YAKUSHIMA RADIO.

MINIMA THR elev. 124 AD elev. 122

CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	580 (458)	1500	660 (538)	1600
B				
C		2000	700 (578)	2400
D	—	—	—	—

Circling to EAST side of RWY only.

CHANGE : FREQ of KOBE CONTROL(127.15 \rightarrow 134.6, 251.0 \rightarrow 225.65).

INSTRUMENT APPROACH CHART




CHANGE : FREQ of KOBE CONTROL(127.15 → 134.6, 251.0 → 225.65).

INSTRUMENT APPROACH CHART

RJFC / YAKUSHIMA

RNP RWY 32



INSTRUMENT APPROACH CHART

RJFC / YAKUSHIMA

RNP RWY32

FAS DATA BLOCK

Operation type	0	LTP/FTP ellipsoidal height	+00675
SBAS service provider identifier	2	FPAP latitude	302329.2980N
Airport identifier	RJFC	FPAP longitude	1303907.6190E
Runway	32	Threshold crossing height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M32A	∠ length offset	0192
LTP/FTP latitude	302251.1820N	HAL	40.0
LTP/FTP longitude	1303953.4230E	VAL	50.0
CRC remainder	7043F61C		

Required additional data


LTP/FTP orthometric height	37.0
----------------------------	------

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJFC / YAKUSHIMA

RNP RWY14



INSTRUMENT APPROACH CHART

RJFC / YAKUSHIMA

RNP RWY14


FAS DATA BLOCK

Operation type	0	LTP/FTP ellipsoidal height	+00638
SBAS service provider identifier	2	FPAP latitude	302246.7970N
Airport identifier	RJFC	FPAP longitude	1303958.6910E
Runway	14	Threshold crossing height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M14A	∠ length offset	0192
LTP/FTP latitude	302324.9135N	HAL	40.0
LTP/FTP longitude	1303912.8885E	VAL	50.0
CRC remainder	A76A627B		

Required additional data

LTP/FTP orthometric height	33.2
----------------------------	------

CHANGE : FAS DATA BLOCK; Required additional data established.



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

NOTE : A/G COM from Kagoshima FSC is blinded between 180° and 300° from Yakushima VOR/DME (YKE).

Call sign	BRG / DIST from ARP	Remarks
10NM N	000°T / 10.0NM	海上 Over the sea
10NM NE	045°T / 10.0NM	海上 Over the sea
宮之浦 Miyanouura	302°T / 5.0NM	港 Harbor
10NM SE	135°T / 10.0NM	海上 Over the sea
10NM S	180°T / 10.0NM	海上 Over the sea

CHANGE : VAR.

RJFC / YAKUSHIMA

Minimum Vectoring Altitude CHART

