RJNA / NAGOYA

AD CHART

CHANGE: CEILOMETER, RVR relocated. WIND SPEED METER added.

MARKING AIDS



NAGOYA AD
ELEV 14m(45.9ft)



RJNA / NAGOYA

AIRCRAFT PARKING CHART



CHANGE: Spot 13A,14 installed

STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA SID and TRANSITION

IBUKI FOUR DEPARTURE

RWY16 : Climb RWY HDG to KCC 3.5DME, turn right HDG004˚...
RWY34 : Climb RWY HDG to 700FT, turn left within 4NM from RWY end/KCC 4.0DME,...
...to intercept and proceed via KCC R319 to IBUKI.
Cross IBUKI at or above 11000FT.

Note RWY16 : 5.0% climb gradient required up to 700FT.
OBST ALT 551FT located at 1.9NM 215˚ FM end of RWY16.
RWY34 : 5.0% climb gradient required up to 700FT.

ADGUN TRANSITION

From over IBUKI, via KCC 29.5DME counterclockwise ARC to intercept and proceed via KCC R262 to ADGUN.
Note : This TRANSITION is for TACAN equipped aircraft only.

OHNNO TRANSITION

From over IBUKI, via KCC 29.5DME clockwise ARC to intercept and proceed via KCC R348 to OHNNO.
Cross KCC R336 at or above FL150.
Note : This TRANSITION is for TACAN equipped aircraft only.

CHANGE : ADGUN TRANSITION, OHNNO TRANSITION established. OTSU TRANSITION, KOMATSU TRANSITION abolished.



STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA — RNAV TRANSITION

MIDER TRANSITION	RNAV1

NOTE 1) DME/DME/IRU or GNSS required. 2) RADAR service required.	Critical DME	–
	DME GAP	–
	Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

VAR 8°W(2020)



MIDER TRANSITION

From IBUKI at or above 11000FT, to MIDER.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	IBUKI	-	-	-7.9	-	-	+11000	-	-	RNAV1
002	TF	MIDER	-	230 (222.4)	-7.9	46.2	-	-	-	-	RNAV1

CHANGE : FIX symbol(IBUKI, MIDER).

STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA — RNAV TRANSITION

KOMAZ TRANSITION		RNAV1
NOTE 1) DME/DME/IRU or GNSS required. 2) RADAR service required.	Critical DME	–
	DME GAP	–
	Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1



KOMAZ TRANSITION

From IBUKI at or above 11000FT, to HACHI at or above FL150, to KMC.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	IBUKI	-	-	-7.9	-	-	+11000	-	-	RNAV1
002	TF	HACHI	-	050 (042.4)	-7.9	16.1	-	+FL150	-	-	RNAV1
003	TF	KMC	-	348 (339.9)	-7.9	39.1	-	-	-	-	RNAV1

CHANGE : FIX symbol(HACHI, IBUKI).

STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA SID

HOUBA FOUR DEPARTURE

RWY16 : Climb RWY HDG to 600FT, turn left HDG349˚...

RWY34 : Climb RWY HDG to 700FT, turn right within 4NM from RWY end/ KCC 4.0DME, via HDG079˚...
...to intercept and proceed via KCC R034 to HOUBA.
Cross HOUBA at or above 8000FT.

Note RWY16 : 5.0% climb gradient required up to 600FT.
RWY34 : 5.0% climb gradient required up to 700FT.

HOUBA FOUR DEPARTURE



STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA TRANSITION

KROBE TRANSITION

From over HOUBA, via KCC R034 to KROBE via STRAW.
Cross STRAW at or above FL200.

NIIGATA TRANSITION

From over HOUBA, via KCC R034 to KROBE via STRAW, via GTC R227 to GTC VORTAC.
Cross STRAW at or above FL200.



STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA SID

MORIZ FIVE DEPARTURE

RWY16 : Climb RWY HDG to 600FT, turn left,...

RWY34 : Climb RWY HDG to 700FT, turn right within 4NM from RWY end/KCC 4.0DME, via HDG182˚ to intercept and proceed...
...via KCC R137 to MORIZ.
(Cross KCC R137/10.0DME at or above 5000FT when using KCC TACAN only.)
Cross MORIZ at or above 7000FT.

Note RWY16 : 5.0% climb gradient required up to 600FT.
RWY34 : 5.0% climb gradient required up to 700FT.



STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA TRANSITION

HAMAMATSU TRANSITION

From over MORIZ, via LHT R315 to LHT TACAN.

CHAUS TRANSITION

From over MORIZ, via CBE R067 to CHAUS via TSUGU.
Cross CHAUS at or above FL150.



STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA TRANSITION

ALPUS TRANSITION

From over MORIZ, via CBE R067 to MUGEN via TSUGU, via KCC R088 to ALPUS.

Cross MUGEN at or above FL150.



STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA TRANSITION

SHIMA TRANSITION

From over MORIZ, via CBE 23.9DME clockwise ARC to intercept and proceed via CBE R205 to SHIMA.



STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA SID

NAGOYA EAST REVERSAL ONE DEPARTURE

RWY16 : Climb RWY HDG to 600FT, turn left, direct to KCC VORTAC.
Cross KCC VORTAC at or above 3000FT.

RWY34 : Climb RWY HDG to 700FT, turn right within 4NM from RWY end/KCC 4.0DME, direct to KCC VORTAC.
Cross KCC VORTAC at or above 3000FT.

Note RWY16 : 5.0% climb gradient required up to 600FT.
RWY34 : 5.0% climb gradient required up to 700FT.

NAGOYA EAST REVERSAL ONE DEPARTURE



STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA SID

NAGOYA WEST REVERSAL ONE DEPARTURE

RWY16 : Climb RWY HDG to KCC 3.5DME, turn right, direct to KCC VORTAC.
Cross KCC VORTAC at or above 3000FT.

RWY34 : Climb RWY HDG to 700FT, turn left within 4NM from RWY end/KCC 4.0DME, direct to KCC VORTAC.
Cross KCC VORTAC at or above 3000FT.

Note RWY16 : 5.0% climb gradient required up to 700FT.
OBST ALT 551FT located at 1.9NM 215˚ FM end of RWY16.
RWY34 : 5.0% climb gradient required up to 700FT.

NAGOYA WEST REVERSAL ONE DEPARTURE



STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA SID

TALMI FOUR DEPARTURE

RWY16 : Climb RWY HDG to KCC 3.5DME, turn right HDG004˚...

RWY34 : Climb RWY HDG to 700FT, turn left within 4NM from RWY end/KCC 4.0DME,...

...to intercept and proceed via KCC R319 to TALMI.

Cross TALMI at or above 7000FT.

Note RWY16 : 5.0% climb gradient required up to 700FT.
OBST ALT 551FT located at 1.9NM 215˚ FM end of RWY16.

RWY34 : 5.0% climb gradient required up to 700FT.

TALMI FOUR DEPARTURE



STANDARD DEPARTURE CHART -INSTRUMENT

RJNA / NAGOYA — RNAV TRANSITION

PIONE TRANSITION / WAKIT TRANSITION / KAMMY TRANSITION	RNAV 1

Note 1) DME/DME/IRU or GNSS required. 2) RADAR service required.	Critical DME	TZT : 10.0NM to PIONE - PIONE
	DME GAP	–
	Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1



PIONE TRANSITION

From TALMI at or above 7000FT, to HEIAN, to WAKIT, to PIONE.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	TALMI	—	—	-7.3	—	—	+7000	—	—	RNAV1
002	TF	HEIAN	—	268 (260.2)	-7.3	42.8	—	—	—	—	RNAV1
003	TF	WAKIT	—	253 (245.6)	-7.3	45.2	—	—	—	—	RNAV1
004	TF	PIONE	—	252 (244.4)	-7.3	49.8	—	—	—	—	RNAV1

WAKIT TRANSITION

From TALMI at or above 7000FT, to HEIAN, to WAKIT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	TALMI	—	—	-7.3	—	—	+7000	—	—	RNAV1
002	TF	HEIAN	—	268 (260.2)	-7.3	42.8	—	—	—	—	RNAV1
003	TF	WAKIT	—	253 (245.6)	-7.3	45.2	—	—	—	—	RNAV1

KAMMY TRANSITION

From TALMI at or above 7000FT, to HEIAN, to KAMMY.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	TALMI	—	—	-7.3	—	—	+7000	—	—	RNAV1
002	TF	HEIAN	—	268 (260.2)	-7.3	42.8	—	—	—	—	RNAV1
003	TF	KAMMY	—	255 (248.3)	-7.3	56.8	—	—	—	—	RNAV1

CHANGE : FIX symbol(TALMI).

INTENTIONALLY LEFT BLANK

STANDARD ARRIVAL CHART -INSTRUMENT

RJNA / NAGOYA STAR

EXPOH NORTH ARRIVAL

From over SWING, via KCC 18.4DME clockwise ARC to intercept and proceed via KCC R159 to EXPOH.

Cross KCC R151 at or above 3900FT, cross EXPOH at or above 2500FT.

EXPOH SOUTH ARRIVAL

From over SHIMA, via CBE R205, via CBE 24.0DME counterclockwise ARC to intercept and proceed via KCC R159 to EXPOH.

Cross KCC R159/23.0DME at or above 5000FT, cross EXPOH at or above 2500FT.



STANDARD ARRIVAL CHART -INSTRUMENT

RJNA / NAGOYA — RNAV STAR

ORIBE EAST ARRIVAL
SHINO ARRIVAL

RNAV1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.



ORIBE EAST ARRIVAL

From MAMLA, at or above 9000FT, to SIMON at or above 7000FT, to ORIBE at or above 6000FT.

Critical DME	GFT : 5.0NM to SIMON - 4.0NM to ORIBE YME : 4.0NM to ORIBE - ORIBE
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	MAMLA	–	–	-7.7	–	–	+9000	–	–	RNAV1
002	TF	SIMON	–	278 (270.4)	-7.7	6.6	–	+7000	–	–	RNAV1
003	TF	ORIBE	–	278 (270.3)	-7.7	17.9	–	+6000	–	–	RNAV1

SHINO ARRIVAL

From ADGUN, to DOZAN at or above 7000FT, to SHINO at or above 5100FT.

Critical DME	–
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	ADGUN	–	–	-7.7	–	–	–	–	–	RNAV1
002	TF	DOZAN	–	062 (054.0)	-7.7	24.5	–	+7000	–	–	RNAV1
003	TF	SHINO	–	062 (054.2)	-7.7	14.6	–	+5100	–	–	RNAV1

CHANGE : FIX symbol(ADGUN, MAMLA, SHINO).

STANDARD ARRIVAL CHART -INSTRUMENT

RJNA / NAGOYA — RNAV STAR

ORIBE SOUTH ARRIVAL — RNAV1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.



ORIBE SOUTH ARRIVAL

From SHIMA, to KOHWA at or above 8000FT, to RYUDO, to GRIPP, to ORIBE at or above 6000FT.

Critical DME	GFT : 11.0NM to ORIBE - 6.0NM to ORIBE YME : 2.0NM to ORIBE - ORIBE
DME GAP	3.0NM to ORIBE - 2.0NM to ORIBE
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SHIMA	–	–	-7.9	–	–	–	–	–	RNAV1
002	TF	KOHWA	–	045 (037.1)	-7.9	30.2	–	+8000	–	–	RNAV1
003	TF	RYUDO	–	018 (010.1)	-7.9	20.5	–	–	–	–	RNAV1
004	TF	GRIPP	–	018 (010.2)	-7.9	20.5	–	–	–	–	RNAV1
005	TF	ORIBE	–	327 (319.2)	-7.9	15.0	–	+6000	–	–	RNAV1

CHANGE : Description of HLDG(RYUDO).

INSTRUMENT APPROACH CHART

RJNA / NAGOYA — ILS Z or LOC Z RWY34

CENTRAIR APP	ILS – LOC	NAGOYA TOWER	RADAR AVBL
121.05 – 119.175 228.4 – 245.3	108.9 IKC ILS–GP 329.3 ILS–DME CH–26X	118.7 - 122.7 236.8 - 305.7	CALL CENTRAIR RADAR



DOALA(FAF) : *350944.64N/1365900.87E*

NM to IKC	MAPt	2	3	4	5	FAF
ALT (3.0˚ APCH Path)	–	677	996	1314	1633	1867

MISSED APPROACH

Climb to 500FT on HDG341˚, turn left HDG185˚ to intercept and proceed via KCC R230 to KCC 6.0DME, turn left, direct to KCC VORTAC and hold at 3000FT. Contact CENTRAIR APP.

No turn before IKC 0.6DME.
Timing not authorized for defining the MAPt.



DME to IKC	0.2	0.6	1.5	3.0	5.7	9.6
NM to THR	0	0.5	1.3	2.8	5.6	9.4

Missed APCH climb gradient MNM 4.0%

MINIMA THR elev. 50 AD elev. 46

CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	250 (200)	700	490 (444)	1200	650 (604)	1600
B				1300		
C				1400	850 (804)	2400
D				1600		3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : VAR. Course on Final. HDG after MAPt. DME to IKC.

INSTRUMENT APPROACH CHART

RJNA / NAGOYA — ILS Y or LOC Y RWY34

CENTRAIR APP	ILS – LOC	NAGOYA TOWER	RADAR AVBL
121.05 – 119.175 228.4 – 245.3	108.9 IKC ILS–GP 329.3 ILS–DME CH–26X	118.7 - 122.7 236.8 - 305.7	CALL CENTRAIR RADAR



DOALA(FAF) : *350944.64N/1365900.87E*

NM to IKC	MAPt	2	3	4	5	FAF
ALT (3.0˚ APCH Path)	–	677	996	1314	1633	1867

MISSED APPROACH

Climb to 500FT on HDG341˚, turn left HDG185˚ to intercept and proceed via KCC R230 to KCC 6.0DME, turn left, direct to KCC VORTAC and hold at 3000FT. Contact CENTRAIR APP.

No turn before IKC 0.6DME.
Timing not authorized for defining the MAPt.



DME to IKC	0.2	0.6	1.5	3.0	5.7
NM to THR	0	0.5	1.3	2.8	5.6

Missed APCH climb gradient MNM 4.0%

MINIMA THR elev. 50 AD elev. 46

CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	250 (200)	700	490 (444)	1200	650 (604)	1600
B				1300		
C				1400	850 (804)	2400
D				1600		3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : VAR. Course on Final. HDG after MAPt. DME to IKC.

INSTRUMENT APPROACH CHART

RJNA / NAGOYA — VOR RWY34

CENTRAIR APP	NAGOYA VORTAC	NAGOYA TOWER	RADAR AVBL
121.05 – 119.175 228.4 – 245.3	114.2 KCC CH-89X *35°15´55´´N/136°54´54´´E*	118.7 - 122.7 236.8 - 305.7	CALL CENTRAIR RADAR



NM to KCC	MAPt	3	4	5	6	FAF
ALT (3.0° APCH Path)	–	584	902	1221	1539	1698

EMITT(FAF) : *351020.74N/1365900.12E*

MISSED APPROACH

Turn left HDG185° to intercept and proceed via KCC R230 to KCC 6.0DME, turn left, direct to KCC VORTAC and hold at 3000FT. Contact CENTRAIR APP.



No turn before MAPt.
Timing not authorized for defining the MAPt.

DME to KCC	1.5	2.8	4.0	6.5
NM to THR	0	1.3	2.5	5.0

MINIMA THR elev. 50 AD elev. 46

CAT			CIRCLING	
	MDA(H)	RVR/CMV	MDA(H)	VIS
A	490 (444)	1200	650 (604)	1600
B		1300		
C		1400	850 (804)	2400
D		1600		3200

INSTRUMENT APPROACH CHART

RJNA / NAGOYA — VOR A

CENTRAIR APP	NAGOYA VORTAC	NAGOYA TOWER	RADAR AVBL
121.05 – 119.175 228.4 – 245.3	114.2 KCC CH-89X *35°15′55″ N/136°54′54″E*	118.7 - 122.7 236.8 - 305.7	CALL CENTRAIR RADAR





MISSED APPROACH

Turn right HDG275° to intercept and proceed via KCC R230 to KCC 6.0DME, turn left, direct to KCC VORTAC and hold at 3000FT. Contact CENTRAIR APP.

Timing not authorized for defining the MAPt.

MINIMA		AD elev. 46
CAT	CIRCLING	
	MDA(H)	VIS
A	650 (604)	1600
B		
C		2400
D	690 (644)	3200

Circling to EAST side of RWY only.

INSTRUMENT APPROACH CHART

RJNA / NAGOYA — TACAN A

CENTRAIR APP	NAGOYA VORTAC	NAGOYA TOWER	RADAR AVBL
121.05 – 119.175 228.4 – 245.3	114.2 KCC CH-89X *35°15´55´´ N/136°54´54´´E*	118.7 - 122.7 236.8 - 305.7	CALL CENTRAIR RADAR



RAIKO(FAF) : *352115.95N/1365133.33E*

MISSED APPROACH

Turn left, climb to 4100FT via KCC R131, turn left, via KCC 15.0DME counterclockwise ARC, turn left, via KCC R091 to SHATI and hold.
Contact CENTRAIR APP.

Timing not authorized for defining the MAPt.



MINIMA — AD elev. 46

CAT	CIRCLING	
	MDA(H)	VIS
A	650 (604)	1600
B		
C		2400
D	690 (644)	3200

Circling to EAST side of RWY only.

INSTRUMENT APPROACH CHART

RJNA / NAGOYA — RNP RWY16

CENTRAIR APP	RNP APCH	NAGOYA TOWER	RADAR AVBL
121.05 - 119.175 228.4 - 245.3		118.7 - 122.7 236.8 - 305.7	CALL CENTRAIR RADAR



DIMAC (IAF)	353219.05N 1364437.80E
ORIBE (IAF)	353352.67N 1365417.12E
SHINO (IAF)	352634.71N 1364000.46E
MONET (IF)	352921.80N 1364631.05E
AQTOH (FAF)	352116.73N 1365140.19E
RW16 (MAPt)	351559.16N 1365502.69E
NA651 (MATF)	351131.35N 1364953.92E
KCC (MAHF)	351554.96N 1365453.73E

NM to Next Fix	FAF	5	4	3	2	MAPt
ALT (3.0° APCH Path)	2000	1693	1375	1057	738	-



MISSED APPROACH

Turn right direct to NA651, turn left, direct to KCC and hold at 3000FT.
Contact CENTRAIR APP.
(For using VORTAC)
Turn right HDG275° to intercept and proceed via KCC R230 to KCC 6.0DME, turn left direct to KCC VORTAC and hold at 3000FT.
Contact CENTRAIR APP.

MINIMA — THR elev. 52 — AD elev. 46

CAT	LNAV/VNAV		LNAV		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	610 (558)	1400	610 (564)	1400	650 (604)	1600
B		1500		1500		
C		1600		1600		2400
D		1800		1800	690 (644)	3200

Circling to EAST side of RWY only.

CHANGE:PROC renamed. Requirement for RNP.

RJNA / NAGOYA

Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

Call sign	BRG / DIST from ARP	Remarks
高蔵寺ステーション Kozoji Station	085°T / 5.9NM	JR高蔵寺駅 Station
入鹿 Iruka	035°T / 6.4NM	池 Pond
一宮ステーション Ichinomiya Station	294°T / 6.8NM	JR尾張一宮駅 Station
稲沢ステーション Inazawa Station	269°T / 5.1NM	JR稲沢駅 Station
万場大橋 Manba Bridge	216°T / 7.3NM	庄内川と名古屋高速道路5号万場線との交点 Bridge
*名古屋インターチェンジ *Nagoya Interchange	136°T / 7.0NM	東名高速道路のインターチェンジ Interchange
*瑞穂グラウンド *Mizuho Ground	173°T / 8.0NM	総合陸上競技場 Ground

注：＊は特別管制空域に係る飛行の許可及び指示を受けるため、また、その他必要に応じて当該空域に係る位置通報等に供される目視位置通報点である。

Note：The asterisk (*) indicates the visual reporting point where a pilot is to request ATC clearance regarding to PCA and to make position report as required.

CHANGE : Map updated. BRG/DIST from ARP.


RJNA / NAGOYA
LDG CHART
ELEV 46ft
PAPI ANGLE 3.0
MEHT 19.5m(64ft)
437m FM THR
VAR 7°W
2006
VORTAC
NAGOYA
114.2 KCC
CH-89X
35°15′55″N/136°54′54″E
TWR
118.7-122.7
236.8-305.7
RVR
8990×150ft
Asph-Conc
ABN
RVR
PAPI ANGLE 3.0
MEHT 20.5m(67ft)
419m FM THR
552
BUILDING
(See page
AD2-16)
ELEVATIONS AND
HEIGHTS IN FEET
MEAN SEA LEVEL
SCALE
1000 0 1000 3000 ft
500 0 1000 2000 m
NAGOYA
STATION
CHANGE : OBST
18′
16′
14′
35°12′
53′
55′
57′
136°59′

RJNA / NAGOYA

Minimum Vectoring Altitude CHART

VAR 7˚W (2009)



① 2000
② 3000
③ 4000
④ 5000

(1) *343821N/1371935E*
(2) *342638N/1370237E*
(3) *342240N/1370744E*
(4) *341804N/1370143E*
(5) *340628N/1364640E*
(6) *341414N/1362958E*
(7) *343322N/1362638E*
(8) *343442N/1363458E*
(9) *344656N/1363203E*
(10) *344507N/1362348E*

CENTER : *345129N/1364811E* (C : CBE)
CENTER : *351555N/1365454E* (K : KCC)
✳1 : *343722N/1365140E*
✳2 : *343140N/1364148E*

CHANGE : AKENO NDB(AK) abolished.