AD 2 AERODROMES

RJSR AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJSR - ODATE-NOSHIRO

RJSR AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	401131N/1402218E 109°/1.0km from RWY11 THR
2	Direction and distance from (city)	8.3NM W FM OODATE City
3	Elevation/ Reference temperature	276ft /31°C (1997-2008)
4	Geoid undulation at AD ELEV PSN	126ft
5	MAG VAR/ Annual change	8°W(2006) / 1'E
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	Odate-Noshiro Airport Administration Office (Akita prefectural government) 21-144,Wakigami-aza,karamushi-tai,kita-Akita City,AKITA,018-3454 JAPAN. TEL:0186-63-1001 FAX:0186-63-1009 E-mail:oodatenoshirokuukoujimusho@pref.akita.lg.jp
7	Types of traffic permitted (IFR/VFR)	IFR/VFR
8	Remarks	Nil

RJSR AD 2.3 OPERATIONAL HOURS

1	AD Administration	2300 - 1030
2	Customs and immigration	On request Customs: 018-845-0735 Immigration: 018-895-5221
3	Health and sanitation	Quarantine(human): On request(018-846-8280) Quarantine(animal, plant): Nil
4	AIS Briefing Office	Nil
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	H24(SENDAI)
7	ATS	2300 - 1030 Remarks: Airport Remote Mobile Communication Service provided by Sendai FSC
8	Fuelling	2300 - 0930
9	Handling	2240 - 0900
10	Security	2300 - 1030
11	De-icing	Nil
12	Remarks	Nil

RJSR AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	AVBL up to B767 passenger plane
2	Fuel/ oil types	JET A1
3	Fuelling facilities/ capacity	Fuel truck /200kl
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

RJSR AD 2.5 PASSENGER FACILITIES

1	Hotels	Nil
2	Restaurants	At Airport
3	Transportation	Bus,Taxi
4	Medical facilities	Nil
5	Bank and Post Office	Nil
6	Tourist Office	Nil
7	Remarks	Nil

RJSR AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT 7
2	Rescue equipment	Chemical fire fighting truck x 2 Emergency medical equipments conveyance truck x 1
3	Capability for removal of disabled aircraft	Ask AD administration
4	Remarks	Nil

RJSR AD 2.7 SEASONAL AVAILABILITY-CLEARING

1	Types of clearing equipment	Snow plow x 4, Snow sweeper x 4, rotary x 4, spreader equipment x 1
2	Clearance priorities	RWY, TWY, APRON
3	Remarks	Nil

RJSR AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

Apron surface and strength Surface: Concrete Strength: PCN 55/R/B/X/T Taxiway width, surface and Surface: asphalt-Concrete strength Strength: PCN 75/F/C/X/T 3 ACL and elevation Not available Not available 4 VOR checkpoints 5 INS checkpoints (Spot NR) 1 401142.42N,1402218.33E 2 401142.04N,1402220.50E 3 401141.71N,1402223.00E 5 401141.37N,1402225.50E 6 Nil Remarks

RJSR AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and Visual dock- ing/ parking guidance system of aircraft stands	Nil
2	RWY and TWY markings and LGT	RWY:RWY 11/29 (Marking): RWY designation, RWY CL, RWY THR, RWY middle point, Aiming point, TDZ, RWY side stripe, RWY turn pad edge, RWY turn pad CL (LGT): RCLL, REDL, RTHL, RENL, RTZL(RWY11), WBAR, Turning point indicator LGT, RWY DIST marker LGT TWY: (Marking):TWY CL, RWY HLDG PSN, TWY side stripe (LGT):TWY edge LGT, TWY CL LGT, Taxiing guidance sign
3	Stop bars	Nil
4	Remarks	(Marking):Overrun area (LGT):Apron flood LGT

RJSR / ODATE-NOSHIRO

180° Turn on RWY


B767 型機用の滑走路 180° 転回実施要領


- 1. 滑走路中心線からターニングパッド中心線標識に従って進行する。
- 2. 転回灯 1 が一直線に見えるように進行し、転回灯 2 が一直線に見えたとき転回 を開始する。転回時は MAX STEERING ANGLE を使用する。

180° turn procedure on RWY for B767 aircraft

- Proceed along the RWY Center Line to the starting point of the RWY Turn Pad Center Line Marking; then
- 2. Proceed along the RWY Turn Pad Center Line Marking to see the Turning Point Indicator Light 1 on a straight line, then commence turn at the spot where you (pilot)can see the Turning Point Indicator Light 2 on a straight line at an angle of 9 o'clock. When turning, take MAX STEERING ANGLE.

ODATE-NOSHIRO AP





RJSR AD 2.10 AERODROME OBSTACLES

- In Area2 See Obstacle data
- In Area3 To be developed

RJSR AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	SENDAI
2	Hours of service	H24(SENDAI)
	MET Office outside hours	
3	Office responsible for TAF preparation	Nil
	Periods of validity	
4	Trend forecast	Nil
	Interval of issuance	
5	Briefing/ consultation provided	Briefing is available upon inquiry at SENDAI
6	Flight documentation	С
	Language(s) used	En
7	Charts and other information available	S ₆ , U ₈₅ , U ₇ , U ₅ , U ₃ , U ₂₅ , U ₂ /T _r , P _s , P ₅ , P ₃ , P ₂₅ , P _{SWE} , P _{SWF} , P _{SWG} ,
	for briefing or consultation	P _{SWI} , P _{SWM} , P _{SW} (domestic), E, C, W _E , W _F , W _G , W _I , W, N
8	Supplementary equipment	Nil
	available for providing information	
9	ATS units provided with information	REMOTE
10	Additional information(limitation of	Nil
	service, etc.)	

RJSR AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR TRUE BRG		Dimensions of RWY(M)	Strength(PCN) and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY	
1	2	3	4	4 5		
11	100.30°	2000×45	PCN 401136.37N 75/F/C/X/T 1402135.51E Asphalt-Concrete 125.7FT		THR ELEV:259.2FT TDZ ELEV:269FT	
29 280.30°		2000×45	PCN 75/F/C/X/T Asphalt-Concrete	401125.10N 1402258.78E 126FT	THR ELEV:292.0FT	
Slope o	of RWY	Strip Dimensions(M)	RESA (Overrun) Dimensions (M)		Remarks	
7	7	10	11		14	
See below figure		2120×300	190×(MNM:149 MAX:297)*		RWY Grooving : 2000×45m	
		2120×300	40×(MNN *For detail, ask			
		LONGI	ΓUDINAL PROFILE	OF RUNWAY		
RWY 11					RWY 29	
259.18ft					291.99ft	
•			0.5%		•	
<u>⊢</u> 0m	ı				2000m	

RJSR AD 2.13 DECLARED DISTANCES

	TORA	TODA	ASDA	LDA	
RWY Designator	(m)	(m)	(m)	(m)	Remarks
1	2	3	4	5	6
11	2000	2000	2000	2000	Nil
29	2000	2000	2000	2000	Nil

RJSR AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
11	PALS (CAT I) 900m LIH	Green Green	PAPI 3.0°/Left 347.2m 61ft	900m	2000m 30m Coded color (White/Red) LIH	2000m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)
29	SALS (*1) 420m LIH	Green Nil	PAPI 3.0°/Left 414.9m 61ft	Nil	2000m 30m Coded color (White/Red) LIH	2000m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)
				Remarks				
				10				
SALS with APCH LGT beacon(570m and 900m FM RWY 29 THR)(*1) Overrun area edge LGT(LEN:60m Color:Red) (*2) CGL for RWY 29 only								

RJSR AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and	ABN: 401148N/1402216E, White/Green EV4.3sec, HO
	hours of operation	
2	LDI location and LGT Anemometer location and LGT	LDI:Nil Anemometer: RWY11:300m from RWY11 THR. LGTD RWY29:300m from RWY29 THR. LGTD
3	TWY edge and centerline lighting	TWY edge and center line lights installed, see AD 2.9
4	Secondary power supply/ switch-over time	Within 15sec : ALL LGT
5	Remarks	WDILGT

RJSR AD 2.16 HELICOPTER LANDING AREA

Nil	

RJSR AD 2.17 ATS AIRSPACE


	Designation and lateral limits	Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
	1	2	3	4	6
Odate Noshiro information zone	Area within a radius of 9km(5NM) of Odate-Noshiro ARP.	3,000 or below	E	Odate Remote En	

RJSR AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
A/G	Odate Remote	118.75MHz	2300 - 1030	RAG Controlled by Sendai FSC

RJSR AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid (VOR declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
VOR (9°W/2015)	ODE	114.75MHz	2300 - 1030	401154.03N/ 1402142.68E		VOR unusable: 010°-020° beyond 35nm BLW 8000ft. 100°-110° beyond 35nm BLW 6000ft. 110°-130° beyond 35nm BLW 9000ft. 150°-160° beyond 30nm BLW 8000ft. 320°-340° beyond 35nm BLW 6000ft. 340°-350° beyond 25nm BLW 6000ft. 350°-360° beyond 35nm BLW 8000ft.
DME	ODE	1055MHz (CH-94Y)	2300 - 1030	401154.03N/ 1402142.68E	308ft	DME unusable: 100°-110° beyond 35nm BLW 6000ft. 110°-130° beyond 35nm BLW 9000ft. 150°-160° beyond 30nm BLW 8000ft. 320°-340° beyond 35nm BLW 6000ft. 340°-350° beyond 35nm BLW 6000ft. 350°-360° beyond 35nm BLW 8000ft.
ILS-LOC 11	IOD	110.15MHz	2300 - 1030	401123.77N/ 1402308.57E		LOC:235m(771ft) away FM RWY 29 THR, BRG(MAG)110°.
ILS-GP 11	-	334.25MHz	2300 - 1030	401130.74N/ 1402146.51E		GP:287m(942ft) inside FM RWY 11 THR. 125m(410ft) S of RCL. HGT of ILS REF datum 16.5m (54ft). GP angle 3.0°.
ILS-DME 11	IOD	1125MHz	2300 - 1030	401130.42N/ 1402146.43E	278ft	DME:287m(942ft) inside FM RWY 11 THR. 135m(443ft) S of RCL.



1. Ai	RJSR AD 2.20 LOCAL TRAFFIC REGULATIONS 1. Airport regulations						
	Nil						
2. Ta	axiing to and from stands						
	Nil						
3. Pa	arking area for small aircraft(General aviation)						
	Nil						
4. Pa	arking area for helicopters						
	Nil						
5. Ap	oron - taxiing during winter conditions						
	Nil						
6. Ta	uxiing - limitations						
	Nil						
7. Sc	chool and training flights - technical test flights - use of runways						
	Nil						
8. He	elicopter traffic - limitation						
	Nil						

AIP Japan ODATE-NOSHIRO

9. Removal of disabled aircraft from runways

Nil

RJSR AD 2.21 NOISE ABATEMENT PROCEDURES

Nil

RJSR AD 2.22 FLIGHT PROCEDURES

1.TAKE OFF MINIMA

	RWY	ACFT REDL & RCLL		& RCLL		or RCLL Marking	NIL (DAYTIME ONLY)				
		CAI	CEIL-RVR	CEIL-VIS	CEIL-RVR	CEIL-VIS	CEIL-RVR	CEIL-VIS			
Multi-Engine ACFT with	11	A, B, C, D	200′-800m	200′-800m	200′-800m	200′-800m	-	200′-800m			
TKOF ALTN AP FILED	29	A, B, C, D	-	200′-800m	-	200′-800m	-	200′-800m			
OTHER	11	A, B, C, D		AVBL LDG MINIMA							
OTTLER	29	A, B, C, D			AVBL LDG	3 IVIIIVIIVIA					

RJSR AD 2.23 ADDITIONAL INFORMATION

Nil	

RJSR AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome/Heliport Chart

Standard Departure Chart - Instrument (ODATE REVERSAL)

Standard Departure Chart - Instrument (LAGOON)

Standard Arrival Chart - Instrument

Instrument Approach Chart (ILS Z or LOC Z RWY11)

Instrument Approach Chart (ILS Y or LOC Y RWY11)

Instrument Approach Chart (VOR A)


Instrument Approach Chart (RNAV(RNP) Z RWY29)

Instrument Approach Chart (RNAV(RNP) Y RWY29)

Other Chart (Visual REP)

Other Chart (LDG CHART)

Other Chart (MVA CHART)



STANDARD DEPARTURE CHART -INSTRUMENT

RJSR / ODATE-NOSHIRO

SID

ODATE REVERSAL TWO DEPARTURE

RWY11: Climb RWY HDG to 1800FT, turn right HDG332° to intercept and proceed...

RWY29: Climb RWY HDG to ODE 3.0DME,...

...via ODE R287 to 6.0DME, turn left, direct to ODE VOR/DME.


Cross ODE VOR/DME at or above 6000FT.

Note RWY11: 5.0% climb gradient required up to 1800FT.

OBST ALT 1313FT located at 4.3NM 093° FM end of RWY11. OBST ALT 2100FT located at 9.5NM 137° FM end of RWY11.

RWY29: 4.0% climb gradient required up to 700FT.


OBST ALT 656FT located at 2.1NM 276° FM end of RWY29.



STANDARD DEPARTURE CHART -INSTRUMENT

SID RJSR / ODATE-NOSHIRO LAGOON THREE DEPARTURE RWY11: Climb RWY HDG to 1800FT, turn right HDG332° to intercept and proceed... RWY29: Climb RWY HDG to ODE 3.0DME,... ...via ODE R287 to NOSSY, turn left, via UWE R360 to UWE VOR/DME. Cross NOSSY at or above 3000FT. Note RWY11: 5.0% climb gradient required up to 1800FT. OBST ALT 1313FT located at 4.3NM 093° FM end of RWY11. OBST ALT 2100FT located at 9.5NM 137° FM end of RWY11. RWY29: 4.0% climb gradient required up to 700FT. OBST ALT 656FT located at 2.1NM 276° FM end of RWY29. **UWE R360** NOSSY VOR/DME **D9.9 ODE** ODE R₂₈₇ **ODATE** 3000 114.75 ODE CH-94Y = :-D3.0 40°11′54″N/140°21′43″E 287 ODE 300FT R287 (1800 327(51) RWY Α A 332(56) RWY11 and 29: See TAKE OFF MINIMA LAGOON THREE DEPARTURE VOR/DME YUWA \odot 110.65 UWE CH-43Y :--39°37′02″N/140°11′13″E 300FT


STANDARD ARRIVAL CHART - INSTRUMENT




NOSSY ARRIVAL


From BONJI at or above 6000FT, to TEBAR, to NOSSY at or above 4000FT.


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation		Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	BONJI	_	_	-8.8	_	_	+6000	_	_	Basic RNP1
002	TF	TEBAR	_	335 (326.0)	-8.8	10.0	_	_	_	_	Basic RNP1
003	TF	NOSSY	_	357 (347.8)	-8.8	6.0	_	+4000	_	_	Basic RNP1





Circling to SOUTH side of RWY only.





RJSR / ODATE-NOSHIRO

RNAV(RNP) Z RWY29


RNAV(RNP) Z RWY29

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course [°M(°T)]	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	MAGGY	_	_	-8.5	_	_	+6000	_	_	_
002	TF	SR960	_	035 (026.1)	-8.5	8.7	_	+3900	_	_	1.0
003	TF	SR961	_	035 (026.1)	-8.5	2.0	_	3500	_	_	1.0
004	TF	SR962	_	035 (026.1)	-8.5	3.8	_	2296	_	-3.00	0.27 0.30
005	RF Center: SRRF1 r=2.15NM	SR963	_	_	-8.5	4.0	L	1031	_	-3.00	0.27 0.30
006	TF	RW29	Υ	289 (280.1)	-8.5	2.2	_	342	_	-3.00/50	0.27 0.30
007	TF	NOSSY	_	289 (280.3)	-8.5	10.9	_	4000	_	_	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
MAGGY	395456.61N / 1401926.80E	SRRF1	400855.54N / 1402516.24E
SR960	400247.11N / 1402427.29E		
SR961	400434.91N / 1402536.32E		
SR962	400758.60N / 1402746.93E		
SR963	401102.48N / 1402545.54E		
RW29	401125.10N / 1402258.78E		
NOSSY	401321.82N / 1400854.64E		



RJSR / ODATE-NOSHIRO

RNAV(RNP) Y RWY29


RNAV(RNP) Y RWY29

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course [°M(°T)]	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	NOSSY	_	_	-8.5	_	_	+4000	_	_	_
002	TF	SR950	_	086 (077.7)	-8.5	15.2	_	+3500	-185	_	1.0
003	RF Center: SRRF2 r=3.00NM	SR951	_	_	-8.5	4.9	R	3500	_	_	1.0
004	RF Center: SRRF2 r=3.00NM	SR952	_	_	-8.5	5.7	R	1694	_	-3.00	0.27 0.30
005	TF	RW29	Υ	289 (280.1)	-8.5	4.2	_	342	_	-3.00/50	0.27 0.30
006	TF	NOSSY	_	289 (280.3)	-8.5	10.9	_	4000	_	_	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates	
SR950	401634.48N / 1402818.75E	SRRF2	401338.11N / 1402908.01E	
SR951	401403.14N / 1403301.06E			
SR952	401040.53N / 1402826.85E			
RW29	401125.10N / 1402258.78E			
NOSSY	401321.82N / 1400854.64E			



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

5	Call sign	BRG / DIST from ARP	Remarks		
)	樹海ドーム Jyukai Dome	058°T / 11.6NM	大館市白色ドーム White Dome Odate City		
	藤琴 Fujikoto	314°T / 7.2NM	粕毛川 ・ 藤琴川交点 Intersection Kasuge and Fujikoto River		
	鷹巣 Takanosu	357°T / 2.5NM	JR駅北側 North of JR Station		
	能代 Noshiro	272°T / 17.3NM	能代港 Noshiro Harbor		
	米内沢 Yonaizawa	183°T / 4.2NM	内陸線米内沢駅南側米内沢橋 Bridge		
	阿仁 Ani	173°T / 11.6NM	内陸線阿仁合駅 Station		

