

## AD 2 AERODROMES

## RJBK AD 2.1 AERODROME LOCATION INDICATOR AND NAME

## RJBK - KOHNNAN

## RJBK AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	343529N/1335600E
2	Direction and distance from (city)	7.1km S of Okayama city office
3	Elevation/ Reference temperature	0ft / -
4	Geoid undulation at AD ELEV PSN	to be developed
5	MAG VAR/ Annual change	7°W (2000) / 1°W
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	OKAYAMA PREF. PUBLIC AP. Address: Urayasuminami-machi 640, Okayama-shi, Okayama Pref. Tel: 086-262-0954 Fax: 086-262-5220 E-mail: kounan@pref.okayama.lg.jp Web: <a href="http://www.pref.okayama.jp/soshiki/kakuka.html?sec_sec1=182">http://www.pref.okayama.jp/soshiki/kakuka.html?sec_sec1=182</a>
7	Types of traffic permitted(IFR/VFR)	VFR
8	Remarks	Nil

## RJBK AD 2.3 OPERATIONAL HOURS

1	AD Administration	2330 - 0930
2	Customs and immigration	On request Customs: 0863-31-5375 Immigration: 086-234-3531
3	Health and sanitation	Quarantine(human): On request(086-294-5046) Quarantine(animal, plant): Nil
4	AIS Briefing Office	Nil
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	Nil
7	ATS	2330 - 0930 Kohnan Flight Service
8	Fuelling	0030 - 0830 On Request 2330-0030, 0830-0930 Tel/Fax 086-262-1091
9	Handling	Nil
10	Security	Nil
11	De-icing	Nil
12	Remarks	Nil

**RJBK AD 2.4 HANDLING SERVICES AND FACILITIES**

1	Cargo-handling facilities	Nil
2	Fuel/ oil types	100/130, JET A-1
3	Fuelling facilities/ capacity	Fuel Truck refueling
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

**RJBK AD 2.5 PASSENGER FACILITIES**

1	Hotels	Nil
2	Restaurants	Nil
3	Transportation	Busses
4	Medical facilities	Nil
5	Bank and Post Office	Nil
6	Tourist Office	Nil
7	Remarks	Nil

**RJBK AD 2.6 RESCUE AND FIRE FIGHTING SERVICES**

1	AD category for fire fighting	CAT 3
2	Rescue equipment	Chemical fire fighting truck x 1
3	Capability for removal of disabled aircraft	Ask AD administration
4	Remarks	Nil

**RJBK AD 2.7 SEASONAL AVAILABILITY-CLEARING**

1	Types of clearing equipment	Not applicable
2	Clearance priorities	Ask AD administration
3	Remarks	Nil

**RJBK AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA**

1	Apron surface and strength	Surface : Asphalt-concrete Strength : Apron-1 AUW/5700kg/0.28MPa Apron-2 PCN14/F/D/X/T Apron-3 AUW/5700kg/0.28MPa Apron-4 AUW/11000kg/0.28MPa Apron-5 AUW/4000kg Apron-6 AUW/4000kg
2	Taxiway width, surface and strength	Width: 18m Strength:T1,T3,T4,P1,P2,P3 AUW/5700kg/0.28MPa T2 PCN14/F/D/X/T
3	ACL and elevation	Not available
4	VOR checkpoints	Nil
5	INS checkpoints	Nil
6	Remarks	Nil

**RJBK AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS**

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	Nil
2	RWY and TWY markings and LGT	RWY:09/27 (Marking) RWY designation, RWY CL, RWY middle point, Aiming point, TDZ, RWY side stripe (LGT) REDL, RTHL, RENL  TWY: (Marking) TWY CL, RWY HLDG PSN, TWY side stripe (LGT) TWY edge LGT, Taxiing guidance sign
3	Stop bars	Nil
4	Remarks	(Marking) Apron TWY CL (LGT) Apron flood LGT

**RJBK AD 2.10 AERODROME OBSTACLES**

- In Area2 See Obstacle data
- In Area3 To be developed

**RJBK AD 2.11 METEOROLOGICAL INFORMATION PROVIDED**

1	Associated MET Office	Nil
2	Hours of service MET Office outside hours	Nil
3	Office responsible for TAF preparation Periods of validity	Nil
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Nil
6	Flight documentation Language(s) used	Nil
7	Charts and other information available for briefing or consultation	Nil
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	Nil
10	Additional information (limitation of service, etc.)	Nil

**RJBK AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS**

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN) and Surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
09	085.50°	1200×30	PCN 14/F/D/X/T Asphalt	to be developed	THR ELEV:-1ft
27	265.50°	1200×30	PCN 14/F/D/X/T Asphalt		THR ELEV:2ft
Slope of RWY	Strip Dimensions(M)		RESA (Overrun) Dimensions (M)		Remarks
7	10		11		14
See AD chart	1320×120		3x(MNM:117 MAX:120)*		RWY Grooving : 1200m × 20m
See AD chart	1320×120		40×120 *For detail, ask airport administrator		RWY Grooving : 1200m × 20m

## RJBK AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
09	1200	1200	1200	1200	Nil
27	1200	1200	1200	1200	Nil

## RJBK AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
09	Nil	Green -	PAPI 3.5°/LEFT 230m 45ft	Nil	Nil	1200m 60m Coded color (White/Yellow) LIH	Red -	Nil (*1)
27	Nil	Green -	PAPI 3.5°/LEFT 247m 45ft	Nil	Nil	1200m 60m Coded color (White/Yellow) LIH	Red -	Nil (*1)
Remarks								
10								
Overrun area edge LGT(LEN:60m Color:Red)(*1) RWY THR ID LGT for RWY 09/27 THR (Color: White)								

## RJBK AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	ABN: 343536N1335556E, White/Green EV4.3sec, HO
2	LDI location and LGT Anemometer location and LGT	LDI: Nil Anemometer : 470m WNW from RWY 27 THR, LGTD
3	TWY edge and centerline lighting	TWY edge LGT: Blue TWY CL LGT: Nil
4	Secondary power supply/ switch-over time	All lights within 15 seconds
5	Remarks	WDI LGT

## RJBK AD 2.16 HELICOPTER LANDING AREA

Nil
-----

**RJBK AD 2.17 ATS AIRSPACE**

Designation and lateral limits	Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1	2	3	4	6
Nil				

**RJBK AD 2.18 ATS COMMUNICATION FACILITIES**

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
A/G	KOHANAN FLIGHT SERVICE	130.75MHz	2330 - 0930	Nil

**RJBK AD 2.19 RADIO NAVIGATION AND LANDING AIDS**

Type of aid	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
Nil						

**RJBK AD 2.20 LOCAL TRAFFIC REGULATIONS**

## 1. Airport regulations

PPR For use.TEL 086-262-1954

## 2. Taxiing to and from stands

Nil

## 3. Parking area for small aircraft(General aviation)

Nil

## 4. Parking area for helicopters

Nil

## 5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

Nil
-----

7. School and training flights - technical test flights - use of runways

Nil
-----

8. Helicopter traffic - limitation

Nil
-----

9. Removal of disabled aircraft from runways

Nil
-----

**RJBK AD 2.21 NOISE ABATEMENT PROCEDURES**

See Kohnan Standard traffic pattern and recommended departure/arrival routes
--

**RJBK AD 2.22 FLIGHT PROCEDURES**

<p>The aircraft approaching to Kohnan Aerodrome shall report present position to A/G communication station of Kohnan Aerodrome at 5NM or further from ARP; and receive necessary for the flight.</p> <p>Call sign and frequency of A/G : KOHNAN FLIGHT SERVICE, 130.75Hz</p>
--

**RJBK AD 2.23 ADDITIONAL INFORMATION**

Nil
-----

**RJBK AD 2.24 CHARTS RELATED TO AN AERODROME**

<div style="display: flex; align-items: center;"> <div style="width: 10px; height: 100%; background-color: black; margin-right: 10px;"></div> <div> <p>Aerodrome/Heliport Chart</p> <p>Other Chart (Visual REP)</p> <p>Other Chart (Standard TFC Pattern and DEP/ARR routes)</p> </div> </div>
--

**INTENTIONALLY LEFT BLANK**




KOHNAN AD



27-09 27-09

II  
TWY SIDE  
Installed on TWY T-1 THRU T-4.



## LONGITUDINAL PROFILE OF RWY

LEVEL

REMARKS

RWY GROOVING  
STRENGTH OF RWY

WIDTH OF TWY

STRENGTH OF TWY T-1, T-3, T-4, P-1, P-2 & P-3

STRENGTH OF TWY T-2

## STRENGTH, DIMENSION & STRENGTH OF APRON

Apron-1 125m × 139m

Apron-2  
86m x 88m

April-2 60m x 60m  
Apron-3 82m x 139m

Apron-3	62m x 139m
Apron-4	26m x 121m

April-4 2011 x 121m  
 Apron-5 148m x 121m

April-3	140m x 12m
Apron-6	54m x 40.5m

April-6	34m x 40.3m
Hovering	66m x 71m

Compass setting	60m × 40m	60m × 70m
Hovering		

### Compass setting

RJBK / KOHNAN

Visual REP



Call sign	BRG / DIST from ARP	Remarks
岡南大橋 Ohashi	054°/2.0NM	旭川橋梁 Asahi River
西大寺 Saidaiji	056°/6.7NM	JR駅 JR Station
宇野 Uno	175°/6.0NM	宇野港 Cape
1 マイル南 1 NM South	182°/1.0NM	児島湖 Lake kojima
茶屋町 Chayamachi	267°/5.5NM	JR駅 JR Station
笹ヶ瀬橋 Sasagase	328°/2.2NM	笹ヶ瀬川橋梁 Sasagase River
岡山 Okayama	356°/4.5NM	JR駅 JR Station

注意： 岡南飛行場に進入しようとする飛行機は、飛行場標点から5 NM以遠において位置通報を行い、岡南飛行場の対空通信局から運航に必要な情報の提供を受けること。

対空通信局の呼出符号及び周波数： 岡南Flight Service, 130.75MHz

ATTENTION : The aircraft approaching to Kohnan Aerodrome shall report PPSN to A/G communication station of Kohnan Aerodrome at 5NM or further from ARP; and receive necessary information for the flight.

Call sign and frequency of A/G : KOHNAN FLIGHT SERVICE, 130.75MHz

## RJBK / KOHNAN

## Standard TFC Pattern and DEP/ARR routes

