

RJTH / HACHIJOJIMA

AD CHART



INTENTIONALLY LEFT BLANK

STANDARD DEPARTURE CHART-INSTRUMENT

RJTH / HACHIOJIMA

SID

TEMAR FIVE DEPARTURE

RWY 08 : Climb RWY HDG to 1000FT or above, turn left,....
RWY 26 : Turn left, climb via HCE R240 to 4000FT or above,
turn right proceed to HCE VOR/DME,
....climb via HCE R056 to TEMAR.

HACHIO REVERSAL FOUR DEPARTURE

RWY 08 : Climb RWY HDG to 1000FT or above, turn left, climb via HCE R056
to 4000FT or above, turn left,....
RWY 26 : Turn left, climb via HCE R240 to 4000FT or above,
turn right,....
....proceed to HCE VOR/DME.
Cross HCE VOR/DME at or above 5000FT.

CHANGE : Correction of misdescription (TEMAR)



STANDARD DEPARTURE CHART-INSTRUMENT

RJTH / HACHIJOJIMA

SID

MIYAKE THREE DEPARTURE

RWY 08 : Climb RWY HDG to 1000FT or above, turn left, climb via HCE R055 to 15.0DME, turn left to intercept and proceed via MOE R158 to MOE VOR/DME.

Cross HCE R055/15.0DME at or above 4000FT.

RWY 26 : Turn left, climb via HCE R240 to 18.0DME, turn right to intercept and proceed via MOE R194 to MOE VOR/DME.


Cross HCE R240/18.0DME at or above 6000FT.



STANDARD DEPARTURE CHART-INSTRUMENT

RJTH / HACHIOJIMA

RNAV SID

TOPIT ONE DEPARTURE

RWY08 : Climb on HDG 076° at or above 1400FT, turn left direct to TOPIT.

RWY26 : Climb on HDG 256° at or above 3000FT, turn right direct to TOPIT.

RWY08

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|---------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | VA | — | — | 076 (069.5) | -6.7 | — | — | +1400 | — | — | Basic RNP1 |
| 002 | DF | TOPIT | — | — | -6.7 | — | L | — | — | — | Basic RNP1 |

RWY26

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | Vertical Angle | Navigation Specification |
|---------------|-----------------|---------------------|----------|---------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------------------|
| 001 | VA | — | — | 256 (249.5) | -6.7 | — | — | +3000 | — | — | Basic RNP1 |
| 002 | DF | TOPIT | — | — | -6.7 | — | R | — | — | — | Basic RNP1 |

INTENTIONALLY LEFT BLANK

STANDARD ARRIVAL CHART-INSTRUMENT

RJTH / HACHIOJIMA

STAR

HACHIOJO ARRIVAL

From over SANGO, proceed via HCE R009 to intercept and proceed via HCE 14.0DME clockwise ARC, via IHC-LOC to SHELL or HCE R075 to RURII.

Cross SANGO at or above 5000FT, cross SHELL or RURII at or above 2000FT.

HACHIOJO ARRIVAL





INTENTIONALLY LEFT BLANK

INSTRUMENT APPROACH CHART

RJTH / HACHIOJIMA


LOC Z RWY26



INSTRUMENT APPROACH CHART


RJTH / HACHIOJIMA

LOC Y RWY26



MISSED APPROACH

Climb to 4000FT via HCE
R252, turn right, proceed
to HCE VOR/DME and hold
at 5000FT.
Contact HACHIOJO REMOTE.



| MINIMA | | THR elev. 284 | AD elev. 301 |
|--------|-----------|---------------|--------------|
| CAT | CIRCLING | | |
| | MDA(H) | CMV | MDA(H) VIS |
| A | 800 (516) | 1400 | — — |
| B | | 1500 | |
| C | | 1600 | |
| D | | 1800 | |


Circling NOT authorized.

INSTRUMENT APPROACH CHART

RJTH / HACHIOJIMA

VOR A (For RWY 26)


| | | | |
|--|---|------------------------|----------|
| TOKYO CONTROL 125.9 – 134.15 318.2 – 227.3 | HACHIOJIMA VOR/DME 116.65 HCE CH-113Y 33°06'52"N / 139°47'19"E | HACHIO REMOTE 118.7 | NO RADAR |
|--|---|------------------------|----------|



MISSED APPROACH

Turn right climb to 4000FT via
HCE R060, turn right,
proceed to HCE VOR/DME
and hold at 5000FT.
Contact HACHIO REMOTE.

HCE 5000



DME to HCE
NM to THR

6.0
5.6

12.0
11.6

MINIMA

THR elev. 284

AD elev. 301

| CAT | MDA(H) | Facilities | | | |
|-----|-----------|------------|--------------|-------|-----|
| | | Full | Intermediate | Basic | Nil |
| | | VIS | | VIS | |
| A | 800 (516) | - | | 4800 | |
| B | | | | | |
| C | | | | | |
| D | | | | | |

MINIMA APPLICATION CRITERIA in AD1.1.6.10.1.4 are not applicable.

INSTRUMENT APPROACH CHART

RJTH / HACHIJOJIMA

VOR B (For RWY 26)

| | | | |
|--|--|-------------------------|----------|
| TOKYO CONTROL 125.9 – 134.15 318.2 – 227.3 | HACHIJOJIMA VOR/DME 116.65 HCE CH-113Y 33°06'52"N / 139°47'19"E | HACHIJO REMOTE 118.7 | NO RADAR |
|--|--|-------------------------|----------|



MISSED APPROACH

Turn right, climb to 4000FT
via HCE R060, turn right,
proceed to HCE VOR/DME
and hold at 5000FT.
Contact HACHIJO REMOTE.



| | |
|------------|-----|
| DME to HCE | 6.0 |
| NM to THR | 5.6 |

| MINIMA | | THR elev. 284 | | AD elev. 301 | |
|--------|-----------|---------------|--------------|--------------|-----|
| CAT | MDA(H) | Facilities | | | |
| | | Full | Intermediate | Basic | Nil |
| | | VIS | VIS | | |
| A | 800 (516) | – | 4800 | | |
| B | | | | | |
| C | | | | | |
| D | | | | | |

MINIMA APPLICATION CRITERIA in AD1.1.6.10.1.4 are not applicable.

INSTRUMENT APPROACH CHART

RJTH / HACHIOJIMA

VOR C (For RWY 26)



INSTRUMENT APPROACH CHART

RJTH / HACHIOJIMA

VOR D (For RWY 08)





INSTRUMENT APPROACH CHART

RJTH / HACHIOJIMA

RNAV(RNP) RWY08

| | | | |
|--|----------------------|--------------------------|----------|
| TOKYO CONTROL 125.9 – 134.15 318.2 – 227.3 | GNSS and RF required | HACHIOJO REMOTE 118.7 | NO RADAR |
|--|----------------------|--------------------------|----------|

For uncompensated Baro-VNAV systems, procedure not authorized below 0°C / above 45°C



| Missed APCH climb gradient MNM 5.0% | | | | |
|-------------------------------------|----------|---------------|----------|--------------|
| MINIMA | | THR elev. 282 | | AD elev. 301 |
| CAT | RNP 0.29 | | RNP 0.30 | |
| | DA(H) | CMV | DA(H) | CMV |
| A | — | — | — | — |
| B | — | — | — | — |
| C | 806(524) | 2000 | 824(542) | 2000 |
| D | — | — | — | — |

MINIMA with Missed APCH climb gradient of 2.5% are not established.

RNP AR
Special Authorization Required

INSTRUMENT APPROACH CHART

RJTH / HACHIJOJIMA

RNAV(RNP) RWY08

RNAV(RNP) RWY08Coding Table

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | VPA/RDH (°/FT) | RNP Value |
|---------------|------------------------------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|----------------|--------------|
| 001 | IF | SANGO | — | — | -6.5 | — | — | +5000 | — | — | — |
| 002 | TF | OJARI | — | 219 (212.3) | -6.5 | 16.1 | — | 4400 | — | — | 1.0 |
| 003 | TF | TH851 | — | 219 (212.2) | -6.5 | 1.5 | — | 3914 | — | -3.00 | 0.29 0.30 |
| 004 | RF Center: THRF1 r=2.19NM | TH852 | — | — | -6.5 | 5.5 | L | 2175 | — | -3.00 | 0.29 0.30 |
| 005 | TF | RW08 | Y | 076 (069.4) | -6.5 | 5.8 | — | 332 | — | -3.00/50 | 0.29 0.30 |
| 006 | TF | TH861 | — | 076 (069.5) | -6.5 | 3.1 | — | — | — | — | 0.29 0.30 |
| 007 | TF | TH862 | — | 076 (069.5) | -6.5 | 4.0 | — | — | — | — | 1.0 |
| 008 | TF | TH863 | — | 016 (009.6) | -6.5 | 5.5 | — | — | — | — | 1.0 |
| 009 | TF | SANGO | — | 330 (323.0) | -6.5 | 10.3 | — | 5000 | — | — | 1.0 |


Waypoint Coordinates

| Waypoint Identifier | Coordinates | RF Arc Center Identifier | Coordinates |
|---------------------|------------------------|--------------------------|------------------------|
| SANGO | 332250.44N/1394814.02E | THRF1 | 330644.49N/1393910.78E |
| OJARI | 330912.37N/1393756.80E | | |
| TH851 | 330754.90N/1393658.54E | | |
| TH852 | 330441.17N/1394005.63E | | |
| RW08 | 330643.03N/1394633.07E | | |
| TH861 | 330749.27N/1395004.24E | | |
| TH862 | 330913.15N/1395432.21E | | |
| TH863 | 331439.22N/1395537.92E | | |

INSTRUMENT APPROACH CHART

RJTH / HACHIOJIMA

RNAV(RNP) RWY26



RNP AR
Special Authorization Required

INSTRUMENT APPROACH CHART

RJTH / HACHIJOJIMA

RNAV(RNP) RWY26


RNAV(RNP) RWY26Coding Table

| Serial Number | Path Descriptor | Waypoint Identifier | Fly Over | Course 'M('T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed (KIAS) | VPA/ RDH ('/FT) | RNP Value |
|---------------|------------------------------------|---------------------|----------|----------------|--------------------|---------------|----------------|---------------|--------------|-----------------|--------------|
| 001 | IF | SANGO | — | — | -6.5 | — | — | +5000 | — | — | — |
| 002 | TF | ASITA | — | 158 (151.8) | -6.5 | 10.7 | — | 3700 | — | — | 1.0 |
| 003 | TF | TH651 | — | 158 (151.9) | -6.5 | 1.4 | — | 3243 | — | -3.00 | 0.21 0.30 |
| 004 | RF Center: THRF2 r=2.26NM | TH652 | — | — | -6.5 | 3.9 | R | 2014 | — | -3.00 | 0.21 0.30 |
| 005 | TF | RW26 | Y | 256 (249.5) | -6.5 | 5.3 | — | 334 | — | -3.00/50 | 0.21 0.30 |
| 006 | TF | TH661 | — | 256 (249.5) | -6.5 | 2.2 | — | — | — | — | 0.21 0.30 |
| 007 | TF | TH662 | — | 256 (249.4) | -6.5 | 5.4 | — | — | — | — | 1.0 |
| 008 | TF | TH663 | — | 346 (339.6) | -6.5 | 7.5 | — | — | — | — | 1.0 |
| 009 | TF | SANGO | — | 048 (041.6) | -6.5 | 15.2 | — | 5000 | — | — | 1.0 |

Waypoint Coordinates

| Waypoint Identifier | Coordinates | RF Arc Center Identifier | Coordinates |
|---------------------|------------------------|--------------------------|------------------------|
| SANGO | 332250.44N/1394814.02E | THRF2 | 331103.88N/1395242.68E |
| ASITA | 331324.04N/1395416.62E | | |
| TH651 | 331208.17N/1395505.07E | | |
| TH652 | 330856.50N/1395339.00E | | |
| RW26 | 330705.72N/1394745.36E | | |
| TH661 | 330619.39N/1394517.79E | | |
| TH662 | 330425.68N/1393916.49E | | |
| TH663 | 331127.97N/1393608.44E | | |

Visual REP



| Call sign | BRG / DIST from ARP | Remarks |
|-----------|---------------------|--------------------|
| 10NM N | 360° /10.0NM | 海上 Over the sea |

RJTH / HACHIOJIMA

LDG CHART



RJTH / HACHIOJIMA

Minimum Vectoring Altitude CHART



CENTER : 330654N/1394709E (ARP)

INTENTIONALLY LEFT BLANK