

STANDARD DEPARTURE CHART - INSTRUMENT

RJKB / OKIERABU

SID

ERABU REVERSAL TWO DEPARTURE

RWY04 : Climb RWY HDG to 500FT, turn right, via ONC R090 to ONC 12.0DME, turn right, via ONC R110 to ONC VORTAC.


Cross ONC R090/8.0DME at or below 4000FT, cross ONC R110/6.0DME at assigned altitude.

RWY22 : Climb RWY HDG to 600FT, turn left HDG087 to intercept and proceed via ONC R132 to ONC 12.0DME, turn left, via ONC R110 to ONC VORTAC.

Cross ONC R132/8.0DME at or below 4000FT, cross ONC R110/6.0DME at assigned altitude.

Note RWY22 : 5.0% climb gradient required up to 600FT.

OBST ALT 145FT located at 0.2NM 257° FM end of RWY22.




CHANGE : Description of PROC name.

RJKB / OKIERABU

NEORI TWO DEPARTURE
MEKAX TRANSITION

RNP1

VAR 6° W



OBST ALT 145FT located at 0.2NM 257° FM end of RWY22.

From NEORI to MEKAX.

CHANGE : PROC name added. MEKAX TRANSITION added.

STANDARD DEPARTURE CHART - INSTRUMENT

RJKB / OKIERABU

RNAV SID and TRANSITION

NEORI TWO DEPARTURE

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	040 (034.0)	-6.2	—	—	+500	—	—	RNP1
002	DF	NEORI	—	—	-6.2	—	L	—	—	—	RNP1

RWY22

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	220 (214.0)	-6.2	—	—	+600	—	—	RNP1
002	DF	NEORI	—	—	-6.2	—	L	—	—	—	RNP1


MEKAX TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	NEORI	—	—	-6.2	—	—	—	—	—	RNP1
002	TF	MEKAX	—	027 (021.0)	-6.2	35.2	—	—	—	—	RNP1

CHANGE : PROC name added. NEORI TWO DEPARTURE added. True bearing. VAR.

STANDARD DEPARTURE CHART - INSTRUMENT

CHANGE : PROC name added. INOBE TRANSITION added. SID renamed(AZEFU FOUR DEPARTURE).
Course FM INOBE to MEKAX. ALT restriction at AZEFU deleted.



STANDARD DEPARTURE CHART - INSTRUMENT

RJKB / OKIERABU RNAV SID and TRANSITION

AZEFU FOUR DEPARTURE

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	040 (034.0)	-6.2	—	—	+500	—	—	RNP1
002	DF	AZEFU	—	—	-6.2	—	L	—	—	—	RNP1
003	TF	INOBE	—	027 (020.9)	-6.2	16.4	—	—	—	—	RNP1

RWY22

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	220 (214.0)	-6.2	—	—	+600	—	—	RNP1
002	DF	AZEFU	—	—	-6.2	—	L	—	—	—	RNP1
003	TF	INOBE	—	027 (020.9)	-6.2	16.4	—	—	—	—	RNP1

INOBE TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	INOBE	—	—	-6.2	—	—	—	—	—	RNP1
002	TF	MEKAX	—	040 (033.3)	-6.2	37.2	—	—	—	—	RNP1

CHANGE : PROC name added. AZEFU FOUR DEPARTURE added. VAR. True bearing. ALT restriction at AZEFU deleted.


STANDARD DEPARTURE CHART - INSTRUMENT

RJKB / OKIERABU

RNAV SID and TRANSITION

SONNA TWO DEPARTURE YUWAN TRANSITION	RNP1
---	------

Note GNSS required.



SONNA TWO DEPARTURE
RWY04: Climb on HDG040° at or above 500FT, direct to SONNA.
RWY22: Climb on HDG220° at or above 600FT, turn left direct to SONNA.
Note RWY22 : 5.0% climb gradient required up to 600FT.
OBST ALT 145FT located at 0.2NM 257° FM end of RWY22.

YUWAN TRANSITION
From SONNA to YUWAN.

CHANGE : PROC name added. YUWAN TRANSITION added.

STANDARD DEPARTURE CHART - INSTRUMENT

RJKB / OKIERABU

RNAV SID and TRANSITION

SONNA TWO DEPARTURE

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	040 (034.0)	-6.2	—	—	+500	—	—	RNP1
002	DF	SONNA	—	—	-6.2	—	—	—	—	—	RNP1

RWY22

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	220 (214.0)	-6.2	—	—	+600	—	—	RNP1
002	DF	SONNA	—	—	-6.2	—	L	—	—	—	RNP1

YUWAN TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SONNA	—	—	-6.2	—	—	—	—	—	RNP1
002	TF	YUWAN	—	048 (041.8)	-6.2	30.4	—	—	—	—	RNP1

CHANGE : PROC name added. SONNA TWO DEPARTURE added. True bearing. VAR.

STANDARD DEPARTURE CHART - INSTRUMENT

RJKB / OKIERABU

RNAV SID

YUNTA TWO DEPARTURE

RNP1

Note GNSS required.

VAR 6° W

ASATO
271054.2N
1283014.7E

500
040°
600
220°

RWY04: Climb on HDG040° at or above 500FT, turn right direct to ASATO.
RWY22: Climb on HDG220° at or above 600FT, direct to ASATO.
Note RWY22 : 5.0% climb gradient required up to 600FT.
OBST ALT 145FT located at 0.2NM 257° FM end of RWY22.

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	040 (034.0)	-6.2	—	—	+500	—	—	RNP1
002	DF	ASATO	—	—	-6.2	—	R	—	—	—	RNP1

RWY22

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	220 (214.0)	-6.2	—	—	+600	—	—	RNP1
002	DF	ASATO	—	—	-6.2	—	—	—	—	—	RNP1

CHANGE : VAR. True bearing.

STANDARD DEPARTURE CHART - INSTRUMENT

RJKB / OKIERABU

RNAV SID



RWY04 : Climb on HDG 040° at or above 500FT, direct to HORAI.
RWY22 : Climb on HDG 220° at or above 600FT, turn left direct to KB200, to HORAI.

NOTE RWY22 : 5.0% climb gradient required up to 600FT.
OBST ALT 145FT located at 0.2NM 257° FM end of RWY22

RWY04

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	040 (034.0)	-6.2	-	-	+500	-	-	RNP1
002	DF	HORAI	-	-	-6.2	-	-	-	-	-	RNP1

RWY22

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	220 (214.0)	-6.2	-	-	+600	-	-	RNP1
002	DF	KB200	-	-	-6.2	-	L	-	-	-	RNP1
003	TF	HORAI	-	018 (011.8)	-6.2	16.1	-	-	-	-	RNP1

CHANGE : VAR. True bearing.

INTENTIONALLY LEFT BLANK


STANDARD ARRIVAL CHART - INSTRUMENT

RJKB / OKIERABU

RNAV STAR RWY04

HACHA SOUTH ARRIVAL PINNE SOUTH ARRIVAL	RNP1
--	------

Note GNSS required.



STANDARD ARRIVAL CHART - INSTRUMENT

RJKB / OKIERABU

RNAV STAR RWY04

HACHA SOUTH ARRIVAL
From HACHA, to DINGO at or above 3000FT, to GOMES at or above 2000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	HACHA	-	-	-6.2	-	-	-	-	-	RNP1
002	TF	DINGO	-	200 (194.0)	-6.2	45.2	-	+3000	-	-	RNP1
003	TF	GOMES	-	218 (212.2)	-6.2	11.0	-	+2000	-	-	RNP1

PINNE SOUTH ARRIVAL
From PINNE, to DINGO at or above 3000FT, to GOMES at or above 2000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	PINNE	-	-	-6.2	-	-	-	-	-	RNP1
002	TF	DINGO	-	219 (212.3)	-6.2	28.1	-	+3000	-	-	RNP1
003	TF	GOMES	-	218 (212.2)	-6.2	11.0	-	+2000	-	-	RNP1

CHANGE : VAR. Course FM PINNE to DINGO.

STANDARD ARRIVAL CHART - INSTRUMENT

RJKB / OKIERABU RNAV STAR RWY22

HACHA NORTH ARRIVAL / HACHA EAST ARRIVAL PINNE NORTH ARRIVAL / PINNE EAST ARRIVAL	RNP1
--	------

Note GNSS required.



CHANGE : PROC course FM HACHA to WOODS.

STANDARD ARRIVAL CHART - INSTRUMENT

RJKB / OKIERABU

RNAV STAR RWY22

HACHA NORTH ARRIVAL

From HACHA, to LILLY at or above 3000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	HACHA	-	-	-6.2	-	-	-	-	-	RNP1
002	TF	LILLY	-	202 (195.6)	-6.2	34.1	-	+3000	-	-	RNP1

HACHA EAST ARRIVAL

From HACHA, to WOODS at or above 3300FT, to PAULO at or above 2000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	HACHA	-	-	-6.2	-	-	-	-	-	RNP1
002	TF	WOODS	-	189 (182.4)	-6.2	34.4	-	+3300	-	-	RNP1
003	TF	PAULO	-	207 (201.0)	-6.2	5.2	-	+2000	-	-	RNP1

PINNE NORTH ARRIVAL

From PINNE, to LILLY at or above 3000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	PINNE	-	-	-6.2	-	-	-	-	-	RNP1
002	TF	LILLY	-	232 (226.2)	-6.2	18.4	-	+3000	-	-	RNP1


PINNE EAST ARRIVAL

From PINNE, to WOODS at or above 3300FT, to PAULO at or above 2000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	PINNE	-	-	-6.2	-	-	-	-	-	RNP1
002	TF	WOODS	-	207 (201.1)	-6.2	15.3	-	+3300	-	-	RNP1
003	TF	PAULO	-	207 (201.0)	-6.2	5.2	-	+2000	-	-	RNP1

CHANGE : VAR. Course FM HACHA to WOODS.

INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJKB / OKIERABU

RNP RWY04

FAS DATA BLOCK

Operation type	0	LTP/FTP ellipsoidal height	+00608
SBAS service provider identifier	2	FPAP latitude	272621.2280N
Airport identifier	RJKB	FPAP longitude	1284240.8210E
Runway	04	Threshold crossing height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M04A	∟ length offset	0344
LTP/FTP latitude	272535.6665N	HAL	40.0
LTP/FTP longitude	1284206.1585E	VAL	50.0
CRC remainder	78273A92		

Required additional data

LTP/FTP orthometric height	30.1
----------------------------	------

CHANGE : FAS DATA BLOCK and Required additional data established.

INSTRUMENT APPROACH CHART



CHANGE : ALT(3.0° APCH Path). VDP. PROC ALT at EMIKO. NM to THR. VAR.

INSTRUMENT APPROACH CHART




RJKB / OKIERABU

FAS DATA BLOCK

Required additional data

CHANGE : FAS DATA BLOCK and Required additional data established.



Call sign	BRG / DIST from ARP	Remarks
10NM N	000°T / 10.0NM	海上 Over the sea
10NM NE	045°T / 10.0NM	海上 Over the sea
田皆 Tamina	260°T / 9.2NM	岬 Cape
10NM SW	225°T / 10.0NM	海上 Over the sea



Minimum Vectoring Altitude CHART

