

AD 2 AERODROMES

RJBK AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJBK - KOHNNAN

RJBK AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

| | | |
|---|--|---|
| 1 | ARP coordinates and site at AD | 343529N/1335600E |
| 2 | Direction and distance from (city) | 7.1km S of Okayama city office |
| 3 | Elevation/ Reference temperature | 0ft / - |
| 4 | Geoid undulation at AD ELEV PSN | to be developed |
| 5 | MAG VAR/ Annual change | 7°W (2000) / 1°W |
| 6 | AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses | OKAYAMA PREF. PUBLIC AP. Address: Urayasuminami-machi 640, Okayama-shi, Okayama Pref. Tel: 086-262-0954 Fax: 086-262-5220 E-mail: kounan@pref.okayama.lg.jp Web: http://www.pref.okayama.jp/soshiki/kakuka.html?sec_sec1=182 |
| 7 | Types of traffic permitted(IFR/VFR) | VFR |
| 8 | Remarks | Nil |

RJBK AD 2.3 OPERATIONAL HOURS

| | | |
|----|---------------------------|---|
| 1 | AD Administration | 2330 - 0930 |
| 2 | Customs and immigration | On request Customs: 0863-31-5375 Immigration: 086-234-3531 |
| 3 | Health and sanitation | Quarantine(human): On request(086-294-5046) Quarantine(animal, plant): Nil |
| 4 | AIS Briefing Office | Nil |
| 5 | ATS Reporting Office(ARO) | Nil |
| 6 | MET Briefing Office | Nil |
| 7 | ATS | 2330 - 0930 Kohnan Flight Service |
| 8 | Fuelling | 0030 - 0830 On Request 2330-0030, 0830-0930 Tel/Fax 086-262-1091 |
| 9 | Handling | Nil |
| 10 | Security | Nil |
| 11 | De-icing | Nil |
| 12 | Remarks | Nil |

RJBK AD 2.4 HANDLING SERVICES AND FACILITIES

| | | |
|---|---|----------------------|
| 1 | Cargo-handling facilities | Nil |
| 2 | Fuel/ oil types | 100/130, JET A-1 |
| 3 | Fuelling facilities/ capacity | Fuel Truck refueling |
| 4 | De-icing facilities | Nil |
| 5 | Hangar space for visiting aircraft | Nil |
| 6 | Repair facilities for visiting aircraft | Nil |
| 7 | Remarks | Nil |

RJBK AD 2.5 PASSENGER FACILITIES

| | | |
|---|----------------------|--------|
| 1 | Hotels | Nil |
| 2 | Restaurants | Nil |
| 3 | Transportation | Busses |
| 4 | Medical facilities | Nil |
| 5 | Bank and Post Office | Nil |
| 6 | Tourist Office | Nil |
| 7 | Remarks | Nil |

RJBK AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

| | | |
|---|---|----------------------------------|
| 1 | AD category for fire fighting | CAT 3 |
| 2 | Rescue equipment | Chemical fire fighting truck x 1 |
| 3 | Capability for removal of disabled aircraft | Ask AD administration |
| 4 | Remarks | Nil |

RJBK AD 2.7 SEASONAL AVAILABILITY-CLEARING

| | | |
|---|-----------------------------|-----------------------|
| 1 | Types of clearing equipment | Not applicable |
| 2 | Clearance priorities | Ask AD administration |
| 3 | Remarks | Nil |

RJBK AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

| | | |
|---|-------------------------------------|--|
| 1 | Apron surface and strength | Surface : Asphalt-concrete Strength : Apron-1 AUW/5700kg/0.28MPa Apron-2 PCN14/F/D/X/T Apron-3 AUW/5700kg/0.28MPa Apron-4 AUW/11000kg/0.28MPa Apron-5 AUW/4000kg Apron-6 AUW/4000kg |
| 2 | Taxiway width, surface and strength | Width: 18m Strength:T1,T3,T4,P1,P2,P3 AUW/5700kg/0.28MPa T2 PCN14/F/D/X/T |
| 3 | ACL and elevation | Not available |
| 4 | VOR checkpoints | Nil |
| 5 | INS checkpoints | Nil |
| 6 | Remarks | Nil |

RJBK AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

| | | |
|---|--|--|
| 1 | Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands | Nil |
| 2 | RWY and TWY markings and LGT | RWY:09/27 (Marking) RWY designation, RWY CL, RWY middle point, Aiming point, TDZ, RWY side stripe (LGT) REDL, RTHL, RENL TWY: (Marking) TWY CL, RWY HLDG PSN, TWY side stripe (LGT) TWY edge LGT, Taxiing guidance sign |
| 3 | Stop bars | Nil |
| 4 | Remarks | (Marking) Apron TWY CL (LGT) Apron flood LGT |

RJBK AD 2.10 AERODROME OBSTACLES

■ In Area2 See Obstacle data

■ In Area3 To be developed

RJBK AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

| | | |
|----|--|-----|
| 1 | Associated MET Office | Nil |
| 2 | Hours of service MET Office outside hours | Nil |
| 3 | Office responsible for TAF preparation Periods of validity | Nil |
| 4 | Trend forecast Interval of issuance | Nil |
| 5 | Briefing/ consultation provided | Nil |
| 6 | Flight documentation Language(s) used | Nil |
| 7 | Charts and other information available for briefing or consultation | Nil |
| 8 | Supplementary equipment available for providing information | Nil |
| 9 | ATS units provided with information | Nil |
| 10 | Additional information (limitation of service, etc.) | Nil |

RJBK AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

| Designations RWY NR | TRUE BRG | Dimensions of RWY(M) | Strength(PCN) and Surface of RWY | THR coordinates THR geoid undulation | THR elevation and highest elevation of TDZ of precision APP RWY |
|------------------------|------------------------|-------------------------|--|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 09 | 085.50° | 1200×30 | PCN 14/F/D/X/T Asphalt | to be developed | THR ELEV:-1ft |
| 27 | 265.50° | 1200×30 | PCN 14/F/D/X/T Asphalt | | THR ELEV:2ft |
| Slope of RWY | Strip Dimensions(M) | | RESA (Overrun) Dimensions (M) | | Remarks |
| 7 | 10 | | 11 | | 14 |
| See AD chart | 1320×120 | | 3×(MNM:117 MAX:120)* | | RWY Grooving : 1200m × 20m |
| See AD chart | 1320×120 | | 40×120 *For detail, ask airport administrator | | RWY Grooving : 1200m × 20m |

RJBK AD 2.13 DECLARED DISTANCES

| RWY Designator | TORA (m) | TODA (m) | ASDA (m) | LDA (m) | Remarks |
|----------------|----------|----------|----------|---------|---------|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 09 | 1200 | 1200 | 1200 | 1200 | Nil |
| 27 | 1200 | 1200 | 1200 | 1200 | Nil |

RJBK AD 2.14 APPROACH AND RUNWAY LIGHTING

| RWY Designator | APCH LGT type LEN INTST | RTHL Color WBAR | PAPI (VASIS) Angle DIST FM THR MEHT | RTZL LEN | RCLL LEN Spacing Color INTST | REDL LEN Spacing Color INTST | RENL Color WBAR | STWL LEN Color |
|---|-------------------------|-----------------|-------------------------------------|----------|------------------------------|--|-----------------|----------------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 09 | Nil | Green - | PAPI 3.5°/LEFT 230m 45ft | Nil | Nil | 1200m 60m Coded color (White/Yellow) LIH | Red - | Nil (*1) |
| 27 | Nil | Green - | PAPI 3.5°/LEFT 247m 45ft | Nil | Nil | 1200m 60m Coded color (White/Yellow) LIH | Red - | Nil (*1) |
| Remarks | | | | | | | | |
| 10 | | | | | | | | |
| Overrun area edge LGT(LEN:60m Color:Red)(*1) RWY THR ID LGT for RWY 09/27 THR (Color: White) | | | | | | | | |

RJBK AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

| | | |
|---|--|---|
| 1 | ABN/IBN location, characteristics and hours of operation | ABN: 343536N1335556E, White/Green EV4.3sec, HO |
| 2 | LDI location and LGT Anemometer location and LGT | LDI: Nil Anemometer : 470m WNW from RWY 27 THR, LGTD |
| 3 | TWY edge and centerline lighting | TWY edge LGT: Blue TWY CL LGT: Nil |
| 4 | Secondary power supply/ switch-over time | All lights within 15 seconds |
| 5 | Remarks | WDI LGT |

RJBK AD 2.16 HELICOPTER LANDING AREA

| |
|-----|
| Nil |
|-----|

RJBK AD 2.17 ATS AIRSPACE

| Designation and lateral limits | Vertical limits (ft) | Airspace classification | ATS unit call sign Language | Remarks |
|--------------------------------|----------------------|-------------------------|-----------------------------|---------|
| 1 | 2 | 3 | 4 | 6 |
| Nil | | | | |

RJBK AD 2.18 ATS COMMUNICATION FACILITIES

| Service designation | Call sign | Frequency | Hours of operation | Remarks |
|---------------------|------------------------|-----------|--------------------|---------|
| 1 | 2 | 3 | 4 | 5 |
| A/G | KOHANAN FLIGHT SERVICE | 130.75MHz | 2330 - 0930 | Nil |

RJBK AD 2.19 RADIO NAVIGATION AND LANDING AIDS

| Type of aid | ID | Frequency | Hours of operation | Position of transmitting antenna coordinates | Elevation of DME transmitting antenna | Remarks |
|-------------|----|-----------|--------------------|--|---------------------------------------|---------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| Nil | | | | | | |

RJBK AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

PPR For use.TEL 086-262-1954

2. Taxiing to and from stands

Nil

3. Parking area for small aircraft(General aviation)

Nil

4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

| |
|-----|
| Nil |
|-----|

7. School and training flights - technical test flights - use of runways

| |
|-----|
| Nil |
|-----|

8. Helicopter traffic - limitation

| |
|-----|
| Nil |
|-----|

9. Removal of disabled aircraft from runways

| |
|-----|
| Nil |
|-----|

RJBK AD 2.21 NOISE ABATEMENT PROCEDURES

| |
|--|
| See Kohnan Standard traffic pattern and recommended departure/arrival routes |
|--|

RJBK AD 2.22 FLIGHT PROCEDURES

| |
|--|
| <p>The aircraft approaching to Kohnan Aerodrome shall report present position to A/G communication station of Kohnan Aerodrome at 5NM or further from ARP; and receive necessary for the flight.</p> <p>Call sign and frequency of A/G : KOHNAN FLIGHT SERVICE, 130.75Hz</p> |
|--|

RJBK AD 2.23 ADDITIONAL INFORMATION

| |
|-----|
| Nil |
|-----|

RJBK AD 2.24 CHARTS RELATED TO AN AERODROME

| |
|--|
| <p>Aerodrome/Heliport Chart</p> <p>Other Chart (Visual REP)</p> <p>Other Chart (Standard TFC Pattern and DEP/ARR routes)</p> |
|--|

INTENTIONALLY LEFT BLANK

KOHNAN AD



RJBK / KOHNAN

Visual REP



| Call sign | BRG / DIST from ARP | Remarks |
|---------------------|---------------------|--------------------------|
| 岡南大橋 Ohashi | 054°/2.0NM | 旭川橋梁 Asahi River |
| 西大寺 Saidaiji | 056°/6.7NM | JR駅 JR Station |
| 宇野 Uno | 175°/6.0NM | 宇野港 Cape |
| 1マイル南 1 NM South | 182°/1.0NM | 児島湖 Lake kojima |
| 茶屋町 Chayamachi | 267°/5.5NM | JR駅 JR Station |
| 笹ヶ瀬橋 Sasagase | 328°/2.2NM | 笹ヶ瀬川橋梁 Sasagase River |
| 岡山 Okayama | 356°/4.5NM | JR駅 JR Station |

注意： 岡南飛行場に進入しようとする飛行機は、飛行場標点から5 NM以遠において位置通報を行い、岡南飛行場の対空通信局から運航に必要な情報の提供を受けること。

対空通信局の呼出符号及び周波数： 岡南Flight Service, 130.75MHz

ATTENTION : The aircraft approaching to Kohnan Aerodrome shall report PPSN to A/G communication station of Kohnan Aerodrome at 5NM or further from ARP; and receive necessary information for the flight.

Call sign and frequency of A/G : KOHNAN FLIGHT SERVICE, 130.75MHz

RJBK / KOHNAN

Standard TFC Pattern and DEP/ARR routes

