RJOI / IWAKUNI AD CHART



CHANGE : Update.

NOTE: REPRINTING DOD FLIP

RJOI / IWAKUNI

Aircraft Parking / Docking Chart

IWAKUNI AERODROME





STANDARD DEPARTURE CHART - INSTRUMENT

RJOI / IWAKUNI

MATSUYAMA SE THREE DEPARTURE(OBSTACLE) (RNAV)

ATIS ★ 128.4 283.0
CLNC DEL ★
135.7 310.6
GND CON ★
121.3 360.2
TOWER ★
123.8 340.2
DEP CON ★
131.4 363.8

RNAV1-DME/DME/IRU, DME/DME, GNSS, or RNP 2.0

Rwy	Knots	60	120	180	240	300	360
* 02 ⓐ	V/V(fpm)	230	460	690	920	1150	1650
†02/20 ⓑ	V/V(fpm)	330	660	990	1320	1650	1980
† 20 ⓒ	V/V(fpm)	204	408	612	816	1020	1224

* Minimum † ATC Climb Rate

ⓐ to 2300
ⓑ MALTA transtion to 15,000 from MYE to MALTA
ⓒ to 6000



NOTE: Chart not to scale

TA 14,000

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 02: Climb heading 015° to 511, then on depicted route. Cross MATSUYAMA VOR/DME (MYE) at 6000 thence...

TAKEOFF RWY 20: Climb heading 195° to 511, then on depicted route. Cross MATSUYAMA VOR/DME (MYE) at 6000 thence...

KOCHI TRANSITION: As depicted. Cross KOCHI (KRE) at FL150. Maintain FL150 or higher as assigned.

MALTA TRANSITION: As depicted. Cross MALTA at FL150, maintain FL150 or higher as assigned.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RJOI / IWAKUNI

LOC/DME I-IJO	APCH CRS	Rwy ldg	8006
110.15	014°	TDZE	10
Chan 38(Y)		Arpt Elev	10

ILS RWY02

RADAR or MYE VOR/DME required.

T * When ALS inop, increase CAT ABCD vis to ¾ mile.
** When ALS inop, increase CAT AB vis to 1 mile, CAT CD vis to 1⅛ miles.
*** Circling not authorized W of Rwy 02-20. CAT D remain within 2.8 NM.

ALSF-1

MISSED APPROACH: Climb on heading 014° to 700, then climbing right turn to 6000 heading 144° direct MYE VOR/DME and hold.

ATIS★	APP CON★	TOWER★	GND CON★	CLNC DEL★	ASR/PAR
128.4 283.0	131.4 236.2	123.8 340.2	121.3 360.2	135.7 310.6	

Knots	60	120	180	240	300	360
V/V(fpm)	210	420	630	840	1050	1260

Min climb of 210 ft/NM to 2100 - Controlling Obstacle 1457



EMERG SAFE ALT 100 NM 8500





CATEGORY	A	B	C	D
S-ILS 02*	260-½ 250 (300-½)			
S-LOC 02**	400-½ 390 (400-½)		400-⅝ 390 (400-⅝)	
C CIRCLING***	460-1 450 (500-1)		460-1½ 450 (500-1½)	560-2 550 (600-2)

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RJOI / IWAKUNI

APCH CRS	Rwy ldg	8006
015°	THRE	10
	Arpt Elev	10

RNAV(GPS) RWY02

RNP APCH

T * When ALS inop, increase vis to 7/8 mile.
** When ALS inop, increase CAT AB vis to 1 mile, CAT CD vis to 1 1/8 miles.
*** Circling not authorized W of Rwy 02-20. CAT D circling remain within 2.8 NM.

ALSF-1

MISSED APPROACH: Climb to 440 then climbing right turn to 6000 direct MYE and hold.

ATIS ★	APP CON ★	TOWER ★	GND CON ★	CLNC DEL ★	ASR/PAR
128.4 283.0	131.4 236.2	123.8 340.2	121.3 360.2	135.7 310.6	

Knots	60	120	180	240	300	360
V/V(fpm)	260	520	780	1040	1300	1560

Min climb of 260 ft/NM to 2100 - Controlling Obstacle 1457



VGSI and glidepath not coincident
(VGSI Angle 3.00/TCH 67).

440 | 6000 | MYE

TLv FL140
TA 14,000

ELEV 10 | THRE 10





HIRL Rwy 02-20
REIL Rwy 20

CATEGORY	A	B	C	D
LNAV/ * VNAV DA	276-½ 266 (300-½)	287-½ 277 (300-½)	295-½ 285 (300-½)	306-½ 296 (300-½)
LNAV MDA**	400- ½ 390 (400-½)		400-⅝ 390 (400-⅝)	
C CIRCLING***	460-1 450 (500-1)		460-1½ 450 (500-1½)	560-2 550 (600-2)

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

RJOI / IWAKUNI LDG CHART

SEALANE PATTERNS & VFR ARR PATTERNS





IWAKUNI SEALANE(TOWER) :
122.0 - 123.1x - 228.2 - 319.0

IWAKUNI APP : WEST
131.4 - 236.2
EAST 128.0 - 250.6

IWAKUNI TWR :
123.8 - 340.2

RJOI / IWAKUNI

Minimum Vectoring Altitude CHART



CHANGE : Update.