RJSI / HANAMAKI AD CHART



STANDARD DEPARTURE CHART -INSTRUMENT

RJSI / HANAMAKI SID

OHSHU ONE DEPARTURE

RWY 02 : Climb RWY HDG to 900FT, turn left...

RWY 20 : Climb RWY HDG to 1300FT, turn left HDG 324˚...

...to intercept and proceed via HPE R009 to OHSHU.



CHANGE : Description of PROC name.

STANDARD DEPARTURE CHART -INSTRUMENT

RJSI / HANAMAKI SID

NIIGATA FIVE DEPARTURE

RWY 02 : Climb RWY HDG to HPE 3.5 DME, turn right...

RWY 20 : Climb RWY HDG to HPE 3.5 DME, turn left...

...proceed to HPE VOR/DME, via HPE R236 to HPE 50.0DME(GTC 79.6DME), via GTC R055 to GTC.

Cross HPE VOR/DME at or above 2200 FT, cross HPE R236/50.0DME (GTC R055/79.6DME) at or above 11000 FT.

Note RWY02 : 4.5% climb gradient required up to 2400FT.
OBST ALT 1641FT located at 4.1NM 091˚ FM end of RWY02.

RWY20 : 3.9% climb gradient required up to 1100FT.
OBST ALT 722FT located at 2.8NM 166˚ FM end of RWY20.



CHANGE : PROC renamed. PROC course. ALT restriction.

STANDARD DEPARTURE CHART -INSTRUMENT

RJSI / HANAMAKI SID

HANAMAKI REVERSAL TWO DEPARTURE

RWY 02 : Climb RWY HDG to 700FT, via HPE R022 to 6.0 DME, turn right...
RWY 20 : Climb RWY HDG to 700FT, via HPE R194 to 6.0 DME, turn left...
...proceed to HPE VOR/DME.
Cross HPE VOR/DME at or above 6000FT.

Note RWY02 : 5.0% climb gradient required up to 3200FT.
OBST ALT 2691FT located at 9.1NM 058˚ FM end of RWY02.



CHANGE : Description of PROC name.

STANDARD DEPARTURE CHART -INSTRUMENT

RJSI / HANAMAKI RNAV SID

SAMBO ONE DEPARTURE — Basic RNP1

Note GNSS required.



RWY02 : Climb on HDG 019˚ at or above 700FT, direct to AKARI, to DASCO to SAMBO.
RWY20 : Climb on HDG 199˚ at or above 1300FT, turn right direct to SI010, to AKARI, to DASCO to SAMBO .

Note RWY02 : 4.0% climb gradient required up to 700FT.
OBST ALT 318FT located at 0.2NM 061˚ FM end of RWY02.
RWY20 : 4.0% climb gradient required up to 2700FT.
OBST ALT 3117FT located at 10.7NM 351˚ FM end of RWY20.

RWY02

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	019 (010.7)	-8.7	–	–	+700	–	–	Basic RNP1
002	DF	AKARI	–	–	-8.7	–	–	–	–	–	Basic RNP1
003	TF	DASCO	–	009 (000.8)	-8.7	7.9	–	–	–	–	Basic RNP1
004	TF	SAMBO	–	345 (336.6)	-8.7	21.9	–	–	–	–	Basic RNP1

RWY20

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	199 (190.7)	-8.7	–	–	+1300	–	–	Basic RNP1
002	DF	SI010	–	–	-8.7	–	R	–	–	–	Basic RNP1
003	TF	AKARI	–	025 (016.7)	-8.7	17.0	–	–	–	–	Basic RNP1
004	TF	DASCO	–	009 (000.8)	-8.7	7.9	–	–	–	–	Basic RNP1
005	TF	SAMBO	–	345 (336.6)	-8.7	21.9	–	–	–	–	Basic RNP1

CHANGE : Description of VAR and PROC name.

STANDARD DEPARTURE CHART -INSTRUMENT

RJSI / HANAMAKI — RNAV SID

HANKA ONE DEPARTURE — Basic RNP1

Note GNSS required



RWY02 : Climb on HDG 019˚ at or above 1600FT, turn left direct to HANKA, at or above 11000FT.
RWY20 : Climb on HDG 199˚ at or above 800FT, turn right direct to HANKA, at or above 11000FT.
Note RWY02: 5.0% climb gradient required up to 3600FT.
OBST ALT 1936FT located at 5.5NM 340˚ FM end of RWY02.
OBST ALT 3018FT located at 8.2NM 310˚ FM end of RWY02.
RWY20: 5.0% climb gradient required up to 5400FT.
OBST ALT 4593FT located at 18.2NM 227˚ FM end of RWY20.
OBST ALT 5151FT located at 20.8NM 232˚ FM end of RWY20.

RWY02

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	019 (010.7)	-8.7	–	–	+1600	–	–	Basic RNP1
002	DF	HANKA	–	–	-8.7	–	L	+11000	–	–	Basic RNP1

RWY20

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	199 (190.7)	-8.7	–	–	+800	–	–	Basic RNP1
002	DF	HANKA	–	–	-8.7	–	R	+11000	–	–	Basic RNP1

CHANGE : Description of VAR and PROC name.

INTENTIONALLY LEFT BLANK

STANDARD ARRIVAL CHART - INSTRUMENT

RJSI / HANAMAKI — RNAV STAR RWY02

REMEN ARRIVAL — Basic RNP1

Note GNSS required



From MORIO at or above 9000FT, to JAMEN at or above 7400FT, to REMEN at or above 4100FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	MORIO	–	–	-8.8	–	–	+9000	–	–	Basic RNP1
002	TF	JAMEN	–	218 (209.6)	-8.8	10.0	–	+7400	–	–	Basic RNP1
003	TF	REMEN	–	218 (209.5)	-8.8	15.7	–	+4100	–	–	Basic RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	MORIO	244 (235.7)	-8.8	1.0(-14000)	R	9000	FL140	-230(-14000)	Basic RNP1

CHANGE : Description of VAR and PROC name.

STANDARD ARRIVAL CHART - INSTRUMENT

RJSI / HANAMAKI — RNAV STAR RWY20

WANKO ARRIVAL — Basic RNP1

Note GNSS required



From SIOMO at or above 8000FT, to WANKO at or above 5800FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SIOMO	–	–	-8.8	–	–	+8000	–	–	Basic RNP1
002	TF	WANKO	–	021 (012.6)	-8.8	20.6	–	+5800	–	–	Basic RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	SIOMO	039 (030.1)	-8.8	1.0(-14000)	R	8000	FL140	-210(-14000)	Basic RNP1

CHANGE : Description of VAR and PROC name.

STANDARD ARRIVAL CHART - INSTRUMENT

RJSI / HANAMAKI — RNAV STAR RWY02

SIOMO ARRIVAL	Basic RNP1

Note GNSS required.



From ENBIM at or above 9000FT, to NOPID at or above 8200FT, to ANOLA, to SIOMO at or above 8000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	ENBIM	–	–	-8.8	–	–	+9000	–	–	Basic RNP1
002	TF	NOPID	–	204 (195.0)	-8.8	7.9	–	+8200	–	–	Basic RNP1
003	TF	ANOLA	–	204 (194.9)	-8.8	33.4	–	–	–	–	Basic RNP1
004	TF	SIOMO	–	199 (190.6)	-8.8	7.5	–	+8000	–	–	Basic RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	ENBIM	195 (186.5)	-8.8	1.0(-14000)	L	9000	FL140	-230 (-14000)	Basic RNP1

CHANGE : VAR. PROC course. ESBEL, GEIBI abolished. ENBIM, NOPID, ANOLA established. HLDG pattern.

STANDARD ARRIVAL CHART - INSTRUMENT

RJSI / HANAMAKI

RNAV STAR RWY20

SUIHO ARRIVAL

Basic RNP1

Note GNSS required.



CHANGE : VAR. PROC course. ESBEL, MAMEB, NONBE abolished. ENBIM, OMKOS established. HLDG pattern.

From ENBIM at or above 9000FT, to OMKOS at or above 4100FT, to SUIHO at or above 3200FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	ENBIM	–	–	-8.8	–	–	+9000	–	–	Basic RNP1
002	TF	OMKOS	–	187 (178.1)	-8.8	6.1	–	+4100	–	–	Basic RNP1
003	TF	SUIHO	–	187 (178.1)	-8.8	12.4	–	+3200	–	–	Basic RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	ENBIM	195 (186.5)	-8.8	1.0(-14000)	L	9000	FL140	-230 (-14000)	Basic RNP1

STANDARD ARRIVAL CHART - INSTRUMENT

RJSI / HANAMAKI — RNAV STAR RWY20

REMEN WEST ARRIVAL — Basic RNP1

Note GNSS required.



From SIOMO at or above 8000FT, to REMEN at or above 6000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SIOMO	-	-	-8.8	-	-	+8000	-	-	Basic RNP1
002	TF	REMEN	-	074 (064.7)	-8.8	14.9	-	+6000	-	-	Basic RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	SIOMO	039 (030.1)	-8.8	1.0(-14000)	R	8000	FL140	-210(-14000)	Basic RNP1

CHANGE : Description of VAR and PROC name.

INTENTIONALLY LEFT BLANK

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI — ILS Z or LOC Z RWY20

SAPPORO CONTROL	ILS – LOC	HANAMAKI RADIO	NO RADAR
124.5 – 303.8 120.575 – 277.1	109.3 IHP ILS – GP 332.0 ILS – DME CH-30X	118.2 – 126.2	



HIZME(FAF) : *393142.42N/1410935.33E*

NM to IHP	MAPt	2	3	4	5	FAF
ALT (3.0˚ APCH Path)	–	929	1247	1566	1884	2072

MISSED APPROACH

Climb via HPE R202 to HPE 8.0DME, turn left, direct to HPE VOR/DME and hold at 4000FT. Contact HANAMAKI RADIO.

Timing not authorized for defining the MAPt.



DME to IHP		0.2	0.7	1.1	2.5	5.6	9.3
NM to THR		0	0.5	0.9	2.3	5.4	9.1

MINIMA — THR elev. 298 — AD elev. 294

CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	498 (200)	550	640 (346)	900	760 (466)	1600
B				1000	860 (566)	
C					1000 (706)	2400
D				1400		3200

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI — ILS Y or LOC Y RWY20

SAPPORO CONTROL	ILS – LOC	HANAMAKI RADIO	NO RADAR
124.5 – 303.8 120.575 – 277.1	109.3 IHP ILS – GP 332.0 ILS – DME CH-30X	118.2 – 126.2	



NM to IHP	MAPt	2	3	4	5	FAF
ALT (3.0° APCH Path)	–	929	1247	1566	1884	2072

MISSED APPROACH

Climb via HPE R202 to
HPE 8.0DME, turn left,
direct to HPE VOR/DME
and hold at 4000FT.
Contact HANAMAKI RADIO.

Timing not authorized for
defining the MAPt.



DME to IHP	0.2	0.7	1.1	2.5		5.6	9.3	10.8
NM to THR	0	0.5	0.9	2.3		5.4	9.1	10.6

MINIMA		THR elev. 298		AD elev. 294	
CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	498 (200)	550	640 (346)	900	760 (466)	1600
B				1000	860 (566)	
C					1000 (706)	2400
D				1400		3200

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI — VOR RWY20

SAPPORO CONTROL	HANAMAKI VOR/DME	HANAMAKI RADIO	NO RADAR
124.5 – 303.8 120.575 – 277.1	112.8 HPE CH–75X *39°26′00″N/141°08′01″E*	118.2 – 126.2	



MASAH(FAF) : *393052.04N/1410931.09E*

NM to HPE	MAPt	2	3	4	FAF
ALT (3.0° APCH Path)	–	849	1168	1486	1805

MISSED APPROACH

Climb via HPE R202 to HPE 8.0DME, turn left, direct to HPE VOR/DME and hold at 4000FT.

Contact HANAMAKI RADIO.

Timing not authorized for defining the MAPt.



DME to HPE	0.4	1.5	2.5	5.0	10.0
NM to THR	0	1.1	2.1	4.6	9.6

MINIMA		THR elev. 298	AD elev. 294	
CAT			CIRCLING	
	MDA(H)	RVR/CMV	MDA(H)	VIS
A	690 (396)	900	760 (466)	1600
B		1000	860 (566)	
C			1000 (706)	2400
D		1400		3200

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI — VOR RWY02

SAPPORO CONTROL	HANAMAKI VOR/DME	HANAMAKI RADIO	NO RADAR
124.5 – 303.8 120.575 – 277.1	112.8 HPE CH–75X *39°26′00″N/141°08′01″E*	118.2 – 126.2	



NM to HPE	FAF	5	4	3	2	MAPt
ALT (3.0° APCH Path)	1925	1626	1308	989	671	–



MISSED APPROACH

Climb via HPE R014 to HPE 6.0DME, turn right, proceed to HPE VOR/DME and hold at 4500FT. Contact HANAMAKI RADIO.

Timing not authorized for defining the MAPt.

5.9	2.5	1.9	0.9		DME to HPE
5.0	1.6	1.0	0		NM to THR

Missed APCH climb gradient MNM 3.6%

MINIMA THR elev. 283 AD elev. 294

CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	640 (357)	1200	760 (466)	1600
B		1300	860 (566)	
C		1400	1000 (706)	2400
D	650 (367)	1600		3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI

RNP Z RWY02

SAPPORO CONTROL 124.5 – 303.8 120.575 – 277.1	RNP APCH	HANAMAKI RADIO 118.2 – 126.2	NO RADAR



NM to Next Fix	FAF	4	3	2	1	MAPt
ALT(3.0˚ APCH Path)	1900	1606	1288	969	651	–



MISSED APPROACH

Climb direct to SI251, turn right direct to HPE and hold at 4500FT.
Contact HANAMAKI RADIO.

(For using VOR/DME)
Climb via HPE R020 to HPE 6.0DME, turn right, direct to HPE VOR/DME and hold at 4500FT.
Contact HANAMAKI RADIO.

Missed APCH climb gradient MNM 4 .0%

MINIMA	THR elev.283		AD elev.294			
CAT	LNAV/VNAV		LNAV		CIRCLING	
	DA(H)	CMV	MDA(H)	CMV	MDA(H)	VIS
A	610(327)	1200	610(327)	1200	760(466)	1600
B		1300		1300	860(566)	
C	630(347)	1400	630(347)	1400	1000(706)	2400
D	650(367)	1600	650(367)	1600		3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE: Description of VAR.

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI — RNP Y RWY02(AR)

SAPPORO CONTROL 124.5 - 303.8 120.575 - 277.1	RNP AR RF required.	HANAMAKI RADIO 118.2 - 126.2	NO RADAR

For uncompensated Baro-VNAV systems, procedure not authorized below -20°C / above 45°C





MISSED APPROACH

Climb to 4500FT, direct to SI251, turn right direct to HPE and hold.
Contact HANAMAKI RADIO.

Missed APCH climb gradient MNM 4.0%

MINIMA	THR elev. 283	AD elev. 294
CAT	RNP 0.30	
	DA(H)	CMV
A	-	-
B		
C	595(312)	1400
D		1600

MINIMA with Missed APCH climb gradient of 2.5% are not established.

Authorization Required

CHANGE : PROC course. ESBEL,NOJYO abolished. ENBIM established. RNAV HLDG abolished(ESBEL). RNAV HLDG established(ENBIM).

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI RNP Y RWY02(AR)

CHANGE : PROC course. ESBEL,NOJYO abolished. ENBIM established. RNAV HLDG abolished(ESBEL). RNAV HLDG established(ENBIM).

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	ENBIM	-	-	-8.8	-	-	+9000	-	-	-
002	TF	ISIDO	-	189 (180.2)	-8.8	25.4	-	+4000	-	-	1.0
003	TF	KENDA	-	169 (160.3)	-8.8	5.0	-	3800	-	-	1.0
004	TF	SI252	-	169 (160.4)	-8.8	1.5	-	3312	-165	-3.00	0.3
005	RF Center: SIRF1 r=2.10NM	SI253	-	-	-8.8	7.7	R	848	-	-3.00	0.3
006	TF	RW02	Y	020 (010.7)	-8.8	1.6	-	333	-	-3.00/50	0.3
007	DF	SI251	Y	-	-8.8	-	-	-	-	-	1.0
008	DF	HPE	-	-	-8.8	-	R	4500	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	ENBIM	195 (186.5)	-8.8	1.0 (-14000)	L	9000	FL140	-230 (-14000)	1.0
Hold	HPE	178 (169.7)	-8.8	1.0 (-14000)	L	4500	FL140	-230 (-14000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
ENBIM	*395519.34N / 1411002.82E*	SIRF1	*392304.37N / 1411014.42E*
ISIDO	*392956.45N / 1410957.05E*		
KENDA	*392513.70N / 1411207.87E*		
SI252	*392347.07N / 1411247.89E*		
SI253	*392327.97N / 1410734.24E*		
RW02	*392503.58N / 1410757.62E*		
SI251	*393152.68N / 1410937.82E*		
HPE	*392600.09N / 1410800.60E*		

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI — RNP Z RWY20(AR)

SAPPORO CONTROL 124.5 - 303.8 120.575 - 277.1	RNP AR RF required.	HANAMAKI RADIO 118.2 - 126.2	NO RADAR

For uncompensated Baro-VNAV systems, procedure not authorized below -20°C / above 45°C



MISSED APPROACH

Climb to 4000FT, direct to SI052, turn left direct to HPE and hold.
Contact HANAMAKI RADIO.



MINIMA	THR elev. 298	AD elev. 294
CAT	RNP 0.30	
	DA(H)	RVR/CMV
A	-	-
B		
C	607(309)	1000
D		1400

Authorization Required

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI RNP Z RWY20(AR)

CHANGE : PROC renamed.

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	SIOMO	-	-	-8.8	-	-	+8000	-	-	-
002	TF	MOUSU	-	048 (038.8)	-8.8	17.1	-	+4800	-	-	1.0
003	TF	GANSU	-	048 (038.9)	-8.8	5.0	-	3700	-	-	1.0
004	TF	SI050	-	048 (038.9)	-8.8	1.3	-	3285	-165	-3.00	0.3
005	RF Center: SIRF2 r=2.10NM	SI051	-	-	-8.8	7.6	L	853	-	-3.00	0.3
006	TF	RW20	Y	199 (190.7)	-8.8	1.6	-	352	-	-3.00/54	0.3
007	DF	SI052	Y	-	-8.8	-	-	-	-	-	1.0
008	DF	HPE	-	-	-8.8	-	L	4000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	SIOMO	039 (030.1)	-8.8	1.0 (-14000)	R	8000	FL140	-210 (-14000)	1.0
Hold	HPE	006 (357.5)	-8.8	1.0 (-14000)	R	4000	FL140	-230 (-14000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
SIOMO	*390801.78N / 1405430.28E*	SIRF2	*392732.73N / 1411119.82E*
MOUSU	*392119.11N / 1410818.81E*		
GANSU	*392512.44N / 1411222.60E*		
SI050	*392613.23N / 1411326.21E*		
SI051	*392756.30N / 1410839.89E*		
RW20	*392623.24N / 1410817.11E*		
SI052	*391806.42N / 1410615.76E*		
HPE	*392600.09N / 1410800.60E*		

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI — RNP Y RWY20(AR)

SAPPORO CONTROL 124.5 - 303.8 120.575 - 277.1	RNP AR RF required.	HANAMAKI RADIO 118.2 - 126.2	NO RADAR

For uncompensated Baro-VNAV systems, procedure not authorized below -20°C / above 45°C



MISSED APPROACH

Climb to 4000FT, direct to SI052, turn left direct to HPE and hold.
Contact HANAMAKI RADIO.



MINIMA	THR elev. 298	AD elev. 294
CAT	RNP 0.30	
	DA(H)	RVR/CMV
A	-	-
B	-	-
C	607(309)	1000
D		1400

Authorization Required

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI RNP Y RWY20(AR)

CHANGE : PROC renamed.

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	REMEN	-	-	-8.8	-	-	+6000	-	-	-
002	TF	PALPA	-	016 (007.2)	-8.8	5.5	-	-	-	-	1.0
003	TF	NAKAN	-	016 (007.2)	-8.8	5.0	-	3700	-	-	1.0
004	TF	SI053	-	016 (007.2)	-8.8	2.5	-	2913	-165	-3.00	0.3
005	RF Center: SIRF2 r=2.10NM	SI051	-	-	-8.8	6.5	L	853	-	-3.00	0.3
006	TF	RW20	Y	199 (190.7)	-8.8	1.6	-	352	-	-3.00/54	0.3
007	DF	SI052	Y	-	-8.8	-	-	-	-	-	1.0
008	DF	HPE	-	-	-8.8	-	L	4000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	REMEN	074 (065.0)	-8.8	1.0 (-14000)	R	6000	FL140	-230 (-14000)	1.0
Hold	HPE	006 (357.5)	-8.8	1.0 (-14000)	R	4000	FL140	-230 (-14000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
REMEN	*391421.92N / 1411154.27E*	SIRF2	*392732.73N / 1411119.82E*
PALPA	*391951.68N / 1411248.23E*		
NAKAN	*392449.66N / 1411337.11E*		
SI053	*392716.81N / 1411401.29E*		
SI051	*392756.30N / 1410839.89E*		
RW20	*392623.24N / 1410817.11E*		
SI052	*391806.42N / 1410615.76E*		
HPE	*392600.09N / 1410800.60E*		

RJSI / HANAMAKI

Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : Map updated. BRG/DIST from ARP. Taseko established. Tsuchisawa abolished.

Call sign	BRG / DIST from ARP	Remarks
盛岡 Morioka	360°T / 16.4NM	JR駅 JR Station
城山 Shiroyama	012°T / 8.4NM	城跡 The site of a castle
豊沢 Toyosawa	293°T / 8.1NM	豊沢ダム Dam
田瀬湖 Taseko	121°T / 10.0NM	田瀬ダム Dam
北上 Kitakami	184°T / 8.9NM	JR駅 JR Station
水沢 Mizusawa	178°T / 17.4NM	JR駅 JR Station


RJSI / HANAMAKI
LDG CHART
ELEV 294ft
141˚10´
06´
08´
28´
26´
24´
10´
660
720
728
654
855
660
VAR 9˚W (2021)
VOR/DME
HANAMAKI
112.8 HPE
CH-75x
39˚26´00˝N/141˚08´01˝E
300FT
442
446
441
700
ALS
20
02
ABN
8200X150ft Asph-Conc
PAPI ANGLE 3.0˚
MEHT 20.0m (66ft)
429.0m FM THR
PAPI ANGLE 3.0˚
MEHT 22.5m (74ft)
452.4m FM THR
SALS
ALB
HANAMAKI RADIO
118.2-126.2
SCALE
1000 0 1000 3000 ft
500 0 500 1000 m
ELEVATIONS AND
HEIGHTS IN FEET
MEAN SEA LEVEL
CHANGE : VAR.

RJSI / HANAMAKI Minimum Vectoring Altitude CHART