

STANDARD DEPARTURE CHART-INSTRUMENT

RJFZ / TSUIKI

SID and TRANSITION

MISHIMA FIVE DEPARTURE

RWY 07 : Turn right....

RWY 25 : Turn left within 3NM....

....Climb via TQT R150 to TQT 15.0DME, then turn left via TQT 15.0DME counter clockwise ARC to TQT R092, then via MIT R180 to MIT TACAN.

Maintain FL150 between MIT R180/60.0DME and MINNE.

Cross MIT R180/14.0DME at assigned or specified altitude.

Note : Minimum rate of climb

JET....400FT/NM until passing 2800FT(RWY25)

PROP....340FT/NM until passing 2800FT(RWY25)

HIMESHIMA FOUR DEPARTURE

RWY 07 : Turn right....

RWY 25 : Turn left within 3NM....

....Climb via TQT R092 until HIMEH(TQT R092/29.1DME), then proceed as directed by ATC.

Cross HIMEH at assigned or specified altitude.

Note : Minimum rate of climb

JET....400FT/NM until passing 2800FT(RWY25)

PROP....340FT/NM until passing 2800FT(RWY25)

MUSASHI TRANSITION

After HIMEH, via TFE R346 to TFE VOR/DME.

KUGA SIX DEPARTURE

RWY 07 : Turn right....

RWY 25 : Turn left within 3NM....

....Climb via TQT R150 until TQT R150/15.0DME, turn left to intercept and proceed via IWT R240 (MRA5000FT) to IWT TACAN.

Cross HIMEH(IWT R240/33.6DME) at assigned or specified altitude.

Note : Minimum rate of climb

JET....400FT/NM until passing 2800FT(RWY25)

PROP....340FT/NM until passing 2800FT(RWY25)

HIMESHIMA REVERSAL THREE DEPARTURE

RWY 07 : Turn right....

RWY 25 : Turn left within 3NM....

....Climb via TQT R092 within 20NM of TQT TACAN, turn right reverse course to TQT TACAN, then proceed as directed by ATC.

Cross TQT TACAN at assigned or specified altitude.

Note : Minimum rate of climb

JET....400FT/NM until passing 2800FT(RWY25)

PROP....340FT/NM until passing 2800FT(RWY25)

CHANGE : PROC renamed(MISHIMA FIVE DEPARTURE). PROC course(MISHIMA FIVE DEPARTURE).

STANDARD DEPARTURE CHART-INSTRUMENT

RJFZ / TSUIKI

SID and TRANSITION

NAKATSU REVERSAL TWO DEPARTURE

RWY 07 : Turn right....

RWY 25 : Turn left within 3NM....

....Climb via TQT R150 within 20NM of TQT TACAN, turn(direction specified by ATC), reverse course to TQT TACAN, then proceed as directed by ATC.

Cross TQT TACAN at assigned or specified altitude. (MCA at TQT TACAN 6000FT)

Note : Minimum rate of climb

JET....400FT/NM until passing 2800FT(RWY25)

PROP....340FT/NM until passing 2800FT(RWY25)

KANMO TRANSITION

After TQT TACAN, proceed via TQT R351 to KANMO(TQT R351/8.6DME), then proceed as directed by ATC.

MINNE TRANSITION

After TQT TACAN, proceed via TQT R026 to MINNE, then via MIT R180 to MIT TACAN.

OGORI TRANSITION

After TQT TACAN, proceed via TQT R239 to OGORI(TQT R239/39.1DME), then proceed as directed by ATC.

Cross TQT 15.0DME at or above 7000FT.


CHANGE : Course FM MINNE to MIT(MINNE TRANSITION).

STANDARD DEPARTURE CHART-INSTRUMENT

RJFZ / TSUIKI

SID and TRANSITION

CHANGE : PROC renamed(MISHIMA FIVE DEPARTURE). PROC course(MISHIMA FIVE DEPARTURE, MINNE TRANSITION).



STANDARD ARRIVAL CHART - INSTRUMENT


RJFZ / TSUIKI

STAR

HIMEH ARRIVAL

From over HIMEH (IWT R240/33.6DME), proceed via IWT R240,
then turn left, proceed via TQT 24.0DME clockwise ARC to TQT R131,
then turn right proceed via TQT R131 to SANKO (TQT R131/14.1DME).

Cross SANKO at or above 6000FT.



CHANGE : ALT restriction at SANKO. MHA. Description of RADAR Service.

TACAN Z RWY25

VAR 8°W (2022)

20NM

MAPt FAF D10.0 TQT
D1.4 TQT D6.0 TQT^{al} 266

TQT

D12.0 TQT ARC

131°

SANKO(IAF)
R131/D14.1 TQT

131°

311°

D21.1 TQT

MHA 6000

R086

R131

2266°

2335°

3085°

2747°

3111°

3936

090°

180°

360°

MSA 25NM

5000 2900

090° TQT 270°

5900 4200

360°

EMERG SAFE ALT 100NM 8500


Figure 1-1 is a typical instrument approach chart for a VOR/DME approach. The chart shows a 131° heading from the DME to TQT, a 266° heading from the FAF to the TQT R086, and a 311° heading from the TQT R131 to the SANKO (IAF) 6000. The chart also shows the DME to TQT, NM to THR, and the D12.0 TQT ARC. The chart includes a shaded area representing the MDA and a dashed line representing the MAPt VDP.

MINIMA		THR elev. 19	AD elev. 28	
CAT			CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	440 (421)	1500	520 (492)	1600
B			660 (632)	
C		1800	760 (732)	2400
D		2000	810 (782)	3200

INSTRUMENT APPROACH CHART

RJFZ / TSUIKI

TACAN Y RWY25




CHANGE : MHA. Description of RADAR Service.


INSTRUMENT APPROACH CHART

RJFZ / TSUIKI

TACAN X RWY25



INSTRUMENT APPROACH CHART



CHANGE : ENLUG, IPDIM established. VABLA, UPGUN abolished. Missed APCH PROC.