


## RJFE / FUKUE

## AD CHART



**INTENTIONALLY LEFT BLANK**

## STANDARD DEPARTURE CHART - INSTRUMENT

RJFE / FUKUE

SID

NAGASAKI FOUR DEPARTURE


RWY 03 : Climb RWY HDG to 1300FT, turn right HDG127° .....,  
RWY 21 : Climb RWY HDG to 1300FT, turn left HDG037° .....,  
....to intercept and proceed via FUE R082 to OLE VOR/DME.

IKI FOUR DEPARTURE

RWY 03 : Climb RWY HDG to 900FT, turn right .....,  
RWY 21 : Climb RWY HDG to 1300FT, turn left HDG358° .....,  
....to intercept and proceed via FUE R043 to IKI VOR/DME.

FUKUE REVERSAL THREE DEPARTURE


RWY 03 : Climb RWY HDG to 2000FT, turn right .....,  
RWY 21 : Climb RWY HDG to 2000FT, turn left .....,  
....direct to FUE VOR/DME.



STANDARD DEPARTURE CHART - INSTRUMENT

RJFE / FUKUE

RNAV SID



AGRIT ONE DEPARTURE

RWY03 : Climb on HDG033° at or above 700FT, direct to FE300, to AGRIT.  
RWY21 : Climb on HDG213° at or above 700FT, direct to FE100, to FE101, to AGRIT.

RWY03

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	033 (025.6)	-7.5	-	-	+700	-	-	Basic RNP1
002	DF	FE300	-	-	-7.5	-	-	-	-	-	Basic RNP1
003	TF	AGRIT	-	092 (084.9)	-7.5	22.1	-	-	-	-	Basic RNP1

RWY21


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	213 (205.7)	-7.5	-	-	+700	-	-	Basic RNP1
002	DF	FE100	-	-	-7.5	-	-	-	-	-	Basic RNP1
003	TF	FE101	-	123 (115.8)	-7.5	4.8	-	-	-	-	Basic RNP1
004	TF	AGRIT	-	065 (057.4)	-7.5	27.0	-	-	-	-	Basic RNP1

CHANGE : New PROC.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFE / FUKUE

RNAV SID



## STANDARD DEPARTURE CHART - INSTRUMENT

RJFE / FUKUE

RNAV SID

OLVIN ONE DEPARTURE

## RWY03

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	033 (025.6)	-7.5	-	-	+700	-	-	Basic RNP1
002	DF	KAMIG	-	-	-7.5	-	-	+6000	-	-	Basic RNP1
003	TF	OLVIN	-	044 (036.3)	-7.5	35.9	-	-	-	-	Basic RNP1

## RWY21


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	213 (205.7)	-7.5	-	-	+700	-	-	Basic RNP1
002	DF	FE100	-	-	-7.5	-	-	-	-	-	Basic RNP1
003	TF	FE102	-	123 (115.8)	-7.5	6.2	-	-	-	-	Basic RNP1
004	TF	KAMIG	-	029 (021.9)	-7.5	30.9	-	+6000	-	-	Basic RNP1
005	TF	OLVIN	-	044 (036.3)	-7.5	35.9	-	-	-	-	Basic RNP1

CHANGE : New PROC.

## INSTRUMENT APPROACH CHART

RJFE / FUKUE

LOC RWY03



CHANGE : Secondary FREQ abolished(FUKUE RADIO).


RJFE / FUKUE

KOBE CONTROL  
118.9 - 303.8  
134.25 - 315.5


FUKUE VOR/DME  
115.8 FUE  
CH-105X ::=  
32°40'07"N/128°49'36"E

FUKUE RADIO  
118.35  
AFIS provided  
by Fukuoka Airport Office

NO RADAR



NM to FUE	FAF	5	4	MAPt
ALT(3.0° APCH Path)	1865	1366	1048	—



Missed APCH climb gradient MNM 5.0%				
MINIMA		THR elev. 223	AD elev. 251	
CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	880 (657)	1200	880 (629)	1600
B	920 (697)	1400	920 (669)	
C	970 (747)		1280 (1029)	
D	1010 (787)	1800	1810 (1559)	3200

Circling to WEST side of RWY only.  
MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : Secondary FREQ abolished(FUKUE RADIO).




## INSTRUMENT APPROACH CHART



## INSTRUMENT APPROACH CHART

RJFE / FUKUE

LOC Y RWY21




NM to IFE	MAPt	2	3	4	5	6	FAF
ALT(3.0° APCH Path)	—	801	1120	1438	1756	2075	2154

**MISSED APPROACH**

Climb to 2000FT on HDG216°,  
turn left, direct to FUE  
VOR/DME and hold  
at 3000FT.  
Contact FUKUE RADIO.

Timing not authorized for defining the MAPt.



DME to IFE	0.5	1.3	3.0	6.3
NM to THR	0	0.8	2.5	5.8

Missed APCH climb gradient MNM 3.0%

MINIMA      THR elev. 273      AD elev. 251


CAT	CIRCLING		CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	570 (319)	900	700 (449)	1600
B		1000	710 (459)	
C			1280 (1029)	2400
D		1400	1810 (1559)	3200

Circling to WEST side of RWY only.

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : VAR. PROC course. MISSED APPROACH course.

## INSTRUMENT APPROACH CHART





**INTENTIONALLY LEFT BLANK**

## INSTRUMENT APPROACH CHART

RJFE / FUKUE

RNAV(GNSS) RWY03

KOBE CONTROL 118.9 - 303.8 134.25 - 315.5	1. DME/DME RNP0.3 not authorized. 2. RNP0.3 required. 3. GNSS required.	FUKUE RADIO 118.35 AFIS provided by Fukuoka Airport Office	NO RADAR
---	---	---	----------



Missed APCH climb gradient MNM 5.0%

CAT	THR elev. 223		AD elev. 251		CIRCLING	
	DA(H)	CMV	MDA(H)	CMV	MDA(H)	VIS
A	1010(787)	1200	1010(787)	1200	1010(759)	1600
B		1400		1400		
C	1050(827)		1050(827)		1280(1029)	2400
D	1090(867)	1800	1090(867)	1800	1810(1559)	3200

Circling to WEST side of RWY only.


MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : New PROC.

## INSTRUMENT APPROACH CHART

RJFE / FUKUE

RNAV(GNSS) RWY21





RJFE / FUKUE


Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : Secondary FREQ abolished.

Call sign	BRG / DIST from ARP	Remarks
奈留島 Narushima	029°T / 10.8NM	浦港 Harbor
枇島 Kabashima	053°T / 10.2NM	島 Island
京ノ岳 Kyonodake	304°T / 10.1NM	レーダーサイト Radar site
蝶螺島 Sazaejima	055°T / 4.0NM	島 Island
二本楠 Nihongusu	275°T / 5.2NM	十字路 Intersection
富江港 Tomieko	230°T / 4.4NM	港 Harbor
大瀬崎 Osezaki	255°T / 12.2NM	灯台 Lighthouse
黒島 Kuroshima	179°T / 4.0NM	島 Island
黄島 Oshima	151°T / 6.9NM	島 Island






RJFE / FUKUE

Minimum Vectoring Altitude CHART

CHANGE : Shape of segment.



**INTENTIONALLY LEFT BLANK**