AERODROME CHART

KAGOSHIMA AP
ELEV 271.6m(891ft) ARP

MARKING AIDS

RWY-HOLDING POSITION MARKINGS and STOP BAR LIGHTS

RWY-holding position markings and Runway guard lights are located on TWY T1 through T8.
Stop bar lights are located on TWY T1 through T6, T8
: their location are 75m off the RWY centerline of RWY 16/34.
Mandatory instruction markings are located on TWY T1 through T8.

COMMON WAYS OF ITS MARKING AND LIGHTS





CHANGE : AIS abolished.

RJFK / KAGOSHIMA AD CHART



Designation	Call Sign	Frequency (MHz)
ATIS	Kagoshima Airport	127.05
DLVRY	Kagoshima Delivery	121.8
GND	Kagoshima Ground	121.7
TWR	Kagoshima Tower	118.2 126.2 261.2

CHANGE : AIS abolished.

DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC
Transverse Mercator Projection

AERODROME OBSTACLE CHART - ICAO
TYPE A (OPERATING LIMITATIONS)

MAGNETIC VARIATION 7°W - OCT 2022



LEGEND

- IDENTIFICATION NUMBER
- POLE, TOWER, SPIRE, ANTENNA, ETC
- TREE
- LEVEE
- RAILROAD
- RIVER
- TRANSMISSION LINE OR OVERHEAD CABLE
- TRIANGULATION POINT
- AERONAUTICAL GROUND LIGHT
- BUILDING OR LARGE STRUCTURE
- CONTOURS(ft)

AMENDMENT RECORD		
Nr	DATE	ENTERED BY

CHANGE : TWY T7 installed.

測量法に基づく国土地理院長承認(使用) R 5JHs 223、国土数値情報(河川、緊急輸送道路)

AERODROME OBSTACLE CHART-ICAO
TYPE B

DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC
Transverse Mercator Projection



AMENDMENT RECORD

Nr	DATE	ENTERED BY

CHANGE : TWY T7 installed.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFK / KAGOSHIMA SID and TRANSITION

CHANGE : OVSID ONE DEPARTURE established. KAJIKI TRANSITION established. PROC course(SASIK TRANSITION, KAGOSHIMA TRANSITION).
SOGIE THREE DEPARTURE, SAKURAJIMA TRANSITION abolished.

OVSID ONE DEPARTURE

RWY 16 : Climb RWY HDG to KGE2.0DME, turn left HDG 303°...
RWY 34 : Climb RWY HDG to 2000FT, turn right...
... to intercept and proceed via KGE R348 to OVSID.

Note RWY16 : 5.0% climb gradient required up to 1300FT.
RWY34 : 5.0% climb gradient required up to 2000FT.
OBST ALT 1181FT located at 1.4NM 319˚ FM end of RWY34.
OBST ALT 2067FT located at 6.7NM 345˚ FM end of RWY34.

KAJIKI TRANSITION

From over OVSID, turn left, direct to KGE VOR/DME.
Cross KGE VOR/DME at or above 7000FT.

SASIK TRANSITION

From over OVSID, via KGE R348 to SASIK.

KAGOSHIMA TRANSITION

From over OVSID, turn left to intercept and proceed via HKC R003 to HKC VORTAC.



STANDARD DEPARTURE CHART - INSTRUMENT

RJFK / KAGOSHIMA RNAV SID

MIDAI THREE DEPARTURE		RNAV 1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll. 2) RADAR service required.	Critical DME	RWY16 : HKC:7NM to OICHI ─ 2NM to OICHI KGE:7NM to OICHI ─ 2NM to OICHI
	DME GAP	RWY16 : DER ─ 7NM to OICHI RWY34 : DER ─ 12NM to SMIKO
	Inappropriate Navaids	See AD 1.1.6.10.3. Inappropriate NAVAIDs for RNAV1



RWY16 : Climb on HDG 157˚ at or above 1300FT, turn right direct to OICHI, to SMIKO at or above 7000FT, to MIDAI at or above FL160.

RWY34 : Climb on HDG 337˚ at or above 2000FT, turn right direct to FK400, to SMIKO at or above 7000FT, to MIDAI at or above FL160.

Note RWY34 : 5.0% climb gradient required up to 3100FT.
OBST ALT 3117FT located at 7.7NM 046˚ FM end of RWY34.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFK / KAGOSHIMA RNAV SID

MIDAI THREE DEPARTURE

RWY16

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	157 (150.1)	-7.2	–	–	+1300	–	–	RNAV1
002	DF	OICHI	–	–	-7.2	–	R	–	–	–	RNAV1
003	TF	SMIKO	–	099 (091.5)	-7.2	9.4	–	+7000	–	–	RNAV1
004	TF	MIDAI	–	099 (091.6)	-7.2	20.3	–	+FL160	–	–	RNAV1

RWY34

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	337 (330.1)	-7.2	–	–	+2000	–	–	RNAV1
002	DF	FK400	–	–	-7.2	–	R	–	–	–	RNAV1
003	TF	SMIKO	–	156 (148.5)	-7.2	15.8	–	+7000	–	–	RNAV1
004	TF	MIDAI	–	099 (091.6)	-7.2	20.3	–	+FL160	–	–	RNAV1

STANDARD DEPARTURE CHART - INSTRUMENT

RJFK / KAGOSHIMA — RNAV SID and TRANSITION

ATRUK ONE DEPARTURE ASHIKITA TRANSITION		RNAV1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll. 2) RADAR service required.	Critical DME	RWY16 : HKC 6.0NM to FK601 - FK601 11.0NM to ATRUK - 4.0NM to ATRUK KGE 6.0NM to FK601 - 5.0NM to FK601 4.0NM to FK601 - 4.0NM to ATRUK MZE 6.0NM to FK601 - 4.0NM to FK601 3.0NM to ATRUK - 1.0NM to ATRUK RWY34 : HKC 3.0NM from DER - 5.0NM to ATRUK KGE 5.0NM to OVSID - 3.0NM to OVSID 1.0NM to OVSID - 5.0NM to ATRUK MZE 3.0NM to ATRUK - 1.0NM to ATRUK
	DME GAP	RWY16 : DER - 6.0NM to FK601 RWY34 : DER - 3.0NM from DER
	Inappropriate Navaids	See AD1.1.6.10.3 Inappropriate NAVAIDs for RNAV1



ATRUK ONE DEPARTURE

RWY16 : Climb on HDG158° at or above 1300FT, direct to FK602, turn right direct to FK601, to ATRUK.
RWY34 : Climb on HDG338° at or above 2000FT, turn right direct to OVSID, to ATRUK.

Note RWY16 : 7.0% climb gradient required up to 2000FT.
OBST ALT 896FT located at 0.6NM 141° FM end of RWY16.
Note RWY34 : 5.0% climb gradient required up to 2000FT.
OBST ALT 1181FT located at 1.4NM 319° FM end of RWY34.
OBST ALT 2067FT located at 6.7NM 345° FM end of RWY34.

ASHIKITA TRANSITION

From ATRUK, to SASIK.

CHANGE : New PROC.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFK / KAGOSHIMA

RNAV SID and TRANSITION

ATRUK ONE DEPARTURE

RWY16

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	158 (150.1)	-7.4	-	-	+1300	-	-	RNAV1
002	DF	FK602	Y	-	-7.4	-	-	-	-	-	RNAV1
003	DF	FK601	-	-	-7.4	-	R	-	-	-	RNAV1
004	TF	ATRUK	-	006 (358.9)	-7.4	13.7	-	-	-	-	RNAV1

RWY34

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	338 (330.1)	-7.4	-	-	+2000	-	-	RNAV1
002	DF	OVSID	-	-	-7.4	-	R	-	-	-	RNAV1
003	TF	ATRUK	-	348 (340.9)	-7.4	7.5	-	-	-	-	RNAV1

ASHIKITA TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	ATRUK	-	-	-7.4	-	-	-	-	-	RNAV1
002	TF	SASIK	-	348 (340.9)	-7.4	14.4	-	-	-	-	RNAV1

CHANGE : New PROC.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFK / KAGOSHIMA — RNAV SID

MIZOBE ONE DEPARTURE		RNAV1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll. 2) RADAR service required.	Critical DME	RWY16 : HKC 9.0NM to HKC - 3.0NM to HKC KGE 9.0NM to HKC - HKC SGE 3.0NM to HKC - HKC RWY34 : HKC 2.0NM from DER - 14.0NM to HKC KGE 2.0NM from DER - 9.0NM to HKC 7.0NM to HKC - 6.0NM to HKC 4.0NM to HKC - 2.0NM to HKC SGE 3.0NM to HKC - HKC
	DME GAP	RWY16 : DER - 9.0NM to HKC RWY34 : DER - 2.0NM from DER
	Inappropriate Navaids	See AD1.1.6.10.3 Inappropriate NAVAIDs for RNAV1



RWY16 : Climb on HDG158° at or above 1300FT, direct to FK602, turn right direct to HKC at or above 5000FT.

RWY34 : Climb on HDG338° at or above 3500FT, turn left direct to HKC at or above 5000FT.

Note RWY16 : 7.0% climb gradient required up to 2000FT.
OBST ALT 890FT located at 0.6NM 154° FM end of RWY16.

Note RWY34 : 5.0% climb gradient required up to 3500FT.
OBST ALT 1181FT located at 1.4NM 319° FM end of RWY34.
OBST ALT 2067FT located at 6.7NM 345° FM end of RWY34.

RWY16

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	158 (150.1)	-7.4	-	-	+1300	-	-	RNAV1
002	DF	FK602	Y	-	-7.4	-	-	-	-	-	RNAV1
003	DF	HKC	-	-	-7.4	-	R	+5000	-	-	RNAV1

RWY34

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	338 (330.1)	-7.4	-	-	+3500	-	-	RNAV1
002	DF	HKC	-	-	-7.4	-	L	+5000	-	-	RNAV1

CHANGE : New PROC.

STANDARD ARRIVAL CHART -INSTRUMENT

RJFK / KAGOSHIMA — RNAV STAR RWY34

SIMAZ EAST ARRIVAL	RNAV 1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.



From SPICA at or above 10000FT, to JANUS at or above 6000FT, to CELES at or above 4100FT, to KEPLA at or above 3300FT, to MUSES at or above 3100FT, to SIMAZ at above 2800FT.

Critical DME	–
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SPICA	–	–	-7.2	–	–	+10000	–	–	RNAV1
002	TF	JANUS	–	245 (237.8)	-7.2	21.7	–	+6000	–	–	RNAV1
003	TF	CELES	–	245 (237.8)	-7.2	9.6	–	+4100	-230	–	RNAV1
004	TF	KEPLA	–	265 (257.8)	-7.2	3.0	–	+3300	–	–	RNAV1
005	TF	MUSES	–	297 (289.6)	-7.2	1.6	–	+3100	–	–	RNAV1
006	TF	SIMAZ	–	297 (289.6)	-7.2	1.7	–	+2800	-200	–	RNAV1

Path	Waypoint Identifier	Inbound Course ˚M(˚T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	SPICA	277 (270.1)	-7.4	1.0(-14000) 1.5(+14001)	R	10000	–	-230(-14000) -240(+14001)	RNAV1
Hold	CELES	265 (257.8)	-7.2	1.0(-14000) 1.5(+14001)	L	4100	–	-230(-14000) -240(+14001)	RNAV1

CHANGE : RNAV HLDG established(SPICA).

STANDARD ARRIVAL CHART -INSTRUMENT

RJFK / KAGOSHIMA — RNAV STAR RWY34

SIMAZ NORTH ARRIVAL — RNAV 1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.



From HKC at or above 3500FT, to ROKET at or above 3100FT, to TOPPY, to SIMAZ at or above 2800FT.

Critical DME	KGE : 3NM to ROKET - SIMAZ
DME GAP	HKC - 3NM to ROKET
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	HKC	–	–	-6.9	–	–	+3500	–	–	RNAV1
002	TF	ROKET	–	114 (107.2)	-6.9	6.0	–	+3100	–	–	RNAV1
003	TF	TOPPY	–	114 (107.2)	-6.9	3.2	–	–	-185	–	RNAV1
004	TF	SIMAZ	–	067 (059.9)	-6.9	3.0	–	+2800	–	–	RNAV1

Path	Waypoint Identifier	Inbound Course ˚M(˚T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	HKC	115 (107.1)	-7.4	1.0(-14000) 1.5(+14001)	R	5000	–	-230(-14000) -240(+14001)	RNAV1

CHANGE : RNAV HLDG established. HLDG for using NAVAID abolished(HKC).

STANDARD ARRIVAL CHART -INSTRUMENT

RJFK / KAGOSHIMA — RNAV STAR RWY34

SIMAZ SOUTH ARRIVAL — RNAV 1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.



From ISKID, to MAGIL at or above 3500FT, to ROKET at or above 3100FT, to TOPPY, to SIMAZ at or above 2800FT.

Critical DME	–
DME GAP	ISKID - 3NM to MAGIL 1NM to MAGIL - SIMAZ
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	ISKID	–	–	-6.9	–	–	–	–	–	RNAV1
002	TF	MAGIL	–	049 (042.0)	-6.9	5.9	–	+3500	–	–	RNAV1
003	TF	ROKET	–	098 (091.4)	-6.9	4.1	–	+3100	–	–	RNAV1
004	TF	TOPPY	–	114 (107.2)	-6.9	3.2	–	–	-185	–	RNAV1
005	TF	SIMAZ	–	067 (059.9)	-6.9	3.0	–	+2800	–	–	RNAV1

Path	Waypoint Identifier	Inbound Course ˚M(˚T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	ISKID	049 (042.0)	-7.4	1.0(-14000) 1.5(+14001)	L	6000	–	-230(-14000) -240(+14001)	RNAV1

CHANGE : RNAV HLDG established. HLDG for using NAVAID abolished(ISKID).

STANDARD ARRIVAL CHART -INSTRUMENT

RJFK / KAGOSHIMA — RNAV STAR RWY34

KINKOH ARRIVAL — RNAV 1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.



From KINKO, to IROHA at or above 7000FT, to YOGAN at or above 6000FT, to ZAIHO at or above 3300FT.

Critical DME	JAT : 10.2NM to IROHA – 5.7NM to IROHA NHT : 5.6NM to IROHA – 2.4NM to IROHA 2.4NM to ZAIHO – 1.2NM to ZAIHO HKC : 4.4NM to ZAIHO – 1.3NM to ZAIHO
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	KINKO	–	–	-6.9	–	–	–	–	–	RNAV1
002	TF	IROHA	–	045 (038.6)	-6.9	11.1	–	+7000	–	–	RNAV1
003	TF	YOGAN	–	046 (038.6)	-6.9	4.0	–	+6000	–	–	RNAV1
004	TF	ZAIHO	–	337 (330.2)	-6.9	7.2	–	+3300	–	–	RNAV1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	YOGAN	338 (330.2)	-7.4	1.0(-14000) 1.5(+14001)	R	6000	–	-230(-14000) -240(+14001)	RNAV1

CHANGE : RNAV HLDG established. HLDG for using NAVAID abolished(YOGAN).

STANDARD ARRIVAL CHART-INSTRUMENT

RJFK / KAGOSHIMA — RNAV STAR RWY16

OGOJO ARRIVAL — RNAV 1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.



From SPICA at or above 10000FT, to DEMET at or above 10000FT, to PERSE at or above 7000FT, to OGOJO at or above 5000FT.

Critical DME	–	–
DME GAP	–	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1	

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SPICA	–	–	-7.2	–	–	+10000	–	–	RNAV1
002	TF	DEMET	–	284 (276.6)	-7.2	20.1	–	+10000	–	–	RNAV1
003	TF	PERSE	–	284 (276.4)	-7.2	13.7	–	+7000	–	–	RNAV1
004	TF	OGOJO	–	283 (276.3)	-7.2	3.6	–	+5000	–	–	RNAV1

Path	Waypoint Identifier	Inbound Course ˚M(˚T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	SPICA	277 (270.1)	-7.4	1.0(-14000) 1.5(+14001)	R	10000	–	-230(-14000) -240(+14001)	RNAV1

CHANGE : RNAV HLDG established.

STANDARD ARRIVAL CHART-INSTRUMENT

RJFK / KAGOSHIMA — RNAV STAR RWY16

YUKSA ARRIVAL	RNAV 1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.



From MOCOS at or above 10000FT, to SEPPE at or above 10000FT, to JADDO, to YUKSA at or above 5000FT.

Critical DME	MZE	2NM to JADDO - JADDO
	KUE	1NM to YUKSA - YUKSA
	MZE	1NM to YUKSA - YUKSA
DME GAP	–	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1	

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	MOCOS	–	–	-6.9	–	–	+10000	–	–	RNAV1
002	TF	SEPPE	–	281 (273.6)	-6.9	4.0	–	+10000	–	–	RNAV1
003	TF	JADDO	–	280 (273.6)	-6.9	8.7	–	–	–	–	RNAV1
004	TF	YUKSA	–	231 (224.0)	-6.9	7.3	–	+5000	–	–	RNAV1

CHANGE : Description of VAR and PROC name.

STANDARD ARRIVAL CHART-INSTRUMENT

RJFK / KAGOSHIMA

RNAV STAR RWY16

OIDON ARRIVAL	RNAV 1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.

VAR 7˚W



From HKC at or above 4500FT, to OIDON at or above 4500FT.

Critical DME	HKC	7NM to OIDON - OIDON
DME GAP	HKC - 10NM to OIDON	
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1	

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	HKC	–	–	-6.9	–	–	+4500	–	–	RNAV1
002	TF	OIDON	–	351 (343.6)	-6.9	13.7	–	+4500	–	–	RNAV1

CHANGE : Description of VAR and PROC name.

INTENTIONALLY LEFT BLANK

INSTRUMENT APPROACH CHART

RJFK / KAGOSHIMA — ILS Z or LOC Z RWY34

KAGOSHIMA APP	ILS - LOC	KAGOSHIMA TOWER	RADAR AVBL
126.0 –119.4 120.8 –261.2	111.7 IKG ILS–GP 333.5 ILS–DME CH–54X	118.2 –126.2 –261.2	ATIS 127.05



NM to IKG	MAPt	2	3	4	5	FAF
ALT (3.0˚ APCH Path)	–	1490	1809	2127	2446	2471

MISSED APPROACH

Climb to 1300FT on HDG337˚,
turn left, direct to HKC VORTAC
and hold at 5000FT.
Contact KAGOSHIMA APP.

No turn before IKG 0.6DME.
Timing not authorized for defining the MAPt.



DME to IKG	0.2	0.6	1.2	5.1	8.1	11.1
NM to THR	0	0.5	1.1	4.9	7.9	10.9

Missed APCH climb gradient MNM 5.0%

MINIMA THR elev. 859 AD elev. 891

CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	1059 (200)	550	1240 (381)	900	1680 (789)	1600
B				1000		
C						2400
D				1400	1710 (819)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : MINIMA for circling. HLDG pattern.

INSTRUMENT APPROACH CHART

RJFK / KAGOSHIMA

ILS Y or LOC Y RWY34

KAGOSHIMA APP	ILS - LOC	KAGOSHIMA TOWER	RADAR AVBL
126.0 –119.4 120.8 –261.2	111.7 IKG ILS–GP 333.5 ILS–DME CH–54X	118.2 –126.2 –261.2	ATIS 127.05



NM to IKG	MAPt	2	3	4	5	6	7	FAF
ALT (3.0˚ APCH Path)	–	1490	1809	2127	2446	2764	3082	3245

MISSED APPROACH

Climb to 1300FT on HDG337˚,
turn left, direct to HKC
VORTAC and hold at 5000FT.
Contact KAGOSHIMA APP.

No turn before IKG 0.6DME.
Timing not authorized for defining the MAPt.



DME to IKG	0.2	0.6	1.2	7.5
NM to THR	0	0.5	1.1	7.4

Missed APCH climb gradient MNM 5.0%.

MINIMA THR elev. 859 AD elev. 891

CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	1059 (200)	550	1240 (381)	900	1680 (789)	1600
B				1000		
C						2400
D				1400	1710 (819)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : MINIMA for circling. HLDG pattern.

INSTRUMENT APPROACH CHART

RJFK / KAGOSHIMA — VOR RWY34

KAGOSHIMA APP	KAJIKI VOR/DME	KAGOSHIMA TOWER	RADAR AVBL
126.0 –119.4 120.8 –261.2	115.7 KGE CH–104X *31°47′51″N/130°43′34″E*	118.2 –126.2 –261.2	ATIS 127.05



MISSED APPROACH

At KGE VOR/DME, turn right, climb via KGE R354 to 3500FT, turn left, direct to HKC VORTAC and hold at 5000FT. Contact KAGOSHIMA APP.



MINIMA THR elev. 859 AD elev. 891

CAT			CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	1350 (491)	1000	1680 (789)	1600
B		1200		
C				2400
D		1600	1710 (819)	3200

CHANGE : MINIMA for circling. HLDG pattern.

INSTRUMENT APPROACH CHART

RJFK / KAGOSHIMA VOR A

KAGOSHIMA APP	KAJIKI VOR/DME	KAGOSHIMA TOWER	RADAR AVBL
126.0 –119.4 120.8 –261.2	115.7 KGE CH–104X *31˚47´51˝N/130˚43´34˝E*	118.2 –126.2 –261.2	ATIS 127.05





MISSED APPROACH

Turn left, via KGE R348 to KGE 7.0DME, turn left, direct to KGE VOR/DME and hold at 4000FT.
Contact KAGOSHIMA APP.

MINIMA AD elev. 891

CAT	CIRCLING	
	MDA(H)	VIS
A	1680 (789)	1600
B		
C		2400
D	1710 (819)	3200

CHANGE : Missed APCH course. MINIMA. OCA(H) established. TESAB established. HLDG pattern.

INSTRUMENT APPROACH CHART

RJFK / KAGOSHIMA — RNP RWY34(LPV only)

KAGOSHIMA APP	RNP APCH	KAGOSHIMA TOWER	RADAR AVBL
126.0 –119.4 120.8 –261.2	MSAS CH75684 M34A	118.2 –126.2 –261.2	ATIS 127.05

VAR 7°W





Missed APCH climb gradient MNM 5.0%

MINIMA	THR elev.859		AD elev.891	
CAT	LPV		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	VIS
A	1192(333)	900	1680(789)	1600
B		1000		
C				2400
D		1400	1710(819)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJFK / KAGOSHIMA

RNP RWY34(LPV only)

FAS DATA BLOCK

Operation type	0	LTP/FTP ellipsoidal height	+02939
SBAS service provider identifier	2	FPAP latitude	*314854.3765N*
Airport identifier	RJFK	FPAP longitude	*1304241.3430E*
Runway	34	Threshold crossing height	00017.3
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M34A	⊿ length offset	0000
LTP/FTP latitude	*314730.0345N*	HAL	40.0
LTP/FTP longitude	*1304338.3800E*	VAL	50.0
CRC remainder	7F3AEA21		

Required additional data

LTP/FTP orthometric height	262.2

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJFK / KAGOSHIMA

RNP RWY16

KAGOSHIMA APP	RNP APCH	KAGOSHIMA TOWER	RADAR AVBL
126.0 –119.4 120.8 –261.2		118.2 –126.2 –261.2	ATIS 127.05



YUKSA (IAF)	*320313.27N* *1303258.90E*
OIDON (IAF)	*315500.23N* *1303024.92E*
OGOJO (IAF)	*320101.48N* *1304237.57E*
WAZZE (IF)	*315801.01N* *1303631.04E*
FK650 (SDF)	*315550.94N* *1303759.30E*
YUSUI (FAF)	*315340.76N* *1303927.52E*
FK651 (SDF)	*315151.45N* *1304041.55E*
RW16 (MAPt)	*314854.41N* *1304241.34E*
KAGOSHIMA (HKC) (MAHF)	*314150.00N* *1303458.59E*

NM to Next Fix	FAF	5	4	3
ALT (3.0˚ APCH Path)	2707	2548	2229	1911



MISSED APPROACH
Turn right direct to HKC and hold at 5000FT.
Contact KAGOSHIMA APP.

CHANGE : MINIMA for circling.

MINIMA THR elev. 906 AD elev. 891

CAT	LNAV/VNAV		LNAV		CIRCLING	
	DA(H)	CMV	MDA(H)	CMV	MDA(H)	VIS
A	Not applicable		1610 (719)	1500	1680 (789)	1600
B						
C				1800		2400
D				2000	1710 (819)	3200

INTENTIONALLY LEFT BLANK

RJFK / KAGOSHIMA

VISUAL APPROACH
KINKO VISUAL RWY34

KAGOSHIMA APP	ILS - LOC	KAGOSHIMA TOWER	ATIS
126.0 –119.4 120.8 –261.2	111.7 IKG CH–54X ILS–GP 333.5	118.2 –126.2 –261.2	127.05



When visual approaches to RWY34 are in progress, arriving aircraft may be vectored into the ISKID for KINKO VISUAL RWY34 APPROACH.

In the event of a go-around, climb via IKG LOC and RWY HDG to 3500FT until receiving ATC instructions.

<KINKO VISUAL RWY34 APPROACH>

After ISKID, aircraft proceed via seashore lines to the mouth of the Beppu River (KGE R226), proceed via seashore lines to ISLANDs(HKC R089) until intercept to RWY34 RWY center line, and proceed to RWY34(IKG LOC course).

Aircraft is recommended KGE 10.5DME(HKC R168) at or above 3500FT.

Note1: Pilot is urged to report promptly to ATC when lose sight of landmark(SAKURAJIMA, Seashore Lines and ISLANDs) and the preceding aircraft concerned.
Note2: Reference NAVAIDS(KGE, HKC and IKG LOC) must be operating.
Note3: RADAR service required.
Note4: Procedure not authorized at night.

CHANGE : Radial FM HKC. HLDG pattern.

RJFK / KAGOSHIMA Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : Map updated. BRG/DIST from ARP.

Call sign	BRG / DIST from ARP	Remarks
鶴田ダム Tsuruta Dam	314°T / 16.0NM	ダム Dam
栗野 Kurino	001°T / 8.8NM	JR駅 JR Station
神宮 Jingu	081°T / 6.1NM	JR駅 JR Station
蒲生 Kamo	254°T / 6.8NM	住吉池 Pond
都城 Miyakonojo	102°T / 18.6NM	JR駅 JR Station
加治木タウン Kajiki Town	214°T / 5.3NM	網掛川河口 River mouth (The Amikake)
大崎鼻 Osakibana	211°T / 10.0NM	崎 Point
鹿児島シティ Kagoshima City	211°T / 14.7NM	港 Harbor



CHANGE : TWY T7 installed.

RUNWAY LEAD - IN LIGHTING SYSTEM :

NR.1～NR.9 FLASHING WHITE

RJFK / KAGOSHIMA Minimum Vectoring Altitude CHART



① 2800
② 3300
③ 4700

CENTER : *314812N/1304310E* (RJFK ARP)

*1: *313631N/1304919E* RADIUS : 3.1NM
*2: *313507N/1303925E* RADIUS : 4NM

CHANGE : Update

RJFK / KAGOSHIMA Minimum Vectoring Altitude CHART

enlarged view



（1）*315600N/1304528E*
（2）*315250N/1304805E*
（3）*314927N/1305345E*
（4）*314951N/1305709E*
（5）*315042N/1305825E*
（6）*315102N/1310029E*
（7）*314919N/1305824E*
（8）*314801N/1305359E*
（9）*314858N/1304746E*
（10）*314342N/1304742E*
（11）*314059N/1304947E*
（12）*314004N/1305007E*
（13）*314005N/1304809E*
（14）*313829N/1304518E*
（15）*313733N/1304453E*
（16）*313747N/1304326E*
（17）*314616N/1303653E*
（18）*313707N/1304328E*
（19）*313608N/1305004E*