

AD 2 AERODROMES

RJCM AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJCM - MEMANBETSU

RJCM AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	435250N / 1440951E 175° / 1.25km from RWY 18 THR
2	Direction and distance from (city)	9.7nm SSW ABASHIRI
3	Elevation/ Reference temperature	109FT / 26°C (2004-2008)
4	Geoid undulation at AD ELEV PSN	99FT
5	MAG VAR/ Annual change	9° W(2009) / 2.1'E
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	Hokkaido Airports Co.,Ltd. Memanbetsu Airport Office 256-3, Chuo, Memanbetsu, Ozora-cho Abashiri-gun, Hokkaido TEL: 0152-74-2222 FAX: 0152-74-3674 e-MAIL: hap-mmb-unjyo@hokkaido-airports.co.jp
7	Types of traffic permitted(IFR/VFR)	IFR/VFR
8	Remarks	Memanbetsu Airport Branch (CAB) 256, Chuo, Memanbetsu, Ozora-cho Abashiri-gun, Hokkaido TEL:0152-74-2673

RJCM AD 2.3 OPERATIONAL HOURS

1	AD Administration	2300-1200
2	Customs and immigration	On request Customs: 0154-22-3730 Immigration: 0154-22-2430
3	Health and sanitation	Quarantine(human): On request(0154-23-3340) Quarantine(animal, plant): Nil
4	AIS Briefing Office	Nil
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	H24 (NEW CHITOSE)
7	ATS	2300-1200
8	Fuelling	2300-1200
9	Handling	2300-1200
10	Security	2300-1200
11	De-icing	Nil
12	Remarks	Nil

RJCM AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	All the modern institutions that deal with the weight thing to a A306 type freighter
2	Fuel/ oil types	JET A-1
3	Fuelling facilities/ capacity	Fuel truck refueling, 22L/sec
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

RJCM AD 2.5 PASSENGER FACILITIES

1	Hotels	Nil
2	Restaurants	At airport
3	Transportation	Buses and taxis
4	Medical facilities	Hospital in Ozora-town, 5km from AP
5	Bank and Post Office	Nil
6	Tourist Office	At airport
7	Remarks	Nil

RJCM AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT 8
2	Rescue equipment	Chemical fire fighting truck x 3 Emergency medical equipments conveyance truck x 1
3	Capability for removal of disabled aircraft	Nil
4	Remarks	Nil

RJCM AD 2.7 SEASONAL AVAILABILITY-CLEARING

1	Types of clearing equipment	Snow removal equipment: 42
2	Clearance priorities	1) RWY 18/36, T1, T6, P1-P6, Apron A 2) T2-T5, TB, Apron B
3	Remarks	Nil

RJCM AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Apron surface and strength	Apron A : Surface:Cement-concrete, Strength:PCN 74/R/B/X/T Apron B : Surface:Asphalt-concrete, Strength:PCN 20/R/B/Y/T
2	Taxiway width, surface and strength	T1-T6, P1-P6 : Surface:Asphalt-concrete, Width:30m, Strength:PCN 89/F/C/X/T TB : Surface:Asphalt-concrete, Width:9m, Strength:PCN 21/F/B/Y/T
3	ACL and elevation	Not available
4	VOR checkpoints	Not available
5	INS checkpoints	(Spot NR) 1 : 435257.24N/1440933.47E 2 : 435255.56N/1440933.89E 3 : 435253.47N/1440934.16E 4 : 435251.21N/1440934.53E 5 : 435248.95N/1440934.82E 6 : 435246.85N/1440935.01E
6	Remarks	Nil

RJCM AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	Aircraft stand ID sign : Nil ACFT stand taxi lane marking : See AD2.24. AD chart Visual docking guidance system : Nil
2	RWY and TWY markings and LGT	RWY: RWY18/36 (Marking) RWY designation, RWY CL, RWY THR, Aiming point, TDZ, RWY side stripe (LGT) RCLL, REDL, RTHL, RENL, RTZL, RWY DIST marker LGT, WBAR TWY: ALL (Marking) TWY CL, TWY side stripe (LGT) TWY edge LGT TWY: T1-T6 (Marking) RWY HLDG PSN, Mandatory instruction (LGT) TWY CL LGT, RWY guard LGT, Taxiing guidance sign TWY: P1-P6 (LGT) TWY CL LGT TWY: TB (Marking) RWY HLDG PSN, Mandatory instruction (LGT) RWY guard LGT, Taxiing guidance sign
3	Stop bars	Nil
4	Remarks	(Marking) Overrun area (LGT) Apron flood LGT

RJCM AD 2.10 AERODROME OBSTACLES

In Area2 See Obstacle data

In Area3 To be developed

RJCM AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	NEW CHITOSE
2	Hours of service MET Office outside hours	H24 (NEW CHITOSE)
3	Office responsible for TAF preparation Periods of validity	NEW CHITOSE 30 Hours
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Briefing is available upon inquiry at NEW CHITOSE
6	Flight documentation Language(s) used	C En
7	Charts and other information available for briefing or consultation	S ₆ , U ₈₅ , U ₇ , U ₅ , U ₃ , U ₂₅ , U ₂ /T _r , P _s , P ₅ , P ₃ , P ₂₅ , P _{SWE} , P _{SWF} , P _{SWG} , P _{SWI} , P _{SWM} , P _{SW} (domestic), E, C, W _E , W _F , W _G , W _I , W, N
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	TWR
10	Additional information(limitation of service, etc.)	Nil

RJCM AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN) and Surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
18	174.66°	2500x45	PCN 89/F/C/X/T Asphalt-concrete	435330.51N/1440945.38E 98.8FT	THR ELEV: 102.0FT TDZ ELEV: 108FT
36	354.66°	2500x45		435209.85N/1440955.80E 98.8FT	THR ELEV: 135.2FT TDZ ELEV: 131FT
Slope of RWY		Strip Dimensions(M)	RESA (Overrun) Dimensions (M)		Remarks
7		10	11		14
See below figure		2620x300	190x(MNM:140 MAX:300)*		RWY Grooving 2500m x 45m
		2620x300	90x(MNM:90 MAX:300)* *For detail, ask airport administrator		



RJCM AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
18	2500	2500	2500	2500	Nil
36	2500	2500	2500	2500	Nil

RJCM AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
18	PALS (CAT I) 900m LIH	Green Green	PAPI 3.0°/Left 404.5m 65.6ft	900m	2500m 30m Coded color (White/Red) LIH	2500m 60m Coded color (White/Yellow) LIH	Red	Nil(*1)
36	PALS (CAT I) 900m LIH	Green Green	PAPI 3.0°/Left 499.2m 65.6ft	900m	2500m 30m Coded color (White/Red) LIH	2500m 60m Coded color (White/Yellow) LIH	Red	Nil(*1)
Remarks								
10								
Overrun area edge LGT(LEN:60m, Color:Red)(*1)								

RJCM AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	ABN: 435259N /1440926E , ALTN FLG(2)WG EV 4.3SEC, HO
2	LDI location and LGT Anemometer location and LGT	LDI : Nil Anemometer : RWY 18: 285m from RWY 18 THR RWY 36: 289m from RWY 36 THR
3	TWY edge and center line lighting	TWY edge and center line lights installed, see AD2.9
4	Secondary power supply / switch-over time	Within 1sec : REDL, RENL, RTHL, WBAR, RCLL, Overrun area edge LGT Within 15sec : Other LGT
5	Remarks	WDI LGT

RJCM AD 2.16 HELICOPTER LANDING AREA

Nil

RJCM AD 2.17 ATS AIRSPACE

Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
Memambetsu CTR	Area within a radius of 5nm(9km) of Memambetsu ARP (4353N/14410E)	3000 or below	D	Memambetsu TWR En	

RJCM AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
TWR	Memambetsu tower	118.85MHZ(1) 126.2MHZ	2300 - 1200 (1)Primary	

RJCM AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid (VOR declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
VOR (9°W/2010)	TBE	110.85MHz	H24	435305.67N/ 1440958.26E		
DME	TBE	1132MHz (CH-45Y)	H24	435305.67N/ 1440958.26E	132ft	
ILS-LOC 18	ITB	110.1MHz	2300 - 1200	435202.26N/ 1440956.74E		LOC: 235m (771ft) away FM RWY 36 THR, BRG (MAG) 184°
ILS-GP 18	-	334.4MHz	2300 - 1200	435320.20N/ 1440952.07E		GP: 329m (1079ft) inside FM RWY 18 THR, 120m (394ft) E of RCL. Angle 3.0°, HGT of ILS reference datum 16.5m (54ft)
ILS-DME 18	ITB	999MHz (CH-38X)	2300 - 1200	435320.16N/ 1440952.39E	119ft	DME: 331m (1086ft) inside FM RWY 18 THR, 130m(427ft) E of RCL.
ILS-LOC 36	IHM	110.3MHz	2300 - 1200	435316.40N/ 1440950.98E		LOC: 445m(1460ft) inside FM RWY 18 THR, 85m(279ft) E of RCL. LOC offset angle 1.74° BRG(MAG) 5.90° LOC unusable: beyond 17nm from LOC antenna
ILS-GP 36	-	335MHz	2300 - 1200	435221.40N/ 1440948.65E		GP: 370m(1214ft) inside FM RWY 36 THR, 125m(410ft) W of RCL. HGT of ILS REF datum: 16.5m(54ft). GP angle 3.0°.
ILS-DME 36	IHM	1001MHz (CH-40X)	2300 - 1200	435221.65N/ 1440948.07E	137ft	DME: 379m(1243ft) inside FM RWY 36, 136m(446ft) W of RCL.
MSAS		1575.42MHz	H24			Transmitting antennas are satellite based.

ILS for RWY18

REMARKS : 1. LOC beam BRG(MAG) 184°
 2. HGT of ILS REF datum 16.5m(54ft)
 3. GP Angle 3.0°
 4. ELEV of ILS-DME 36.2m(119ft)

ILS for RWY36

REMARKS : 1. LOC OFFSET ANGLE 1.74°
 2. LOC beam BRG(MAG) 5.90°
 3. HGT of ILS REF datum 16.5m(54ft)
 4. GP Angle 3.0°
 5. ELEV of ILS-DME 41.7m (137ft)



LOC unusable in the following area : BEY 17NM FM LOC ANT.

RJCM AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

PPR

Prior permission is required for transient aircraft due to parking congestion except scheduled and/or emergency flight.
Tel: Hokkaido Airports Co.,Ltd. Memanbetsu Airport Office 0152-74-2222

2. Taxiing to and from stands

Nil

3. Parking area for small aircraft(General aviation)

Nil

4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

Nil

7. School and training flights - technical test flights - use of runways

Nil

8. Helicopter traffic - limitation

Nil

9. Removal of disabled aircraft from runways

Nil

RJCM AD 2.21 NOISE ABATEMENT PROCEDURES

Nil

RJCM AD 2.22 FLIGHT PROCEDURES**1.TAKE OFF MINIMA**

	RWY	REDL & RCLL		REDL or RCLL or RCL Marking		NIL (DAY ONLY)	
		RVR	VIS	RVR	VIS	RVR	VIS
Multi-Engine ACFT with TKOF ALTN AP Filed	18/36	400m		400m	400m	-	500m
OTHER	18/36	AVBL LDG MINIMA					

RJCM AD 2.23 ADDITIONAL INFORMATION

双方向に設置されている ILS の輻射について

ILS 18/36

RWY18 および 36 ILS は同時に輻射する。

Two separate ILS radiate at opposite ends of a single runway

ILS 18/36

RWY18 and 36 ILS radiate simultaneously.

RJCM AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome/Heliport Chart

Standard Departure Chart (KUSHIRO)

Standard Departure Chart (RUGMO)

Standard Departure Chart (MEMANBETSU REVERSAL)

Standard Departure Chart (NODUK-RNAV)

Instrument Approach Chart (ILS Z or LOC Z RWY18)

Instrument Approach Chart (ILS Y or LOC Y RWY18)

Instrument Approach Chart (ILS X RWY18)

Instrument Approach Chart (ILS or LOC RWY36)

Instrument Approach Chart (VOR RWY18)

Instrument Approach Chart (VOR RWY36)

Instrument Approach Chart (RNP Z RWY18)

Instrument Approach Chart (RNP Y RWY18 (AR))

Instrument Approach Chart (RNP RWY36)


Other Chart (Visual REP)

Other Chart (LDG CHART)

Other Chart (MVA CHART)

RJCM / MEMANBETSU

24/2/22



STANDARD DEPARTURE CHART -INSTRUMENT

RJCM / MEMANBETSU


SID

KUSHIRO FOUR DEPARTURE

RWY 18 : Climb RWY HDG to 600FT, via TBE R187/TCE R008 to TCE VOR/DME....
RWY 36 : Climb RWY HDG to 800FT, turn right HDG 217° to intercept and proceed via
TBE R187/TCE R008 to TCE VOR/DME....
...Cross TCE VOR/DME at or above 6000FT.

Note RWY18 : 3.9% climb gradient required up to 4500FT.
OBST ALT 3281FT located at 17.0NM 182° FM end of RWY18.
OBST ALT 4593FT located at 24.9NM 190° FM end of RWY18.

CHANGE : PROC renamed. PROC course. ALT restriction at TCE established. KUSHIRO VOR/DME(KSE → TCE). Note(OBST).



STANDARD DEPARTURE CHART-INSTRUMENT

RJCM / MEMANBETSU

SID

RUGMO TWO DEPARTURE


RWY 18 : Climb RWY HDG to 800FT, turn right climb via TBE R220/OBE R040 to RUGMO....

RWY 36 : Climb RWY HDG to 1000FT, turn left HDG 175° to intercept and proceed via
TBE R220/OBE R040 to RUGMO....

....Cross RUGMO at or above 6000FT.

Note RWY36 : 3.9% climb gradient required up to 2000FT.

OBST ALT 1673FT located at 8.2NM 320° FM end of RWY36.



CHANGE : PROC renamed. Radial FM OBE.

STANDARD DEPARTURE CHART-INSTRUMENT

RJCM / MEMANBETSU

SID

MEMANBETSU REVERSAL THREE DEPARTURE

RWY 18 : Climb via TBE R187 to TBE 5.0DME, turn left....

RWY 36 : Climb via TBE R001 to TBE 5.0DME, turn right,....

....Proceed to TBE VOR/DME. Cross TBE VOR/DME at or above 4000FT.



STANDARD DEPARTURE CHART-INSTRUMENT

RJCM / MEMANBETSU

RNAV SID

NODUK ONE DEPARTURE

Basic RNP1

Note GNSS required.

VAR 10° W

NODUK
430605.5N
1430004.4E
9000

NICOL
433912.0N
1434158.7E
7000

45.0
232°

004° 184°

600
600

RWY18: Climb on HDG184° at or above 600FT, turn right direct to NICOL at or above 7000FT, to NODUK at or above 9000FT.

RWY36: Climb on HDG004° at or above 600FT, turn left direct to NICOL at or above 7000FT, to NODUK at or above 9000FT.

Note RWY36 : 5.0% climb gradient required up to 600FT.
OBST ALT 1181FT located at 6.3NM 312° FM end of RWY36.

RWY18


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	184 (174.7)	-9.5	—	—	+600	—	—	Basic RNP1
002	DF	NICOL	—	—	-9.5	—	R	+7000	—	—	Basic RNP1
003	TF	NODUK	—	232 (222.9)	-9.5	45.0	—	+9000	—	—	Basic RNP1

RWY36

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	004 (354.7)	-9.5	—	—	+600	—	—	Basic RNP1
002	DF	NICOL	—	—	-9.5	—	L	+7000	—	—	Basic RNP1
003	TF	NODUK	—	232 (222.9)	-9.5	45.0	—	+9000	—	—	Basic RNP1

CHANGE : New PROC.



INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

ILS Y or LOC Y RWY18



MISSED APPROACH

Climb to 700FT on HDG184°,
turn left HDG001° to intercept and
proceed via TBE R046 to RAUSU
and hold at 3100FT.
Contact MEMANBETSU TOWER.

Timing not authorized for defining the MAPt.



MINIMA		THR elev. 102		AD elev. 109		
CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/ CMV	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	302 (200)	550	450 (341)	900	640 (531)	1600
B				1000		
C					750 (641)	2400
D					1400	760 (651)

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

ILS X RWY18



CHANGE : New PROC.

MINIMA		THR elev. 102	AD elev. 109	
CAT	CAT I		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	VIS
A	302 (200)	550	640 (531)	1600
B			750 (641)	2400
C			760 (651)	3200
D				

INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

ILS X RWY18

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GINGA	—	—	-9.6	—	—	+5000	—	—	Basic RNP1
002	TF	KILOX	—	021 (011.9)	-9.6	17.2	—	—	—	—	Basic RNP1
003	TF	CM853	—	009 (359.2)	-9.6	5.0	—	+2700	-200	—	Basic RNP1
001	IF	OZORA	—	—	-9.6	—	—	+7000	—	—	Basic RNP1
002	TF	KIMUA	—	351 (341.4)	-9.6	18.9	—	+4200	—	—	Basic RNP1
003	TF	KILOX	—	002 (352.2)	-9.6	7.6	—	—	—	—	Basic RNP1
004	TF	CM853	—	009 (359.2)	-9.6	5.0	—	+2700	-200	—	Basic RNP1
001	IF	CM853	—	—	-9.6	—	—	+2700	-200	—	Basic RNP1
002	RF Center: CMRF2 r=2.51NM	CM854	—	—	-9.6	3.8	R	+2200	—	—	Basic RNP1
003	RF Center: CMRF2 r=2.51NM	CM855	—	—	-9.6	3.8	R	1700	—	—	Basic RNP1
001	CA	—	—	184 (174.7)	-9.6	—	—	+700	—	—	Basic RNP1
002	DF	RAUSU	—	—	-9.6	—	L	3100	—	—	Basic RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	GINGA	040 (030.8)	-9.5	1.0(-14000)	R	5400	FL140	-230(-14000)	Basic RNP1
Hold	OZORA	006 (356.7)	-9.5	1.0(-14000)	R	7000	FL140	-230(-14000)	Basic RNP1
Hold	RAUSU	227 (217.0)	-9.5	1.0(-14000)	L	3100	FL140	-230(-14000)	Basic RNP1

Waypoint Coordinates


Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
GINGA	433738.73N/1435710.93E	CMRF2	435931.80N/1440529.11E
OZORA	432908.24N/1441153.19E		
KIMUA	434701.35N/1440331.41E		
KILOX	435429.92N/1440206.12E		
CM853	435929.83N/1440200.57E		
CM854	440202.15N/1440517.96E		
CM855	435945.90N/1440856.76E		
RAUSU	440327.56N/1442052.43E		

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU


ILS or LOC RWY36



INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU


VOR RWY18



INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU


VOR RWY36



MISSED APPROACH

Climb to 1000FT via TBE R006,
turn left HDG224° to intercept
and proceed via TBE R269 to
TSUKA and hold at 5000FT.
Contact MEMANBETSU TOWER.

Timing not authorized for defining the MAPt.



MINIMA		THR elev. 135	AD elev. 109	
CAT			CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	690 (581)	1000	690 (581)	1600
B		1200		
C			750 (641)	2400
D			1600	760 (651)

INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

RNP Z RWY18

SAPPORO CONTROL
128.325 – 246.1
134.25 – 260.4RNP APCH
MSAS CH83687
M18AMEMANBETSU TOWER
118.85 – 126.2

NO RADAR

Baro-VNAV not authorized below -25°C


VAR 10°W

MSA 25NM





ARP: 435250N/1440951E

NOT TO SCALE


MHA 5400
MAX 230KIAS

NOT TO SCALE

MHA 7000
MAX 230KIAS

MISSED APPROACH

Direct to CM852, turn left direct to RAUSU
and hold at 3100FT.
Contact MEMANBETSU TOWER.



Missed APCH climb gradient MNM 5.0%

MINIMA		THR elev.102				AD elev.109	
CAT	LPV		LNAV/VNAV		LNAV		CIRCLING
	DA(H)	RVR/ CMV	DA(H)	RVR/ CMV	MDA(H)	RVR/ CMV	MDA(H) VIS
A	352(250)	800	440(338)	900	440(331)	900	640(531) 1600
B	360(258)			1000		1000	750(641) 2400
C	369(267)			1400		1400	760(651) 3200
D	379(277)	1200					

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : Missed APCH PROC for using VOR/DME abolished. HLDG PROC for using NAVAID abolished.

INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

RNP Z RWY18

FAS DATA BLOCK

Operation type	0	LTP/FTP ellipsoidal height	+00618
SBAS service provider identifier	2	FPAP latitude	435209.8350N
Airport identifier	RJCM	FPAP longitude	1440955.7670E
Runway	18	Threshold crossing height	00016.5
Approach performance designator	0	TCH units selector	1
Route indicator	Z	Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M18A	∠ length offset	0000
LTP/FTP latitude	435330.4920N	HAL	40.0
LTP/FTP longitude	1440945.3395E	VAL	50.0
CRC remainder	257C1F8B		


Required additional data

LTP/FTP orthometric height	31.0
----------------------------	------

INSTRUMENT APPROACH CHART


RJCM / MEMANBETSU

RNP Y RWY18(AR)



MISSED APPROACH

From RW18 on track 184°, at or above 600FT turn left, direct to RAUSU and hold at 3100FT. Contact MEMANBETSU TOWER.



Missed APCH climb gradient MNM 3.0%

MINIMA	THR elev. 102	AD elev. 109
CAT	RNP 0.30	
	DA(H)	RVR/CMV
A	-	-
B	-	-
C	402(300)	1000
D		1400

Authorization Required

MINIMA with Missed APCH climb gradient of 2.5% are not established.

INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

RNP Y RWY18(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	OZORA	-	-	-9.5	-	-	+7000	-	-	-
002	TF	SHARO	-	019 (009.5)	-9.5	14.1	-	+4300	-	-	1.0
003	TF	CM850	-	019 (009.6)	-9.5	12.0	-	+3000	-185	-	1.0
004	RF Center: CMRF1 r=3.04NM	TENTO	-	-	-9.5	4.6	L	2500	-165	-	1.0
005	RF Center: CMRF1 r=3.04NM	CM851	-	-	-9.5	5.7	L	675	-	-3.00	0.3
006	TF	RW18	Y	184 (174.7)	-9.5	1.6	-	156	-	-3.00/54	0.3
007	FA	-	-	184 (174.7)	-9.5	-	-	+600	-	-	1.0
008	DF	RAUSU	-	-	-9.5	-	L	3100	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	OZORA	006 (356.7)	-9.5	1.0 (-14000)	R	7000	FL140	-230 (-14000)	1.0
Hold	RAUSU	227 (217.0)	-9.5	1.0 (-14000)	L	3100	FL140	-230 (-14000)	1.0


Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
OZORA	432908.24N / 1441153.19E	CMRF1	435524.66N / 1441344.15E
SHARO	434301.91N / 1441506.66E		
CM850	435454.27N / 1441753.05E		
TENTO	435822.66N / 1441439.66E		
CM851	435507.75N / 1440932.81E		
RW18	435330.51N / 1440945.38E		
RAUSU	440327.56N / 1442052.43E		

INSTRUMENT APPROACH CHART

RJCM /MEMANBETSU

RNP RWY36



CHANGE : Missed APCH PROC for using VOR/DME abolished.

INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

RNP RWY36

FAS DATA BLOCK

Operation type	0	LTP/FTP ellipsoidal height	+00719
SBAS service provider identifier	2	FPAP latitude	435330.4920N
Airport identifier	RJCM	FPAP longitude	1440945.3395E
Runway	36	Threshold crossing height	00016.5
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M36A	∠ length offset	0000
LTP/FTP latitude	435209.8350N	HAL	40.0
LTP/FTP longitude	1440955.7670E	VAL	50.0
CRC remainder	28C6AB24		

Required additional data

LTP/FTP orthometric height	41.1
----------------------------	------

RJCM / MEMANBETSU

Visual REP




※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : Map updated. BRG/DIST from ARP.

Call sign	BRG / DIST from ARP	Remarks
網走 Abashiri	025°T / 9.2NM	JR駅 Station
湧沸湖 Tofutsuko	074°T / 10.5NM	湖 Lake
小清水 Koshimizu	097°T / 13.3NM	学校 School
東藻琴 Higashimokoto	110°T / 6.1NM	市街地 Town
美幌峠 Bihoro Toge	165°T / 14.4NM	峠 Pass
津別 Tsubetsu	210°T / 12.2NM	市街地 Town
美幌ステーション Bihoro Station	223°T / 3.7NM	JR駅 Station
北見 Kitami	248°T / 12.4NM	JR駅 Station
浜佐呂間 Hamasaroma	321°T / 15.5NM	佐呂間大橋 Bridge

RJCM / MEMANBETSU

LDG CHART



RJCM / MEMANBETSU

Minimum Vectoring Altitude CHART

