



AD CHART



STANDARD DEPARTURE CHART -INSTRUMENT



STANDARD DEPARTURE CHART -INSTRUMENT

RJSI / HANAMAKI

SID

NIIGATA SIX DEPARTURE

RWY 02 : Climb RWY HDG to HPE 3.5 DME, turn right...

RWY 20 : Climb RWY HDG to HPE 3.5 DME, turn left...

...proceed to HPE VOR/DME, via HPE R236 to HPE 50.0DME(GTC 79.6DME),
via GTC R055 to GTC.Cross HPE VOR/DME at or above 2200 FT, cross HPE R236/50.0DME
(GTC R055/79.6DME) at or above 12000 FT.


Note RWY02 : 4.5% climb gradient required up to 2400FT.

OBST ALT 1641FT located at 4.1NM 091° FM end of RWY02.

RWY20 : 3.9% climb gradient required up to 1100FT.

OBST ALT 722FT located at 2.8NM 166° FM end of RWY20.

CHANGE : SID renamed. ALT restriction at R236/D50.0 HPE, R055/D79.6 GTC.



STANDARD DEPARTURE CHART -INSTRUMENT

RJSI / HANAMAKI

SID

HANAMAKI REVERSAL THREE DEPARTURE


RWY 02 : Climb RWY HDG to 700FT, via HPE R022 to 6.0 DME, turn right...

RWY 20 : Climb RWY HDG to 700FT, via HPE R195 to 6.0 DME, turn left...
...direct to HPE VOR/DME.

Cross HPE VOR/DME at or above 6000FT.

Note RWY02 : 5.0% climb gradient required up to 3200FT.

OBST ALT 2691FT located at 9.1NM 058° FM end of RWY02.




CHANGE : PROC renamed. PROC course.

STANDARD DEPARTURE CHART -INSTRUMENT

RJSI / HANAMAKI

RNAV SID



CHANGE : Description of VOR/DME.

STANDARD DEPARTURE CHART -INSTRUMENT


RJSI / HANAMAKI

RNAV SID

HANKA ONE DEPARTURE

RNP1

Note GNSS required



RWY02 : Climb on HDG 019° at or above 1600FT, turn left direct to HANKA, at or above 11000FT.
RWY20 : Climb on HDG 199° at or above 800FT, turn right direct to HANKA, at or above 11000FT.
Note RWY02: 5.0% climb gradient required up to 3600FT.
OBST ALT 1936FT located at 5.5NM 340° FM end of RWY02.
OBST ALT 3018FT located at 8.2NM 310° FM end of RWY02.
RWY20: 5.0% climb gradient required up to 5400FT.
OBST ALT 4593FT located at 18.2NM 227° FM end of RWY20.
OBST ALT 5151FT located at 20.8NM 232° FM end of RWY20.

CHANGE : Description of VOR/DME:

RWY02											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	019 (010.7)	-8.7	—	—	+1600	—	—	RNP1
002	DF	HANKA	—	—	-8.7	—	L	+11000	—	—	RNP1

RWY20											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	199 (190.7)	-8.7	—	—	+800	—	—	RNP1
002	DF	HANKA	—	—	-8.7	—	R	+11000	—	—	RNP1

INTENTIONALLY LEFT BLANK


STANDARD ARRIVAL CHART - INSTRUMENT

RJSI / HANAMAKI

RNAV STAR RWY02

REMEN ARRIVAL	RNP1
---------------	------

Note GNSS required



From MORIO at or above 9000FT, to JAMEN at or above 7400FT, to REMEN at or above 4100FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	MORIO	—	—	-8.8	—	—	+9000	—	—	RNP1
002	TF	JAMEN	—	218 (209.6)	-8.8	10.0	—	+7400	—	—	RNP1
003	TF	REMEN	—	218 (209.5)	-8.8	15.7	—	+4100	—	—	RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	MORIO	244 (235.7)	-8.8	1.0(-14000)	R	9000	FL140	-230(-14000)	RNP1

CHANGE : Description of VOR/DME.

STANDARD ARRIVAL CHART - INSTRUMENT


RJSI / HANAMAKI

RNAV STAR RWY20

WANKO ARRIVAL

RNP1

Note GNSS required



From SIOMO at or above 8000FT, to WANKO at or above 5800FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SIOMO	—	—	-8.8	—	—	+8000	—	—	RNP1
002	TF	WANKO	—	021 (012.6)	-8.8	20.6	—	+5800	—	—	RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	SIOMO	039 (030.1)	-8.8	1.0(-14000)	R	8000	FL140	-210(-14000)	RNP1

CHANGE : Description of VOR/DME.



STANDARD ARRIVAL CHART - INSTRUMENT

RJSI / HANAMAKIRNAV STAR RWY02

SIOMO ARRIVAL	RNP1
---------------	------

Note GNSS required.

VAR 9°W



From ENBIM at or above 9000FT, to NOPID at or above 8200FT, to ANOLA, to SIOMO at or above 8000FT.

CHANGE : Description of VOR/DME.


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	ENBIM	—	—	-8.8	—	—	+9000	—	—	RNP1
002	TF	NOPID	—	204 (195.0)	-8.8	7.9	—	+8200	—	—	RNP1
003	TF	ANOLA	—	204 (194.9)	-8.8	33.4	—	—	—	—	RNP1
004	TF	SIOMO	—	199 (190.6)	-8.8	7.5	—	+8000	—	—	RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	ENBIM	195 (186.5)	-8.8	1.0(-14000)	L	9000	FL140	-230 (-14000)	RNP1

STANDARD ARRIVAL CHART - INSTRUMENT

RJSI / HANAMAKI

RNAV STAR RWY20



From ENBIM at or above 9000FT, to OMKOS at or above 4100FT, to SUIHO at or above 3200FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	ENBIM	—	—	-8.8	—	—	+9000	—	—	RNP1
002	TF	OMKOS	—	187 (178.1)	-8.8	6.1	—	+4100	—	—	RNP1
003	TF	SUIHO	—	187 (178.1)	-8.8	12.4	—	+3200	—	—	RNP1


Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	ENBIM	195 (186.5)	-8.8	1.0(-14000)	L	9000	FL140	-230 (-14000)	RNP1

CHANGE : Description of VOR/DME.

STANDARD ARRIVAL CHART - INSTRUMENT

RJSI / HANAMAKI

RNAV STAR RWY20



CHANGE : Description of VOR/DME:

From SIOMO at or above 8000FT, to REMEN at or above 6000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SIOMO	-	-	-8.8	-	-	+8000	-	-	RNP1
002	TF	REMEN	-	074 (064.7)	-8.8	14.9	-	+6000	-	-	RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	SIOMO	039 (030.1)	-8.8	1.0(-14000)	R	8000	FL140	-210(-14000)	RNP1

INTENTIONALLY LEFT BLANK

RJSI / HANAMAKI


ILS Z or LOC Z RWY20

HIZME(FAF) : 393142.42N/1410935.33E

NM to IHP	MAPt	2	3	4	5	FAF
ALT (3.0° APCH Path)	—	929	1247	1566	1884	2072

Climb via HPE R202 to
HPE 8.0DME, turn left,
direct to HPE VOR/DME
and hold at 4000FT.
Contact SHIRAKAMI APP.

Timing not authorized for
defining the MAPt.



DME to IHP	0.2	0.7	1.3	2.5	5.6	9.3
NM to THR	0	0.5	1.2	2.3	5.4	9.1


MINIMA		THR elev. 298		AD elev. 294		
CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/ CMV	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	498 (200)	550	700 (406)	900	760 (466)	1600
B				1000	860 (566)	
C					1000 (706)	2400
D						1400

CHANGE : VAR. MSA(BTN 270° and 360°). DME to IHP. NM to THR. MDA(H) for LOC.

RJSI / HANAMAKI


ILS Y or LOC Y RWY20

SHIRAKAMI APP 119.25 - 315.3 - 120.65	ILS – LOC 109.3 IHP ILS – GP 332.0 ILS – DME CH-30X	HANAMAKI RADIO 118.2 – 126.2	RADAR AVBL
--	--	---------------------------------	------------



Climb via HPE R202 to
HPE 8.0DME, turn left,
direct to HPE VOR/DME
and hold at 4000FT.
Contact SHIRAKAMI APP.

Timing not authorized for
defining the MAPt.



DME to IHP	0.2	0.7	1.3	2.5	5.6	9.3	10.8
NM to THR	0	0.5	1.2	2.3	5.4	9.1	10.6

MINIMA		THR elev. 298		AD elev. 294		
CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/ CMV	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	498 (200)	550	700 (406)	900	760 (466)	1600
B				1000	860 (566)	
C					1000 (706)	2400
D						1400

CHANGE : DME to IHP. NM to THR. MDA(H) for LOC. MSA(BTN 270° and 360°).
VAR. Course FM WANKO to RYUHO. HLDG pattern at MORIO. HLDG pattern for using NAVAID.

RJSI / HANAMAKI

VOR RWY20

VAR 9°W

MSA 25NM

7800
7400
6200
7000

HPE

10NM

3086
3045
2746
2577
2812
2893
1049
1176

1854
442
1674
446
441
700

HANAMAKI CITY

MASAH(FAF)
D5.0 HPE

MAPt
446

MHA 4000
MAX 230KIAS

007°
202°
187°
090°
270°
180°
090°
270°
360°

EQPT REQUIRED
DME

6290

MASAH(FAF) : 393052.04N/1410931.09E

NM to HPE	MAPt	2	3	4	FAF
ALT (3.0° APCH Path)	—	849	1168	1486	1805

MISSED APPROACH

Climb via HPE R202 to HPE
8.0DME, turn left, direct to
HPE VOR/DME and hold
at 4000FT.


Contact SHIRAKAMI APP.

Timing not authorized for defining the MAPt.

Distance (DME)	Altitude (FT)
0.4	800 (526)
1.6	820 (526)
2.5	1008 (300)
5.0	1500 (1206)
10.0	2600 (2306)

MINIMA					THR elev. 298	AD elev. 294
CAT			CIRCLING			
	MDA(H)	RVR/ CMV	MDA(H)	VIS		
A	700 (406)	900	760 (466)	1600		
B		1000	860 (566)			
C			1000 (706)		2400	
D					1400	3200

INSTRUMENT APPROACH CHART




CHANGE : VAR. MSA(BTN 270° and 360°). PROC course. Missed APCH course. HLDG pattern.
OCA(H). DME to HPE. MINIMA for MDA(H).

RJSI / HANAMAKI

RNP Z RWY02



INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJSI / HANAMAKI

RNP Y RWY02(AR)


Coding Table											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	ENBIM	-	-	-8.8	-	-	+9000	-	-	-
002	TF	ISIDO	-	189 (180.2)	-8.8	25.4	-	+4000	-	-	1.0
003	TF	KENDA	-	169 (160.3)	-8.8	5.0	-	3800	-	-	1.0
004	TF	SI252	-	169 (160.4)	-8.8	1.5	-	3312	-165	-3.00	0.3
005	RF Center: SIRF1 r=2.10NM	SI253	-	-	-8.8	7.7	R	848	-	-3.00	0.3
006	TF	RW02	Y	020 (010.7)	-8.8	1.6	-	333	-	-3.00/50	0.3
007	DF	SI251	Y	-	-8.8	-	-	-	-	-	1.0
008	DF	HPE	-	-	-8.8	-	R	4500	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	ENBIM	195 (186.5)	-8.8	1.0 (-14000)	L	9000	FL140	-230 (-14000)	1.0
Hold	HPE	179 (169.7)	-8.9	1.0 (-14000)	L	4500	FL140	-230 (-14000)	1.0

Waypoint Coordinates			
Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
ENBIM	395519.34N / 1411002.82E	SIRF1	392304.37N / 1411014.42E
ISIDO	392956.45N / 1410957.05E		
KENDA	392513.70N / 1411207.87E		
SI252	392347.07N / 1411247.89E		
SI253	392327.97N / 1410734.24E		
RW02	392503.58N / 1410757.62E		
SI251	393152.68N / 1410937.82E		
HPE	392600.09N / 1410800.60E		

CHANGE : HLDG at HPE. VAR.

INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJSI / HANAMAKI

RNP Z RWY20(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	SIOMO	-	-	-8.8	-	-	+8000	-	-	-
002	TF	MOUSU	-	048 (038.8)	-8.8	17.1	-	+4800	-	-	1.0
003	TF	GANSU	-	048 (038.9)	-8.8	5.0	-	3700	-	-	1.0
004	TF	SI050	-	048 (038.9)	-8.8	1.3	-	3285	-165	-3.00	0.3
005	RF Center: SIRF2 r=2.10NM	SI051	-	-	-8.8	7.6	L	853	-	-3.00	0.3
006	TF	RW20	Y	199 (190.7)	-8.8	1.6	-	352	-	-3.00/54	0.3
007	DF	SI052	Y	-	-8.8	-	-	-	-	-	1.0
008	DF	HPE	-	-	-8.8	-	L	4000	-	-	1.0


Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	SIOMO	039 (030.1)	-8.8	1.0 (-14000)	R	8000	FL140	-210 (-14000)	1.0
Hold	HPE	006 (357.5)	-8.8	1.0 (-14000)	R	4000	FL140	-230 (-14000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
SIOMO	390801.78N / 1405430.28E	SIRF2	392732.73N / 1411119.82E
MOUSU	392119.11N / 1410818.81E		
GANSU	392512.44N / 1411222.60E		
SI050	392613.23N / 1411326.21E		
SI051	392756.30N / 1410839.89E		
RW20	392623.24N / 1410817.11E		
SI052	391806.42N / 1410615.76E		
HPE	392600.09N / 1410800.60E		

CHANGE : PROC renamed.

INSTRUMENT APPROACH CHART



CHANGE : ATC call sign and FREQ. Description of RADAR Service. Missed APCH PROC.

INSTRUMENT APPROACH CHART

RJSI / HANAMAKI

RNP Y RWY20(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	REMEN	-	-	-8.8	-	-	+6000	-	-	-
002	TF	PALPA	-	016 (007.2)	-8.8	5.5	-	-	-	-	1.0
003	TF	NAKAN	-	016 (007.2)	-8.8	5.0	-	3700	-	-	1.0
004	TF	SI053	-	016 (007.2)	-8.8	2.5	-	2913	-165	-3.00	0.3
005	RF Center: SIRF2 r=2.10NM	SI051	-	-	-8.8	6.5	L	853	-	-3.00	0.3
006	TF	RW20	Y	199 (190.7)	-8.8	1.6	-	352	-	-3.00/54	0.3
007	DF	SI052	Y	-	-8.8	-	-	-	-	-	1.0
008	DF	HPE	-	-	-8.8	-	L	4000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	REMEN	074 (065.0)	-8.8	1.0 (-14000)	R	6000	FL140	-230 (-14000)	1.0
Hold	HPE	006 (357.5)	-8.8	1.0 (-14000)	R	4000	FL140	-230 (-14000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
REMEN	391421.92N / 1411154.27E	SIRF2	392732.73N / 1411119.82E
PALPA	391951.68N / 1411248.23E		
NAKAN	392449.66N / 1411337.11E		
SI053	392716.81N / 1411401.29E		
SI051	392756.30N / 1410839.89E		
RW20	392623.24N / 1410817.11E		
SI052	391806.42N / 1410615.76E		
HPE	392600.09N / 1410800.60E		

CHANGE : PROC renamed.

RJSI / HANAMAKI

Visual REP




※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : Map updated. BRG/DIST from ARP. Taseko established. Tsuchisawa abolished.

Call sign	BRG / DIST from ARP	Remarks
盛岡 Morioka	360°T / 16.4NM	JR駅 JR Station
城山 Shiroyama	012°T / 8.4NM	城跡 The site of a castle
豊沢 Toyosawa	293°T / 8.1NM	豊沢ダム Dam
田瀬湖 Taseko	121°T / 10.0NM	田瀬ダム Dam
北上 Kitakami	184°T / 8.9NM	JR駅 JR Station
水沢 Mizusawa	178°T / 17.4NM	JR駅 JR Station



RJSI / HANAMAKI Minimum Vectoring Altitude CHART



CHANGE : Update.