


RJAF / MATSUMOTO

AD CHART

CHANGE: RADIO deleted.



**INTENTIONALLY LEFT BLANK**

STANDARD DEPARTURE CHART-INSTRUMENT

RJAF / MATSUMOTO

SID


MATSUMOTO REVERSAL ONE DEPARTURE

- RWY 18 : Climb RWY HDG to 2700FT, turn left HDG321° to intercept and proceed via MBE R006 to 5.0DME, turn right direct to MBE VOR/DME.  
Cross MBE R006/5.0DME at or above 6000FT, cross MBE VOR/DME at or above 10000FT.
- RWY 36 : Climb via MBE R006 to 5900FT, turn right direct to MBE VOR/DME.  
Cross MBE VOR/DME at or above 10000FT.

NOTE RWY18 : 1) 6.6% climb gradient required up to 4200FT.

OBST ALT 3740FT located at 111°/4.40NM FM end of RWY18.

2) Departure turn limited to 150KIAS maximum until completing left turn.



## STANDARD DEPARTURE CHART-INSTRUMENT

RJAF / MATSUMOTO

SID

HAPPO ONE DEPARTURE

RWY 18 : Climb RWY HDG to 2700FT, turn left HDG321° to intercept and proceed via MBE R006 to HAPPO.

RWY 36 : Climb via MBE R006 to HAPPO.

NOTE RWY18 : 1) 6.6% climb gradient required up to 4200FT.

OBST ALT 3740FT located at 111°/4.40NM FM end of RWY18.


2) Departure turn limited to 150KIAS maximum until completing left turn.



STANDARD DEPARTURE CHART-INSTRUMENT

RJAF / MATSUMOTO

RNAV SID



## STANDARD DEPARTURE CHART-INSTRUMENT

RJAF / MATSUMOTO

RNAV SID

NIIGATA ONE DEPARTURE

## RWY36

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	359 (351.1)	-8.2	-	-	+2600	-	-	Basic RNP1
002	DF	AZUMI	-	-	-8.2	-	-	-	-	-	Basic RNP1
003	TF	HOKUE	-	041 (032.6)	-8.2	45.1	-	+9000	-	-	Basic RNP1
004	TF	GTC	-	041 (033.0)	-8.2	60.7	-	-	-	-	Basic RNP1

MATSUMOTO ONE DEPARTURE

## RWY36


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	359 (351.1)	-8.2	-	-	+2600	-	-	Basic RNP1
002	DF	AF600	Y	-	-8.2	-	-	-	-	-	Basic RNP1
003	DF	MBE	-	-	-8.2	-	R	+10000	-	-	Basic RNP1

CHANGE: VAR. True course(VA).

INSTRUMENT APPROACH CHART

RJAF / MATSUMOTO

VOR RWY18



CHANGE : Secondary FREQ of MATSUMOTO RADIO abolished. AFIS unit added.


**INTENTIONALLY LEFT BLANK**



INSTRUMENT APPROACH CHART


RJAF / MATSUMOTO

RNP Z RWY18(AR)



MISSED APPROACH

Climb to 10000FT, direct to AF859, turn left, direct to MBE and hold. Contact MATSUMOTO RADIO.



Missed APCH climb gradient MNM 7.0%

CAT	THR elev. 2132		AD elev. 2157	
	RNP 0.20		RNP 0.30	
	DA(H)	CMV	DA(H)	CMV
A	-	-	-	-
B	-	-	-	-
C	2432(300)	1000	2448(316)	1000
D	-	-	-	-

MINIMA with Missed APCH climb gradient of 2.5% are not established.

**Authorization Required**

CHANGE : PROC renamed. Requirement for RNP.

## INSTRUMENT APPROACH CHART

RJAF / MATSUMOTO

RNP Z RWY18(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	RIPSI	-	-	-8.2	-	-	+12000	-250	-	-
002	TF	AF850	-	096 (087.7)	-8.2	12.3	-	+8600	-	-	1.0
003	TF	AF851	-	043 (035.2)	-8.2	6.0	-	-	-	-	0.3
004	TF	AF852	-	008 (359.9)	-8.2	16.6	-	+5800	-	-	0.3
005	RF Center: AFRF5 r=3.15NM	AF853	-	-	-8.2	7.4	L	4700	-	-	0.3
006	RF Center: AFRF5 r=3.15NM	AF854	-	-	-8.2	4.4	L	3306	-	-3.00	0.2 0.3
007	TF	AF855	-	154 (146.1)	-8.2	1.0	-	2987	-	-3.00	0.2 0.3
008	RF Center: AFRF6 r=2.06NM	AF856	-	-	-8.2	0.9	R	2700	-	-3.00	0.2 0.3
009	TF	RW18	Y	179 (171.1)	-8.2	1.6	-	2182	-	-3.00/50	0.2 0.3
010	DF	AF859	Y	-	-8.2	-	-	-	-	-	1.0
011	DF	MBE	-	-	-8.2	-	L	10000	-	-	1.0

Waypoint Coordinates


Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
RIPSI	355340.33N / 1374133.41E	AFRF5	361534.43N / 1375704.35E
AF850	355408.74N / 1375645.79E	AFRF6	361149.74N / 1375225.49E
AF851	355901.18N / 1380100.60E		
AF852	361534.92N / 1380057.71E		
AF853	361749.79N / 1375421.45E		
AF854	361348.83N / 1375350.85E		
AF855	361259.03N / 1375432.28E		
AF856	361209.11N / 1375456.52E		
RW18	361032.37N / 1375515.37E		
AF859	360155.80N / 1375655.84E		
MBE	360921.51N / 1375511.34E		

CHANGE : PROC renamed.

INSTRUMENT APPROACH CHART

RJAF / MATSUMOTO

RNP Y RWY18(AR)



**MISSED APPROACH**

Climb to 10000FT, direct to AF859,  
turn left, direct to MBE and hold.  
Contact MATSUMOTO RADIO.



Missed APCH climb gradient MNM 7.0%

CAT	THR elev. 2132		AD elev. 2157	
	RNP 0.20		RNP 0.30	
	DA(H)	CMV	DA(H)	CMV
A	-	-	-	-
B	-	-	-	-
C	2432(300)	1000	2448(316)	1000
D	-	-	-	-

MINIMA with Missed APCH climb gradient of 2.5% are not established.

**Authorization Required**

CHANGE : PROC renamed. Requirement for RNP.

## INSTRUMENT APPROACH CHART

RJAF / MATSUMOTO

RNP Y RWY18(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	PAPNA	-	-	-8.2	-	-	+12000	-	-	-
002	TF	AF857	-	221 (212.8)	-8.2	13.6	-	+5200	-	-	1.0
003	TF	AF858	-	179 (171.0)	-8.2	9.9	-	4000	-	-	1.0
004	TF	RW18	Y	179 (171.1)	-8.2	5.7	-	2182	-	-3.00/50	0.2 0.3
005	DF	AF859	Y	-	-8.2	-	-	-	-	-	1.0
006	DF	MBE	-	-	-8.2	-	L	10000	-	-	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates
PAPNA	363721.74N / 1380122.92E
AF857	362557.23N / 1375214.72E
AF858	361611.17N / 1375409.31E
RW18	361032.37N / 1375515.37E
AF859	360155.80N / 1375655.84E
MBE	360921.51N / 1375511.34E


CHANGE : PROC renamed.



INSTRUMENT APPROACH CHART

RJAF / MATSUMOTO


RNP Z RWY36(AR)



**MISSED APPROACH**

From RW36 on track 359°, at or above 7000FT turn right, direct to MBE and hold at 10000FT. Contact MATSUMOTO RADIO.

PAPI not coincident with VPA.



Missed APCH climb gradient MNM 3.0%

CAT	RNP 0.20		RNP 0.30	
	DA(H)	CMV	DA(H)	CMV
A	-	-	-	-
B	-	-	-	-
C	2482(300)	1800	2551(369)	1800
D	-	-	-	-

MINIMA with Missed APCH climb gradient of 2.5% are not established.

**Authorization Required**

CHANGE : PROC renamed. Requirement for RNP.

## INSTRUMENT APPROACH CHART

RJAF / MATSUMOTO

RNP Z RWY36(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	RIPSI	-	-	-8.2	-	-	+12000	-250	-	-
002	TF	AF850	-	096 (087.7)	-8.2	12.3	-	+8600	-	-	1.0
003	TF	AF851	-	043 (035.2)	-8.2	6.0	-	+5700	-	-	1.0
004	RF Center: AFRF1 r=4.60NM	AF650	-	-	-8.2	5.6	L	5000	-	-	1.0
005	RF Center: AFRF1 r=4.60NM	AF651	-	-	-8.2	3.0	L	3880	-	-3.50	0.2 0.3
006	TF	AF652	-	297 (288.3)	-8.2	0.6	-	3657	-	-3.50	0.2 0.3
007	RF Center: AFRF2 r=2.02NM	AF653	-	-	-8.2	2.2	R	2837	-	-3.50	0.2 0.3
008	TF	RW36	Y	359 (351.1)	-8.2	1.6	-	2232	-	-3.50/50	0.2 0.3
009	FA	-	-	359 (351.1)	-8.2	-	-	+7000	-	-	1.0
010	DF	MBE	-	-	-8.2	-	R	10000	-	-	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
RIPSI	355340.33N / 1374133.41E	AFRF1	360141.27N / 1375622.53E
AF850	355408.74N / 1375645.79E	AFRF2	360810.39N / 1375813.97E
AF851	355901.18N / 1380100.60E		
AF650	360417.29N / 1380104.24E		
AF651	360604.23N / 1375809.40E		
AF652	360615.53N / 1375727.24E		
AF653	360751.55N / 1375546.68E		
RW36	360928.29N / 1375527.85E		
MBE	360921.51N / 1375511.34E		

CHANGE : PROC renamed.

## RJAF / MATSUMOTO

RNP Y RWY36(AR)



## INSTRUMENT APPROACH CHART

RJAF / MATSUMOTO

RNP Y RWY36(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	PAPNA	-	-	-8.2	-	-	+12000	-	-	-
002	TF	AF658	-	178 (170.2)	-8.2	21.5	-	-	-	-	1.0
003	TF	AF659	-	178 (170.3)	-8.2	2.5	-	+8500	-	-	0.3
004	TF	AF660	-	178 (170.3)	-8.2	2.5	-	+7700	-230	-	0.3
005	RF Center: AFRF4 r=4.89NM	AF661	-	-	-8.2	3.0	R	6800	-	-	0.3
006	RF Center: AFRF4 r=4.89NM	AF662	-	-	-8.2	7.1	R	4179	-	-3.50	0.2 0.3
007	TF	AF652	-	297 (288.4)	-8.2	1.4	-	3657	-	-3.50	0.2 0.3
008	RF Center: AFRF2 r=2.02NM	AF653	-	-	-8.2	2.2	R	2837	-	-3.50	0.2 0.3
009	TF	RW36	Y	359 (351.1)	-8.2	1.6	-	2232	-	-3.50/50	0.2 0.3
010	FA	-	-	359 (351.1)	-8.2	-	-	+7000	-	-	1.0
011	DF	MBE	-	-	-8.2	-	R	10000	-	-	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
PAPNA	363721.74N / 1380122.92E	AFRF4	361027.73N / 1380059.34E
AF658	361613.48N / 1380553.24E	AFRF2	360810.39N / 1375813.97E
AF659	361345.52N / 1380624.64E		
AF660	361117.56N / 1380656.02E		
AF661	360820.76N / 1380625.54E		
AF662	360549.12N / 1375905.80E		
AF652	360615.53N / 1375727.24E		
AF653	360751.55N / 1375546.68E		
RW36	360928.29N / 1375527.85E		
MBE	360921.51N / 1375511.34E		

CHANGE : PROC renamed.



RJAF / MATSUMOTO

Visual REP



CHANGE : Secondary FREQ of MATSUMOTO RADIO abolished.

※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

Call sign	BRG / DIST from ARP	Remarks
安曇野インターチェンジ Azumino Interchange	001°T / 7.9NM	長野自動車道 安曇野インターチェンジ Interchange
松本ステーション Matsumoto Station	028°T / 4.3NM	JR駅 Station
美ヶ原 Utsukushigahara	068°T / 9.7NM	美ヶ原王ヶ頭 Peak
島島 Shimashima	286°T / 5.1NM	松本電鉄新島島駅 Station
塩尻インターチェンジ Shiojiri Interchange	136°T / 4.1NM	長野自動車道 塩尻インターチェンジ Interchange
諏訪湖 Suwako	132°T / 10.6NM	諏訪湖上空 Lake
鳥居峠 Torii Toge	205°T / 14.3NM	峠 Mountain Pass



RJAF / MATSUMOTO

Minimum Vectoring Altitude CHART

