

RJSM / MISAWA

AD CHART



NOTE: REPRINTING DOD FLIP

RJSM / MISAWA

Aircraft Parking / Docking Chart



STANDARD DEPARTURE CHART - INSTRUMENT


RJSM / MISAWA

ATIS ★ 128.4 315.35
CLNC DEL
118.65 275.8
TOWER
118.1 315.8
DEP CON
125.3 363.8

ENKAI THREE DEPARTURE

Rwy	Knots	60	120	180	240	300	360
10	V/V(fpm)	350	700	1050	1400	1750	2100

ATC Climb Rate to 3500



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 10: Climb on MIS VORTAC R-105 to ENKAI.
Cross ENKAI at or above 3500.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART - INSTRUMENT

RJSM / MISAWA

KOSUI THREE DEPARTURE



▼

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 28: Climb on MIS VORTAC R-282 to KOSUI.
Cross KOSUI at or above 3600.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

RJSM / MISAWA

MISAWA SEVEN DEPARTURE

Rwy	Knots	60	120	180	240	300	360
*28 (a) (c)	V/V(fpm)	215	430	645	860	1075	1290
*28 (b)	V/V(fpm)	251	502	753	1004	1255	1506
†28 (d)	V/V(fpm)	221	442	663	884	1105	1326
†28 (e)	V/V(fpm)	313	626	939	1252	1565	1878
†10 (f)	V/V(fpm)	299	598	897	1196	1495	1794
†28 (f)	V/V(fpm)	336	672	1008	1344	1680	2016
†10 (g)	V/V(fpm)	218	436	654	872	1090	1308
†28 (g)	V/V(fpm)	218	436	645	872	1090	1308
†10 (h)	V/V(fpm)	256	512	768	1024	1280	1536
†28 (h)	V/V(fpm)	220	440	660	880	1100	1320

- (a) OLSAE Transition to 5000
- (b) JYONA Transition to 600
- (c) SAMBO Transition to 4900
- (d) OLSAE Transition to 9000
- (e) JYONA Transition to 3500
- (f) SAMBO Transition to 13,000
- (g) HANAMAKI Transition to 10,000
- (h) MIYAKO Transition to 8000

CHANGE : Update.



NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART - INSTRUMENT

RJSM / MISAWA

MISAWA SEVEN DEPARTURE



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 10: Climb heading 103° to 1500 (2000 for JYONA TRANSITION), thence

TAKEOFF RWY 28: Climb heading 283° to 1500 (1000 for JYONA TRANSITION), thence

HANAMAKI TRANSITION:

TAKEOFF RWY 10: ...turn right heading 226° to intercept MIS VORTAC R-196 (HPE VOR/DME R-017) to HANAMAKI VOR/DME. Cross OMBOE at or above 10,000. Maintain ATC assigned altitude.

TAKEOFF RWY 28: ...turn left heading 167° to intercept MIS VORTAC R-196 (HPE VOR/DME R-017) to HANAMAKI VOR/DME. Cross OMBOE at or above 10,000. Maintain ATC assigned altitude.

JYONA TRANSITION:

TAKEOFF RWY 10: ...turn right, climb via MIS VORTAC to intercept MIS R-310 direct JYONA. Cross JYONA at or above 3500. Maintain ATC assigned altitude.

TAKEOFF RWY 28: ...turn right heading 358° to intercept MIS VORTAC R-310 to JYONA. Cross JYONA at or above 3500. Maintain ATC assigned altitude.

MIYAKO TRANSITION:

TAKEOFF RWY 10: ...turn right heading 191° to intercept MIS VORTAC R-161 (MQE VOR/DME R-340) to MIYAKO VOR/DME. Cross SESEA at or above 8000. Maintain ATC assigned altitude.

TAKEOFF RWY 28: ...turn left heading 131° to intercept MIS VORTAC R-161 (MQE VOR/DME R-340) to MIYAKO VOR/DME. Cross SESEA at or above 8000. Maintain ATC assigned altitude.

OLSAE TRANSITION:

TAKEOFF RWY 10: ...turn right heading 267° to intercept MIS VORTAC R-233 to OLSAE (MIS R-233/40 DME). Cross OLSAE at or above 9000. Maintain ATC assigned altitude.

TAKEOFF RWY 28: ...turn left heading 203° to intercept MIS VORTAC R-233 to OLSAE (MIS R-233/40 DME). Cross OLSAE at or above 9000. Maintain ATC assigned altitude.

SAMBO TRANSITION:

TAKEOFF RWY 10: ...turn right heading 257° to intercept MIS VORTAC R-221 to SAMBO (MIS R-221/36.7 DME). Cross SAMBO at or above 13,000. Maintain ATC assigned altitude.

TAKEOFF RWY 28: ...turn left heading 189° to intercept MIS VORTAC R-221 to SAMBO (MIS R-221/36.7 DME). Cross SAMBO at or above 13,000. Maintain ATC assigned altitude.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART - INSTRUMENT

RJSM / MISAWA

ATIS★128.4 315.35
CLNC DEL
118.65 275.8
TOWER
118.1 315.8
DEP CON
125.3 363.8

REIWA TWO DEPARTURE

Rwy	Knots	60	120	180	240	300	360
10	V/V(fpm)	289	578	867	1156	1445	1734
28	V/V(fpm)	249	498	747	996	1245	1494

ATC Climb Rate to 10,000



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 10: Climb heading 109° to HESEI, then turn right to intercept MIS VORTAC R-169 to cross TASHO (MIS R-169/14 DME) at or below 4000, then cross REIWA at or above 10,000. Maintain ATC assigned altitude.

TAKEOFF RWY 28: Climb heading 282° to SHOWA, then turn left to intercept MIS VORTAC R-169 to cross TAIKA (MIS R-169/18 DME) at or above 5200, then cross REIWA at or above 10,000. Maintain ATC assigned altitude.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INTENTIONALLY LEFT BLANK


RJSM / MISAWA

CHANGE : Update.

10/8/23

INSTRUMENT APPROACH CHART

RJSM /MISAWA



CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RJSM / MISAWA

VORTAC MIS 115.4 Chan 101	APCH CRS 290°	Rwy ldg TDZE Arpt Elev	9999 109 119
---	-------------------------	------------------------------	---

HI-VOR Y or TACAN Y RWY28

RADAR or DME required

▼ *When ALS inop, increase CAT AB RVR to 55
and vis to 1 mile, CAT CDE vis to 1¼ miles.
**Circling S of Rwy 10-28 not authorized.


ALSF-1



MISSED APPROACH: Climb to 7000 on MIS R-280 to KISSA,
then climbing left turn heading 150° to intercept MIS R-200
outbound to SHOJU and hold. Continue climb-in holding to 7000.


ATIS ★ 128.4 315.35	APP CON 120.7 317.8	TOWER 118.1 315.8	GND CON 118.65 275.8	CLNC DEL 118.65 275.8	ASR/PAR
-------------------------------	-------------------------------	-----------------------------	--------------------------------	---------------------------------	---------

Missed approach requires use of RNAV or ATC RADAR.




EMERG SAFE ALT 100 NM 8700

7000 ↑ MIS R-280	KISSA MIS 8	hdg 150°	MIS R-200	TLv FL140 TA 14,000	VGSI and descent angles not coincident (VGSI Angle 2.50/TCH 55).
---------------------------	-------------------	-------------	--------------	------------------------	--



CATEGORY	A	B	C	D	E
S-28*	540/24 431 (500-½)		540/40 431 (500-¾)		
CIRCLING**	580-1 461(500-1)	600-1 481(500-1)	600-1½ 481(500-1½)	680-2 561 (600-2)	

ELEV 119	TDZE 109
----------	----------



CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RJSM / MISAWA

VORTAC MIS 115.4 Chan 101	APCH CRS 290°	Rwy ldg TDZE 109 Arpt Elev 119
---	-------------------------	--

VOR Z or TACAN Z RWY28

RADAR or DME required

▼ * When ALS inop, increase CAT AB RVR to 55 vis to 1 mile, CAT CDE vis to 1¼ miles.
** Circling S of Rwy 10-28 not authorized.


ALSF-1



MISSED APPROACH: Climb to 7000 on MIS R-280 to KISSA, then climbing left turn heading 150° to intercept MIS R-200 outbound to SHOJU and hold. Continue climb in holding to 7000.

ATIS ★ 128.4 315.35	APP CON 120.7 317.8	TOWER 118.1 315.8	GND CON 118.65 275.8	CLNC DEL 118.65 275.8	ASR/PAR
-------------------------------	-------------------------------	-----------------------------	--------------------------------	---------------------------------	---------


Missed approach requires use of RNAV or ATC RADAR.



EMERG SAFE ALT 100 NM 8700


ELEV 119

TDZE 109




VGSI and descent angles
not coincident
(VGSI Angle 2.50/TCH 55).

TLv FL140
TA 14,000



CATEGORY	A	B	C	D	E
S-28*	540/24 431 (500-½)	540/40 431 (500-¾)			
CIRCLING**	580-1 461(500-1)	600-1 481(500-1)	600-1½ 481(500-1½)	680-2 561 (600-2)	



HIRL Rwy 10-28

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART


RJSM / MISAWA



NOTE: REPRINTING DOD FLIP


INSTRUMENT APPROACH CHART

RJSM / MISAWA



INSTRUMENT APPROACH CHART

RJSM / MISAWA



NOTE: REPRINTING DOD FLIP

INTENTIONALLY LEFT BLANK

RJSM / MISAWA

Minimum Vectoring Altitude CHART

