CHANGE : CEILOMETER, WIND SPEED METER added.



RWY-HOLDING POSITION MARKINGS and STOP BAR LGT, RWY GUARD LGT

RWY-holding position markings and Stop bar LGT are located on TWY T-1 through T-6
RWY guard lights are located on TWY T-1 through T-6
; their locations are 90m off the RWY centerline.
Mandatory instruction markings are located on TWY T-1 through T-6.

COMMON WAYS OF ITS MARKINGS AND LGT

REMARKS :

RWY GROOVING		3000m × 40m
RWY STRENGTH		PCN 72/F/A/X/T
WIDTH & STRENGTH OF TWY		
	T-2, T-3, T-4, T-5 34m	PCN 72/F/A/X/T
	T-1, T-6 32m	PCN 72/F/A/X/T
	P-1 thru P-5 30m	PCN 72/F/A/X/T
	SUB TWY 18m	PCN 16/F/B/Y/T
APRON	619.5m × 190m	55m × 80m

INTENTIONALLY LEFT BLANK

AERODROME OBSTACLE CHART-ICAO

TYPE A (OPERATING LIMITATIONS)

DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC

MAGNETIC VARIATION 8° W–JUN 2022

HIROSHIMA AIRPORT
RWY : 10/28

DECLARED DISTANCES	
RWY 10	RWY 28
3000m TAKE OFF RUN AVAILABLE	3000m
3000m TAKE OFF DISTANCE AVAILABLE	3000m
3000m ACCELERATE STOP DISTANCE AVAILABLE	3000m
3000m LANDING DISTANCE AVAILABLE	3000m





HORIZONTAL SCALE

FEET

1000 500 0 1000 2000 3000 4000 5000 6000 7000 8000ft

300 0 500 1000 1500 2000 2500m

METER

LEGEND	
①	IDENTIFICATION NUMBER
⊙	POLE, TOWER, SPIRE, ANTENNA, ETC
✳	OBSTRUCTION LIGHT
▬	BUILDING OR LARGE STRUCTURE
─┼─	RAILROAD
△	TRIANGULATION POINT
─T─T─	TRANSMISSION LINE OR OVERHEAD CABLE
▥	LEVEE
✱	TREE
⬭	LAKE
≈	RIVER
≈	CONTOURS(ft)

AMENDMENT RECORD		
Nr	DATE	ENTERED BY

CHANGE : VAR.

AERODROME OBSTACLE CHART-ICAO

TYPE B (OPERATING LIMITATIONS)

DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC

AERODROME ELEVATION 1086ft ARP



HORIZONTAL SCALE

FEET
1000 0 1000 2000 3000 4000 5000 6000 7000 8000 9000 10000ft

METER
300 0 500 1000 1500 2000 2500 3000m

LEGEND

- AERODROME REFERENCE POINT 34°26'10"N 132°55'10"E
- POLE, TOWER, SPIRE, ANTENNA, ETC
- AERONAUTICAL GROUND LIGHT
- OBSTRUCTION LIGHT
- BUILDING OR LARGE STRUCTURE
- RAILROAD
- TERRAIN PENETRATING OBSTACLE PLANE
- TRANSMISSION LINE OR OVERHEAD CABLE
- LEVEE
- TREE
- RIVER
- LAKE
- CONTOURS(ft)

AMENDMENT RECORD		
NO	DATE	ENTERED BY

CHANGE : VAR.

PRECISION APPROACH TERRAIN CHART-ICAO

PRICISION APPROACH TERRAIN CHART

DISTANCES AND HEIGHTS IN METERS

RWY 10



CONTOUR AND HEIGHTS ARE RELATED
TO ELEVATION OF RWY THR

STANDARD DEPARTURE CHART - INSTRUMENT

RJOA / HIROSHIMA SID

CHANGE : PROC renamed. PROC course. Note RWY10(OBST). Note RWY28(Climb gradient, OBST).

HONGO REVERSAL FOUR DEPARTURE

RWY 10 : Climb RWY HDG to HGE 4.6DME(4.0NM FM DER), turn left....,
RWY 28 : Climb on HDG 271° to HGE 5.0DME(4.0NM FM DER), turn right....,
....direct to HGE VOR/DME. Cross HGE VOR/DME at or above 5000FT.

Note : RWY10 : 3.8% climb gradient required up to 2300FT.
OBST ALT 2002FT located at 088°/5.7NM FM DER.
RWY28 : 3.8% climb gradient required up to 1600FT.
OBST ALT 2559FT located at 338°/7.7NM FM DER.



STANDARD DEPARTURE CHART - INSTRUMENT

RJOA / HIROSHIMA — RNAV SID

MARCO TWO DEPARTURE — Basic RNP1

Note GNSS required.

VAR 8˚W



RWY10 : Climb on HDG098˚ at or above 1500FT, direct to OA021, turn right direct to LEMON at or above 11000FT, to MARCO.

RWY28 : Climb on HDG278˚ at or above 1600FT, direct to OA811, turn left direct to LEMON at or above 11000FT, to MARCO.

NOTE RWY10 : 5.0% climb gradient required up to 1500FT.
RWY28 : 3.6% climb gradient required up to 1600FT.

RWY10

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	098 (090.0)	-8.1	–	–	+1500	–	–	Basic RNP1
002	DF	OA021	Y	–	-8.1	–	–	–	–	–	Basic RNP1
003	DF	LEMON	–	–	-8.1	–	R	+11000	–	–	Basic RNP1
004	TF	MARCO	–	249 (241.1)	-8.1	18.0	–	–	–	–	Basic RNP1

RWY28

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	278 (270.0)	-8.1	–	–	+1600	–	–	Basic RNP1
002	DF	OA811	Y	–	-8.1	–	–	–	–	–	Basic RNP1
003	DF	LEMON	–	–	-8.1	–	L	+11000	–	–	Basic RNP1
004	TF	MARCO	–	249 (241.1)	-8.1	18.0	–	–	–	–	Basic RNP1

CHANGE : Description of VAR.

STANDARD DEPARTURE CHART - INSTRUMENT

RJOA / HIROSHIMA — RNAV SID and TRANSITION

KIJYY THREE DEPARTURE	Basic RNP1

Note GNSS required.



CHANGE : Description of VAR.

KIJYY THREE DEPARTURE

RWY10 : Climb on HDG098˚ at or above 1500FT, direct to OA021, turn left direct to TOJYO at or above 12000FT, to KIJYY.

RWY28 : Climb on HDG278˚ at or above 1600FT, direct to OA811, turn right direct to TOJYO at or above 12000FT, to KIJYY.

NOTE RWY10 : 5.0% climb gradient required up to 1600FT.
OBST ALT 2090FT located at 5.74NM 087˚ FM end of RWY10.
RWY28 : 3.6% climb gradient required up to 2700FT.
OBST ALT 2570FT located at 7.71NM 337˚ FM end of RWY28.

TOZAN TRANSITION

From KIJYY, to TOZAN, to YME.

STANDARD DEPARTURE CHART - INSTRUMENT

RJOA / HIROSHIMA RNAV SID and TRANSITION

KIJYY THREE DEPARTURE

RWY10

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	098 (090.0)	-8.1	–	–	+1500	–	–	Basic RNP1
002	DF	OA021	Y	–	-8.1	–	–	–	–	–	Basic RNP1
003	DF	TOJYO	–	–	-8.1	–	L	+12000	–	–	Basic RNP1
004	TF	KIJYY	–	076 (067.9)	-8.1	43.4	–	–	–	–	Basic RNP1

RWY28

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	278 (270.0)	-8.1	–	–	+1600	–	–	Basic RNP1
002	DF	OA811	Y	–	-8.1	–	–	–	–	–	Basic RNP1
003	DF	TOJYO	–	–	-8.1	–	R	+12000	–	–	Basic RNP1
004	TF	KIJYY	–	076 (067.9)	-8.1	43.4	–	–	–	–	Basic RNP1

TOZAN TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	KIJYY	–	–	-8.1	–	–	–	–	–	Basic RNP1
002	TF	TOZAN	–	077 (069.0)	-8.1	20.3	–	–	–	–	Basic RNP1
003	TF	YME	–	076 (068.3)	-8.1	34.3	–	–	–	–	Basic RNP1

CHANGE : PROC renamed(KIJYY THREE DEPARTURE). VAR. Navigation specification.

STANDARD DEPARTURE CHART - INSTRUMENT

RJOA / HIROSHIMA — RNAV SID and TRANSITION

MOMOT THREE DEPARTURE		RNAV1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll. 2) RADAR service required.	Critical DME	HGE : OA021 ～ 27NM to TOJYO TZT : OA021 ～ 24NM to TOJYO OKT : 25NM to IKUNO ～ 19NM to IKUNO
	DME GAP	RWY10 : DER – OA021 RWY28 : DER – 2NM to OA811
	Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

VAR 8˚W



CHANGE : Description of VAR.

MOMOT THREE DEPARTURE

RWY10 : Climb on HDG098˚ at or above 1500FT, direct to OA021, turn left direct to TOJYO at or above 12000FT, to MOMOT.

RWY28 : Climb on HDG278˚ at or above 1600FT, direct to OA811, turn right direct to TOJYO at or above 12000FT, to MOMOT.

NOTE RWY10 : 5.0% climb gradient required up to 1600FT.
OBST ALT 2090FT located at 5.74NM 087˚ FM end of RWY10.
RWY28 : 3.6% climb gradient required up to 2700FT.
OBST ALT 2570FT located at 7.71NM 337˚ FM end of RWY28.

IKUNO TRANSITION

From MOMOT, to IKUNO, to MIDER.

STANDARD DEPARTURE CHART - INSTRUMENT

RJOA / HIROSHIMA RNAV SID and TRANSITION

MOMOT THREE DEPARTURE

RWY10

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	098 (090.0)	-7.9	–	–	+1500	–	–	RNAV1
002	DF	OA021	Y	–	-7.9	–	–	–	–	–	RNAV1
003	DF	TOJYO	–	–	-7.9	–	L	+12000	–	–	RNAV1
004	TF	MOMOT	–	084 (075.7)	-7.9	32.6	–	–	–	–	RNAV1

RWY28

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	278 (270.0)	-7.9	–	–	+1600	–	–	RNAV1
002	DF	OA811	Y	–	-7.9	–	–	–	–	–	RNAV1
003	DF	TOJYO	–	–	-7.9	–	R	+12000	–	–	RNAV1
004	TF	MOMOT	–	084 (075.7)	-7.9	32.6	–	–	–	–	RNAV1

IKUNO TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	MOMOT	–	–	-7.9	–	–	–	–	–	RNAV1
002	TF	IKUNO	–	084 (076.0)	-7.9	47.2	–	–	–	–	RNAV1
003	TF	MIDER	–	111 (102.8)	-7.9	48.9	–	–	–	–	RNAV1

STANDARD DEPARTURE CHART -INSTRUMENT

RJOA / HIROSHIMA — RNAV SID and TRANSITION

SINFO THREE DEPARTURE	Basic RNP1

Note GNSS required.

VAR 8˚W



SINFO THREE DEPARTURE

RWY10 : Climb on HDG098˚ at or above 1500FT, direct to OA021, turn left direct to AKANA at or above 11000FT, to SINFO.

RWY28 : Climb on HDG278˚ at or above 1600FT, direct to OA811, turn right direct to AKANA at or above 11000FT, to SINFO.

NOTE RWY10 : 5.0% climb gradient required up to 1800FT.
OBST ALT 1780FT located at 2.30NM 006˚ FM end of RWY10.
RWY28 : 3.8% climb gradient required up to 3700FT.
OBST ALT 3150FT located at 11.02NM 322˚ FM end of RWY28.

STAGE TRANSITION

From SINFO, to STAGE.

CHANGE : Description of VAR.

STANDARD DEPARTURE CHART -INSTRUMENT

RJOA / HIROSHIMA RNAV SID and TRANSITION

CHANGE : PROC renamed(SINFO THREE DEPARTURE). VAR. Course(FM AKANA TO STAGE). Navigation specification.

SINFO THREE DEPARTURE

RWY10

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	098 (090.0)	-8.1	–	–	+1500	–	–	Basic RNP1
002	DF	OA021	Y	–	-8.1	–	–	–	–	–	Basic RNP1
003	DF	AKANA	–	–	-8.1	–	L	+11000	–	–	Basic RNP1
004	TF	SINFO	–	359 (350.7)	-8.1	14.4	–	–	–	–	Basic RNP1

RWY28

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	278 (270.0)	-8.1	–	–	+1600	–	–	Basic RNP1
002	DF	OA811	Y	–	-8.1	–	–	–	–	–	Basic RNP1
003	DF	AKANA	–	–	-8.1	–	R	+11000	–	–	Basic RNP1
004	TF	SINFO	–	359 (350.7)	-8.1	14.4	–	–	–	–	Basic RNP1

STAGE TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	SINFO	–	–	-8.1	–	–	–	–	–	Basic RNP1
002	TF	STAGE	–	359 (350.6)	-8.1	23.2	–	–	–	–	Basic RNP1

STANDARD ARRIVAL CHART -INSTRUMENT

RJOA / HIROSHIMA STAR

HONGO ARRIVAL

From over HGE VOR/DME, via HGE R249 to intercept and proceed via HGE 14.0DME clockwise ARC to MISEN.
Cross MISEN at or above 4100FT.



CHANGE : Course FM HGE to MISEN.

STANDARD ARRIVAL CHART -INSTRUMENT

RJOA / HIROSHIMA — RNAV STAR RWY10

MISEN ARRIVAL	RNAV1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.



From AMURO at or above 8000FT, to SAILA at or above 7000FT, to SEAWA at or above 5500FT, to MISEN at or above 4100FT.

Critical DME	–
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AMURO	–	–	-7.6	–	–	+8000	–	–	RNAV1
002	TF	SAILA	–	262 (254.5)	-7.6	6.7	–	+7000	–	–	RNAV1
003	TF	SEAWA	–	262 (254.4)	-7.6	29.2	–	+5500	–	–	RNAV1
004	TF	MISEN	–	187 (179.8)	-7.6	5.7	–	+4100	–	–	RNAV1

CHANGE : Description of VAR.

STANDARD ARRIVAL CHART-INSTRUMENT

RJOA / HIROSHIMA

RNAV STAR RWY10

AXELA ARRIVAL | Basic RNP1

Note GNSS required.



From AMURO at or above 8000FT, to CAROL between 8000FT and 6000FT, to TIIDA at or above 4000FT, to VISTA, to ATENZ, to AXELA at or above 3300FT.

CHANGE : Description of VAR.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AMURO	–	–	-8.1	–	–	+8000	–	–	Basic RNP1
002	TF	CAROL	–	221 (213.0)	-8.1	6.7	–	-8000 +6000	–	–	Basic RNP1
003	TF	TIIDA	–	221 (213.0)	-8.1	5.9	–	+4000	–	–	Basic RNP1
004	TF	VISTA	–	221 (212.9)	-8.1	5.7	–	–	–	–	Basic RNP1
005	TF	ATENZ	–	221 (212.9)	-8.1	6.6	–	–	–	–	Basic RNP1
006	TF	AXELA	–	278 (270.1)	-8.1	6.9	–	+3300	–	–	Basic RNP1

STANDARD ARRIVAL CHART-INSTRUMENT

RJOA / HIROSHIMA — RNAV STAR RWY10

DEMIO ARRIVAL	Basic RNP1

Note GNSS required.



From AMURO at or above 8000FT, to MIATA at or above 7000FT, to DEMIO at or above 5500FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AMURO	–	–	-8.1	–	–	+8000	–	–	Basic RNP1
002	TF	MIATA	–	255 (247.4)	-8.1	6.3	–	+7000	–	–	Basic RNP1
003	TF	DEMIO	–	255 (247.3)	-8.1	16.2	–	+5500	–	–	Basic RNP1

CHANGE : Description of VAR.

STANDARD ARRIVAL CHART -INSTRUMENT

RJOA / HIROSHIMA

RNAV STAR RWY28

VISTA ARRIVAL	RNAV1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.



From AMURO at or above 8000FT, to CAROL between 8000FT and 6000FT, to TIIDA at or above 4000FT, to VISTA at or above 3300FT.

Critical DME	–
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AMURO	–	–	-7.6	–	–	+8000	–	–	RNAV1
002	TF	CAROL	–	221 (213.0)	-7.6	6.7	–	-8000 +6000	–	–	RNAV1
003	TF	TIIDA	–	221 (213.0)	-7.6	5.9	–	+4000	–	–	RNAV1
004	TF	VISTA	–	221 (212.9)	-7.6	5.7	–	+3300	–	–	RNAV1

CHANGE : Description of VAR.

STANDARD ARRIVAL CHART -INSTRUMENT

RJOA / HIROSHIMA — RNAV STAR RWY10

PUNUP ARRIVAL	Basic RNP1

Note GNSS required.



From AMURO at or above 8000FT, to AVDAK at or above 7000FT, to PUNUP at or above 5500FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AMURO	—	—	-8.1	—	—	+8000	—	—	Basic RNP1
002	TF	AVDAK	—	259 (250.5)	-8.1	6.5	—	+7000	—	—	Basic RNP1
003	TF	PUNUP	—	259 (250.4)	-8.1	15.3	—	+5500	—	—	Basic RNP1

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJOA / HIROSHIMA — ILS Z or LOC RWY10 (CAT Ⅲ)

HIROSHIMA APP	ILS-LOC	HIROSHIMA TOWER	RADAR AVBL
124.05–119.9	108.7 IHG ILS–GP 330.5 ILS–DME CH–24X	118.6–126.2	ATIS 127.25



NM to IHG	FAF	7	6	5	4	3	2	MAPt
ALT (3.0° APCH Path)	3541	3293	2975	2657	2338	2020	1701	–



MISSED APPROACH

Climb on HDG098° to 1600FT,
via HGE R105 to BINGO
and hold at 3300FT.
Contact HIROSHIMA APP.

Timing not authorized for defining the MAPt.

Missed APCH climb gradient MNM 5.0%

MINIMA THR elev. 1072 AD elev. 1086

CAT	CAT Ⅲ	CAT Ⅱ			CAT Ⅰ		LOC		CIRCLING	
	RVR	DA(H)	RA	RVR	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	100	Not applicable			1272 (200)	550	1410 (338)	900	1510 (424)	1600
B								1000	1540 (454)	
C										2400
D								1400	1640 (554)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.
Circling to SOUTH side of RWY only
Values of RA may increase or decrease rapidly affected by terrain until IHG 0.3DME.

CHANGE : PROC renamed. Description of VAR.

INSTRUMENT APPROACH CHART

RJOA / HIROSHIMA — ILS Y RWY10(CAT Ⅲ)

HIROSHIMA APP	ILS-LOC	HIROSHIMA TOWER	RADAR AVBL
124.05–119.9	108.7 IHG ILS–GP 330.5 ILS–DME CH–24X	118.6–126.2	ATIS 127.25





MISSED APPROACH

Climb on course 098°, at or above 1600FT turn right, direct to BINGO and hold at 5000FT.
Contact HIROSHIMA APP.

Missed APCH climb gradient MNM 5.0%

MINIMA — THR elev. 1072 — AD elev. 1086

CAT	CAT Ⅲ	CAT Ⅱ			CAT Ⅰ		CIRCLING	
	RVR	DA(H)	RA	RVR	DA(H)	RVR/ CMV	MDA(H)	VIS
A	100	Not applicable			1272 (200)	550	1510 (424)	1600
B							1540 (454)	
C								2400
D							1640 (554)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.
Circling to SOUTH side of RWY only
Values of RA may increase or decrease rapidly affected by terrain until IHG 0.3DME.

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJOA / HIROSHIMA

ILS Y RWY10(CATⅢ)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	PUNUP	—	—	-8.1	—	—	+5500	—	—	Basic RNP1
002	TF	PEGLU	—	258 (250.3)	-8.1	4.2	—	—	—	—	Basic RNP1
003	TF	OA054	—	258 (250.2)	-8.1	5.0	—	+3600	-200	—	Basic RNP1
004	RF Center: OARF3 r=2.55NM	OA055	—	—	-8.1	3.6	L	+3100	—	—	Basic RNP1
005	RF Center: OARF3 r=2.55NM	OA056	—	—	-8.1	3.5	L	2800	—	—	Basic RNP1
001	CA	—	—	098 (090.0)	-8.1	—	—	+1600	—	—	Basic RNP1
002	DF	BINGO	—	—	-8.1	—	R	5000	—	—	Basic RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	PUNUP	258 (250.3)	-8.1	1.0(-14000)	R	5500	FL140	-230(-14000)	Basic RNP1
Hold	BINGO	304 (296.1)	-8.1	1.0(-14000)	L	5000	FL140	-210(-14000)	Basic RNP1

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
PUNUP	*343412.97N/1325532.36E*	OARF3	*342842.60N/1324606.23E*
PEGLU	*343248.19N/1325045.55E*		
OA054	*343106.85N/1324503.74E*		
OA055	*342814.80N/1324304.26E*		
OA056	*342609.36N/1324606.51E*		
BINGO	*342425.72N/1331040.68E*		

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJOA / HIROSHIMA — VOR RWY10

HIROSHIMA APP	HONGO VOR/DME 117.9 HGE CH–126X 34°26′02″N/132°55′26″E	HIROSHIMA TOWER	RADAR AVBL
124.05 – 119.9		118.6 - 126.2	ATIS 127.25



NM to HGE	FAF	6	5	4	3	MAPt
ALT (3.0° APCH Path)	2860	2701	2383	2064	1746	–



MISSED APPROACH
Climb via HGE R105 to BINGO
and hold at 3300FT.
Contact HIROSHIMA APP.

Timing not authorized for defining the MAPt.

MINIMA THR elev. 1072 AD elev. 1086

CAT			CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	1600 (528)	1000	1600 (514)	1600
B		1200		
C				2400
D		1600	1640 (554)	3200

Circling to SOUTH side of RWY only.

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJOA / HIROSHIMA — VOR RWY28

HIROSHIMA APP	HONGO VOR/DME	HIROSHIMA TOWER	RADAR AVBL
124.05 – 119.9	117.9 HGE CH–126X 34˚26′02″N/132˚55′26″E	118.6 - 126.2	ATIS 127.25



NM to HGE	MAPt	3	4	5	6	7	FAF
ALT (3.5˚ APCH Path)	–	2006	2377	2748	3118	3489	3674

MISSED APPROACH

Climb to 1700FT on HDG272˚,
turn left climb to 3300FT via
HDG060˚ to intercept and
proceed via HGE R105
to BINGO and hold.
Contact HIROSHIMA APP.

PAPI and descent angles not coincident.
Timing not authorized for defining the MAPt.



DME to HGE	0	1.3	4.0	7.5
NM to THR	0	0.8	3.4	6.9

MINIMA THR elev. 1067 AD elev. 1086

CAT			CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	1420 (353)	1200	1510 (424)	1600
B	1450 (383)	1300	1540 (454)	
C	1480 (413)	1400		2400
D	1500 (433)	1600	1640 (554)	3200

Circling to SOUTH side of RWY only.
VDP not applicable.

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJOA / HIROSHIMA — RNP RWY28

HIROSHIMA APP	RNP APCH	HIROSHIMA TOWER	RADAR AVBL
124.05–119.9		118.6–126.2	ATIS 127.25



NM to Next Fix	MAPt	1	2	3	4	FAF
ALT (3.0˚ APCH Path)	–	1753	2072	2390	2709	2800

MISSED APPROACH
Direct to MISEN and hold at 4100FT.
Contact HIROSHIMA APP.

(for using VOR/DME)
Climb via HGE R279 to MISEN and hold at 4100FT.
Contact HIROSHIMA APP.



Missed APCH climb gradient MNM 4.0%

MINIMA — THR elev. 1067 — AD elev. 1086

CAT	LNAV/VNAV		LNAV		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	1440 (373)	1200	1440 (373)	1200	1510 (424)	1600
B		1300		1300	1540 (454)	
C		1400		1400		2400
D		1600		1600	1640 (554)	3200

Circling to SOUTH side of RWY only.
MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJOA / HIROSHIMA — RNP Z RWY10(AR)

HIROSHIMA APP 124.05 - 119.9	RNP AR RF required.	HIROSHIMA TOWER 118.6 - 126.2	RADAR AVBL ATIS 127.25

For uncompensated Baro-VNAV systems, procedure not authorized below -10°C / above 45°C





MISSED APPROACH

Climb to 5000FT, to OA053,
to BINGO and hold.
Contact HIROSHIMA APP.

Missed APCH climb gradient MNM 5.0%

MINIMA	THR elev. 1072		AD elev. 1086	
CAT	RNP 0.10		RNP 0.30	
	DA(H)	RVR/CMV	DA(H)	RVR/CMV
A	-	-	-	-
B				
C	1515(443)	1000	1598(526)	1200
D		1400		1600

MINIMA with Missed APCH climb gradient of 2.5% are not established.

Authorization Required

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJOA / HIROSHIMA RNP Z RWY10(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	DEMIO	-	-	-8.1	-	-	+5500	-	-	-
002	TF	OA050	-	255 (247.1)	-8.1	4.5	-	+3200	-185	-	1.0
003	RF Center: OARF1 r=2.54NM	OA051	-	-	-8.1	2.8	L	3200	-	-	1.0
004	RF Center: OARF1 r=2.54NM	OA052	-	-	-8.1	4.2	L	1874	-	-3.00	0.10 0.30
005	TF	RW10	Y	098 (090.0)	-8.1	2.3	-	1126	-	-3.00/54	0.10 0.30
006	TF	OA053	-	098 (090.0)	-8.1	6.2	-	-	-	-	1.0
007	TF	BINGO	-	111 (103.2)	-8.1	7.6	-	5000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	DEMIO	255 (247.1)	-8.1	1.0 (-14000)	R	5500	FL140	-230(-14000)	1.0
Hold	BINGO	304 (296.1)	-8.1	1.0 (-14000)	L	5000	FL140	-210(-14000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
DEMIO	*343248.47N / 1325512.50E*	OARF1	*342842.28N / 1325120.72E*
OA050	*343102.99N / 1325009.23E*		
OA051	*342852.58N / 1324816.81E*		
OA052	*342609.63N / 1325120.84E*		
RW10	*342609.69N / 1325411.25E*		
OA053	*342609.67N / 1330143.51E*		
BINGO	*342425.72N / 1331040.68E*		

INSTRUMENT APPROACH CHART

RJOA / HIROSHIMA — RNP Y RWY10(AR)

HIROSHIMA APP 124.05 - 119.9	RNP AR RF required.	HIROSHIMA TOWER 118.6 - 126.2	RADAR AVBL ATIS 127.25

For uncompensated Baro-VNAV systems, procedure not authorized below -10°C / above 45°C





Missed APCH climb gradient MNM 5.0%

MINIMA	THR elev. 1072		AD elev. 1086	
CAT	RNP 0.10		RNP 0.30	
	DA(H)	RVR/CMV	DA(H)	RVR/CMV
A	-	-	-	-
B				
C	1515(443)	1000	1598(526)	1200
D		1400		1600

MINIMA with Missed APCH climb gradient of 2.5% are not established.

Authorization Required

CHANGE : Description of VAR.

INSTRUMENT APPROACH CHART

RJOA / HIROSHIMA RNP Y RWY10(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	AXELA	-	-	-8.1	-	-	+3300	-	-	1.0
002	TF	OA061	-	278 (270.0)	-8.1	3.5	-	+3200	-185	-	1.0
003	RF Center: OARF2 r=2.79NM	OA062	-	-	-8.1	4.6	R	3200	-	-	1.0
004	RF Center: OARF2 r=2.79NM	OA052	-	-	-8.1	4.2	R	1874	-	-3.00	0.10 0.30
005	TF	RW10	Y	098 (090.0)	-8.1	2.3	-	1126	-	-3.00/54	0.10 0.30
006	TF	OA053	-	098 (090.0)	-8.1	6.2	-	-	-	-	1.0
007	TF	BINGO	-	111 (103.2)	-8.1	7.6	-	5000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	AXELA	278 (270.0)	-8.1	1.0 (-14000)	L	3300	FL140	-230(-14000)	1.0
Hold	BINGO	304 (296.1)	-8.1	1.0 (-14000)	L	5000	FL140	-210(-14000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
AXELA	*342034.40N / 1325534.80E*	OARF2	*342321.96N / 1325120.96E*
OA061	*342034.29N / 1325121.21E*		
OA062	*342334.91N / 1324759.36E*		
OA052	*342609.63N / 1325120.84E*		
RW10	*342609.69N / 1325411.25E*		
OA053	*342609.67N / 1330143.51E*		
BINGO	*342425.72N / 1331040.68E*		

RJOA / HIROSHIMA

Visual REP

※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : VAR.

Call sign	BRG / DIST from ARP	Remarks
白竜 Hakuryu	345°T / 4.3NM	湖 Lake
小佐木 Kosagi	115°T / 10.1NM	小佐木島 Kosagi - Island
竹原 Takehara	184°T / 5.8NM	竹原駅 Railway Station
三永サウス Minaga South	251°T / 8.4NM	東広島駅 Railway Station
新庄 Shinjo	209°T / 2.9NM	新庄交差点 Shinjo Intersection


RJOA / HIROSHIMA
LDG CHART
ELEV 1086 ft
VAR 8°W 2022
Annual change 4.8'W
34°29´
27´
25´
23´
1882
1320
1320
1320
1302
•1697
1582
1390
1623
1688
1320
1585
1666
1485
1475
PAPI ANGLE 3.0°
MEHT 20.0m (66ft)
397m FM THR
HIROSHIMA TWR
118.6 - 126.2
121.5 - 243.0
ABN
10
28
ALS
SALS
1207
1160
1008
1133
VOR/DME
HONGO
117.9 HGE
CH-126X
34°26´02"N/132°55´26"E
PAPI ANGLE 3.0°
MEHT 22.5m (73.8ft)
416.3m FM THR
1074
ELEVATIONS AND
HEIGHTS IN FEET
MEAN SEA LEVEL
SCALE
1000 500 0 1000 2000 m
500 0 3000 ft
• 1323
132°54´
56´
58´
CHANGE : VAR.

RJOA / HIROSHIMA Minimum Vectoring Altitude CHART

VAR 8˚W (2022)



CENTER：*342602N/1325458E* (RADAR SITE)

CHANGE : VAR.