

STANDARD DEPARTURE CHART-INSTRUMENT

RJOZ / OZUKI

SID

OZUKI REVERSAL THREE DEPARTURE

RWY 17: ...

RWY 35: Turn left ...

... Climb via OCT R170, turn left to OCT TACAN within 10DME.

Cross OCT TACAN at or above 4000FT.

Then proceed via OCT R330, turn right to OCT TACAN within 5DME.

Cross OCT TACAN at or above 5000FT or specified altitude.

Note RWY 35: Maintain visual contact until passing 1700FT.

KUGA TRANSITION

From over OCT TACAN, via OCT R170 to intercept and proceed via IWT R267 to IWT TACAN.

FUKUOKA TRANSITION

From over OCT TACAN, via OCT R170 to intercept and proceed via DGC R080 (MRA 11000FT) to DGC VORTAC.

Note: This TRANSITION is for TACAN equipped aircraft only.

CHANGE : PROC course(KUGA TRANSITION).

## STANDARD DEPARTURE CHART-INSTRUMENT

RJOZ / OZUKI

SID

CHANGE : PROC course(KUGA TRANSITION).




RJOZ / OZUKI

## TACAN A



At 0.5DME prior to OCT TACAN,  
turn right climb via OCT R-120 to  
2,000ft, turn right and proceed via  
OCT 10DME ARC to MAZYA  
then proceed via OCT R-157  
to 7DME and hold.  
Contact TSUIKI APP.




MINIMA		AD elev. 13
CAT	CIRCLING	
	MDA(H)	VIS
A	900 (887)	1600
B		
C	—	—
D		

## INSTRUMENT APPROACH CHART


RJOZ / OZUKI

TACAN B



## MISSED APPROACH

At 0.5 DME prior to OCT TACAN, turn right climb via OCT R-120 to 2,000ft, turn right and proceed via OCT 10DME ARC to MAZYA then proceed via OCT R-157 to 7DME and hold.  
Contact TSUIKI APP.



## MINIMA

AD elev. 13

CAT	CIRCLING	
	MDA(H)	VIS
A	900 (887)	1600
B		
C	—	—
D		

CHANGE : FREQ of OZUKI TOWER abolished(126.2,236.8)

## LDG CHART



## RADIO DATA

TWR 122.0, 228.2, 302.2, EU-EV

FACILITIES AVAILABLE

Weather, fuel (JETA-1 PLUS), Hangar

Other lighting : Blue taxiway edge lights,  
lighted wind direction indicator, obstruction light,  
take-off target light.  
angle of approach lights.