AD 2 AERODROMES

RJFO AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJFO - OITA

RJFO AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	*332846N/1314414E* 007 Degrees /1.5KM FM RWY 01 THR
2	Direction and distance from (city)	16NM NE FM OITA City
3	Elevation/ Reference temperature	17FT / 30°C
4	Geoid undulation at AD ELEV PSN	104FT
5	MAG VAR/ Annual change	7°W(2009) / 2'W
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	JCAB Aza Omida, Itoharu, Musashi-machi, Kunisaki-shi, Oita Pref. 873-0421 JAPAN. Tel:0978(67)3771, 0978(67)3773 Fax:0978(67)3780, 0978(67)3781(AIS) AFS:RJFOYFYX
7	Types of traffic permitted (IFR/VFR)	IFR/VFR
8	Remarks	Nil

RJFO AD 2.3 OPERATIONAL HOURS

1	AD Administration	2230 - 1330
2	Customs and immigration	Customs:2330-0815 Immigration:INTL SKED FLT hours only
3	Health and sanitation	INTL SKED FLT hours only
4	AIS Briefing Office	2230 - 1330
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	H24 (FUKUOKA)
7	ATS	2230 - 1330
8	Fuelling	2230 - 1330
9	Handling	2230 - 1330
10	Security	2230 - 1330
11	De-icing	Nil
12	Remarks	Nil

RJFO AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	All the modern institutions that with the weight thing to Boeing 747 type freighter.
2	Fuel/ oil types	JET A-1
3	Fuelling facilities/ capacity	Fuel Truck / Not Limitation
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

RJFO AD 2.5 PASSENGER FACILITIES

1	Hotels	Near FM Airport
2	Restaurants	At Airport
3	Transportation	Buses and Taxis
4	Medical facilities	Hospital in Aki-town 3km
5	Bank and Post Office	BANK ATM at Airport
6	Tourist Office	At Airport
7	Remarks	Nil

RJFO AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT 9
2	Rescue equipment	Chemical fire fighting truck x 3 Water-supply truck Lighting power supply truck Emergency medical equipments conveyance truck
3	Capability for removal of disabled aircraft	Ask AD Administration
4	Remarks	Nil

RJFO AD 2.7 SEASONAL AVAILABILITY-CLEARING

1	Types of clearing equipment	Clearing equipments: Sweeper x 1 Snow removal equipments: NIL(commission)
2	Clearance priorities	(1) RWY, TWY T0 T6 P, Spot 7-9 (2) TWY T1 T5, Spot 5-6 (3) TWY T2 T3 T4, Spot 1-3 10 11
3	Remarks	Snow removal will be commenced when the RWY and TWY are covered with snow its depth 3cm or more(Ask AD administration for details)

RJFO AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Apron surface and strength	Surface: Asphalt-concrete and Cement-concrete Strength : Spot NR1A, 1B, 2, 3 : PCR 640/F/D/X/T Spot NR5, 6 : PCR 797/R/B/W/T Spot NR7, 8, 9, 10 : PCR 925/R/B/W/T Spot NR11 : PCR 1132/R/B/W/T
2	Taxiway width, surface and strength	Surface: Asphalt-concrete and Cement-concrete Strength : TWY T0, T1, T2, T3, T4, T5, T6: PCR 1041/F/C/X/T TWY P0, P1, P3, P4, P5: PCR 1041/F/C/X/T TWY P2: PCR 1132/R/B/W/T Width: TWY T1, T2, T3, T4, T5: 34m TWY T0, T6: 28.5m TWY P0, P1, P2, P3, P4, P5: 23m
3	ACL and elevation	Not Available
4	VOR checkpoints	Not Available
5	INS checkpoints	(Spot NR) 2 : *332844.43N,1314403.07E* 3 : *332842.98N,1314403.05E* 5 : *332841.51N,1314403.02E* 6 : *332840.05N,1314403.01E* 7 : *332837.39N,1314359.83E* 8 : *332835.12N,1314359.81E* 9 : *332832.85N,1314359.79E* 10 : *332830.58N,1314359.77E* 11 : *332828.47N,1314359.71E*
6	Remarks	Nil

RJFO AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	ACFT stand ID signs: Spot 1-11
2	RWY and TWY markings and LGT	RWY:RWY01/19(SEE RJFO AD2.24) (Marking) RWY designation, RWY CL, RWY THR, RWY middle point, Aiming point, TDZ, RWY side stripe (LGT) RCLL, REDL, RTHL, RENL, RTZL(RWY01), WBAR(RWY01) TWY:ALL TWY (Marking) TWY CL, RWY HLDG PSN, TWY side stripe (LGT) TWY edge LGT, TWY CL LGT, RWY guard LGT, Taxiing guidance sign
3	Stop bars	Nil
4	Remarks	(Marking) Overrun area (LGT) Apron flood LGT

RJFO AD 2.10 AERODROME OBSTACLES

- In Area2 See Obstacle data

- In Area3 To be developed

RJFO AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	FUKUOKA
2	Hours of service MET Office outside hours	H24 (FUKUOKA)
3	Office responsible for TAF preparation Periods of validity	FUKUOKA 30 Hours
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Briefing is available upon inquiry at FUKUOKA
6	Flight documentation Language(s) used	C En
7	Charts and other information available for briefing or consultation	S_6, U_{85}, U_7, U_5, U_3, U_{25}, U_2/Tr, P_S, P_5, P_3, P_{25}, P_{SWE}, P_{SWF}, P_{SWG}, P_{SWI}, P_{SWM}, P_{SW}(domestic), E, C, W_E, W_F, W_G, W_I, W, N
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	TWR, APP, ATIS
10	Additional information(limitation of service, etc.)	Nil

RJFO AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCR) and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
01	000°	3000×45	PCR 1041/F/C/X/T Asphalt-Concrete	*332757.53N 1314413.22E* 104F*T*	THR ELEV:19FT TDZ ELEV:19FT
19	180°	3000×45	PCR 1041/F/C/X/T Asphalt-Concrete	*332934.89N 1314414.08E* 104FT	THR ELEV:17FT

Slope of RWY	Strip Dimensions(M)	RESA (Overrun) Dimensions (M)	Remarks
7	10	11	14
See AD CHART	3120×300	190×(MNM:152 MAX:300)*	RWY Grooving 3000m × 30m
	3120×300	40×300	
		*For detail, ask airport administrator	

RJFO AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
01	3000	3000	3000	3000	Nil
19	3000	3000	3000	3000	Nil

RJFO AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
01	PALS (CAT I) 900M LIH	Green Green	PAPI 3.0°/LEFT 413M 66FT	900M	3000M 30M Coded color (White/Red) LIH	3000M 60M Coded color (White/Yellow) LIH	Red	Nil (*2)
19	SALS (*1) 420M LIH	Green -	PAPI 3.0°/LEFT 457M 74FT	Nil	3000M 30M Coded color (White/Red) LIH	3000M 60M Coded color (White/Yellow) LIH	Red	Nil (*2)
Remarks								
10								
SALS with APCH LGT beacon(600m and 900m FM RWY THR)(*1) Overrun area edge LGT(LEN:60m Color:Red)(*2) CGL for RWY 19								

RJFO AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	ABN: *332833N/1314353E*, White/Green EV4.3sec, HO Operating in night, IMC, and when requested
2	LDI location and LGT Anemometer location and LGT	LDI:Nil Anemometer: RWY01: 355m from RWY 01 THR, LGTD RWY19: 300m from RWY 19 THR, LGTD
3	TWY edge and center line lighting	TWY edge and center line lights installed, see AD2.9
4	Secondary power supply / switch-over time	Within 1 sec : REDL, RENL, RTHL, WBAR, RCLL, Overrun area edge LGT Within 15 sec : Other LGT
5	Remarks	WDI LGT

RJFO AD 2.16 HELICOPTER LANDING AREA

Nil

RJFO AD 2.17 ATS AIRSPACE

Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
OITA CTR	Area within a radius of 5nm of OITA ARP	3000 or below	D	OITA TOWER	
OITA ACA	SEE RJFO ATTACHED CHART				

大分進入管制区
Oita Approach Control Area



Point list

(1) *334923N1315428E*
(2) *333820N1313835E*
(3) *333112N1313754E*
(4) *331835N1313643E*
(5) *331513N1312903E*
(6) *330719N1312355E*
(7) *325619N1311408E*
(8) *332346N1321425E*
(9) *332258N1320939E*
(10) *333116N1320253E*
(11) *334410N1320642E*
(12) *340827N1321357E*
(13) *331313N1314212E*
(14) *335858N1315956E*
(15) *334822N1320757E*
(16) *335336N1321117E*

RJFO AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
APP	Oita Approach	120.6MHz(1) 127.7MHz 119.05MHz 261.2MHz 121.5MHz(E) 243.0MHz(E)	2230 - 1330	(1)Primary
ASR	Oita Radar	119.05MHz 120.6MHz 127.7MHz 261.2MHz 121.5MHz(E) 243.0MHz(E)	2230 - 1330	
DEP	Oita Departure	127.7MHz 120.6MHz 119.05MHz 261.2MHz 121.5MHz(E) 243.0MHz(E)	2230 - 1330	
TWR	Oita Tower	118.8MHz(1) 126.2MHz 261.2MHz 121.5MHz(E) 243.0MHz(E)	2230 - 1330	
GND	Oita Ground	121.6MHz	2230 - 1330	
ATIS	Oita Airport	127.8MHz	2230 - 1330	

RJFO AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid (VOR declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	*5*	6	7
ILS-LOC 01	ITF	111.5MHz	2230 - 1330	*332942.19N/ 1314414.15E*		LOC:225m(738ft) away FM RWY19 THR, BRG(MAG)007°. Unusable beyond 16nm.
ILS-GP 01	-	332.9MHz	2230 - 1330	*332807.70N/ 1314417.95E*		GP:315m (1034ft) inside FM RWY 01 THR,120m(394ft) E of RCL. HGT of ILS Ref datum16.5m (54ft) GP angle 3.0°.
ILS-DME 01	ITF	1013MHz (CH-52X)	2230 - 1330	*332808.01N/ 1314418.31E*	37ft	DME: 325m(1066ft) inside FM RWY 01 THR, 130m(427ft) E of RCL.
VOR (7°W/2016)	TFE	117.7MHz	H24	*332922.97N/ 1314343.52E*		VOR Unusable: 210°-220° beyond 35NM below 8,000FT. 240°-260° beyond 35NM below 8,000FT. 270°-330° beyond 30NM below 6,000FT.
DME	TFE	1211MHz (CH-124X)	H24	*332922.97N/ 1314343.52E*	100ft	DME Unusable: 260°-270° beyond 35NM below 8,000FT. 270°-290° beyond 15NM below 6,000FT. 290°-330° beyond 30NM below 6,000FT. 330°-340° beyond 30NM below 5,000FT.
MSAS		1575.42MHz	H24			Transmitting antennas are satellite based.

RJFO / OITA

ILS

ILS



REMARKS :	1. LOC beam BRG(MAG)	007°
	2. HGT of ILS REF datum	16.5m(54ft)
	3. GP angle	3.0°
	4. ELEV of ILS-DME	11.2m(37ft)



LOC UNUSABLE : BEYOND 16NM.

RJFO AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

On use of this airport by transient ACFT, the operator is required to obtain the prior permission of the airport administrator in order to adjust of parking area, except scheduled flight and ACFT in an emergency.

2. Taxiing to and from stands

Nil

3. Parking area for small aircraft(General aviation)

Nil

4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

Nil

7. School and training flights - technical test flights - use of runways

Nil

8. Helicopter traffic - limitation

Nil

9. Removal of disabled aircraft from runways

Nil

RJFO AD 2.21 NOISE ABATEMENT PROCEDURES

Nil

RJFO AD 2.22 FLIGHT PROCEDURES

1. TAKE OFF MINIMA

	RWY	ACFT CAT	REDL & RCLL		REDL or RCLL or RCL marking		NIL (DAYTIME ONLY)	
			RVR	VIS	RVR	VIS	RVR	VIS
Multi-Engine ACFT with TKOF ALTN AP Filed	01	A,B,C,D	400	400	400	400	-	500
	19	A,B,C,D	-	400	-	400	-	500
OTHER	01	A,B,C,D	AVBL LDG MINIMA					
	19	A,B,C,D						

2. Lost Communication Procedures for Arrival Aircraft under radar navigational guidance

If radio Communications with Oita Approach/Radar are lost for 30 seconds, squawk Mode A/3 Code 7600 and;

I 1. Contact Oita Tower.
2. If unable, proceed in accordance with Visual Flight Rules.
3. If unable, proceed to Musashi VOR/DME at last assigned altitude or 3500 feet whichever is higher and execute Instrument Approach.

II Procedures other than above will be issued when situation required.

3. Trajectorized Airport Traffic Data Processing System (TAPS)

Aircraft flying in Oita approach control area under its control will be instructed to reply with discrete code on Mode A/3 and Mode C.

If an aircraft has no capability of replying with discrete code, the pilot shall report ATC if so instructed.

大分アプローチの指示のもとに、当該進入管制区を飛行する航空機は、モード A/3 の二次レーダー個別コード及びモード C による応答を指示される。
二次レーダー個別コードを搭載していない航空機が当該コードによる応答を指示された場合は、管制機関に対しその旨通報すること。

RJFO AD 2.23 ADDITIONAL INFORMATION

Nil

RJFO AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart
Aerodrome Obstacle Chart-ICAO type A (RWY01/19)
Aerodrome Obstacle Chart-ICAO type B
Standard Departure Chart-Instrument (MUSASHI)
Standard Departure Chart-Instrument (EBOSHI-RNAV)
Standard Departure Chart-Instrument (TOYO-RNAV)
Standard Departure Chart-Instrument (FUSHA-RNAV)
Standard Departure Chart-Instrument (TRANSITION-RNAV)
Standard Arrival Chart-Instrument (JEWEL)
Standard Arrival Chart-Instrument (KABOS, BAIEN, HOVER, TANSO, LUISU-RNAV)
Instrument Approach Chart (ILS Z RWY01)
Instrument Approach Chart (ILS Y or LOC Y RWY01)
Instrument Approach Chart (ILS X or LOC X RWY01)
Instrument Approach Chart (VOR RWY01)
Instrument Approach Chart (VOR A)
Instrument Approach Chart (RNP Z RWY19)
Instrument Approach Chart (RNP RWY01(AR))
Instrument Approach Chart (RNP Y RWY19(AR))
Other Chart (Visual REP)
Other Chart (MVA CHART)

RJFO / OITA

AD CHART

CHANGE : Description of strength of pavement.



AERODROME OBSTACLE CHART-ICAO
TYPE A (OPERATING LIMITATIONS)

DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC

MAGNETIC VARIATION 7°17' W-APR 2016



DECLARED DISTANCES		
RWY 01		RWY 19
3000m	TAKE OFF RUN AVAILABLE	3000m
3000m	TAKE OFF DISTANCE AVAILABLE	3000m
3000m	ACCELERATE STOP DISTANCE AVAILABLE	3000m
3000m	LANDING DISTANCE AVAILABLE	3000m



LEGEND

- IDENTIFICATION NUMBER
- POLE, TOWER, SPIRE, ANTENNA, ETC
- TREE
- LEVEE
- RAILROAD
- RIVER
- TRANSMISSION LINE OR OVERHEAD CABLE
- TRIANGULATION POINT
- AERONAUTICAL GROUND LIGHT

AMENDMENT RECORD		
Nr	DATE	ENTERED BY

HORIZONTAL SCALE



DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC

Transverse Mercator Projection

AERODROME OBSTACLE CHART-ICAO
TYPE B

LEGEND

- AERODROME REFERENCE POINT 33° 28 '46 "N 131° 44 '14 "E
- POLE, TOWER, SPIRE, ANTENNA, ETC
- AERONAUTICAL GROUND LIGHT
- OBSTRUCTION LIGHT
- BUILDING OR LARGE STRUCTURE
- RAILROAD
- TRIANGULATION POINT
- TREE
- RIVER
- LAKE
- CONTOURS(ft)

AMENDMENT RECORD

Nr	DATE	ENTERED BY

CHANGE : Update.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA SID

MUSASHI REVERSAL TWO DEPARTURE

RWY01 : Climb RWY HDG to 500FT, turn right HDG177˚ to intercept and proceed via TFE R132 to TFE 10.0DME,...

RWY19 : Turn left, climb via TFE R132 to TFE 10.0DME,...
...turn right, direct to TFE VOR/DME.
Cross TFE VOR/DME at or above 4000FT.

Note RWY01 : 5.0% climb gradient required up to 500FT.
OBST ALT 266FT located at 2.5NM 351˚ FM end of RWY01.



STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA RNAV SID

EBOSHI TWO DEPARTURE		RNAV1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll. 2) RADAR service required.	Critical DME	–
	DME GAP	RWY01 : DER ～ 19NM to YANAI RWY19 : DER ～ 26NM to YANAI
	Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1



EBOSHI TWO DEPARTURE

RWY01 : Climb on HDG007˚ at or above 500FT, turn right direct to YANAI.

RWY19 : Climb on HDG187˚ at or above 500FT, turn left direct to YANAI.

Note RWY01 : 5.0% climb gradient required up to 500FT.
OBST ALT 266FT located at 2.5NM 351˚ FM end of RWY01.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA RNAV SID

EBOSHI TWO DEPARTURE

RWY01

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	007 (000.4)	-7.0	—	—	+500	—	—	RNAV1
002	DF	YANAI	—	—	-7.0	—	R	—	—	—	RNAV1

RWY19

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	187 (180.4)	-7.0	—	—	+500	—	—	RNAV1
002	DF	YANAI	—	—	-7.0	—	L	—	—	—	RNAV1

STANDARD DEPARTURE CHART- INSTRUMENT

RJFO / OITA RNAV SID

TOYO THREE DEPARTURE		RNAV1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll. 2) RADAR service required.	Critical DME	–
	DME GAP	RWY01 : DER ～ 9NM to TACHI RWY19 : DER ～ 3NM to FO901
	Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1



TOYO THREE DEPARTURE

RWY01 : Climb on HDG007˚ at or above 500FT, turn right direct to TACHI,...

RWY19 : Climb on HDG187˚ at or above 500FT, direct to FO901,...
...to OOITA at or above 4000FT.

Note RWY01 : 5.0% climb gradient required up to 500FT.
OBST ALT 266FT located at 2.5NM 351˚ FM end of RWY01.

STANDARD DEPARTURE CHART- INSTRUMENT

RJFO / OITA RNAV SID

TOYO THREE DEPARTURE

RWY01

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	007 (000.4)	-7.0	–	–	+500	–	–	RNAV1
002	DF	TACHI	–	–	-7.0	–	R	–	–	–	RNAV1
003	TF	OOITA	–	215 (208.1)	-7.0	13.8	–	+4000	–	–	RNAV1

RWY19

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	–	–	187 (180.4)	-7.0	–	–	+500	–	–	RNAV1
002	DF	FO901	–	–	-7.0	–	–	–	–	–	RNAV1
003	TF	OOITA	–	197 (189.8)	-7.0	9.8	–	+4000	–	–	RNAV1

STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA RNAV SID

FUSHA ONE DEPARTURE		RNAV1
Note 1) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll. 2) RADAR service required.	Critical DME	RWY01 : MYE 25NM to FUSHA ～ 24NM to FUSHA
	DME GAP	RWY01 : DER ～ 25NM to FUSHA RWY19 : DER ～ 23NM to FUSHA
	Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1



FUSHA ONE DEPARTURE

RWY01 : Climb on HDG007˚ at or above 500FT, turn right direct to FUSHA.

RWY19 : Climb on HDG187˚ at or above 500FT, turn left direct to FUSHA.

Note RWY01 : 5.0% climb gradient required up to 500FT.
OBST ALT 266FT located at 2.5NM 351˚ FM end of RWY01.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA RNAV SID

FUSHA ONE DEPARTURE

RWY01

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	007 (000.4)	-7.0	—	—	+500	—	—	RNAV1
002	DF	FUSHA	—	—	-7.0	—	R	—	—	—	RNAV1

RWY19

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	187 (180.4)	-7.0	—	—	+500	—	—	RNAV1
002	DF	FUSHA	—	—	-7.0	—	L	—	—	—	RNAV1

STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA — RNAV TRANSITION

DONAR TRANSITION / DOUGO TRANSITION / FIATO TRANSITION SALTY TRANSITION / SPIDE TRANSITION / ASHIZURI TRANSITION		RNAV1
Note 1) DME/DME/IRU or GNSS required. 2) RADAR service required.	Critical DME	–
	DME GAP	–
	Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1



DONAR TRANSITION
From FUSHA, to DONAR at or above FL160.

DOUGO TRANSITION
From FUSHA, to DONAR at or above FL160, to MYE.

FIATO TRANSITION
From FUSHA, to DONAR at or above FL160, to SALTY, to FIATO.

SALTY TRANSITION
From FUSHA, to DONAR at or above FL160, to SALTY.

SPIDE TRANSITION
From FUSHA, to DONAR at or above FL160, to SPIDE.

ASHIZURI TRANSITION
From FUSHA, to SUC.

CHANGE : Critical DME deleted.

STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA RNAV TRANSITION

DONAR TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	FUSHA	–	–	-7.4	–	–	–	–	–	RNAV1
002	TF	DONAR	–	086 (078.7)	-7.4	17.8	–	+FL160	–	–	RNAV1

DOUGO TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	FUSHA	–	–	-7.4	–	–	–	–	–	RNAV1
002	TF	DONAR	–	086 (078.7)	-7.4	17.8	–	+FL160	–	–	RNAV1
003	TF	MYE	–	027 (019.8)	-7.4	30.6	–	–	–	–	RNAV1

FIATO TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	FUSHA	–	–	-7.4	–	–	–	–	–	RNAV1
002	TF	DONAR	–	086 (078.7)	-7.4	17.8	–	+FL160	–	–	RNAV1
003	TF	SALTY	–	043 (036.1)	-7.4	37.3	–	–	–	–	RNAV1
004	TF	FIATO	–	044 (036.3)	-7.4	11.8	–	–	–	–	RNAV1

SALTY TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	FUSHA	–	–	-7.4	–	–	–	–	–	RNAV1
002	TF	DONAR	–	086 (078.7)	-7.4	17.8	–	+FL160	–	–	RNAV1
003	TF	SALTY	–	043 (036.1)	-7.4	37.3	–	–	–	–	RNAV1

STANDARD DEPARTURE CHART - INSTRUMENT

RJFO / OITA RNAV TRANSITION

SPIDE TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	FUSHA	–	–	-7.4	–	–	–	–	–	RNAV1
002	TF	DONAR	–	086 (078.7)	-7.4	17.8	–	+FL160	–	–	RNAV1
003	TF	SPIDE	–	061 (054.1)	-7.4	30.1	–	–	–	–	RNAV1

ASHIZURI TRANSITION

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	FUSHA	–	–	-7.4	–	–	–	–	–	RNAV1
002	TF	SUC	–	134 (126.5)	-7.4	54.0	–	–	–	–	RNAV1

STANDARD ARRIVAL CHART- INSTRUMENT

RJFO / OITA STAR

JEWEL ARRIVAL
From over DONKO, via TFE R038 to JEWEL.
Cross DONKO at or above 5000FT, cross JEWEL at or above 3000FT.



STANDARD ARRIVAL CHART- INSTRUMENT

RJFO / OITA

RNAV STAR

KABOS ARRIVAL / BAIEN ARRIVAL HOVER ARRIVAL / TANSO ARRIVAL	RNAV1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.



STANDARD ARRIVAL CHART - INSTRUMENT

RJFO / OITA RNAV STAR

KABOS ARRIVAL

From YANAI at or above 5000FT, to KABOS at or above 3000FT.

Critical DME	–
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	YANAI	–	–	-7.4	–	–	+5000	–	–	RNAV1
002	TF	KABOS	–	243 (236.2)	-7.4	9.0	–	+3000	–	–	RNAV1

HOVER ARRIVAL

From YANAI at or above 5000FT, to FO161 at or above 3000FT, to SELEN, to METAL, to HOVER at or above 1800FT.

Critical DME	–
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	YANAI	–	–	-7.4	–	–	+5000	–	–	RNAV1
002	TF	FO161	–	203 (196.4)	-7.4	7.4	–	+3000	–	–	RNAV1
003	TF	SELEN	–	203 (196.4)	-7.4	21.9	–	–	-220	–	RNAV1
004	TF	METAL	–	277 (270.5)	-7.4	3.1	–	–	-220	–	RNAV1
005	TF	HOVER	–	338 (330.5)	-7.4	2.6	–	+1800	–	–	RNAV1

STANDARD ARRIVAL CHART - INSTRUMENT

RJFO / OITA RNAV STAR

BAIEN ARRIVAL

From YANAI at or above 5000FT, to BAIEN at or above 3000FT.

Critical DME	–
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	YANAI	–	–	-7.4	–	–	+5000	–	–	RNAV1
002	TF	BAIEN	–	224 (217.4)	-7.4	11.4	–	+3000	–	–	RNAV1

TANSO ARRIVAL

From YANAI at or above 5000FT, to FO162 at or above 3000FT, to TANSO at or above 2400FT.

Critical DME	–
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	YANAI	–	–	-7.4	–	–	+5000	–	–	RNAV1
002	TF	FO162	–	206 (199.4)	-7.4	7.2	–	+3000	–	–	RNAV1
003	TF	TANSO	–	206 (199.4)	-7.4	12.2	–	+2400	–	–	RNAV1

STANDARD ARRIVAL CHART - INSTRUMENT

RJFO / OITA

RNAV STAR

LUISU ARRIVAL	RNAV1

Note 1) DME/DME/IRU or GNSS required.
2) RADAR service required.

VAR 7˚W(2016)



LUISU ARRIVAL

From OOITA at or above 4000FT, to LUISU at or above 1800FT.

Critical DME	–
DME GAP	–
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course ˚M(˚T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	OOITA	–	–	-7.3	–	–	+4000	–	–	RNAV1
002	TF	LUISU	–	028 (020.2)	-7.3	4.7	–	+1800	–	–	RNAV1

INSTRUMENT APPROACH CHART

RJFO / OITA — ILS Z RWY01

OITA APP	ILS-LOC	OITA TOWER	RADAR AVBL
120.6	111.5 ITF ILS–GP 332.9 ILS–DME CH–52X	118.8 – 126.2	ATIS 127.8





MISSED APPROACH

Climb on HDG007˚ to TFE 2.0DME, turn right HDG136˚ to intercept and proceed via TFE R091 to 3000FT, turn left, direct to TFE VOR/DME and hold. Contact OITA APP.

Missed APCH climb gradient MNM 4.0%.

MINIMA THR elev. 19 AD elev. 17

CAT	CAT I		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	VIS
A	219 (200)	550	430 (413)	1600
B			470 (453)	
C			690 (673)	2400
D			760 (743)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.
Circling to EAST side of RWY only.

INSTRUMENT APPROACH CHART

RJFO / OITA — ILS Y or LOC Y RWY01

OITA APP	ILS-LOC	OITA TOWER	RADAR AVBL
120.6	111.5 ITF ILS-GP 332.9 ILS-DME CH-52X	118.8 - 126.2	ATIS 127.8



NM to ITF	FAF	5	4	3	2	1	MAPt
ALT (3.0° APCH Path)	1770	1604	1286	968	649	330	–



MISSED APPROACH
Climb on HDG007° to TFE 2.0DME, turn right HDG136° to intercept and proceed via TFE R091 to 3000FT, turn left, direct to TFE VOR/DME and hold. Contact OITA APP.

Timing not authorized for defining the MAPt.

Missed APCH climb gradient MNM 4.0%.

MINIMA THR elev. 19 AD elev. 17

CAT	CAT I DA(H)	CAT I RVR/CMV	LOC MDA(H)	LOC RVR/CMV	CIRCLING MDA(H)	CIRCLING VIS
A	219 (200)	550	300 (283)	800	430 (413)	1600
B					470 (453)	
C					690 (673)	2400
D				1200	760 (743)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.
Circling to EAST side of RWY only.

CHANGE : MDA(H), VDP

INSTRUMENT APPROACH CHART

RJFO / OITA — ILS X or LOC X RWY01

OITA APP	ILS - LOC	OITA TOWER	RADAR AVBL
120.6	111.5 ITF ILS-GP 332.9 ILS-DME CH-52X	118.8 - 126.2	ATIS 127.8



NM to ITF	FAF	5	4	3	2	1	MAPt
ALT (3.0˚ APCH Path)	1770	1604	1286	968	649	330	–



MISSED APPROACH

Climb on HDG007˚ to TFE 2.0DME, turn right HDG136˚ to intercept and proceed via TFE R091 to 3000FT, turn left, direct to TFE VOR/DME and hold.
Contact OITA APP.

Timing not authorized for defining the MAPt.

Missed APCH climb gradient MNM 4.0%.

MINIMA THR elev. 19 AD elev. 17

CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/CMV	MDA(H)	RVR/CMV	MDA(H)	VIS
A	219 (200)	550	300 (283)	800	430 (413)	1600
B					470 (453)	
C					690 (673)	2400
D				1200	760 (743)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.
Circling to EAST side of RWY only.

CHANGE : MDA(H), VDP

INSTRUMENT APPROACH CHART

RJFO / OITA VOR RWY01

OITA APP	MUSASHI VOR/DME 117.7 TFE CH–124X 33°29′23″N/131°43′44″E	OITA TOWER	RADAR AVBL
120.6		118.8 – 126.2	ATIS 127.8



NM to TFE	FAF	7	6	5	4	3	MAPt
ALT (3.0° APCH Path)	1986	1825	1507	1189	871	552	–



MISSED APPROACH

Turn right, climb to 3000FT via TFE R091, turn left, direct to TFE VOR/DME and hold. Contact OITA APP.

Timing not authorized for defining the MAPt.

MINIMA THR elev. 19 AD elev. 17

CAT			CIRCLING	
	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	500 (483)	1000	500 (483)	1600
B		1200		
C			690 (673)	2400
D		1600	760 (743)	3200

Circling to EAST side of RWY only.

INSTRUMENT APPROACH CHART

RJFO / OITA VOR A

OITA APP	MUSASHI VOR/DME 117.7 TFE	OITA TOWER	RADAR AVBL
120.6	CH–124X 33˚29´23˜N/131˚43´44˜E	118.8 – 126.2	ATIS 127.8



MISSED APPROACH
Climb to 3000FT via TFE R218 to TFE 1.1DME, turn left HDG046˚ to intercept and proceed via TFE R091 to TFE 13.0DME, turn left, via TFE 13.0DME counterclockwise ARC to intercept and proceed via TFE R038 to JEWEL and hold.
Contact OITA APP.

Timing not authorized for defining the MAPt.



Missed APCH climb gradient MNM 5.0%.

MINIMA		AD elev. 17
CAT	CIRCLING	
	MDA(H)	VIS
A	440 (423)	1600
B	480 (463)	
C	660 (643)	2400
D	760 (743)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.
Circling to EAST side of RWY only.

INSTRUMENT APPROACH CHART

RJFO / OITA — RNP Z RWY19

OITA APP	RNP APCH	OITA TOWER	RADAR AVBL
120.6		118.8 – 126.2	ATIS 127.8

Baro-VNAV not authorized below -10˚C

VAR 7˚W (2016)

KABOS (IAF)	334121.16N 1315016.71E
KAREI (IF)	333800.48N 1314418.57E
KUROZ (FAF)	333420.67N 1314416.61E
RW19 (MAPt)	332934.89N 1314414.08E
FO950 (MATF)	332634.63N 1314412.49E
TFE (MAHF)	332922.97N 1314343.52E



NM to Next Fix	MAPt	2	3	4	FAF
ALT (3.0˚ APCH Path)	–	703	1021	1340	1600

MISSED APPROACH

Climb direct to FO950, turn left direct to TFE and hold at 3000FT.
Contact OITA APP.

(For using VOR/DME)
Climb via TFE R179 to TFE 2.8DME, turn left, direct to TFE VOR/DME and hold at 3000FT.
Contact OITA APP.



MINIMA THR elev. 17 AD elev. 17

CAT	LNAV/VNAV DA(H)	LNAV/VNAV CMV	LNAV MDA(H)	LNAV CMV	CIRCLING MDA(H)	CIRCLING VIS
A	580 (563)	1400	580 (563)	1400	580 (563)	1600
B		1500		1500		
C		1600		1600	690 (673)	2400
D		1800		1800	760 (743)	3200

Circling to EAST side of RWY only

CHANGE:PROC renamed. Requirement for RNP.

INSTRUMENT APPROACH CHART

RJFO / OITA

RNP RWY01(AR)

OITA APP 120.6	RNP AR RF required.	OITA TOWER 118.8 - 126.2	RADAR AVBL ATIS 127.8

For uncompensated Baro-VNAV systems, procedure not authorized below -5°C / above 45°C



MISSED APPROACH

From RW01 on track 007°,
at or above 500FT turn right,
direct to BAIEN and hold at
3000FT.
Contact OITA APP.



Missed APCH climb gradient MNM 5.0%

MINIMA	THR elev. 19	AD elev. 17
CAT	RNP 0.30	
	DA(H)	RVR/CMV
A	-	-
B		
C	326(307)	1000
D		1400

MINIMA with Missed APCH climb gradient of 2.5% are not established.

Authorization Required

CHANGE : PROC renamed. Requirement for RNP.

INSTRUMENT APPROACH CHART

RJFO / OITA RNP RWY01(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	TANSO	-	-	-7.0	-	-	+2400	-220	-	-
002	TF	FO151	-	221 (214.2)	-7.0	3.6	-	2400	-165	-	1.0
003	RF Center: FORF1 r=2.25NM	FO152	-	-	-7.0	5.7	R	570	-	-3.00	0.3
004	TF	RW01	Y	007 (000.4)	-7.0	1.6	-	73	-	-3.00/54	0.3
005	FA	-	-	007 (000.4)	-7.0	-	-	+500	-	-	1.0
006	DF	BAIEN	-	-	-7.0	-	R	3000	-	-	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
TANSO	*332806.56N / 1315133.74E*	FORF1	*332622.64N / 1314653.79E*
FO151	*332506.40N / 1314907.12E*		
FO152	*332623.67N / 1314412.39E*		
RW01	*332757.53N / 1314413.22E*		
BAIEN	*333720.39N / 1315059.77E*		

CHANGE : PROC renamed.

INSTRUMENT APPROACH CHART

RJFO / OITA — RNP Y RWY19(AR)

OITA APP 120.6	RNP AR RF required.	OITA TOWER 118.8 - 126.2	RADAR AVBL ATIS 127.8

For uncompensated Baro-VNAV systems, procedure not authorized below -5°C / above 45°C



MISSED APPROACH

From RW19 on track 187°, at or above 500FT turn left, direct to BAIEN and hold at 3000FT.
Contact OITA APP.



Missed APCH climb gradient MNM 5.0%

MINIMA	THR elev. 17	AD elev. 17
CAT	RNP 0.30	
	DA(H)	CMV
A	-	-
B		
C	334(317)	1400
D		1600

Authorization Required

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : PROC renamed. Requirement for RNP.

INSTRUMENT APPROACH CHART

RJFO / OITA RNP Y RWY19(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	BAIEN	-	-	-7.0	-	-	+3000	-210	-	-
002	TF	FO951	-	234 (226.8)	-7.0	5.0	-	1700	-	-	1.0
003	TF	FO952	-	234 (226.8)	-7.0	1.9	-	1101	-165	-3.00	0.3
004	RF Center: FORF2 r=2.02NM	FO953	-	-	-7.0	1.6	L	578	-	-3.00	0.3
005	TF	RW19	Y	187 (180.4)	-7.0	1.6	-	67	-	-3.00/50	0.3
006	FA	-	-	187 (180.4)	-7.0	-	-	+500	-	-	1.0
007	DF	BAIEN	-	-	-7.0	-	L	3000	-	-	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
BAIEN	*333720.39N / 1315059.77E*	FORF2	*333110.65N / 1314640.11E*
FO951	*333356.67N / 1314639.45E*		
FO952	*333239.42N / 1314500.88E*		
FO953	*333111.58N / 1314414.94E*		
RW19	*332934.89N / 1314414.08E*		

CHANGE : PROC renamed.

RJFO / OITA

Visual REP

※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : Map updated. BRG/DIST from ARP.

Call sign	BRG / DIST from ARP	Remarks
姫島 Himeshima	346 °T / 15.3NM	島 Island
ゴルフコース Golf course	345 °T / 9.7NM	ゴルフ場 Golf course
行入ダム Gyonyu dam	321 °T / 7.0NM	ダム Dam
イーストポイント East point	090 °T / 10.0NM	海上 Over the sea
杵築 Kitsuki	232 °T / 6.7NM	八坂川河口 River mouth (The Yasaka)
佐賀関 Saganoseki	152 °T / 15.0NM	精錬所煙突 Chimney

RJFO / OITA Minimum Vectoring Altitude CHART

VAR 7˚W (2008)



CENTER : *332842N/1314351E* (RADAR SITE)