

RJSM / MISAWA

AD CHART



RJSM / MISAWA

Aircraft Parking / Docking Chart




RJSM / MISAWA

ATIS ★ 128.4 315.35
CLNC DEL
118.65 275.8
TOWER
118.1 315.8
DEP CON
125.3 363.8

Rwy	Knots	60	120	180	240	300	360
10	V/V(fpm)	350	700	1050	1400	1750	2100

ATC Climb Rate to 3500



• 3802

TA 14,000

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RWY 10: Climb on MIS VORTAC R-105 to ENKAI.
Cross ENKAI at or above 3500.

CHANGE : Update.


NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART - INSTRUMENT

RJSM / MISAWA

KOSUI TWO DEPARTURE

ATIS ★128.4 315.35	Rwy	Knots	60	120	180	240	300	360
CLNC DEL	28	V/V(fpm)	406	812	1218	1624	2030	2436
118.65 275.8	ATC Climb Rate to 3600							
TOWER								
118.1 315.8								
DEP CON								
125.3 363.8								



▼

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RWY 28: Climb on MIS VORTAC R-282 to KOSUI.
Cross KOSUI at or above 3600.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART - INSTRUMENT

RJSM / MISAWA


ATIS ★128.4 315.35
CLNC DEL
118.65 275.8
TOWER
118.1 315.8
DEP CON
125.3 363.8

MISAWA SIX DEPARTURE

Rwy	Knots	60	120	180	240	300	360
*28 (a) (c)	V/V(fpm)	215	430	645	860	1075	1290
*28 (b)	V/V(fpm)	251	502	753	1004	1255	1506
†28 (d)	V/V(fpm)	221	442	663	884	1105	1326
†28 (e)	V/V(fpm)	313	626	939	1252	1565	1878
†10 (f)	V/V(fpm)	299	598	897	1196	1495	1794
†28 (f)	V/V(fpm)	336	672	1008	1344	1680	2016
†10 (g)	V/V(fpm)	216	432	648	864	1080	1296
†28 (g)	V/V(fpm)	218	436	645	872	1090	1308
†10 (h)	V/V(fpm)	256	512	768	1024	1280	1536
†28 (h)	V/V(fpm)	220	440	660	880	1100	1320

* Minimum Climb Rate † ATC Climb Rate

- (a) OLSAE Transition to 5000
- (b) JYONA Transition to 600
- (c) SAMBO Transition to 4900
- (d) OLSAE Transition to 9000
- (e) JYONA Transition to 3500
- (f) SAMBO Transition to 13,000
- (g) HANAMAKI Transition to 10,000
- (h) MIYAKO Transition to 8000



DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RWY 10: Climb heading 103° to 1500, thence

TAKE-OFF RWY 28: Climb heading 283° to 1500 (1000 for JYONA TRANSITION), thence

(Continued on next page)

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART - INSTRUMENT

RJSM / MISAWA

MISAWA SIX DEPARTURE

DEPARTURE ROUTE DESCRIPTION
(Continued)HANAMAKI TRANSITION:

TAKE-OFF RWY 10: ...turn right to intercept MIS TACAN R-196 (HPE VOR/DME R-017) to HANAMAKI VOR/DME. Cross OMBOE at or above 10,000. Maintain ATC assigned altitude.

TAKE-OFF RWY 28: ...turn left to intercept MIS R-196 (HPE R-017) to HANAMAKI VOR/DME. Cross OMBOE at or above 10,000. Maintain ATC assigned altitude.

JYONA TRANSITION:

TAKE-OFF RWY 10: ...continue climb to 2000, then turn right and climb via MIS VORTAC to intercept MIS R-310 direct to JYONA. Cross JYONA at or above 3500. Maintain ATC assigned altitude.

TAKE-OFF RWY 28: ...then turn right to intercept MIS R-310 to JYONA. Cross JYONA at or above 3500. Maintain ATC assigned altitude.

MIYAKO TRANSITION:

TAKE-OFF RWY 10: ...turn right to intercept MIS R-161 (MQE VOR/DME R-340) to MIYAKO VOR/DME. Cross the SESEA at or above 8000. Maintain ATC assigned altitude.

TAKE-OFF RWY 28: ...turn left to intercept MIS R-161 (MQE R-340) to MIYAKO VOR/DME. Cross the SESEA at or above 8000. Maintain ATC assigned altitude.

OLSAE TRANSITION:

TAKE-OFF RWY 10: ...turn right to intercept MIS R-233 to OLSAE (MIS R-233/40 DME). Cross OLSAE at or above 9000. Maintain ATC assigned altitude.

TAKE-OFF RWY 28: ...turn left to intercept MIS R-233 to OLSAE (MIS R-233/40 DME). Cross OLSAE at or above 9000. Maintain ATC assigned altitude.

SAMBO TRANSITION:


TAKE-OFF RWY 10: ...turn right to intercept MIS R-221 to SAMBO (MIS R-221/36.7 DME). Cross SAMBO at or above 13,000. Maintain ATC assigned altitude.

TAKE-OFF RWY 28: ...turn left to intercept MIS R-221 to SAMBO (MIS R-221/36.7 DME). Cross SAMBO at or above 13,000. Maintain ATC assigned altitude.

CHANGE : Update.

NOTE: REPRINTING DOD FLIP

STANDARD DEPARTURE CHART - INSTRUMENT




NOTE: REPRINTING DOD FLIP

INTENTIONALLY LEFT BLANK


INSTRUMENT APPROACH CHART

RJSM / MISAWA




INSTRUMENT APPROACH CHART

RJSM / MISAWA

LOC I-MIS 109.7		APCH CRS 283°		Rwy ldg 9999 TDZE 109 Arpt Elev 119	ILS or LOC RWY28			
RADAR or DME required.				ALSF-1 	† MISSED APPROACH: Climb to 7000 on MIS VORTAC R-280 to KISSA, then climbing left turn direct SHOJU and hold. Continue climb-in-holding to 7000.			
<div><div>▼</div><div>* When ALS inop, increase RVR to 40 and vis to ¾ mile. ** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE RVR to 60 and vis to 1 ½ miles.</div></div>								
ATIS ★ 128.4 315.35		APP CON 120.7 317.8		TOWER 118.1 315.8		GND CON 118.65 275.8	CLNC DEL 118.65 275.8	ASR/PAR


*** Circling not authorized S of Rwy 10-28.

† Holding below FL150 on MIS VOR not authorized.



EMERG SAFE ALT 100 NM 8700

<div>7000 MIS R-280</div>		<div>KISSA MIS 8</div>		<div>SHOJU R-200 20</div>		<div>GABII RADAR 7.1</div>		<div>DEVLIS 15</div>	
TLv FL140 TA 14,000		VORTAC		JORJE RADAR 0.9		10,000 4000		103°	
		0.6 NM		6.2 NM		283°		4000	
CATEGORY		A		B		C		D	
S-ILS 28*		317/24		208		(200-½)		E	
S-LOC 28**		480/24 371 (400-½)		480/35		371		(400-¾)	
CIRCLING		580-1 461 (500-1)		580-1½ 461(500-1½)		680-2 561 (600-2)			




CHANGE : Update.

NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RJSM / MISAWA




NOTE: REPRINTING DOD FLIP

RJSM / MISAWA


TACAN or VOR RWY28

ALSF-1

MISSED APPROACH: Climb to 7000 on MIS VORTAC R-280 to KISSA, then climbing left direct SHOJU and hold. Continue climb in holding to 7000.

ASR/PAR


ELEV	119		TDZE	109
------	-----	--	------	-----

HIRL Rwy 10-28

30/12/21

INSTRUMENT APPROACH CHART

RJSM / MISAWA



NOTE: REPRINTING DOD FLIP

INSTRUMENT APPROACH CHART

RJSM / MISAWA

VORTAC MIS 115.4 Chan 101	APCH CRS 101°	Rwy Idg 9999 TDZE 119 Arpt Elev 119
---	-------------------------	--

HI-TACAN or VOR RWY10

RADAR or DME required.


* When ALS inop, increase RVR CAT AB to 55 and vis to 1 mile,
CAT CDE vis to 1½ miles.
** Circling S of Rwy 10-28 not authorized.

ALSF-1



MISSED APPROACH: Climb to 4000 on MIS
VORTAC R-106 to STICK and hold. Continue
climb in holding to 4000.

ATIS ★ 128.4 315.35	APP CON 120.7 317.8	TOWER 118.1 315.8	GND CON 118.65 275.8	CLNC DEL 118.65 275.8	ASR/PAR
-------------------------------	-------------------------------	-----------------------------	--------------------------------	---------------------------------	---------



EMERG SAFE ALT 100 NM 8700

ELEV 119 TDZE 119

VGS and descent
angles not coincidentTLv FL140
TA 14,0004000
MIS
R-106STICK
MIS
14KENII
RADAR
R-281
15

4400

HAMAV
RADAR
10

2900

HABIX
RADAR
7

2200

2.8

FOSEM
RADAR
1.9


VORTAC

3.43°
TCH 47

5.1 NM

0.5 NM

CATEGORY	A	B	C	D	E
S-10 *	620/24	501 (600-½)	620/55	501 (600-1)	
CIRCLING **	620-1	501 (600-1)	620-1½ 501 (600-1½)	680-2	561 (600-2)



HIRL Rwy 10-28

NOTE: REPRINTING DOD FLIP

Minimum Vectoring Altitude CHART

