

## AD CHART

**KOCHI AP**

TRUE NORTH

ABN

TOWER

WIND SPEED METER

VOR/DME(KRE)

RUNWAY GUARD LIGHTS

T-1

CEILOMETER

RVR WDI

T-2

TAXIING GUIDANCE SIGNS

ARP

T-3

T-4

CIRCLING GUIDANCE LIGHTS

T-5

WDI

T-6

OVERRUN LIGHTS

WIND SPEED METER

PAPI Angle 3.0° MEHT 25.5m(84ft)

583.5m

404.4m

PAPI Angle 3.0° MEHT 20m(66ft)

REMARKS: RUNWAY GROOVING 2500m x 30m  
WIDTH OF TAXIWAY  
T-2, T-3, T-4 & T-5 34m  
T-1 & T-6 28.5m  
A-1, A-2, A-3, A-4 & A-5 23m

Example for MANDATORY INSTRUCTION MARKING

32-14

Installed on TWY T1 THRU T6.

APPROACH LIGHTING SYSTEM

SEQUENCED FLASHING LIGHT (SFL-V)

420m

420m

420m

362.929m(169.358m)

37ft (11.26m)

32ft (9.63m)

0.55%

0.69%

0.10%

0.60%

0.15%

0.34%

0.20%

0.03%

LONGITUDINAL PROFILE OF RUNWAY

RWY 14

RWY 32

0m 275m 511.5m 1240m 1540m 1940m 2060m 2400m 2500m

STANDARD DEPARTURE CHART - INSTRUMENT

RJOK / KOCHI

SID

SHIMIZU SIX DEPARTURE


RWY 14 : Climb RWY HDG to 500FT, turn right HDG 268°...

RWY 32 : Climb RWY HDG to 800FT, turn right...

...to intercept and proceed via KRE R223/SUC R043 to SUC VORTAC.

Note RWY32 : 6.0% climb gradient required up to 2500FT.

OBST ALT 2165FT located at 6.6NM 358° FM end of RWY32.



## STANDARD DEPARTURE CHART - INSTRUMENT

RJOK / KOCHI

SID

KOCHI REVERSAL FIVE DEPARTURE

RWY 14 : Climb RWY HDG to 500FT, turn right...

RWY 32 : Climb RWY HDG to 800FT, turn right HDG 205°...

...to intercept and proceed via KRE R160 to KRE 10.0DME, then turn left  
proceed to KRE VOR/DME.

Cross KRE VOR/DME at or above 6000FT.

Note RWY32 : 6.0% climb gradient required up to 2500FT.

OBST ALT 2165FT located at 6.6NM 358° FM end of RWY32.

KOCHI REVERSAL FIVE DEPARTURE

STANDARD DEPARTURE CHART - INSTRUMENT

RJOK / KOCHI

SID

URADO REVERSAL THREE DEPARTURE

RWY 14 : Climb RWY HDG to 500FT, turn right HDG 255°...

RWY 32 : Climb RWY HDG to 800FT, turn right...


...to intercept and proceed via KRE R210 to KRE 15.0DME, then turn right  
proceed to KRE VOR/DME.

Cross KRE VOR/DME at or above 6000FT.

Note RWY32 : 6.0% climb gradient required up to 2500FT.

OBST ALT 2165FT located at 6.6NM 358° FM end of RWY32.

URADO REVERSAL THREE DEPARTURE



## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

## KARIN ONE RNAV DEPARTURE

## RNAV 1

Note 1) DME/DME/IRU or GNSS required.

※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll.

2) RADAR service required.

Critical DME

RWY14 : KRE 3.0NM fm DER - 7NM to KARIN  
SUC 3.0NM fm DER - 10NM to KARIN  
RWY32 : KRE 9NM to OK32C - 10NM to KARIN  
SUC 9NM to OK32C - 4NM to OK32C


DME GAP

RWY14 : DER - 3.0NM fm DER  
RWY32 : DER - 9NM fm OK32C

Inappropriate NavAids

See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

VAR 7° W(2009)



DESIGNATION	COORDINATES
OK14A	33 24 50.3N 133 43 34.2E
OK14B	33 24 02.9N 133 50 40.3E
OK32A	33 36 15.7N 133 44 17.5E
OK32C	33 28 04.1N 133 55 42.6E
KARIN	33 40 24.4N 134 11 14.9E

Note RWY32: 6.0% climb gradient required up to 2300FT.

RWY14 : Climb on HDG137° at or above 500FT, turn right direct to OK14A, to OK14B, to KARIN at or above 8000FT.

RWY32 : Climb on HDG317° at or above 600FT, turn right direct to OK32A, to OK32C, to KARIN at or above 8000FT.

Note RWY32: 6.0% climb gradient required up to 2300FT.

OBST ALT 1970FT located at 6.13NM 004° FM end of RWY32.

## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

KARIN ONE RNAV DEPARTURE

## RWY14

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	137° (130.6°)	—	+500	—	—	RNAV1
DF	OK14A	—	—	—	R	—	—	—	RNAV1
TF	OK14B	—	6.0	104° (097.5°)	—	—	—	—	RNAV1
TF	KARIN	—	23.7	053° (046.3°)	—	+8000	—	—	RNAV1

## RWY32

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	317° (310.6°)	—	+600	—	—	RNAV1
DF	OK32A	—	—	—	R	—	—	—	RNAV1
TF	OK32C	—	12.6	138° (130.7°)	—	—	—	—	RNAV1
TF	KARIN	—	17.9	053° (046.3°)	—	+8000	—	—	RNAV1

## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

## KAIFU ONE RNAV DEPARTURE

## RNAV 1

Note 1 ) DME/DME/IRU or GNSS required.

※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll.

2 ) RADAR service required.

Critical DME

RWY14 : KRE 3.0NM fm DER - 23NM to KAIFU  
SUC 3.0NM fm DER - 32NM to KAIFU  
RWY32 : KRE 9NM to OK32C - 28NM to KAIFU  
SUC 9NM to OK32C - 4NM to OK32C


DME GAP

RWY14 : DER - 3.0NM fm DER  
RWY32 : DER - 9NM to OK32C

Inappropriate NavAids

See AD1.1.6.10.3. Inappropriate NAVAIDS for RNAV1

VAR 7° W(2009)



DESIGNATION	COORDINATES
OK14A	33 24 50.3N 133 43 34.2E
OK14B	33 24 02.9N 133 50 40.3E
OK32A	33 36 15.7N 133 44 17.5E
OK32C	33 28 04.1N 133 55 42.6E
KAIFU	33 36 10.0N 134 32 31.2E

Note RWY32: 6.0% climb gradient required up to 2300FT.

RWY14 : Climb on HDG137° at or above 500FT, turn right direct to OK14A, to OK14B, to KAIFU.

RWY32 : Climb on HDG317° at or above 600FT, turn right direct to OK32A, to OK32C, to KAIFU.

Note RWY32: 6.0% climb gradient required up to 2300FT.

OBST ALT 1970FT located at 6.13NM 004° FM end of RWY32.

## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

KAIFU ONE RNAV DEPARTURE

## RWY14

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	137° (130.6°)	—	+500	—	—	RNAV1
DF	OK14A	—	—	—	R	—	—	—	RNAV1
TF	OK14B	—	6.0	104° (097.5°)	—	—	—	—	RNAV1
TF	KAIFU	—	37.0	077° (070.7°)	—	—	—	—	RNAV1

## RWY32

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	317° (310.6°)	—	+600	—	—	RNAV1
DF	OK32A	—	—	—	R	—	—	—	RNAV1
TF	OK32C	—	12.6	138° (130.7°)	—	—	—	—	RNAV1
TF	KAIFU	—	31.8	082° (075.0°)	—	—	—	—	RNAV1




STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID and TRANSITION

MUROT ONE RNAV DEPARTURE		RNAV 1
<div>Note 1 ) DME/DME/IRU or GNSS required. ※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll. 2 ) RADAR service required.</div>	Critical DME	—
	DME GAP	RWY14 : DER - 3.0NM fm DER RWY32 : DER - 18.0NM to OK32D
	Inappropriate Nav aids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1



## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID and TRANSITION

MUROT ONE RNAV DEPARTURE

## RWY14

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	137° (130.6°)	—	+500	—	—	RNAV1
DF	OK14A	—	—	—	R	—	—	—	RNAV1
TF	MUROT	—	30.9	104° (097.6°)	—	—	—	—	RNAV1

## RWY32

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
VA	—	—	—	317° (310.6°)	—	+600	—	—	RNAV1
DF	OK32A	—	—	—	R	—	—	—	RNAV1
TF	OK32D	—	20.9	138° (130.7°)	—	—	—	—	RNAV1
TF	MUROT	—	14.3	105° (097.7°)	—	—	—	—	RNAV1

KUSHIMOTO TRANSITION

Rcmd. Path Terminator	Fix ID (Waypoint Name)	Fly Over	Distance (NM)	MAG Track (TRUE Track)	Turn Direction	Altitude (FT)	Speed Limit (KIAS)	Vertical Angle	Navigation Performance
IF	MUROT	—	—	—	—	—	—	—	RNAV1
TF	MIYAT	—	19.0	100° (093.3°)	—	—	—	—	RNAV1
TF	MERID	—	12.3	089° (082.0°)	—	—	—	—	RNAV1
TF	KUSHIMOTO (KEC)	—	42.3	089° (082.2°)	—	—	—	—	RNAV1

## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

## OMOGO TWO RNAV DEPARTURE

## RNAV 1

Note 1 ) DME/DME/IRU or GNSS required.

※The aircraft equipped with only DME/DME/IRU must be able to update its position without delay at the starting point of take-off roll.

2 ) RADAR service required.

Critical DME

RWY14 : KRE 16NM to YUZNO - 7NM to YUZNO  
SUC 16NM to YUZNO - 7NM to YUZNO  
RWY32 : KRE 4NM to OK32B - 25NM to YUZNO  
SUC 4NM to OK32B - 25NM to YUZNO

DME GAP

RWY14 : DER - 16NM to YUZNO  
RWY32 : DER - 4NM to OK32B  
25NM to YUZNO - 18NM to YUZNO

Inappropriate NavAids

See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1

VAR 7° W(2017)



RWY14 : Climb on HDG138° at or above 500FT, turn right direct to OK14C, to YUZNO, to OMOGO.

RWY32 : Climb on HDG318° at or above 600FT, turn right direct to OK32A, to OK32B, to OK32E,  
to YUZNO, to OMOGO.

Note RWY32: 6.0% climb gradient required up to 2300FT.

OBST ALT 1970FT located at 6.1NM 004° FM end of RWY32.

## STANDARD DEPARTURE CHART -INSTRUMENT

RJOK / KOCHI

RNAV SID

OMOGO TWO RNAV DEPARTURE

## RWY14

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	138 (130.6)	-7.4	—	—	+500	—	—	RNAV1
002	DF	OK14C	—	—	-7.4	—	R	—	—	—	RNAV1
003	TF	YUZNO	—	320 (312.9)	-7.4	18.8	—	—	—	—	RNAV1
004	TF	OMOGO	—	296 (288.5)	-7.4	4.0	—	—	—	—	RNAV1

## RWY32

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	318 (310.6)	-7.4	—	—	+600	—	—	RNAV1
002	DF	OK32A	—	—	-7.4	—	R	—	—	—	RNAV1
003	TF	OK32B	—	138 (130.7)	-7.4	7.0	—	—	—	—	RNAV1
004	TF	OK32E	—	230 (222.8)	-7.4	13.3	—	—	—	—	RNAV1
005	TF	YUZNO	—	320 (312.9)	-7.4	25.9	—	—	—	—	RNAV1
006	TF	OMOGO	—	296 (288.5)	-7.4	4.0	—	—	—	—	RNAV1

STANDARD ARRIVAL CHART -INSTRUMENT

RJOK / KOCHI


RNAV STAR

YOSAKOI NORTH ARRIVAL

RNAV 1

Note 1 ) DME/DME/IRU or GNSS required.  
2 ) RADAR service required.

VAR 7° W(2012)



From POPPY, to JYAMU at or above 8000FT, to BATAK at or above 6000FT, to CHEEZ at or above 4500FT, to ANPAN.

Critical DME	SUC	BATAK - ANPAN
	KRE	BATAK - ANPAN
DME GAP	-	
Inappropriate Navaids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1	

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course [°M(°T)]	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	POPPY	-	-	-6.9	-	-	-	-	-	RNAV1
002	TF	JYAMU	-	171 (164.2)	-6.9	3.9	-	+8000	-	-	RNAV1
003	TF	BATAK	-	171 (164.2)	-6.9	11.7	-	+6000	-	-	RNAV1
004	TF	CHEEZ	-	182 (175.5)	-6.9	8.2	-	+4500	-200	-	RNAV1
005	TF	ANPAN	-	264 (257.6)	-6.9	3.7	-	-	-	-	RNAV1

CHANGE : Critical DME.

## STANDARD ARRIVAL CHART -INSTRUMENT

RJOK / KOCHI

RNAV STAR

## YOSAKOI EAST ARRIVAL

RNAV 1

Note 1 ) DME/DME/IRU or GNSS required.  
2 ) RADAR service required.

VAR 7° W(2012)



From PANCH, to ANPAN.

Critical DME	KRE	PANCH - ANPAN
	SUC	8NM to ANPAN - ANPAN
DME GAP	-	
Inappropriate NavAids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1	

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course [°M(°T)]	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	PANCH	—	—	-6.9	—	—	—	—	—	RNAV1
002	TF	ANPAN	—	326 (318.7)	-6.9	18.3	—	—	—	—	RNAV1

STANDARD ARRIVAL CHART -INSTRUMENT



CHANGE : Critical DME(IWT) deleted. DME GAP.

## STANDARD ARRIVAL CHART -INSTRUMENT

RJOK / KOCHI


RNAV STAR

## YOSAKOI WEST ARRIVAL

RNAV 1

Note 1 ) DME/DME/IRU or GNSS required.  
2 ) RADAR service required.

VAR 7° W(2012)



From KABIL, to DOKIN at or above 5000FT, to BIRKN, to ANPAN.

Critical DME	KRE	1NM to DOKIN - 16NM to BIRKN 7NM to BIRKN - ANPAN
	SUC	1NM to DOKIN - 16NM to BIRKN 7NM to BIRKN - ANPAN
DME GAP	16NM to BIRKN - 7NM to BIRKN	
Inappropriate Nav aids	See AD1.1.6.10.3. Inappropriate NAVAIDs for RNAV1	

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course [°M(°T)]	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	KABIL	—	—	-6.9	—	—	—	—	—	RNAV1
002	TF	DOKIN	—	113 (105.9)	-6.9	5.8	—	+5000	—	—	RNAV1
003	TF	BIRKN	—	113 (105.9)	-6.9	20.3	—	—	-230	—	RNAV1
004	TF	ANPAN	—	047 (040.6)	-6.9	4.5	—	—	—	—	RNAV1



## INSTRUMENT APPROACH CHART

RJOK / KOCHI

ILS Z or LOC Z RWY32



## INSTRUMENT APPROACH CHART

RJOK / KOCHI

ILS Y or LOC Y RWY32



## RJOK / KOCHI

VOR RWY32

VAR 7°W (2009)

EQPT REQUIRED DME

MSA 25NM

MHA 5000  
MAX 230KIAS above 6000FT  
MAX 210KIAS at or below 6000FT

KOCHI CITY

MAPt KRE

YASIE(FAF) D5.0 KRE

SUSAK D15.0 KRE

MHA 3000  
MAX 230KIAS

D21.0 KRE

VOR/DME KOCHI  
113.7 KRE  
CH-84X  
33°32'30"N/133°40'49"E


Max Turning speed 200KIAS

Turn initiation within D11.0 KRE

YASIE(FAF): 332848.86N/1334451.13E

NM to KRE	MAPt	2	3	4	FAF
ALT (3.0° APCH Path)	—	669	987	1305	1624

Climb via KRE R324 to 500FT,  
turn left HDG178° to intercept  
and proceed via KRE R223 to  
SUSAK and hold at 3000FT.  
Contact KANSAS APP.



Missed APCH climb gradient MNM 4.5%

Circling to **EAST** side of RWY only.  
MINIMA with Missed APCH climb gradient of 2.5% are not established.

## INSTRUMENT APPROACH CHART

RJOK / KOCHI

RNP Z RWY14(AR)



CHANGE : PROC renamed. Requirement for RNP.

## INSTRUMENT APPROACH CHART

RJOK / KOCHI

RNP Z RWY14(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	ANPAN	-	-	-6.9	-	-	+4000	-	-	-
002	TF	NOITI	-	343 (335.9)	-6.9	9.7	-	+4000	-	-	1.0
003	TF	IGENO	-	318 (310.7)	-6.9	4.2	-	3500	-	-	1.0
004	TF	OK451	-	318 (310.7)	-6.9	1.8	-	2922	-165	-3.00	0.14 0.30
005	RF Center: OKRF1 r=2.07NM	OK477	-	-	-6.9	6.5	L	856	-	-3.00	0.14 0.30
006	TF	RW14	Y	138 (130.6)	-6.9	2.4	-	92	-	-3.00/50	0.14 0.30
007	TF	ANPAN	-	138 (130.6)	-6.9	12.4	-	4000	-	-	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
ANPAN	332507.54N / 1335048.52E	OKRF1	333620.13N / 1333858.11E
NOITI	333400.03N / 1334602.07E		
IGENO	333643.39N / 1334213.86E		
OK451	333754.48N / 1334034.43E		
OK477	333445.76N / 1333721.85E		
RW14	333312.04N / 1333932.98E		

CHANGE : PROC renamed.

## RJOK / KOCHI

RNP Y RWY14(AR)

KANSAI APP 125.0 - 124.8	RNP AR RF required.	KOCHI TOWER 118.75 - 126.2	RADAR AVBL ATIS 126.45
-----------------------------	------------------------	-------------------------------	---------------------------

Profile view diagram of the approach to Kansai International Airport. The diagram shows a descent path from 4000 feet at 24.6 NM to THR to 856 feet at 0 NM to THR. Key waypoints include ANPAN (IAF) at 24.6 NM, KATUO (IF) at 14.9 NM, TATKY (FAF) at 10.7 NM, OK481 at 8.9 NM, OK477 at 2.4 NM, and RW14 at 0 NM. The path includes a missed approach climb to 4000 feet and a contact with KANSAI APP. The diagram also shows a 318° heading from KATUO to TATKY, a 300° heading from TATKY to OK481, and a 138° heading from OK477 to RW14. The diagram is labeled "MISSED APPROACH" and "RDH 50".

MINIMA		THR elev. 42	AD elev. 29	
CAT	RNP 0.14		RNP 0.30	
	DA(H)	CMV	DA(H)	CMV
A	-	-	-	-
B				
C	342(300)	1400	611(569)	1600
D		1600		1800

## Authorization Required

## INSTRUMENT APPROACH CHART

RJOK / KOCHI

RNP Y RWY14(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	ANPAN	-	-	-6.9	-	-	+4000	-	-	-
002	TF	KATUO	-	292 (285.5)	-6.9	9.7	-	+4000	-	-	1.0
003	TF	TATKY	-	318 (310.6)	-6.9	4.2	-	3500	-	-	1.0
004	TF	OK481	-	318 (310.6)	-6.9	1.8	-	2922	-165	-3.00	0.14 0.30
005	RF Center: OKRF2 r=2.07NM	OK477	-	-	-6.9	6.5	R	856	-	-3.00	0.14 0.30
006	TF	RW14	Y	138 (130.6)	-6.9	2.4	-	92	-	-3.00/50	0.14 0.30
007	TF	ANPAN	-	138 (130.6)	-6.9	12.4	-	4000	-	-	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
ANPAN	332507.54N / 1335048.52E	OKRF2	333311.37N / 1333545.65E
KATUO	332742.79N / 1333937.02E		
TATKY	333025.96N / 1333548.91E		
OK481	333136.96N / 1333409.51E		
OK477	333445.76N / 1333721.85E		
RW14	333312.04N / 1333932.98E		

CHANGE : PROC renamed.



RJOK / KOCHI

Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : Map updated. BRG/DIST from ARP: Call sign(Kochi city → Kochi Station). Remarks(Geisei, Yokonami).

Call sign	BRG / DIST from ARP	Remarks
植野 Ueno	349°T / 5.0NM	ゴルフ場 Golf Course
工科大 Kokadai	029°T / 5.2NM	高知工科大学 Kochi University of Technology
高知駅 Kochi Station	281°T / 6.4NM	JR高知駅 Station
芸西 Geisei	104°T / 6.0NM	ホテル Hotel
桂浜 Katsurahama	242°T / 5.8NM	浦戸大橋 Bridge
安芸 Aki	104°T / 12.5NM	安芸川河口 River mouth
横浪 Yokonami	236°T / 13.0NM	ホテル Hotel





RJOK / KOCHI

Minimum Vectoring Altitude CHART

VAR 7°W (2009)



- ① 2000
- ② 2300
- ③ 2500
- ④ 3000
- ⑤ 3500
- ⑥ 4000
- ⑦ 4500



CENTER : 333245N/1334039E (RADAR SITE)