

## AD 2 AERODROMES

## RJFU AD 2.1 AERODROME LOCATION INDICATOR AND NAME

## RJFU - NAGASAKI

## RJFU AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	325501N/1295449E
2	Direction and distance from (city)	18Km (9.7nm) NNE of Nagasaki railway station, 4km (2.2nm) W of Omura railway station.
3	Elevation/ Reference temperature	8ft / 33°C (2004-2008)
4	Geoid undulation at AD ELEV PSN	105.89ft
5	MAG VAR/ Annual change	7° W (2008) / Annual change 2' W
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	Civil Aviation Bureau, Ministry of Land, Infrastructure, Transport and Tourism Nagasaki Airport, 593-2 Mishima-cho, Omura City, Nagasaki Pref. Tel: 0957(53)6901 Fax: 0957(54)4539 AFS: RJFUZYX
7	Types of traffic permitted (IFR/VFR)	IFR/VFR
8	Remarks	Nil

## RJFU AD 2.3 OPERATIONAL HOURS

1	AD Administration	2200 - 1300
2	Customs and immigration	Customs: 2330-0815 Immigration: INTL SKED FLT hours only
3	Health and sanitation	INTL SKED FLT hours only
4	AIS Briefing Office	2200 - 1300
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	H24 (FUKUOKA)
7	ATS	2200 - 1300 Remarks: 2200-2245 and 1215-1300, AFIS provided by Fukuoka Airport Office.
8	Fuelling	2200 - 1300
9	Handling	DOM/JAL:2240-1240, ANA:2200-1230, ORC:2200-0910 INTL/2330-0800
10	Security	2130 - 1200
11	De-icing	Nil
12	Remarks	Nil

**RJFU AD 2.4 HANDLING SERVICES AND FACILITIES**

1	Cargo-handling facilities	No limitation
2	Fuel/ oil types	Fuel Grades : JET A-1 Oil Grade : W80, W100, AERO80, AERO100
3	Fuelling facilities/ capacity	Fuel Truck Refueling, No limitation
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

**RJFU AD 2.5 PASSENGER FACILITIES**

1	Hotels	Hotels in the city
2	Restaurants	Available, Not Continuous
3	Transportation	Buses, Taxies and Ships
4	Medical facilities	Hospitals in the city
5	Bank and Post Office	Bank in the city. Post office in the city.
6	Tourist Office	Tourist Office in the city
7	Remarks	Nil

**RJFU AD 2.6 RESCUE AND FIRE FIGHTING SERVICES**

1	AD category for fire fighting	CAT 9
2	Rescue equipment	Chemical fire fighting truck x 3, Water supply truck x 1, Lighting power supply truck x 1, Emergency medical equipments conveyance truck x 1
3	Capability for removal of disabled aircraft	B744
4	Remarks	Nil

**RJFU AD 2.7 SEASONAL AVAILABILITY-CLEARING**

1	Types of clearing equipment	
2	Clearance priorities	1.RWY 2.TWY 3.APRON
3	Remarks	Seasonal availability:ALL seasons

## RJFU AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Apron surface and strength	Surface : Surface Concrete, Asphalt Concrete in part. Strength : PCN 56/R/A/X/T spot NR 2 PCN 52/R/B/X/T spot NR 3 PCN 70/R/B/X/T spot NR 5 PCN 70/R/A/X/T spot NR 6 PCN 62/R/B/X/T spot NR 7, 8, 9, 10 PCN 74/R/B/X/T spot NR 11, 12, 14
2	Taxiway width, surface and strength	Width : B2.....9m P1 - P5.....23m T1, T6.....28.5m T2, T3, T4, T5....34m Surface : Asphalt Concrete Strength : B2.....PCN 5/F/C/X/T P1, P3, P4, T1...PCN 65/F/A/X/T P5, T6.....PCN 97/F/C/X/T T2, T3, T4, T5....PCN 54/F/A/X/T P2.....PCN 62/R/B/X/T
3	ACL and elevation	Not available
4	VOR checkpoints	Not available
5	INS checkpoints	Spot NR 5 : 325447.08N/1295522.18E* 6 : 325448.42N/1295520.75E 7 : 325449.91N/1295519.11E 8 : 325451.60N/1295517.31E 9 : 325453.29N/1295515.51E 10 : 325454.98N/1295513.71E 11 : 325456.73N/1295511.84E 12 : 325458.53N/1295509.91E
6	Remarks	Nil

**RJFU AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS**

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	ACFT stand ID signs: SPOT 2, 5-9
2	RWY and TWY markings and LGT	<p>RWY14/32: (Marking) RWY designation, RWY CL, RWY THR, Aiming point, TDZ, RWY side stripe (LGT) RCLL, REDL, RTHL, RENL, RTZL(RWY32), WBAR(RWY32), RWY DIST marker LGT</p> <p>TWY: T1 - T6 (Marking) TWY CL, RWY HLDG PSN, Mandatory Instructions, TWY side stripe (LGT) TWY edge LGT, TWY CL LGT, RWY guard LGT, Taxiing guidance sign</p> <p>TWY: P1, P3, P4, P5 (Marking) TWY CL, TWY side stripe (LGT) TWY edge LGT, TWY CL LGT</p> <p>TWY: P2 (Marking) TWY CL, TWY side stripe (LGT) TWY edge LGT, TWY CL LGT, Taxiing guidance sign</p> <p>TWY: B2 (Marking) TWY CL, TWY side stripe (LGT) TWY edge LGT, Taxiing guidance sign</p>
3	Stop bars	Nil
4	Remarks	<p>(Marking) Overrun area (LGT) Apron flood LGT</p>

**RJFU AD 2.10 AERODROME OBSTACLES**

■ In Area2 See Obstacle data

■ In Area3 To be developed

## RJFU AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	FUKUOKA
2	Hours of service MET Office outside hours	H24 (FUKUOKA)
3	Office responsible for TAF preparation Periods of validity	FUKUOKA 30 Hours
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Briefing is available upon inquiry at FUKUOKA
6	Flight documentation Language(s) used	C En
7	Charts and other information available for briefing or consultation	S <sub>6</sub> , U <sub>85</sub> , U <sub>7</sub> , U <sub>5</sub> , U <sub>3</sub> , U <sub>25</sub> , P <sub>s</sub> , P <sub>5</sub> , P <sub>3</sub> , P <sub>25</sub> , P <sub>SWE</sub> , P <sub>SWF</sub> , P <sub>SWG</sub> , P <sub>SWI</sub> , P <sub>SWM</sub> , P <sub>SW</sub> (domestic), U <sub>2</sub> /Tr, E, C, W <sub>E</sub> , W <sub>F</sub> , W <sub>G</sub> , W <sub>I</sub> , W, N
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	TWR, APP, ATIS, RADIO
10	Additional information(limitation of service, etc.)	Nil

## RJFU AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN) and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
14	138.00°	3000x60	PCN 65/F/A/X/T Asphalt Concrete	325537.28N 1295409.77E 105.8ft	THR ELEV: 14ft
32	318.00°	3000x60	PCN 65/F/A/X/T Asphalt Concrete	325424.91N 1295527.04E 106.0ft	THR ELEV: 15ft
Slope of RWY		Strip Dimen- sions(M)	RESA (Overrun) Dimensions (M)		Remarks
7		10	11		14
See below chart		3120x300	40x300		RWY 14 grooving: 3000 x 40m
See below chart		3120x300	190x(MNM:120 MAX:300)* *For detail, ask airport administrator		RWY 32 grooving: 3000 x 40m

**RWY 14**      **RWY 32**

14ft      11ft      8ft      8ft      9ft      8ft      15ft

0.22%      0.12%      0.01%      0.01%      0.03%      0.33%

0m      451.5m      1120m      1500m      2060m      2360m      3000m

## RJFU AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
14	3000	3000	3000	3000	Nil
32	3000	3000	3000	3000	Nil

## RJFU AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
14	SALS (*1) 420m LIH	Green -	PAPI 3.0°/LEFT 471m 74ft	-	3000m 30m Coded color (White/Red) LIH	3000m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)
32	PALS (CAT I) 900m LIH	Green Green	PAPI 3.0°/LEFT 444m 65ft	900m	3000m 30m Coded color (White/Red) LIH	3000m 60m Coded color (White/Yellow) LIH	Red	Nil (*2)
Remarks								
10								
SALS with APCH LGT beacon(600m and 900m FM RWY THR)(*1) Overrun area edge LGT(LEN:60m Color:Red)(*2)								

## RJFU AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	ABN:325428N/1295457E, White/Green EV4.3sec, HO
2	LDI location and LGT Anemometer location and LGT	LDI : Nil Anemometer : RWY 32 : 438m from RWY 32 THR, LGTD RWY 14 : 430m from RWY 14 THR, LGTD
3	TWY edge and centerline lighting	TWY edge and center line lights installed, see AD2.9
4	Secondary power supply/ switch-over time	Within 1 sec : REDL, RENL, RTHL, WBAR, RCLL, Overrun area edge LGT Within 15 sec : Other LGT
5	Remarks	WDI LGT

## RJFU AD 2.16 HELICOPTER LANDING AREA

Nil
-----

## RJFU AD 2.17 ATS AIRSPACE

Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
NAGASAKI CTR	Area within a radius of 5 nm of NAGASAKI ARP (325501N1295449E)	3,000 or below	D	NAGASAKI TWR NAGASAKI RADIO (1) En	(1)2200-2245 1215-1300
NAGASAKI ACA	See attached chart		E	NAGASAKI APP NAGASAKI RADAR NAGASAKI DEP En	
NAGASAKI TCA	See attached chart		E	NAGASAKI TCA En	


長崎進入管制区  
Nagasaki Approach Control Area

## Point list

(1) 332519N1300516E	(11) 323917N1292246E	(21) 324950N1302218E
(2) 332227N1293413E	(12) 322522N1293021E	(22) 330132N1302113E
(3) 332219N1293406E	(13) 322522N1295325E	(23) 330147N1301316E
(4) 330615N1293818E	(14) 325752N1291235E	(24) 330951N1300318E
(5) 330921N1295252E	(15) 322522N1295913E	(25) 331929N1301048E
(6) 332024N1300955E	(16) 323353N1300008E	(26) 330915N1302028E
(7) 334508N1294656E	(17) 323544N1295905E	(27) 322522N1302306E
(8) 324312N1295325E	(18) 323828N1300526E	(28) 322734N1302215E
(9) 324312N1293323E	(19) 324018N1301840E	
(10) 324053N1293041E	(20) 324407N1301735E	



長崎ターミナルコントロールエリア  
Nagasaki Terminal Control Area



## RJFU AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
APP	Nagasaki Approach	119.175MHz(1) 261.2MHz  121.5MHz(E) 243.0MHz(E)	2200 - 1300	(1)Primary
ASR	Nagasaki Radar	119.175MHz 121.025MHz 261.2MHz  121.5MHz(E) 243.0MHz(E)	2200 - 1300	
DEP	Nagasaki Departure	121.0MHz 261.2MHz  121.5MHz(E) 243.0MHz(E)	2200 - 1300	
TCA	Nagasaki TCA	121.175MHz 245.3MHz	2300 - 1030	
TWR	Nagasaki Tower	118.5MHz 126.2MHz 122.7MHz 236.8MHz 121.5MHz(E) 243.0MHz(E)	2245 - 1215(*)	
GND	Nagasaki Ground	121.6MHz	2245 - 1215(*)	
ATIS	NAGASAKI Airport	126.85MHz	2200 - 1300	
AFIS	Nagasaki Radio	118.5MHz	2200-2245 1215-1300(*)	Operated by Fukuoka Airport Office
*Depending on air traffic situation, ATC service will be provided from 2230 to 2245 and from 1215 to 1230.				

## RJFU AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid (VOR declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
VOR (7°W/2020)	OLE	116.6MHz	H24	325418.89N/ 1295504.73E		VOR unusable : 040°-070° beyond 25nm BLW 6000ft 070°-090° beyond 20nm BLW 6000ft
DME	OLE	1200 MHz (CH-113X)	H24	325418.89N/ 1295504.73E	154ft	DME unusable : 030°-070° beyond 20nm BLW 6000ft 070°-090° beyond 15nm BLW 6000ft 160°-170° beyond 30nm BLW 5000ft 170°-200° beyond 20nm BLW 4000ft 200°-210° beyond 10nm BLW 4000ft 210°-240° beyond 20nm BLW 4000ft 260°-300° beyond 20nm BLW 4000ft
ILS-LOC 32	IOL	110.9MHz	2200 - 1300	325542.95N/ 1295403.71E		LOC : 235m(771ft) away FM RWY 14THR, BRG(MAG)325°.
ILS-GP 32	-	330.8MHz	2200 - 1300	325430.22N/ 1295515.11E		GP : 330m(1084ft) inside FM RWY 32 THR. 120m SW of RCL. HGT of ILS Ref datum 16.2m(53ft). GP Angle 3.0°.
ILS-DME 32	IOL	1007MHz (CH-46X)	2200 - 1300	325429.87N/ 1295514.76E	25ft	DME : 330m(1084ft) inside FM RWY 32 THR, 134m(439ft) SW of RCL.
MSAS		1575.42M Hz	H24			Transmitting antennas are satellite based.

**ILS**

REMARKS : 1. LOC beam BRG(MAG) 325°  
 2. HGT of ILS REF datum 16.2m (53ft)  
 3. GP Angle 3.0°  
 4. ELEV of ILS-DME 7.6m (25ft)

## RJFU AD 2.20 LOCAL TRAFFIC REGULATIONS

## 1. Airport regulations

- 1.1 Without prior permission of the airport administrator, the transient aircraft shall not use on this airport.
- 1.2 Prior notification should be required with AD Administration for the purpose of getting the permission when crossing Nagasaki CTR from 2200UTC to 2245UTC or from 1215UTC to 1300UTC.  
For further information (0000UTC-0800UTC MON-FRI EXC HOL)  
Air Traffic Controller Office, Nagasaki Airport Office  
TEL: 0957-53-6870  
7時00分から7時45分または21時15分から22時00分までの間、長崎管制圏を通過する場合は、当該通過の許可を得るためにあらかじめ長崎空港事務所へ調整すること。  
問い合わせ先  
長崎空港事務所管制官事務室  
(月曜日から金曜日までのうち、9時00分から17時00分までの間。ただし休日を除く。)  
TEL: 0957-53-6870

## 2. Taxiing to and from stands

Nil

## 3. Parking area for small aircraft(General aviation)

Unable to stay at spot NR 2B, C, D from sunset to sunrise. Ask AD administration for detail.

## 4. Parking area for helicopters

Nil

## 5. Apron - taxiing during winter conditions

Nil

## 6. Taxiing - limitations

Wing tip clearance at the TWY intersection (REF AD1.1.6.8)

Wing tip clearance at the TWY intersection between the aircraft holding at the stop marking on the TWY and the other aircraft taxiing behind it are as follows.

When B74D holding at the stop marking on TWY T2 or T5

Wing span (WS) of aircraft taxiing on TWY P1-P2 or P4-P5	WS ≤19.4m	19.4m < WS ≤ 36.4m	WS >36.4m
wing tip clearance	*A	*B	*C

Legend

\*A : wing tip clearance ≥ 15m

\*B : 6.5m ≤ wing tip clearance &lt; 15m

\*C : wing tip clearance &lt; 6.5m

## 7. School and training flights - technical test flights - use of runways

On use of this airport by training operation, the operator is required to arrange and obtain the prior permission of the airport administrator.

## 8. Helicopter traffic - limitation

Nil

## 9. Removal of disabled aircraft from runways

Nil

## RJFU AD 2.21 NOISE ABATEMENT PROCEDURES

Nil

## RJFU AD 2.22 FLIGHT PROCEDURES

## 1. TAKE OFF MINIMA

	RWY	ACFT CAT	REDL & RCLL		REDL or RCLL or RCL Marking		NIL (DAYTIME ONLY)	
			RVR	VIS	RVR	VIS	RVR	VIS
Multi-Engine ACFT with TKOF ALTN AP FILED	14	A,B,C,D	-	400m	-	400m	-	500m
	32		400m	400m	400m	400m	-	500m
OTHER	14	A,B,C,D	AVBL LDG MINIMA					
	32							

## 2. Lost communication procedures for Arrival Aircraft under radar navigational guidance.

If radio communications with NAGASAKI Approach/Radar are lost for 30 seconds, squawk Mode A/3 Code 7600 and :

- (I)
1. Contact NAGASAKI Tower / NAGASAKI Radio.
  2. If unable, proceed in accordance with Visual Flight Rules.
  3. If unable, proceed to NAGASAKI VOR/DME at last assigned altitude or 4,000 feet whichever is higher, and execute instrument approach.
- (II) Procedures other than above will be issued when situation required.

## 3. Trajectorized Airport Traffic Data Processing System (TAPS)

Aircraft flying under control of Nagasaki approach control in the approach control area will be instructed to reply with discrete code on Mode A/3 and Mode C.

If an aircraft with non-discrete capability be instructed to reply with the discrete code, it shall report a controller accordingly.

長崎アプローチの指示のもとに、当該進入管制区を飛行する航空機は、モード A/3 の二次レーダー個別コード及びモード C による応答を指示される。

二次レーダー個別コードを搭載していない航空機が当該コードによる応答を指示された場合は、管制官に対しその旨通報すること。

---

**RJFU AD 2.23 ADDITIONAL INFORMATION**


Nil
-----

**RJFU AD 2.24 CHARTS RELATED TO AN AERODROME**

<p>Aerodrome/Heliport Chart Aerodrome Obstacle Chart -ICAO type A (RWY 14/32) Aerodrome Obstacle Chart -ICAO type B Standard Departure Chart - Instrument (NORTH) Standard Departure Chart - Instrument (WEST) Standard Departure Chart - Instrument (NAGASAKI REVERSAL) Standard Departure Chart - Instrument (CHIKUGO-RNAV) Standard Departure Chart - Instrument (KAZSA-RNAV) Standard Departure Chart - Instrument (AKNAG-RNAV) Standard Departure Chart - Instrument (CARCO-RNAV) Standard Arrival Chart - Instrument (RNAV) Instrument Approach Chart (ILS Z or LOC Z RWY 32) Instrument Approach Chart (ILS Y or LOC Y RWY 32) Instrument Approach Chart (RNP RWY 32) Instrument Approach Chart (RNP RWY 14) Instrument Approach Chart (VOR RWY 32) Instrument Approach Chart (VOR RWY 14) Other Chart (Visual REP) Other Chart (LDG CHART) Other Chart (HOLDING PATTERN) Other Chart (MVA CHART)</p>
--

## AD CHART

**NAGASAKI AIRPORT**  
ELEV 8ft





**INTENTIONALLY LEFT BLANK**




# AERODROME OBSTACLE CHART-ICAO TYPE A (OPERATING LIMITATIONS)

NAGASAKI AIRPORT  
RWY : 14/32

DECLARED DISTANCES	
<b>RWY 14</b>	<b>RWY 32</b>
3000m TAKE OFF RUN AVAILABLE	3000m
3000m TAKE OFF DISTANCE AVAILABLE	3000m
3000m ACCELERATE STOP DISTANCE AVAILABLE	3000m
3000m LANDING DISTANCE AVAILABLE	3000m



LEGEND		AMENDMENT RECORD	
		N <sup>O</sup> .	DATE
		ENTERED BY	
	IDENTIFICATION NUMBER		
	POLE, TOWER, SPIRE, ANTENNA, ETC		
	AERONAUTICAL GROUND LIGHT		
	OBSTRUCTION LIGHT		
	BUILDING OR LARGE STRUCTURE		
	RAILROAD       TRIANGULATION POINT		
	TRANSMISSION LINE OR OVERHEAD CABLE		
	LEEVE       RIVER		
	TREE		
	LAKE       CONTOURS(S)		





DIMENSIONS AND ELEVATIONS IN FEET BEARINGS ARE MAGNETIC





STANDARD DEPARTURE CHART -INSTRUMENT

RJFU / NAGASAKI

SID

NORTH ONE DEPARTURE

RWY 14: Climb RWY HDG to 500FT, via OLE R144 to 6.0 DME,  
turn right HDG324° until crossing OLE R258, turn right HDG016°  
to intercept and proceed via OLE R331 to PEARL....

RWY 32: Climb via OLE R331 to PEARL....


... Cross PEARL at or above 6000FT(\*).

\* For FUKUOKA TRANSITION : Cross PEARL at or above 8000FT.

Note RWY 14: 5.0% climb gradient required up to 1200FT.

OBST ALT 1411FT located at 6.9NM 158° FM end of RWY14.

OBST ALT 1575FT located at 7.7NM 165° FM end of RWY14.



CHANGE : Description of PROC name.

## STANDARD DEPARTURE CHART -INSTRUMENT

RJFU / NAGASAKI

TRANSITION


FUKUOKA TRANSITION

From over PEARL, via DGC R244 to DGC VORTAC.

Note : Not applicable for aircraft equipped with TACAN only.

IKI TRANSITION

From over PEARL, via IKE R202 to IKE VOR/DME.



STANDARD DEPARTURE CHART -INSTRUMENT

RJFU / NAGASAKI

SID

WEST SEVEN DEPARTURE

RWY 14: Climb RWY HDG to 500FT, climb via OLE R144 to 1800FT,  
turn right HDG292° to intercept and proceed via OLE R247...

RWY 32: Climb RWY HDG 1500FT, turn left HDG202° to intercept  
and proceed via OLE R247...

... to SUMOU.


Cross SUMOU at or above 4000FT.

Note RWY 14: 5.0% climb gradient required up to 1800FT.

OBST ALT 854FT located at 3.4NM 170° FM end of RWY14.

RWY 32: 5.0% climb gradient required up to 1500FT.

OBST ALT 1969FT located at 8.0NM 272° FM end of RWY32.



CHANGE : Description of PROC name.

## STANDARD DEPARTURE CHART -INSTRUMENT

RJFU / NAGASAKI


TRANSITION

OMURA TRANSITION

From over SUMOU, turn right to intercept and proceed via OLE R279 to OLE VOR/DME.


Maintain 12000FT or below until intercepting OLE R279.

Cross OLE R279/13.0DME at or above 9000FT.

CARCO TRANSITION

From over SUMOU, turn right HDG308° to intercept and proceed via OLE R263 /FUE R082 to CARCO.

Maintain 12000FT or below until intercepting OLE R263.



CHANGE : PROC course(OMURA TRANSITION, CARCO TRANSITION). Radial/DIST FM OLE added(SUMOU).  
DIST FM OLE, FUE added(CARCO).

STANDARD DEPARTURE CHART -INSTRUMENT

RJFU / NAGASAKI


SID

NAGASAKI REVERSAL FIVE DEPARTURE

RWY 14: Climb RWY HDG to 500FT, climb via OLE R144 to 6.0DME, turn right, direct to OLE VOR/DME.  
Cross OLE VOR/DME at or above 5000FT.


RWY 32: Climb via OLE R331 to 6.3DME, turn left, direct to OLE VOR/DME.  
Cross OLE VOR/DME at or above 5000FT.

Note RWY 14: 5.0% climb gradient required up to 1800FT.  
OBST ALT 1575FT located at 7.7NM 165° FM end of RWY14.  
RWY 32: 5.0% climb gradient required up to 1600FT.  
OBST ALT 1969FT located at 8.0NM 272° FM end of RWY32.



CHANGE : Description of PROC name.

STANDARD DEPARTURE CHART -INSTRUMENT



CHANGE : Description of PROC name.



## STANDARD DEPARTURE CHART -INSTRUMENT

RJFU / NAGASAKI

RNAV SID

CHIKUGO FIVE DEPARTURE

## RWY14

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	146 (138.1)	-7.6	—	—	+500	—	—	Basic RNP1
002	DF	FU401	—	—	-7.6	—	—	—	—	—	Basic RNP1
003	TF	UNZEN	—	029 (021.5)	-7.6	7.7	—	—	—	—	Basic RNP1
004	TF	WARAS	—	019 (011.9)	-7.6	4.3	—	-FL170	—	—	Basic RNP1
005	TF	GOROH	—	019 (011.9)	-7.6	8.2	—	+FL170	—	—	Basic RNP1

## RWY32

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	326 (318.1)	-7.6	—	—	+500	—	—	Basic RNP1
002	DF	FU200	—	—	-7.6	—	—	—	—	—	Basic RNP1
003	TF	TOHKI	—	055 (047.8)	-7.6	12.0	—	—	—	—	Basic RNP1
004	TF	HIZEN	—	131 (123.8)	-7.6	6.7	—	+13000	—	—	Basic RNP1
005	TF	MUTUU	—	131 (123.9)	-7.6	7.9	—	-FL170	—	—	Basic RNP1
006	TF	GOROH	—	132 (124.0)	-7.6	5.1	—	+FL170	—	—	Basic RNP1

CHANGE : VAR. PROC renamed. Course FM MUTUU to GOROH.

## STANDARD DEPARTURE CHART -INSTRUMENT

RJFU / NAGASAKI


RNAV TRANSITION

SALTY TRANSITION / OOITA TRANSITION

Basic RNP1

Note GNSS required.

VAR 8° W(2021)

SALTY TRANSITION

From GOROH at or above FL170, to KROKI at or above FL190, to OOITA, to SALTY.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GOROH	—	—	-7.6	—	—	+FL170	—	—	Basic RNP1
002	TF	KROKI	—	086 (077.9)	-7.6	17.8	—	+FL190	—	—	Basic RNP1
003	TF	OOITA	—	086 (078.1)	-7.6	54.3	—	—	—	—	Basic RNP1
004	TF	SALTY	—	065 (057.8)	-7.6	72.0	—	—	—	—	Basic RNP1


OOITA TRANSITION

From GOROH at or above FL170, to KROKI at or above FL190, to OOITA.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	GOROH	—	—	-7.6	—	—	+FL170	—	—	Basic RNP1
002	TF	KROKI	—	086 (077.9)	-7.6	17.8	—	+FL190	—	—	Basic RNP1
003	TF	OOITA	—	086 (078.1)	-7.6	54.3	—	—	—	—	Basic RNP1

CHANGE : VAR. Navigation specification. Course FM GOROH to KROKI.

STANDARD DEPARTURE CHART -INSTRUMENT



## STANDARD DEPARTURE CHART -INSTRUMENT

RJFU / NAGASAKI

RNAV SID

KAZSA ONE DEPARTURE

## RWY14

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	146 (138.1)	-7.6	—	—	+1200	—	—	Basic RNP1
002	DF	KAZSA	—	—	-7.6	—	—	—	—	—	Basic RNP1

## RWY32

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	326 (318.1)	-7.6	—	—	+500	—	—	Basic RNP1
002	DF	FU201	Y	—	-7.6	—	—	—	—	—	Basic RNP1
003	DF	FU202	—	—	-7.6	—	L	—	—	—	Basic RNP1
004	TF	KAZSA	—	137 (129.3)	-7.6	25.5	—	—	—	—	Basic RNP1

CHANGE : New PROC.

## STANDARD DEPARTURE CHART -INSTRUMENT


RJFU / NAGASAKI

RNAV SID

## AKNAG ONE DEPARTURE

Basic RNP1

Note GNSS required.



RWY14 : Climb on HDG146° at or above 500FT, direct to FU400, turn right direct to MIGAP, to AKNAG at or above 7000FT.

RWY32 : Climb on HDG326° at or above 500FT, turn right direct to AKNAG at or above 7000FT.

Note RWY14 : 5.0% climb gradient required up to 1800FT.

OBST ALT 1247FT located at 4.2NM 177° FM end of RWY14.

OBST ALT 1634FT located at 3.6NM 211° FM end of RWY14.

RWY32 : 5.0% climb gradient required up to 1200FT.

OBST ALT 1739FT located at 8.7NM 010° FM end of RWY32.

## RWY14

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	146 (138.1)	-7.7	-	-	+500	-	-	Basic RNP1
002	DF	FU400	Y	-	-7.7	-	-	-	-	-	Basic RNP1
003	DF	MIGAP	-	-	-7.7	-	R	-	-	-	Basic RNP1
004	TF	AKNAG	-	008 (000.3)	-7.7	26.4	-	+7000	-	-	Basic RNP1

## RWY32

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	326 (318.1)	-7.7	-	-	+500	-	-	Basic RNP1
002	DF	AKNAG	-	-	-7.7	-	R	+7000	-	-	Basic RNP1

CHANGE : New PROC.

## STANDARD DEPARTURE CHART -INSTRUMENT

RJFU / NAGASAKI


RNAV SID

## CARCO ONE DEPARTURE

Basic RNP1

Note GNSS required.

VAR 8°W (2022)



RWY14 : Climb on HDG146° at or above 500FT, direct to FU400, turn right direct to AKMEP, to CARCO.

RWY32 : Climb on HDG326° at or above 1500FT, turn left direct to AKMEP, to CARCO.

Note RWY14 : 5.0% climb gradient required up to 1800FT.

OBST ALT 1247FT located at 4.2NM 177° FM end of RWY14.

OBST ALT 1634FT located at 3.6NM 211° FM end of RWY14.

RWY32 : 5.0% climb gradient required up to 1500FT.

OBST ALT 1969FT located at 8.0NM 272° FM end of RWY32.

## RWY14


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	146 (138.1)	-7.7	-	-	+500	-	-	Basic RNP1
002	DF	FU400	Y	-	-7.7	-	-	-	-	-	Basic RNP1
003	DF	AKMEP	-	-	-7.7	-	R	-	-	-	Basic RNP1
004	TF	CARCO	-	263 (255.7)	-7.7	34.2	-	-	-	-	Basic RNP1

## RWY32

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	326 (318.1)	-7.7	-	-	+1500	-	-	Basic RNP1
002	DF	AKMEP	-	-	-7.7	-	L	-	-	-	Basic RNP1
003	TF	CARCO	-	263 (255.7)	-7.7	34.2	-	-	-	-	Basic RNP1

CHANGE : New PROC.

STANDARD ARRIVAL CHART-INSTRUMENT



## STANDARD ARRIVAL CHART-INSTRUMENT

RJFU / NAGASAKI

RNAV STAR

SARUKU ARRIVAL

From OHGIE at or above 11000FT, to GLOVR at or above 7000FT, to OTAXA at or above 4000FT, to SARUK at or above 3700FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	OHGIE	—	—	-7.6	—	—	+11000	—	—	Basic RNP1
002	TF	GLOVR	—	237 (229.3)	-7.6	9.2	—	+7000	—	—	Basic RNP1
003	TF	OTAXA	—	237 (229.2)	-7.6	6.1	—	+4000	—	—	Basic RNP1
004	TF	SARUK	—	237 (229.2)	-7.6	6.2	—	+3700	—	—	Basic RNP1

FUBUKI ARRIVAL

From OHGIE at or above 11000FT, to PADDY, to TARAH at or above 7000FT, to TAKAK at or above 5000FT, to OBAMA, to AINOH, to FUBKI at or above 2600FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	OHGIE	—	—	-7.6	—	—	+11000	—	—	Basic RNP1
002	TF	PADDY	—	191 (183.1)	-7.6	6.8	—	—	—	—	Basic RNP1
003	TF	TARAH	—	191 (183.1)	-7.6	10.9	—	+7000	—	—	Basic RNP1
004	TF	TAKAK	—	191 (183.0)	-7.6	8.0	—	+5000	—	—	Basic RNP1
005	TF	OBAMA	—	191 (183.0)	-7.6	6.1	—	—	-230	—	Basic RNP1
006	TF	AINOH	—	236 (228.0)	-7.6	2.7	—	—	-210	—	Basic RNP1
007	TF	FUBKI	—	296 (288.2)	-7.6	2.7	—	+2600	—	—	Basic RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	TAKAK	191 (183.0)	-7.6	1.0(-14000) 1.5(+14001)	R	5000	—	-210(-14000) -240(+14001)	Basic RNP1


CHANGE : VAR. Navigation specification: PROC course(FUBUKI ARRIVAL). HLDG course.



INSTRUMENT APPROACH CHART

RJFU / NAGASAKI

ILS Z or LOC Z RWY32




CHANGE : AFIS unit added.

## INSTRUMENT APPROACH CHART

RJFU / NAGASAKI

ILS Y or LOC Y RWY32




CHANGE : AFIS unit added.

## INSTRUMENT APPROACH CHART

RJFU / NAGASAKI

RNP RWY32



## INSTRUMENT APPROACH CHART

RJFU / NAGASAKI

RNP RWY32

**FAS DATA BLOCK**

Operation type	0	LTP/FTP ellipsoidal height	+00370
SBAS service provider identifier	2	FPAP latitude	325537.2480N
Airport identifier	RJFU	FPAP longitude	1295409.7775E
Runway	32	Threshold crossing height	00016.2
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M32A	∠ length offset	0000
LTP/FTP latitude	325424.8850N	HAL	40.0
LTP/FTP longitude	1295527.0410E	VAL	50.0
CRC remainder	10898D02		

**Required additional data**

LTP/FTP orthometric height	4.8
----------------------------	-----

CHANGE : Description of FAS DATA BLOCK ITEM(CRC remainder).

## RJFU / NAGASAKI

CHANGE : MSAS CH added, NODEP, FU450, FU451 established, OMRAN, ETARI, RW14 abolished, RNAV HLDG established (SARUK, IORIE, KOHNO), Course FM SARUK to TENBO, HLDG for NAVAIDS abolished (SARUK, IORIE, KOHNO), ALT(3.0°APCH Path): MINIMA for LPV established.

1/12/22

## INSTRUMENT APPROACH CHART

RJFU / NAGASAKI

RNP RWY14

**FAS DATA BLOCK**

Operation type	0	LTP/FTP ellipsoidal height	+00367
SBAS service provider identifier	2	FPAP latitude	325424.8850N
Airport identifier	RJFU	FPAP longitude	1295527.0410E
Runway	14	Threshold crossing height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M14A	∠ length offset	0000
LTP/FTP latitude	325537.2480N	HAL	40.0
LTP/FTP longitude	1295409.7775E	VAL	50.0
CRC remainder	B756639A		

**Required additional data**

LTP/FTP orthometric height	4.5
----------------------------	-----

CHANGE : Description of FAS DATA BLOCK ITEM(CRC remainder).

## RJFU / NAGASAKI


VOR RWY32

Civil Aviation Bureau, Japan (EFF:29 DEC 2022) 1/12/22

## INSTRUMENT APPROACH CHART

RJFU / NAGASAKI


VOR RWY14





## RJFU / NAGASAKI


## Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

Call sign	BRG / DIST from ARP	Remarks
川棚 Kawatana	345°T / 9.4NM	JR駅 JR Station
彼杵 Sonogi	360°T / 7.4NM	JR駅 JR Station
鈴田 Suzuta	113°T / 4.3NM	長崎自動車道と国道34号線の交点 Intersection
長田 Nagata	112°T / 9.4NM	不知火橋 Bridge
西彼 Seihi	301°T / 9.2NM	オランダ村 Windmill
二島 Futashima	244°T / 3.1NM	二島 Island
堂崎 Dozaki	217°T / 2.7NM	堂崎鼻 A point of land
鷹島 Takashima	237°T / 5.4NM	鷹島 Island
時津 Tokitsu	213°T / 6.0NM	時津港 Harbor
三重 Mie	233°T / 11.1NM	三重崎 A point of land


CHANGE : Map updated. BRG/DIST from ARP.



RJFU / NAGASAKI

HOLDING PATTERN


CHANGE : HLDG course.



RJFU / NAGASAKI

Minimum Vectoring Altitude CHART

VAR 7°W (2011)



① 2300

CENTER : 325458N/1295428E (RADAR SITE)

\* : 324540N/1301756E RADIUS : 3NM