

## AD CHART

LONGITUDINAL PROFILE OF RWY

Distance (m)	Distance (ft)	Elevation (m)	Elevation (ft)	Slope (%)
0	223ft	68.1	223ft	-
240	230ft	70.0	230ft	0.8%
340	232ft	70.6	232ft	0.68%
560	237ft	72.4	237ft	0.8%
660	240ft	73.3	240ft	0.91%
760	243ft	74.2	243ft	0.85%
1280	260ft	79.4	260ft	1.0%
1590	268ft	81.7	268ft	0.56%
1700	270ft	82.3	270ft	-
2000	273ft	83.2	273ft	-

**INTENTIONALLY LEFT BLANK**

STANDARD DEPARTURE CHART - INSTRUMENT

RJFE / FUKUE

SID

NAGASAKI FIVE DEPARTURE

RWY 03 : Climb RWY HDG to 1300FT, turn right HDG128°...  
RWY 21 : Climb RWY HDG to 1300FT, turn left HDG038°...  
...to intercept and proceed via FUE R083/OLE R263 to OLE VOR/DME.


IKI SIX DEPARTURE

RWY 03 : Climb RWY HDG to 900FT, turn right...  
RWY 21 : Climb RWY HDG to 1300FT, turn left HDG359°...  
...to intercept and proceed via FUE R044/IKE R224 to IKE VOR/DME

FUKUE REVERSAL THREE DEPARTURE

RWY 03 : Climb RWY HDG to 2000FT, turn right...  
RWY 21 : Climb RWY HDG to 2000FT, turn left...  
...direct to FUE VOR/DME.


CHANGE : PROC renamed(NAGASAKI FIVE DEPARTURE, IKI SIX DEPARTURE). PROC course.



STANDARD DEPARTURE CHART - INSTRUMENT

RJFE / FUKUE

RNAV SID



RWY03 : Climb on HDG033° at or above 700FT, direct to FE300, to AGRIT.  
RWY21 : Climb on HDG213° at or above 700FT, direct to FE100, to FE101, to AGRIT.

RWY03


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	033 (025.6)	-7.5	-	-	+700	-	-	RNP1
002	DF	FE300	-	-	-7.5	-	-	-	-	-	RNP1
003	TF	AGRIT	-	092 (084.9)	-7.5	22.1	-	-	-	-	RNP1

RWY21

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	213 (205.7)	-7.5	-	-	+700	-	-	RNP1
002	DF	FE100	-	-	-7.5	-	-	-	-	-	RNP1
003	TF	FE101	-	123 (115.8)	-7.5	4.8	-	-	-	-	RNP1
004	TF	AGRIT	-	065 (057.4)	-7.5	27.0	-	-	-	-	RNP1

CHANGE : Navigation Specification(Basic RNP1→RNP1).

STANDARD DEPARTURE CHART - INSTRUMENT



## RJFE / FUKUE


## OLVIN ONE DEPARTURE

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	033 (025.6)	-7.5	-	-	+700	-	-	RNP1
002	DF	KAMIG	-	-	-7.5	-	-	+6000	-	-	RNP1
003	TF	OLVIN	-	044 (036.3)	-7.5	35.9	-	-	-	-	RNP1


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	213 (205.7)	-7.5	-	-	+700	-	-	RNP1
002	DF	FE100	-	-	-7.5	-	-	-	-	-	RNP1
003	TF	FE102	-	123 (115.8)	-7.5	6.2	-	-	-	-	RNP1
004	TF	KAMIG	-	029 (021.9)	-7.5	30.9	-	+6000	-	-	RNP1
005	TF	OLVIN	-	044 (036.3)	-7.5	35.9	-	-	-	-	RNP1

CHANGE : Navigation Specification(Basic RNP1  $\rightarrow$  RNP1).


INSTRUMENT APPROACH CHART




INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART



## CHANGE: PROC course. HLDG pattern. Missed APCH course. MSA(BTN 180° and 360°). VAR.

VOR RWY21

[illegible]

**MISSED APPROACH**

Climb to 2000FT via FUE R224,  
turn left, direct to FUE  
VOR/DME and hold  
at 3000FT.  
Contact FUKUE RADIO.

Timing not authorized for defining the MAPt.

Diagram illustrating the missed approach procedure for FUE R224:

- Initial climb to 2000FT via FUE R224.
- Turn left, direct to FUE VOR/DME and hold at 3000FT.
- Contact FUKUE RADIO.
- Timing not authorized for defining the MAPt.
- MAPt (Missed Approach Point) is indicated at 1407 SDF 3.0°.
- VDP (Visual Descent Point) is indicated at 1210 (959) MDA.
- Turn initiation within D11.0 FUE.
- Altitude markers: 3000, 2282 (FAF), 224°, 2200, 1407 SDF 3.0°, 1210 (959), 1500 (1249).
- Directional markers: 061°, 224°.
- Final altitude: 2000.
- VDP (Visual Descent Point) is defined for D2.0 FUE (CAT A,B,C) and D2.1 FUE (CAT D).

Missed APCH climb gradient MNM 3.0%				
MINIMA		THR elev. 273	AD elev. 251	
CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	780 (529)	1000	780 (529)	1600
B		1200		
C	790 (539)			1280 (1029)
D	810 (559)	1600	1810 (1559)	3200

Circling to WEST side of RWY only.  
MINIMA with Missed APCH climb gradient of 2.5% are not established.



## INSTRUMENT APPROACH CHART

RJFE / FUKUE

RNP RWY03

KOBE CONTROL 118.9 - 303.8 134.25 - 315.5	RNP APCH MSAS CH88033 M03A	FUKUE RADIO 118.35 AFIS provided by Fukuoka Airport Office	NO RADAR
---	----------------------------------	---	----------

Baro-VNAV not authorized below -5°C



Missed APCH climb gradient MNM 5.0%

CAT	THR elev. 223		AD elev. 251		LNAV		CIRCLING	
	DA(H)	CMV	DA(H)	CMV	MDA(H)	CMV	MDA(H)	VIS
A	611(388)	900	1010(787)	1200	1010(787)	1200	1010(759)	1600
B	621(398)	1000	1050(827)	1400	1050(827)	1400	1280(1029)	2400
C	631(408)	1400	1090(867)	1800	1090(867)	1800	1810(1559)	3200
D	641(418)							

Circling to WEST side of RWY only.

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : Missed APCH for using VOR/DME abolished. HLDG pattern for using NAVAID abolished.

## INSTRUMENT APPROACH CHART

RJFE / FUKUE

RNP RWY03

**FAS DATA BLOCK**


Operation type	0	LTP/FTP ellipsoidal height	+00987
SBAS service provider identifier	2	FPAP latitude	324027.7825N
Airport identifier	RJFE	FPAP longitude	1285014.8040E
Runway	03	Threshold crossing height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M03A	∠ length offset	0000
LTP/FTP latitude	323929.3105N	HAL	40.0
LTP/FTP longitude	1284941.4435E	VAL	50.0
CRC remainder	E0818BF5		

**Required additional data**

LTP/FTP orthometric height	67.7
----------------------------	------

CHANGE : Description of FAS DATA BLOCK ITEM(CRC remainder).

INSTRUMENT APPROACH CHART



CHANGE : Missed APCH for using VOR/DME abolished. HLDG pattern for using NAVAID abolished.

## INSTRUMENT APPROACH CHART

RJFE / FUKUE

RNP RWY21

**FAS DATA BLOCK**

Operation type	0	LTP/FTP ellipsoidal height	+01140
SBAS service provider identifier	2	FPAP latitude	323929.3105N
Airport identifier	RJFE	FPAP longitude	1284941.4435E
Runway	21	Threshold crossing height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M21A	∠ length offset	0000
LTP/FTP latitude	324027.7825N	HAL	40.0
LTP/FTP longitude	1285014.8040E	VAL	50.0
CRC remainder	7B7068FB		


**Required additional data**

LTP/FTP orthometric height	82.9
----------------------------	------

CHANGE : Description of FAS DATA BLOCK ITEM(CRC remainder).

RJFE / FUKUE


Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : Secondary FREQ abolished.


Call sign	BRG / DIST from ARP	Remarks
奈留島 Narushima	029°T / 10.8NM	浦港 Harbor
枇島 Kabashima	053°T / 10.2NM	島 Island
京ノ岳 Kyonodake	304°T / 10.1NM	レーダーサイト Radar site
蝶螺島 Sazaejima	055°T / 4.0NM	島 Island
二本楠 Nihongusu	275°T / 5.2NM	十字路 Intersection
富江港 Tomieko	230°T / 4.4NM	港 Harbor
大瀬崎 Osezaki	255°T / 12.2NM	灯台 Lighthouse
黒島 Kuroshima	179°T / 4.0NM	島 Island
黄島 Oshima	151°T / 6.9NM	島 Island



RJFE / FUKUE

Minimum Vectoring Altitude CHART

CHANGE : Shape of segment.



**INTENTIONALLY LEFT BLANK**