

STANDARD DEPARTURE CHART -INSTRUMENT

RJCM / MEMANBETSU

SID

KUSHIRO THREE DEPARTURE

RWY 18 : Climb via TBE R187/KSE R007 to KSE VOR/DME.

RWY 36 : Climb RWY HDG to 800FT, turn right HDG 217° to intercept and proceed via TBE R187/KSE R007 to KSE VOR/DME.

Note RWY18 : 3.9% climb gradient required up to 4500FT.

OBST ALT 3281FT located at 17.0NM 179° FM end of RWY18.



## STANDARD DEPARTURE CHART-INSTRUMENT

RJCM / MEMANBETSU

SID

EATAK THREE DEPARTURE


RWY 18 : Climb RWY HDG to 800FT, turn right climb via TBE R220/OBE R039 to EATAK....

RWY 36 : Climb RWY HDG to 1000FT, turn left HDG 175° to intercept and proceed via  
TBE R220/OBE R039 to EATAK....

....Cross EATAK at or above 6000FT.

Note RWY36 : 3.9% climb gradient required up to 2000FT.

OBST ALT 1181FT located at 4.5NM 290° FM end of RWY36.



STANDARD DEPARTURE CHART-INSTRUMENT

RJCM / MEMANBETSU

SID

MEMANBETSU REVERSAL THREE DEPARTURE

RWY 18 : Climb via TBE R187 to TBE 5.0DME, turn left....

RWY 36 : Climb via TBE R001 to TBE 5.0DME, turn right,....

....Proceed to TBE VOR/DME. Cross TBE VOR/DME at or above 4000FT.



## STANDARD DEPARTURE CHART-INSTRUMENT

RJCM / MEMANBETSU

RNAV SID

## SHIBARE ONE DEPARTURE

Basic RNP1

Note GNSS required.

VAR 9° W(2016)

## SHIBARE ONE DEPARTURE



## SHIBARE ONE DEPARTURE

RWY18: Climb on HDG184° at or above 600FT, turn right direct to NICOL at or above 7000FT, to NOTAK at or above 9000FT.

RWY36: Climb on HDG004° at or above 600FT, turn left direct to NICOL at or above 7000FT, to NOTAK at or above 9000FT.

Note RWY36 : 5.0% climb gradient required up to 600FT.

OBST ALT 1181FT located at 6.3NM 312° FM end of RWY36.

## RWY18

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	184 (174.7)	-9.2	—	—	+600	—	—	Basic RNP1
002	DF	NICOL	—	—	-9.2	—	R	+7000	—	—	Basic RNP1
003	TF	NOTAK	—	231 (222.1)	-9.2	45.3	—	+9000	—	—	Basic RNP1

## RWY36

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	004 (354.7)	-9.2	—	—	+600	—	—	Basic RNP1
002	DF	NICOL	—	—	-9.2	—	L	+7000	—	—	Basic RNP1
003	TF	NOTAK	—	231 (222.1)	-9.2	45.3	—	+9000	—	—	Basic RNP1


STANDARD ARRIVAL CHART-INSTRUMENT

RJCM / MEMANBETSU

STAR

QURIO ARC ARRIVAL

From over GINGA or TSUKA, turn left via TBE 13.0DME clockwise ARC to QURIO.  
Cross QURIO at or above 4000FT.



INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU


ILS Z or LOC Z RWY18



## INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU


ILS Y or LOC Y RWY18



MINIMA		THR elev. 102		AD elev. 109		
CAT	CAT I		LOC		CIRCLING	
	DA(H)	RVR/ CMV	MDA(H)	RVR/ CMV	MDA(H)	VIS
A	302 (200)	550	450 (341)	900	640 (531)	1600
B				1000		
C					750 (641)	2400
D					1400	760 (651)



## INSTRUMENT APPROACH CHART



## INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

VOR RWY18



## INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

VOR RWY36



## MISSED APPROACH

Climb to 1000FT via TBE R006,  
turn left HDG224° to intercept  
and proceed via TBE R269 to  
TSUKA and hold at 5000FT.  
Contact MEMANBETSU TOWER.

Timing not authorized for defining the MAPt.




MINIMA		THR elev. 135		AD elev. 109	
CAT			CIRCLING		
	MDA(H)	RVR/ CMV	MDA(H)	VIS	
A	690 (581)	1000	690 (581)	1600	
B		1200			
C			750 (641)	2400	
D			1600	760 (651)	3200

INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

RNP Z RWY18



## INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

RNP Z RWY18

**FAS DATA BLOCK**

Operation type	0	LTP/FTP ellipsoidal height	+00618
SBAS service provider identifier	2	FPAP latitude	435209.8350N
Airport identifier	RJCM	FPAP longitude	1440955.7670E
Runway	18	Threshold crossing height	00016.5
Approach performance designator	0	TCH units selector	1
Route indicator	Z	Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M18A	∠ length offset	0000
LTP/FTP latitude	435330.4920N	HAL	40.0
LTP/FTP longitude	1440945.3395E	VAL	50.0
CRC remainder	257C1F8B		

**Required additional data**


LTP/FTP orthometric height	31.0
----------------------------	------

CHANGE : Description of FAS DATA BLOCK ITEM(CRC remainder).

INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

RNP Y RWY18(AR)



CHANGE : PROC renamed.

## INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

RNP Y RWY18(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/RDH (°/FT)	RNP Value
001	IF	OZORA	—	—	-9.2	—	—	+7000	—	—	—
002	TF	SHARO	—	019 (009.5)	-9.2	14.1	—	+4300	—	—	1.0
003	TF	CM850	—	019 (009.6)	-9.2	12.0	—	+3000	-185	—	1.0
004	RF Center: CMRF1 r=3.04	TENTO	—	—	-9.2	4.6	L	2500	-165	—	1.0
005	RF Center: CMRF1 r=3.04	CM851	—	—	-9.2	5.7	L	675	—	-3.00	0.3
006	TF	RW18	Y	184 (174.7)	-9.2	1.6	—	156	—	-3.00/54	0.3
007	FA	—	—	184 (174.7)	-9.2	—	—	+600	—	—	1.0
008	DF	RAUSU	—	—	-9.2	—	L	3100	—	—	1.0

Waypoint Coordinates


Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
OZORA	432908.24N / 1441153.19E	CMRF1	435524.66N / 1441344.15E
SHARO	434301.91N / 1441506.66E		
CM850	435454.27N / 1441753.05E		
TENTO	435822.66N / 1441439.66E		
CM851	435507.75N / 1440932.81E		
RW18	435330.51N / 1440945.38E		
RAUSU	440327.56N / 1442052.43E		

CHANGE:PROC renamed.

## INSTRUMENT APPROACH CHART

RJCM /MEMANBETSU

RNP RWY36



CHANGE : New PROC.



## INSTRUMENT APPROACH CHART

RJCM / MEMANBETSU

RNP RWY36

**FAS DATA BLOCK**

Operation type	0	LTP/FTP ellipsoidal height	+00719
SBAS service provider identifier	2	FPAP latitude	435330.4920N
Airport identifier	RJCM	FPAP longitude	1440945.3395E
Runway	36	Threshold crossing height	00016.5
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M36A	∠ length offset	0000
LTP/FTP latitude	435209.8350N	HAL	40.0
LTP/FTP longitude	1440955.7670E	VAL	50.0
CRC remainder	28C6AB24		

**Required additional data**

LTP/FTP orthometric height	41.1
----------------------------	------

CHANGE : Description of FAS DATA BLOCK ITEM(CRC remainder).

RJCM / MEMANBETSU


Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : Map updated. BRG/DIST from ARP.

Call sign	BRG / DIST from ARP	Remarks
網走 Abashiri	025°T / 9.2NM	JR駅 Station
湧湖 Tofutsuko	074°T / 10.5NM	湖 Lake
小清水 Koshimizu	097°T / 13.3NM	学校 School
東藻琴 Higashimokoto	110°T / 6.1NM	市街地 Town
美幌峠 Bihoro Toge	165°T / 14.4NM	峠 Pass
津別 Tsubetsu	210°T / 12.2NM	市街地 Town
美幌ステーション Bihoro Station	223°T / 3.7NM	JR駅 Station
北見 Kitami	248°T / 12.4NM	JR駅 Station
浜佐呂間 Hamasaroma	321°T / 15.5NM	佐呂間大橋 Bridge



RJCM / MEMANBETSU

Minimum Vectoring Altitude CHART

