



AD CHART



INTENTIONALLY LEFT BLANK

RJCK/KUSHIRO

PRECISION APPROACH TERRAIN CHART – ICAO



STANDARD DEPARTURE CHART -INSTRUMENT

RJCK / KUSHIRO

SID

KUSHIRO REVERSAL FIVE DEPARTURE


RWY17 : Climb RWY HDG to 1000FT, turn right...

RWY35 : Climb RWY HDG to 1000FT, turn left HDG155°...

...to intercept and proceed via TCE R200 to 3000FT, turn left, direct to
TCE VOR/DME.

Cross TCE VOR/DME at or above 5000FT.

Note : No turn before DER.




CHANGE : PROC abolished(ALICE THREE DEPARTURE, ERIMO FOUR DEPARTURE, OBIHIRO THREE DEPARTURE, YUDOH TWO DEPARTURE, EATAK ONE DEPARTURE).
PROC renamed. KUSHIRO VOR/DME relocated(KSE→TCE).

STANDARD DEPARTURE CHART -INSTRUMENT

RJCK / KUSHIRO	RNAV SID
TANCHO ONE DEPARTURE	RNP1

Note GNSS required.



RWY17 : Climb on HDG168° at or above 700FT, turn right direct to YUDOH at or above 10000FT.
RWY35 : Climb on HDG348° at or above 800FT, turn left direct to YUDOH at or above 10000FT.

RWY17

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	168 (159.0)	-9.2	—	—	+700	—	—	RNP1
002	DF	YUDOH	—	—	-9.2	—	R	+10000	—	—	RNP1

RWY35


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	348 (339.0)	-9.2	—	—	+800	—	—	RNP1
002	DF	YUDOH	—	—	-9.2	—	L	+10000	—	—	RNP1

Waypoint Coordinates

Waypoint Identifier	Coordinates
YUDOH	423005.4N / 1434446.5E

CHANGE : Waypoint Coordinates added.

STANDARD DEPARTURE CHART -INSTRUMENT



CHANGE : Waypoint Coordinates added.

STANDARD DEPARTURE CHART -INSTRUMENT

RJCK / KUSHIRO


RNAV SID

RUGMO ONE DEPARTURE

RNP1

Note GNSS required.

VAR 9°W



RUGMO 6000

RWY17 : Climb on HDG168° at or above 700FT, turn right direct to RUGMO at or above 6000FT.

RWY35 : Climb on HDG348° at or above 800FT, turn left direct to RUGMO at or above 6000FT.

RWY17

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	168 (159.0)	-9.2	—	—	+700	—	—	RNP1
002	DF	RUGMO	—	—	-9.2	—	R	+6000	—	—	RNP1

RWY35

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	348 (339.0)	-9.2	—	—	+800	—	—	RNP1
002	DF	RUGMO	—	—	-9.2	—	L	+6000	—	—	RNP1

Waypoint Coordinates


Waypoint Identifier	Coordinates
RUGMO	430433.6N / 1432949.1E

CHANGE : Waypoint Coordinates added.

STANDARD DEPARTURE CHART -INSTRUMENT

RJCK / KUSHIRO

RNAV SID



RWY17 : Climb on HDG168° at or above 700FT, direct to MULNA, to ENTOD at or above 10000FT.
RWY35 : Climb on HDG348° at or above 900FT, turn left direct to TASAB, to MUBLA at or above 4600FT, to ENTOD at or above 10000FT.

RWY17

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	168 (159.0)	-9.3	—	—	+700	—	—	RNP1
002	DF	MULNA	—	—	-9.3	—	—	—	—	—	RNP1
003	TF	ENTOD	—	181 (171.4)	-9.3	21.3	—	+10000	—	—	RNP1

RWY35

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	—	—	348 (339.0)	-9.3	—	—	+900	—	—	RNP1
002	DF	TASAB	—	—	-9.3	—	L	—	—	—	RNP1
003	TF	MUBLA	—	168 (159.0)	-9.3	5.8	—	+4600	—	—	RNP1
004	TF	ENTOD	—	167 (157.5)	-9.3	24.9	—	+10000	—	—	RNP1

CHANGE : Description of latitude and longitude.

STANDARD DEPARTURE CHART -INSTRUMENT

RJCK / KUSHIRO


RNAV SID

Waypoint Coordinates

Waypoint Identifier	Coordinates
MULNA	425251.7N / 1441636.0E
TASAB	430015.6N / 1440508.3E
MUBLA	425452.9N / 1440757.8E
ENTOD	423150.2N / 1442054.3E


CHANGE : Waypoint Coordinates added.

STANDARD ARRIVAL CHART -INSTRUMENT



INTENTIONALLY LEFT BLANK

STANDARD ARRIVAL CHART -INSTRUMENT



STANDARD ARRIVAL CHART -INSTRUMENT

RJCK / KUSHIRO

RNAV STAR RWY17

AKESI ARRIVAL

From AKESI at or above 10000FT, to KANPO at or above 7000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKESI	-	-	-9.2	-	-	+10000	-	-	RNP1
002	TF	KANPO	-	360 (350.3)	-9.2	35.3	-	+7000	-	-	RNP1

IGAMO NORTH ARRIVAL

From IGAMO, to RUNPA, to KANPO at or above 7000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	IGAMO	-	-	-9.2	-	-	-	-	-	RNP1
002	TF	RUNPA	-	050 (040.9)	-9.2	9.8	-	-	-	-	RNP1
003	TF	KANPO	-	050 (041.0)	-9.2	12.5	-	+7000	-	-	RNP1

RUGMO NORTH ARRIVAL

From RUGMO at or above 9000FT, to KANPO at or above 7000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	RUGMO	-	-	-9.2	-	-	+9000	-	-	RNP1
002	TF	KANPO	-	089 (079.6)	-9.2	19.6	-	+7000	-	-	RNP1

RUNPA NORTH ARRIVAL

From RUNPA, to KANPO at or above 7000FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	RUNPA	-	-	-9.2	-	-	-	-	-	RNP1
002	TF	KANPO	-	050 (041.0)	-9.2	12.5	-	+7000	-	-	RNP1

Waypoint Coordinates


Waypoint Identifier	Coordinates
AKESI	423316.4N / 1440423.6E
IGAMO	425112.6N / 1433614.5E
RUNPA	425838.2N / 1434501.8E
RUGMO	430433.6N / 1432949.1E
KANPO	430802.7N / 1435613.8E

CHANGE : Waypoint Coordinates added.

STANDARD ARRIVAL CHART -INSTRUMENT

RJCK / KUSHIRO

RNAV STAR RWY35



STANDARD ARRIVAL CHART -INSTRUMENT

RJCK / KUSHIRO

RNAV STAR RWY35

IGAMO SOUTH ARRIVAL

From IGAMO, to OBKAL at or above 7000FT, to CRANE at or above 3600FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	IGAMO	-	-	-9.2	-	-	-	-	-	RNP1
002	TF	OBKAL	-	104 (094.4)	-9.2	16.2	-	+7000	-	-	RNP1
003	TF	CRANE	-	104 (094.7)	-9.2	7.7	-	+3600	-	-	RNP1

RUGMO SOUTH ARRIVAL

From RUGMO at or above 9000FT, to RUNPA, to BESRU at or above 7000FT, to CRANE at or above 3600FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	RUGMO	-	-	-9.2	-	-	+9000	-	-	RNP1
002	TF	RUNPA	-	127 (118.0)	-9.2	12.6	-	-	-	-	RNP1
003	TF	BESRU	-	127 (118.1)	-9.2	12.0	-	+7000	-	-	RNP1
004	TF	CRANE	-	128 (118.3)	-9.2	7.8	-	+3600	-	-	RNP1

RUNPA SOUTH ARRIVAL

From RUNPA, to BESRU at or above 7000FT, to CRANE at or above 3600FT.


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	RUNPA	-	-	-9.2	-	-	-	-	-	RNP1
002	TF	BESRU	-	127 (118.1)	-9.2	12.0	-	+7000	-	-	RNP1
003	TF	CRANE	-	128 (118.3)	-9.2	7.8	-	+3600	-	-	RNP1

Waypoint Coordinates

Waypoint Identifier	Coordinates
IGAMO	425112.6N / 1433614.5E
OBKAL	424955.3N / 1435815.3E
RUGMO	430433.6N / 1432949.1E
RUNPA	425838.2N / 1434501.8E
BESRU	425257.7N / 1435928.5E
CRANE	424916.8N / 1440846.6E

CHANGE : Waypoint Coordinates added.

STANDARD ARRIVAL CHART -INSTRUMENT



STANDARD ARRIVAL CHART -INSTRUMENT

RJCK / KUSHIRO

RNAV STAR

LEKUP NORTH ARRIVAL

From LEKUP at or above 3200FT, to OTGET, to ONAGA at or above 3200FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	LEKUP	-	-	-9.2	-	-	+3200	-	-	RNP1
002	TF	OTGET	-	318 (308.5)	-9.2	15.1	-	-	-	-	RNP1
003	TF	ONAGA	-	258 (248.9)	-9.2	4.5	-	+3200	-	-	RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	LEKUP	277 (268.1)	-9.2	1.0(-14000)	R	3200	FL140	-230(-14000)	RNP1

LEKUP SOUTH ARRIVAL

From LEKUP at or above 3200FT, to OMDUX at or above 2900FT,
to NOKKA at or above 1200FT.

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	LEKUP	-	-	-9.2	-	-	+3200	-	-	RNP1
002	TF	OMDUX	-	206 (196.8)	-9.2	12.8	-	+2900	-	-	RNP1
003	TF	NOKKA	-	258 (249.0)	-9.2	4.4	-	+1200	-	-	RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	LEKUP	277 (268.1)	-9.2	1.0(-14000)	R	3200	FL140	-230(-14000)	RNP1
Hold	OMDUX	258 (249.0)	-9.2	1.0(-14000)	L	2900	FL140	-230(-14000)	RNP1

Waypoint Coordinates


Waypoint Identifier	Coordinates
LEKUP	430627.2N / 1442719.9E
OTGET	431550.0N / 1441108.1E
ONAGA	431412.9N / 1440523.5E
OMDUX	425410.9N / 1442216.8E
NOKKA	425237.1N / 1441643.5E

CHANGE : Waypoint Coordinates added.

INSTRUMENT APPROACH CHART

RJCK / KUSHIRO


ILS Z or LOC Z RWY17 (CAT III)



INSTRUMENT APPROACH CHART

RJCK / KUSHIRO

ILS Y or LOC Y RWY17 (CAT III)



RJCK / KUSHIRO

HIDAKA APP
128.325 - 246.1 – 134.55

ILS-LOC
108.9 IKS :::-
ILS-GP 329.3
ILS-DME CH-26X

KUSHIRO TOWER
118.05 – 126.2

RADAR AVBL

VAR 9°W

MSA 25NM
6000
ARP
ARP : 430227N/1441135E 1236

RNAV HLDG
MHA 4500
MAX 230KIAS
VAVLO
186°
1MIN
NOT TO SCALE

RNAV HLDG
NOT TO SCALE
MHA 3200
MAX 230KIAS
LEKUP
097°
1MIN
277°

MISSED APPROACH
Direct to CK763, turn left direct to CK767, to LEKUP and hold at 3200FT.
Contact HIDAKA APP.

CAT	CAT III	CAT II		CAT I		CIRCLING		
	RVR	DA(H)	RA	RVR	DA(H)	RVR/ CMV	MDA(H) VIS	
A	100	Not applicable.			523 (200)	550	730 (419)	1600
B							770 (459)	
C							2400	
D							870 (559)	

MINIMA with Missed APCH climb gradient of 2.5% are not established.
Circling to EAST side of RWY only.
Values of RA may increase or decrease rapidly affected by terrain between IKS 0.4DME and 0.8DME.

INSTRUMENT APPROACH CHART

RJCK / KUSHIRO

ILS X RWY17(CATⅢ)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	AKESI	—	—	-9.3	—	—	+10000	—	—	RNP1
002	TF	VAVLO	—	006 (357.1)	-9.3	28.8	—	+4500	—	—	RNP1
003	TF	CK764	—	006 (357.0)	-9.3	5.0	—	+2400	-200	—	RNP1
004	RF Center: CKRF3 r=2.51NM	CK765	—	—	-9.3	3.5	R	+2000	—	—	RNP1
005	RF Center: CKRF3 r=2.51NM	CK766	—	—	-9.3	3.5	R	1600	—	—	RNP1
001	DF	CK763	Y	—	-9.3	—	—	—	—	—	RNP1
002	DF	CK767	—	—	-9.3	—	L	—	—	—	RNP1
003	TF	LEKUP	—	056 (046.9)	-9.3	5.1	—	3200	—	—	RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	VAVLO	006 (357.0)	-9.3	1.0(-14000)	L	4500	FL140	-230(-14000)	RNP1
Hold	LEKUP	277 (268.1)	-9.3	1.0(-14000)	R	3200	FL140	-230(-14000)	RNP1

Waypoint Coordinates


Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
AKESI	423316.40N / 1440423.57E	CKRF3	430707.83N / 1440527.18E
VAVLO	430200.49N / 1440223.10E		
CK764	430700.07N / 1440201.89E		
CK765	430935.11N / 1440444.33E		
CK766	430802.03N / 1440839.00E		
CK763	430017.29N / 1441242.98E		
CK767	430257.41N / 1442212.36E		
LEKUP	430627.23N / 1442719.94E		

CHANGE : New PROC.

INSTRUMENT APPROACH CHART


RJCK / KUSHIRO

VOR RWY17




INSTRUMENT APPROACH CHART

RJCK / KUSHIROVOR RWY35



INSTRUMENT APPROACH CHART



CHANGE : PINEN, ANDAS established. MARIM, MILKY abolished.

INSTRUMENT APPROACH CHART

RJCK / KUSHIRO

RNP Z RWY17(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	CRANE	-	-	-9.2	-	-	+3600	-	-	-
002	TF	PINEN	-	358 (349.1)	-9.2	7.1	-	+3300	-	-	1.0
003	TF	ANDAS	-	358 (349.0)	-9.2	6.0	-	3300	-165	-	1.0
004	TF	CK752	-	358 (349.0)	-9.2	1.4	-	2864	-	-3.00	0.3
005	RF Center: CKRF1 r=2.08NM	CK751	-	-	-9.2	6.2	R	901	-	-3.00	0.3
006	TF	RW17	Y	168 (159.0)	-9.2	1.6	-	378	-	-3.00/55	0.3
007	TF	CK753	-	168 (159.0)	-9.2	9.8	-	-	-	-	1.0
008	TF	CRANE	-	238 (229.0)	-9.2	7.1	-	3600	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	CRANE	020 (010.5)	-9.2	1.0 (-14000)	R	3600	FL140	-230(-14000)	1.0


Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
CRANE	424916.84N / 1440846.59E	CKRF1	430352.65N / 1440747.87E
PINEN	425614.81N / 1440656.16E		
ANDAS	430208.16N / 1440522.44E		
CK752	430328.83N / 1440501.00E		
CK751	430437.47N / 1441026.54E		
RW17	430305.30N / 1441114.92E		
CK753	425355.48N / 1441602.58E		

CHANGE : PINEN, ANDAS established. MARIM, MILKY abolished.

RJCK / KUSHIRO

RNP Y RWY17(AR)



INSTRUMENT APPROACH CHART

RJCK / KUSHIRO

RNP Y RWY17(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	PIBAM	-	-	-9.2	-	-	+3800	-	-	-
002	TF	BEPPPO	-	348 (339.1)	-9.2	9.7	-	3800	-165	-	1.0
003	TF	CK755	-	348 (339.1)	-9.2	2.5	-	3005	-	-3.00	0.3
004	RF Center: CKRF2 r=2.10NM	CK751	-	-	-9.2	6.6	L	901	-	-3.00	0.3
005	TF	RW17	Y	168 (159.0)	-9.2	1.6	-	378	-	-3.00/55	0.3
006	TF	CK753	-	168 (159.0)	-9.2	9.8	-	-	-	-	1.0
007	TF	CRANE	-	238 (229.0)	-9.2	7.1	-	3600	-	-	1.0


Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	CRANE	020 (010.5)	-9.2	1.0 (-14000)	R	3600	FL140	-230(-14000)	1.0
Hold	PIBAM	326 (316.4)	-9.2	1.0 (-14000)	R	3800	FL140	-230(-14000)	1.0

Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
PIBAM	425443.27N / 1442145.22E	CKRF2	430522.76N / 1441307.17E
BEPPPO	430348.15N / 1441701.05E		
CK755	430607.99N / 1441547.87E		
CK751	430437.47N / 1441026.54E		
RW17	430305.30N / 1441114.92E		
CK753	425355.48N / 1441602.58E		
CRANE	424916.84N / 1440846.59E		

CHANGE : PIBAM established. MARNY abolished.

INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJCK /KUSHIRO

RNP X RWY17

FAS DATA BLOCK

Operation type	0	LTP/FTP ellipsoidal height	+01279
SBAS service provider identifier	2	FPAP latitude	430149.6680N
Airport identifier	RJCK	FPAP longitude	1441154.5465E
Runway	17	Threshold crossing height	00016.7
Approach performance designator	0	TCH units selector	1
Route indicator	X	Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M17A	∠ length offset	0000
LTP/FTP latitude	430305.2840N	HAL	40.0
LTP/FTP longitude	1441114.8770E	VAL	50.0
CRC remainder	A0B919FD		

Required additional data

LTP/FTP orthometric height	98.0
----------------------------	------

RJCK / KUSHIRO

RNP RWY35



INSTRUMENT APPROACH CHART

RJCK /KUSHIRORNP RWY35

FAS DATA BLOCK


Operation type	0	LTP/FTP ellipsoidal height	+01179
SBAS service provider identifier	2	FPAP latitude	430305.2840N
Airport identifier	RJCK	FPAP longitude	1441114.8770E
Runway	35	Threshold crossing height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M35A	∠ length offset	0000
LTP/FTP latitude	430149.6680N	HAL	40.0
LTP/FTP longitude	1441154.5465E	VAL	50.0
CRC remainder	F9C3454C		

Required additional data

LTP/FTP orthometric height	88.1
----------------------------	------

RJCK / KUSHIRO

Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).


Call sign	BRG / DIST from ARP	Remarks
北斗 Hokuto	080°T / 4.6NM	T字路交差点 Intersection
大楽毛 Otanoshike	113°T / 4.2NM	製紙工場煙突群 Chimneys
釧路ステーション Kushiro Station	110°T / 8.8NM	JR駅 Station
西庶路 Nishisyoro	215°T / 4.7NM	JR駅 Station
白糖 Shiranuka	225°T / 7.2NM	JR駅 Station

CHANGE : Map updated. BRG/DIST from ARP.

RJCK / KUSHIRO

Minimum Vectoring Altitude CHART

VAR 9°W (2007)



① 7000

CHANGE : KSE deleted.