
AD 2 AERODROMES**RJOF AD 2.1 AERODROME LOCATION INDICATOR AND NAME****RJOF - HOFU****RJOF AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	340204N/1313247E
2	Direction and distance from (city)	1.1nm SW
3	Elevation/ Reference temperature	7ft / -
4	Geoid undulation at AD ELEV PSN	Nil
5	MAG VAR/ Annual change	Nil
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	JSDF-A
7	Types of traffic permitted(IFR/ VFR)	IFR/VFR
8	Remarks	Nil

RJOF AD 2.3 OPERATIONAL HOURS

1	AD Administration	2200 - 1000 Other time 1HR PN
2	Customs and immigration	Nil
3	Health and sanitation	Nil
4	AIS Briefing Office	2200 - 1000 Other time 1HR PN
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	2100 - 0900 Other time on request
7	ATS	2200 - 1000 Other time 1HR PN
8	Fuelling	Nil
9	Handling	Nil
10	Security	Nil
11	De-icing	Nil
12	Remarks	Nil

RJOF AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Nil
2	Fuel/ oil types	JET A-1 PLUS
3	Fuelling facilities/ capacity	To be issued later
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

RJOF AD 2.5 PASSENGER FACILITIES

1	Hotels	Nil
2	Restaurants	Nil
3	Transportation	Nil
4	Medical facilities	Nil
5	Bank and Post Office	Nil
6	Tourist Office	Nil
7	Remarks	Nil

RJOF AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	Nil
2	Rescue equipment	Nil
3	Capability for removal of disabled aircraft	Nil
4	Remarks	Nil

RJOF AD 2.7 SEASONAL AVAILABILITY-CLEARING

1	Types of clearing equipment	Nil
2	Clearance priorities	Nil
3	Remarks	Nil

RJOF AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Apron surface and strength	To be issued later
2	Taxiway width, surface and strength	To be issued later
3	ACL and elevation	Not available
4	VOR checkpoints	Nil
5	INS checkpoints	Nil
6	Remarks	Nil

RJOF AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	Nil
2	RWY and TWY markings and LGT	RWY: RWY 12/30,01/19 (LGT): RTHL(RWY 12/30),TKOF aiming LGT TWY: (LGT): TWY edge LGT
3	Stop bars	Nil
4	Remarks	Nil

RJOF AD 2.10 AERODROME OBSTACLES

RWY/Area affected	Obstacle type	Coordinates	Elevation	Markings/ LGT	Remarks
Nil					

RJOF AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	HOFU
2	Hours of service MET Office outside hours	2100 - 0900 Other time on request
3	Office responsible for TAF preparation Periods of validity	Nil
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Nil
6	Flight documentation Language(s) used	Ja,En
7	Charts and other information available for briefing or consultation	S,U
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	Nil
10	Additional information(limitation of service, etc.)	Nil

RJOF AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCN) and surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
12	To be	1480×45	TTW20250kg(44600lbs)	Nil	Nil
30	issued later	1480×45	Asphalt		Nil
01		1180×45	TTW20250kg(44600lbs)	Nil	Nil
19		1180×45	Asphalt		Nil
Slope of RWY		Strip Dimensions(M)	Remarks		
7		10	12		
Nil		1600×150 1600×150	Nil		
Nil		1300×150 1300×150			

RJOF AD 2.13 DECLARED DISTANCES

	TORA	TODA	ASDA	LDA	
RWY Designator	(m)	(m)	(m)	(m)	Remarks
1	2	3	4	5	6

RJOF AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
12			PAPI 4.5° 152m 37.9ft					
30			PAPI 4.5° 152m 38.2ft					
01								
19								
Remarks								
10								
Nil								

RJOF AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	ABN: 340116N/1313154E, White/Green EV10sec, HO
2	LDI location and LGT Anemometer location and LGT	Nil
3	TWY edge and centerline lighting	TWY edge LGT : AVBL
4	Secondary power supply/ switch-over time	Nil
5	Remarks	WDI LGT, OBST LGT

RJOF AD 2.16 HELICOPTER LANDING AREA

Nil

RJOF AD 2.17 ATS AIRSPACE

Designation and lateral limits		Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1		2	3	4	6
HOFU CTR	Area within a radius of 5 nm of HOFU ARP(34°02'N131°33'E).	4 000 or below	D	HOFU TOWER	

RJOF AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
TWR	Hofu Tower	236.8MHz 126.2MHz 138.3MHz 133.4MHz(2) 120.1MHz(2) 247.0MHz(1)(2) 123.1MHz(1)(2) 121.5MHz(E) 243.0MHz(E)	2200-1000 Other time 1HR PN	APP provided by Tsuiki APP. (1) For rescue only. (2) AVBL on request.
GND	Hofu Ground	133.0MHz	2200-1000 Other time 1HR PN	

RJOF AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
TACAN	FMT	1164MHz (CH-77X)	H24	340218N/1313245E	57.7ft	Unusable on R360-010 beyond 15NM BLW 5000ft R010-020 beyond 13NM BLW 5000ft R020-030 beyond 22NM BLW 6000ft R030-040 beyond 35NM BLW 7000ft R040-070 beyond 18NM BLW 7000ft R070-080 beyond 15NM BLW 6000ft R080-090 beyond 20NM BLW 5000ft R090-100 beyond 35NM BLW 5000ft R100-110 beyond 22NM BLW 5000ft R120-130 beyond 28NM BLW 5000ft R130-140 beyond 12NM BLW 4000ft R140-150 beyond 10NM BLW 4000ft R150-160 beyond 23NM BLW 4000ft R160-170 beyond 34NM BLW 5000ft R170-180 beyond 38NM BLW 5000ft R200-210 beyond 30NM BLW 7000ft R210-220 beyond 16NM BLW 7000ft R220-230 beyond 14NM BLW 6000ft R230-250 beyond 31NM BLW 6000ft R250-270 beyond 19NM BLW 5000ft R270-280 beyond 28NM BLW 5000ft R280-290 beyond 23NM BLW 5000ft R290-300 beyond 32NM BLW 5000ft R300-310 beyond 22NM BLW 5000ft R310-330 beyond 12NM BLW 5000ft R330-350 beyond 17NM BLW 5000ft R350-360 beyond 15NM BLW 5000ft

RJOF AD 2.20 LOCAL TRAFFIC REGULATIONS**1. Airport regulations**

Nil

2. Taxiing to and from stands

Nil

3. Parking area for small aircraft(General aviation)

Nil

4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

Nil

7. School and training flights - technical test flights - use of runways

Nil

8. Helicopter traffic - limitation

Nil

9. Removal of disabled aircraft from runways

Nil

RJOF AD 2.21 NOISE ABATEMENT PROCEDURES

Nil

RJOF AD 2.22 FLIGHT PROCEDURES

1. TAKE OFF MINIMA

	RWY	ACFT CAT	REDL & RCLL		REDL or RCLL or RCL Marking		NIL (DAYTIME ONLY)	
			RVR	VIS	RVR	VIS	RVR	VIS
Multi-Engine ACFT with TKOF ALTN AP FILED	12	A,B,C,D	-	-	400m	400m	-	500m
	30		-	-	400m	400m	-	500m
OTHER	12	A,B,C,D	AVBL LDG MINIMA					
	30							

2. Lost communication procedures for arrival aircraft under radar navigational guidance

If radio communications with Tsuiki Radar are lost for 1 minute, squawk Mode A/3 Code 7600 and,

- (I) 1. Contact TSUIKI Radar / HOFU Tower.
2. If unable, proceed in accordance with Visual Flight Rules.
3. If unable, proceed to NANYO IAF last assigned altitude or 4,000 feet whichever is higher, and execute TACAN approach.
- (II) Procedures other than above will be issued when situation required.

3. Automated Radar Terminal System(ARTS)

Aircraft flying under control of Tsuiki approach control in the approach control area will be instructed to reply with discrete code on Mode A/3 and Mode C.

If an aircraft with non-discrete code capability is instructed to reply with the discrete code, it shall report a controller accordingly.

築城ターミナル管制所の指示のもとに、当該進入管制区を飛行する航空機は、モード A / 3 の二次レーダー個別コード及びモード C による応答を指示される。
二次レーダー個別コードを搭載していない航空機が当該コードによる応答を指示された場合は、管制官に対しその旨を通報すること。

RJOF AD 2.23 ADDITIONAL INFORMATION

Nil

RJOF AD 2.24 CHARTS RELATED TO AN AERODROME

Standard Departure Chart-Instrument-1
Standard Departure Chart-Instrument-2
Instrument Approach Chart (TACAN)

INTENTIONALLY LEFT BLANK

STANDARD DEPARTURE CHART -INSTRUMENT

RJOF / HOFU

SID

HOFU REVERSAL FOUR DEPARTURE

RWY 12 : Climb RWY HDG to 1500FT, turn right ...

RWY 30 : Climb RWY HDG to 1500FT, turn left ...

...direct to FMT TACAN.

Cross FMT TACAN at or above 5000FT.

Note RWY 12 : 6.7% climb gradient required up to 1500FT.

OBST ALT 722FT located at 2.0NM 127°FM end of RWY12.


OBST ALT 1249FT located at 2.1NM 146°FM end of RWY12.

RWY 30 : 5.7% climb gradient required up to 1500FT.

OBST ALT 1148FT located at 3.9NM 284°FM end of RWY30.

OBST ALT 1280FT located at 2.0NM 331°FM end of RWY30.

CHANGE : PROC renamed. PROC course. Note added. YASAKA TRANSITION and YAMAGUCHI TRANSITION abolished.



STANDARD DEPARTURE CHART -INSTRUMENT

RJOF / HOFU

SID

KUGA FIVE DEPARTURE

RWY 12 : Climb RWY HDG to 1200FT, turn left ...

RWY 30 : Climb RWY HDG to 1500FT, turn left HDG063° ...

... to intercept and proceed via FMT R093 to IWT TACAN.

Cross FMT R093/19.0DME at assigned altitude.

Note RWY 12 : 6.7% climb gradient required up to 1200FT.


OBST ALT 722FT located at 2.0NM 127°FM end of RWY12.

OBST ALT 1647FT located at 4.6NM 074°FM end of RWY12.

RWY 30 : 5.7% climb gradient required up to 1500FT.


OBST ALT 1148FT located at 3.9NM 284°FM end of RWY30.

OBST ALT 2253FT located at 5.1NM 073°FM end of RWY30.



CHANGE : PROC renamed. PROC course. Note added.

INSTRUMENT APPROACH CHART



INTENTIONALLY LEFT BLANK