

AD 2 AERODROMES

RJSD AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RJSD - SADO

RJSD AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	380338N 1382454E 97°/0.6km from RWY10 THR
2	Direction and distance from (city)	4km SW of Ryotsu in Sado city
3	Elevation/ Reference temperature	75ft / 35.9°C(2004-2008)
4	Geoid undulation at AD ELEV PSN	125FT
5	MAG VAR/ Annual change	9°W(2024)/4°W
6	AD Administration, address, telephone, telefax, telex, AFS, e-mail and/or Web-site addresses	Niigata Pref. 1814-3 Akitsu Sado-city Niigata Tel : 0259-27-3041 Fax : 0259-58-8084 e-mail : ngt111141@pref.niigata.lg.jp (Web1) https://www.pref.niigata.lg.jp/sec/sado_seibi/1204045245988.html (Web2) https://www.pref.niigata.lg.jp/sec/sado_seibi/1201021235487.html
7	Types of traffic permitted (IFR/VFR)	VFR
8	Remarks	Nil

RJSD AD 2.3 OPERATIONAL HOURS

1	AD Administration	2345 - 0815
2	Customs and immigration	On request Customs: 0259-23-4870 Immigration: 025-275-4735
3	Health and sanitation	Quarantine(human): On request(025-275-4615) Quarantine(animal, plant): Nil
4	AIS Briefing Office	Nil
5	ATS Reporting Office(ARO)	Nil
6	MET Briefing Office	Nil
7	ATS	Nil
8	Fuelling	Nil
9	Handling	Nil
10	Security	2345 - 0815
11	De-icing	Nil
12	Remarks	Nil

RJSD AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Nil
2	Fuel/ oil types	Nil
3	Fuelling facilities/ capacity	Nil
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

RJSD AD 2.5 PASSENGER FACILITIES

1	Hotels	Nil
2	Restaurants	Nil
3	Transportation	Nil
4	Medical facilities	Nil
5	Bank and Post Office	Nil
6	Tourist Office	Nil
7	Remarks	Nil

RJSD AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT 4
2	Rescue equipment	Chemical fire fighting truck x 2
3	Capability for removal of disabled aircraft	Crane(small type)
4	Remarks	Nil

RJSD AD 2.7 SEASONAL AVAILABILITY-CLEARING

1	Types of clearing equipment	Snow Removal Equipments : graders x 1 , dozer x 1
2	Clearance priorities	1.RWY 2.TWY 3.Apron
3	Remarks	Nil

RJSD AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Apron surface and strength	Surface: Asphalt-concrete Strength: PCR 363/F/D/X/T
2	Taxiway width, surface and strength	WIDTH : 11m Surface: Asphalt-concrete Strength: PCR 363/F/D/X/T
3	ACL and elevation	Not available
4	VOR checkpoints	Not available
5	INS checkpoints	Not available
6	Remarks	Nil

RJSD AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and Visual docking/ parking guidance system of aircraft stands	Nil
2	RWY and TWY markings and LGT	RWY:10/28 (Marking)RWY designation, RWY THR, RWY Middle Point, Aiming point, RWY side stripe TWY: (Marking)TWY CL, TWY side stripe
3	Stop bars	Nil
4	Remarks	(Marking)Overrun area (LGT)Apron flood LGT

RJSD AD 2.10 AERODROME OBSTACLES

In Area2 See Obstacle data

In Area3 To be developed

RJSD AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	Niigata prefecture Sado airport branch office
2	Hours of service MET Office outside hours	2345-0815 Nil
3	Office responsible for TAF preparation Periods of validity	Nil
4	Trend forecast Interval of issuance	Nil
5	Briefing/ consultation provided	Nil
6	Flight documentation Language(s) used	Nil
7	Charts and other information available for briefing or consultation	Nil
8	Supplementary equipment available for providing information	Nil
9	ATS units provided with information	Nil
10	Additional information(limitation of service, etc.)	Nil

RJSD AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY(M)	Strength(PCR) and Surface of RWY	THR coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
10	097.33°	890×25	PCR 131/F/D/Z/T Asphalt-Concret	380339.36N1382436.21E 125FT	THR ELEV: 97FT
28	277.33°	890×25	PCR 131/F/D/Z/T Asphalt-Concrete	380335.71N1382512.43E 125FT	THR ELEV: 53FT
Slope of RWY		Strip Dimensions(M)		RESA (Overrun) Dimensions(M)	Remarks
7		10		11	14
See RJSD AD2.24 AD Chart		1010×60		Nil	RWY grooving:890×25m
		1010×60		210 × 60	

RJSD AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
10	890	890	890	890	Nil
28	890	890	890	890	Nil

RJSD AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	RTHL Color WBAR	PAPI (VASIS) Angle DIST FM THR MEHT	RTZL LEN	RCLL LEN Spacing Color INTST	REDL LEN Spacing Color INTST	RENL Color WBAR	STWL LEN Color
1	2	3	4	5	6	7	8	9
10	Nil	Nil	PAPI(*1) 4.5°/Left 114m 25ft	Nil	Nil	Nil	Nil	Nil
28	Nil	Nil	PAPI 4.5°/Left 86m 25ft	Nil	Nil	Nil	Nil	Nil
Remarks								
10								
PAPI for RWY 10: Unusable beyond 1.5NM(*1) RWY THR ID LGT for RWY 10/28 THR(Color:White)								

RJSD AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	Nil
2	LDI location and LGT Anemometer location and LGT	Nil
3	TWY edge and center line lighting	Nil
4	Secondary power supply/ switch-over time	Within 15sec:PAPI,RWY THR ID LGT
5	Remarks	Nil

RJSD AD 2.16 HELICOPTER LANDING AREA

Nil

RJSD AD 2.17 ATS AIRSPACE

Designation and lateral limits	Vertical limits (ft)	Airspace classification	ATS unit call sign Language	Remarks
1	2	3	4	6
Nil				

RJSD AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
Nil				

RJSD AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
Nil						

RJSD AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport regulations

Nil

2. Taxiing to and from stands

Nil

3. Parking area for small aircraft(General aviation)

Nil

4. Parking area for helicopters

Nil

5. Apron - taxiing during winter conditions

Nil

6. Taxiing - limitations

Nil

7. School and training flights - technical test flights - use of runways

Nil

8. Helicopter traffic - limitation

Nil

9. Removal of disabled aircraft from runways

Nil

RJSD AD 2.21 NOISE ABATEMENT PROCEDURES

Nil

RJSD AD 2.22 FLIGHT PROCEDURES

Nil

RJSD AD 2.23 ADDITIONAL INFORMATION

Nil

RJSD AD 2.24 CHARTS RELATED TO AN AERODROME



Aerodrome Chart

INTENTIONALLY LEFT BLANK

SADO AIRPORT

VAR 9° W (2024)
ANNUAL CHANGE 4° W

RUNWAY THRESHOLD IDENTIFICATION LIGHTS

RUNWAY MIDDLE POINT

PAPI Angle 4.5°
MEHT 7.68m(25ft)

WDI

86.1m

PAPI Angle 4.5°
MEHT 7.68m(25ft)

WDI

28

10

113.8m

PAPI Angle 4.5°
MEHT 7.68m(25ft)

REMARKS :
1. RUNWAY GROOVING 890m x 25m
2. WIDTH OF TAXIWAY 10.5m
3. UNUSABLE AREA OF PAPI
FOR RWY 10 : beyond 1.5NM

LONGITUDINAL PROFILE OF RUNWAY

RWY 28
53ft
(16.2m)

71ft
(21.6m)

1.23%

450m

890m

RWY 10
88ft
(26.7m)

1.12%

0m

INTENTIONALLY LEFT BLANK