




OKUSHIRI AIRPORT



LONGITUDINAL PROFILE OF RUNWAY



INTENTIONALLY LEFT BLANK

STANDARD DEPARTURE CHART - INSTRUMENT

RJEO / OKUSHIRI

SID

ESASI TWO DEPARTURE

RWY13 : Turn left,...

RWY31 : Climb via RWY HDG until 1500FT or above, complete left turn within
ORE 10DME,...


...climb via ORE R115 to ESASI.

Cross ESASI at assigned or specified altitude.

Note : When take off from RWY13, following climb gradient should be
maintained until 700FT.

Speed (Knots)	60	90	120	150	180	210
Rate (Feet/Min)	300	450	600	750	900	1050


CHANGE : TAKE OFF MINIMA deleted.



STANDARD DEPARTURE CHART - INSTRUMENT

RJEO / OKUSHIRI

RNAV SID



AONAE ONE DEPARTURE

RWY13:Climb on HDG130°at or above 600FT, turn left direct to AONAE, to ESASI.
RWY31:Climb on HDG310°at or above 600FT, turn left direct to EO100, to AONAE, to ESASI.


Note RWY31: 4.5% climb gradient required up to 600FT.
OBST ALT 209FT located at 0.1NM 354°FM end of RWY31

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	130 (120.3)	-9.8	-	-	+600	-	-	RNP1
002	DF	AONAE	-	-	-9.8	-	L	-	-	-	RNP1
003	TF	ESASI	-	115 (105.6)	-9.8	20.6	-	-	-	-	RNP1

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	310 (300.3)	-9.8	-	-	+600	-	-	RNP1
002	DF	EO100	-	-	-9.8	-	L	-	-	-	RNP1
003	TF	AONAE	-	095 (084.9)	-9.8	17.1	-	-	-	-	RNP1
004	TF	ESASI	-	115 (105.6)	-9.8	20.6	-	-	-	-	RNP1

CHANGE : Navigation Specification(Basic RNP1 → RNP1).


STANDARD ARRIVAL CHART - INSTRUMENT




CHANGE : Navigation Specification(Basic RNP1→RNP1).

INTENTIONALLY LEFT BLANK

INSTRUMENT APPROACH CHART




INSTRUMENT APPROACH CHART



INSTRUMENT APPROACH CHART

RJEO / OKUSHIRI

VOR A




CHANGE : ATC call sign.

INSTRUMENT APPROACH CHART

RJEO / OKUSHIRI

RNP RWY31



RJE0 / OKUSHIRI

RNP RWY31

Operation type	0	LTP/FTP ellipsoidal height	+00760
SBAS service provider identifier	2	FPAP Latitude	420433.0405N
Airport identifier	RJEO	FPAP Longitude	1392523.3970E
Runway	31	Threshold Crossing Height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M31A	∠ length offset	0192
LTP/FTP latitude	420405.4465N	HAL	40.0
LTP/FTP longitude	1392627.1545E	VAL	50.0
CRC remainder	D0B5F768		


LTP/FTP orthometric height	42.8
----------------------------	------

CHANGE : Description of FAS DATA BLOCK ITEM(CRC remainder).

INSTRUMENT APPROACH CHART

RJEO / OKUSHIRI

RNP RWY13



CHANGE : ATC call sign.

INSTRUMENT APPROACH CHART

RJEO / OKUSHIRI

RNP RWY13

FAS DATA BLOCK

Operation type	0	LTP/FTP ellipsoidal height	+00878
SBAS service provider identifier	2	FPAP Latitude	420402.2720N
Airport identifier	RJEO	FPAP Longitude	1392634.4865E
Runway	13	Threshold Crossing Height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M13A	∠ length offset	0192
LTP/FTP latitude	420429.8670N	HAL	40.0
LTP/FTP longitude	1392530.7315E	VAL	50.0
CRC remainder	D63254BC		


Required additional data

LTP/FTP orthometric height	54.8
----------------------------	------

CHANGE : Description of FAS DATA BLOCK ITEM(CRC remainder).

RJEO / OKUSHIRI

Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : VAR.

Call sign	BRG / DIST from ARP	Remarks
稲穂岬 Inahomisaki	028°T / 12.0NM	灯台 Lighthouse
10NM E	090°T / 10.0NM	海上 Over the sea
10NM SE	135°T / 10.0NM	海上 Over the sea

INTENTIONALLY LEFT BLANK