


RORY / YORON

AD CHART

CHANGE : WIND SPEED METER, CEILOMETER added.


YORON AP



REMARKS :
WIDTH OF TWY 18m
RWY GROOVING 1200 x 20m

RWY 32

LONGITUDINAL PROFILE OF RWY



STANDARD DEPARTURE CHART-INSTRUMENT

RORY / YORON


SID

CHANGE : OKUMA ONE DEPARTURE abolished. PROC renamed(YORON REVERSAL THREE DEPARTURE). PROC course, NOTE.

YORON REVERSAL THREE DEPARTURE

RWY14 : Climb RWY HDG until 700FT, climb via YRE R142 to 8.8DME, turn left...
RWY32 : Climb RWY HDG until 500FT, climb via YRE R324 to 9.0DME, turn right...
...direct to YRE VOR/DME.

Note : RWY14 : 5.0% climb gradient required up to 700FT.
OBST ALT 353FT located at 1.5NM 127° FM end of RWY14.



STANDARD DEPARTURE CHART-INSTRUMENT


RORY / YORON

RNAV SID

ERABU ONE DEPARTURE

RNP1

Note GNSS required.



CHANGE : Navigation Specification(Basic RNP1 → RNP1).

RWY14 : Climb on HDG144° at or above 700FT, turn left direct to MARIX, to ONC.
 RWY32 : Climb on HDG324° at or above 500FT, turn right direct to MARIX, to ONC.

Note RWY14 : 5.0% climb gradient required up to 700FT.
 OBST ALT 353FT located at 1.5NM 127° FM end of RWY14.

STANDARD DEPARTURE CHART-INSTRUMENT

RORY / YORON

RNAV SID

ERABU ONE DEPARTURE

RWY14

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	144 (138.2)	-6.0	-	-	+700	-	-	RNP1
002	DF	MARIX	-	-	-6.0	-	L	-	-	-	RNP1
003	TF	ONC	-	026 (019.8)	-6.0	10.0	-	-	-	-	RNP1

RWY32


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	324 (318.2)	-6.0	-	-	+500	-	-	RNP1
002	DF	MARIX	-	-	-6.0	-	R	-	-	-	RNP1
003	TF	ONC	-	026 (019.8)	-6.0	10.0	-	-	-	-	RNP1

CHANGE : Navigation Specification(Basic RNP1 → RNP1).

STANDARD DEPARTURE CHART-INSTRUMENT

RORY / YORON

RNAV SID



RWY14 : Climb on HDG144° at or above 700FT, turn right direct to RY400, to MIDIP at or below 5000FT, to MEKAX.

RWY32 : Climb on HDG324° at or above 500FT, turn right direct to MIDIP at or below 5000FT, to MEKAX.

Note RWY14 : 5.0% climb gradient required up to 700FT.
OBST ALT 353FT located at 1.5NM 127° FM end of RWY14.

CHANGE : Navigation Specification(Basic RNP1 → RNP1).

STANDARD DEPARTURE CHART-INSTRUMENT

RORY / YORON

RNAV SID

MEKAX ONE DEPARTURE

RWY14


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	144 (138.2)	-6.0	-	-	+700	-	-	RNP1
002	DF	RY400	-	-	-6.0	-	R	-	-	-	RNP1
003	TF	MIDIP	-	014 (008.2)	-6.0	12.1	-	-5000	-	-	RNP1
004	TF	MEKAX	-	036 (030.0)	-6.0	83.9	-	-	-	-	RNP1

RWY32

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	324 (318.2)	-6.0	-	-	+500	-	-	RNP1
002	DF	MIDIP	-	-	-6.0	-	R	-5000	-	-	RNP1
003	TF	MEKAX	-	036 (030.0)	-6.0	83.9	-	-	-	-	RNP1

CHANGE : Navigation Specification(Basic RNP1 → RNP1).

STANDARD DEPARTURE CHART-INSTRUMENT



STANDARD DEPARTURE CHART-INSTRUMENT

RORY / YORON

RNAV SID

TOMORI ONE DEPARTURE

RWY14

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	144 (138.2)	-6.0	-	-	+700	-	-	RNP1
002	DF	TONOD	-	-	-6.0	-	R	-	-	-	RNP1
003	TF	OKUMA	-	225 (218.9)	-6.0	20.1	-	-	-	-	RNP1

RWY32


Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	VA	-	-	324 (318.2)	-6.0	-	-	+500	-	-	RNP1
002	DF	TONOD	-	-	-6.0	-	L	-	-	-	RNP1
003	TF	OKUMA	-	225 (218.9)	-6.0	20.1	-	-	-	-	RNP1

CHANGE : Navigation Specification(Basic RNP1 → RNP1).

INSTRUMENT APPROACH CHART

RORY / YORON

VOR RWY14



CHANGE : CIRCLING MDA(H) for CAT B, C.

RORY / YORON

NAHA APP 124.95 – 280.1	YORON VOR/DME 112.25 YRE CH-59Y 27°02'40"N/128°23'53"E	YORON RADIO 118.3 AFIS provided by Kagoshima Airport Office	RADAR AVBL
----------------------------	---	--	------------

EQPT REQUIRED
DME

VAR 6°W

MSA 25NM

YRE

10NM

**MHA 2000
MAX 210KIAS**

**MAPt
YRE**

**NUPDA(FAF)
D5.0 YRE**


**Turn initiation within
D8.0 YRE**

**MAX turning speed
200KIAS**

NUPDA(FAF) : 265904.27N/1282747.30E

NM to YRE	MAPt	3	4	FAF
ALT (3.0° APCH Path)	–	904	1223	1541

Climb to 1500FT via YRE R321,
turn right, direct to YRE VOR/DME
and hold at 2000FT.
Contact NAHA APP.



Timing not authorized for defining the MAPt.

DME to YRE	0.5	2.5	5.0
NM to THR	0	2.0	4.5

	MINIMA	THR elev. 52	AD elev. 47	
CAT			CIRCLING	
	MDA(H)	CMV	MDA(H)	VIS
A	690 (643)	1500	690 (643)	1600
B		2000		2400
C				
D	—	—	—	—


Circling to WEST side of RWY only.

CHANGE : DME to YRE, NM to THR. MINIMA.

INSTRUMENT APPROACH CHART

RORY / YORON

RNP RWY14



INSTRUMENT APPROACH CHART

RORY / YORON

RNP RWY14

FAS DATA BLOCK

Operation type	0	LTP/FTP ellipsoidal height	+00421
SBAS service provider identifier	2	FPAP latitude	270211.4935N
Airport identifier	RORY	FPAP longitude	1282432.5860E
Runway	14	Threshold crossing height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M14A	∠ length offset	0496
LTP/FTP latitude	270252.4555N	HAL	40.0
LTP/FTP longitude	1282351.4800E	VAL	50.0
CRC remainder	B6A26D6F		

Required additional data


LTP/FTP orthometric height	10.7
----------------------------	------

CHANGE : FAS DATA BLOCK ITEM and Required additional data ITEM established.

INSTRUMENT APPROACH CHART


RORY / YORON

RNP RWY32



MISSED APPROACH

Direct to RY250, turn right direct to
YRE and hold at 3000FT.
Contact NAHA APP.



CHANGE : CIRCLING MDA(H) for CAT B, C.

CAT	THR elev. 52		AD elev. 47		LNAV		CIRCLING	
	DA(H)	CMV	DA(H)	CMV	MDA(H)	CMV	MDA(H)	VIS
A	302(250)	1500	640(588)	1500	640(593)	1500	640(593)	1600
B							690(643)	
C		1600		2000		2000	-	2400
D	-	-	-	-	-	-	-	-

Circling to WEST side of RWY only.

INSTRUMENT APPROACH CHART

RORY / YORON

RNP RWY32

FAS DATA BLOCK

Operation type	0	LTP/FTP ellipsoidal height	+00472
SBAS service provider identifier	2	FPAP latitude	270304.4175N
Airport identifier	RORY	FPAP longitude	1282339.4735E
Runway	32	Threshold crossing height	00015.0
Approach performance designator	0	TCH units selector	1
Route indicator		Glide path angle	03.00
Reference path data selector	0	Course width at threshold	105.00
Reference path ID	M32A	∟ length offset	0496
LTP/FTP latitude	270223.4560N	HAL	40.0
LTP/FTP longitude	1282420.5825E	VAL	50.0
CRC remainder	977D3979		


Required additional data

LTP/FTP orthometric height	15.8
----------------------------	------

CHANGE : FAS DATA BLOCK ITEM and Required additional data ITEM established.

RORY / YORON


Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).

CHANGE : VAR.

Call sign	BRG / DIST from ARP	Remarks
10NM NE	045°T / 10.0NM	海上 Over the sea
赤崎 Akazaki	111°T / 3.2NM	灯台 Lighthouse
10NM SW	225°T / 10.0NM	海上 Over the sea



RORY / YORON

Minimum Vectoring Altitude CHART

