




INTENTIONALLY LEFT BLANK

STANDARD DEPARTURE CHART - INSTRUMENT

RJOR / TOTTORI

SID

AYABE THREE DEPARTURE

RWY 10 : Climb RWY HDG to 500FT, turn left HDG345°...

RWY 28 : Climb RWY HDG to 500FT, turn right HDG075°...

...to intercept and proceed via TRE R030 to 13.0DME, turn right, via YME R300 to YME VOR/DME.

Note RWY10 : 5.5% climb gradient required up to 1300FT.

OBST ALT 1247FT located at 3.73NM 105° FM end of RWY10.

RWY28 : 4.0% climb gradient required up to 700FT.

OBST ALT 374FT located at 2.62NM 271° FM end of RWY28.

TOTTORI REVERSAL THREE DEPARTURE

RWY 10 : Climb RWY HDG to 500FT, turn left HDG345°...

RWY 28 : Climb RWY HDG to 500FT, turn right HDG075°...

...to intercept and proceed via TRE R030 to 13.0DME, turn left, direct to TRE VOR/DME.


Note RWY10 : 5.5% climb gradient required up to 1300FT.

OBST ALT 1247FT located at 3.73NM 105° FM end of RWY10.


RWY28 : 4.0% climb gradient required up to 700FT.

OBST ALT 374FT located at 2.62NM 271° FM end of RWY28.

TOTTORI REVERSAL THREE DEPARTURE



STANDARD DEPARTURE CHART -INSTRUMENT




CHANGE : PROC renamed. PROC course. NAVAIDS deleted. Waypoint Coordinates added. description of Note (OBST radial).

INSTRUMENT APPROACH CHART

RJOR / TOTTORI

ILS Z or LOC RWY10



INSTRUMENT APPROACH CHART

RJOR / TOTTORI

ILS Y RWY10

KOBE CONTROL
133.8 – 126.1
287.6 – 278.2


ILS - LOC ITR 111.5
ILS - GP 332.9
ILS - DME CH - 52X

TOTTORI RADIO 118.5
AFIS provided
by Osaka Airport Office

NO RADAR

VAR8°W

MSA 25NM




ARP : 353148N/1340954E

RNAV HLDG

MHA 6000
MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)

NOT TO SCALE


1MIN(at or below FL140)
1.5MIN(above FL140)



EQPT REQUIRED

DME

RNP1
RF required.



RNAV HLDG

1MIN(at or below FL140)
1.5MIN(above FL140)


132°
312°

NOT TO SCALE

MHA 7000
MAX 230KIAS(at or below FL140)
MAX 240KIAS(above FL140)

MISSED APPROACH

Climb on course 101°,
at or above 600FT turn left,
direct to OR054,
turn left direct to TRE
and hold at 6000FT.
Contact TOTTORI RADIO.



5.1 3.6 0.2 NM to ITR
5.0 3.5 0 NM to THR

Missed APCH climb gradient MNM 5.0%

MINIMA THR elev. 29 AD elev. 48

CAT	CAT I		CIRCLING		VIS
	DA(H)	RVR/CMV	MDA(H) TOTAL AREA NORTH of RWY		
A	229 (200)	550	790 (742)	590 (542)	1600
B				630 (582)	2400
C			840 (792)	760 (712)	3200

MINIMA with Missed APCH climb gradient of 2.5% are not established.

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJOR / TOTTORI

ILS Y RWY10

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	Vertical Angle	Navigation Specification
001	IF	KANNA	—	—	-8.5	—	—	+7000	—	—	RNP1
002	TF	AGULI	—	292 (283.9)	-8.5	14.3	—	+7000	—	—	RNP1
003	TF	OR055	—	292 (283.7)	-8.5	14.3	—	+2100	—	—	RNP1
004	TF	OR056	—	282 (273.8)	-8.5	3.0	—	+1200	-200	—	RNP1
005	RF Center: ORRF6 r=2.50NM	OR057	—	—	-8.5	7.9	L	1200	—	—	RNP1
001	CA	—	—	101 (093.8)	-8.5	—	—	+600	—	—	RNP1
002	DF	OR054	Y	—	-8.5	—	L	—	—	—	RNP1
003	DF	TRE	—	—	-8.5	—	L	6000	—	—	RNP1

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	Navigation Specification
Hold	KANNA	312 (303.4)	-8.5	1.0(-14000) 1.5(+14001)	R	7000	—	-230(-14000) -240(+14001)	RNP1
Hold	TRE	329 (321.0)	-8.5	1.0(-14000) 1.5(+14001)	L	6000	—	-230(-14000) -240(+14001)	RNP1

Waypoint Coordinates


Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
KANNA	353011.27N / 1344121.95E	ORRF6	353439.86N / 1340321.51E
AGULI	353335.27N / 1342421.62E		
OR055	353658.03N / 1340713.85E		
OR056	353709.81N / 1340333.47E		
OR057	353209.90N / 1340309.56E		
OR054	354013.71N / 1341418.65E		
TRE	353138.28N / 1340953.59E		

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJOR / TOTTORI



VOR RWY10



INSTRUMENT APPROACH CHART

RJOR / TOTTORI

RNP Z RWY10(AR)



CHANGE : New PROC.

Missed APCH climb gradient MNM 5.0%

CAT	THR elev. 29		AD elev. 48	
	DA(H)	RVR/CMV	DA(H)	RVR/CMV
A	-	-	-	-
B	-	-	-	-
C	279(250)	800	424(395)	1000
D		1200	434(405)	1400

MINIMA with Missed APCH climb gradient of 2.5% are not established.

Authorization Required

INSTRUMENT APPROACH CHART

RJOR / TOTTORI

RNP Z RWY10(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	KANNA	-	-	-8.5	-	-	+7000	-	-	-
002	TF	OSVIR	-	291 (282.0)	-8.5	14.3	-	+7000	-	-	1.0
003	TF	OR050	-	290 (281.9)	-8.5	12.2	-	3100	-	-	1.0
004	TF	OR051	-	290 (281.7)	-8.5	1.3	-	2681	-	-3.00	0.10 0.30
005	RF Center: ORRF4 r=2.00NM	OR053	-	-	-8.5	6.6	L	593	-	-3.00	0.10 0.30
006	TF	RW10	Y	102 (093.8)	-8.5	1.6	-	83	-	-3.00/54	0.10 0.30
007	FA	-	-	102 (093.8)	-8.5	-	-	+500	-	-	1.0
008	DF	OR054	Y	-	-8.5	-	L	-	-	-	1.0
009	DF	TRE	-	-	-8.5	-	L	6000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	KANNA	312 (303.4)	-8.5	1.0 (-14000) 1.5 (+14001)	R	7000	-	-230(-14000) -240(+14001)	1.0
Hold	TRE	329 (321.0)	-8.5	1.0 (-14000) 1.5 (+14001)	L	6000	-	-230(-14000) -240(+14001)	1.0

Waypoint Coordinates


Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
KANNA	353011.27N / 1344121.95E	ORRF4	353356.61N / 1340726.83E
OSVIR	353308.46N / 1342413.64E		
OR050	353538.36N / 1340931.40E		
OR051	353554.35N / 1340756.57E		
OR053	353156.66N / 1340716.98E		
RW10	353150.32N / 1340914.57E		
OR054	354013.71N / 1341418.65E		
TRE	353138.28N / 1340953.59E		

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJOR / TOTTORI

RNP Y RWY10(AR)



CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJOR / TOTTORI

RNP Y RWY10(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	TRE	-	-	-8.5	-	-	+6000	-	-	-
002	TF	OR450	-	009 (000.3)	-8.5	5.9	-	+2100	-210	-	1.0
003	RF Center: ORRF5 r=2.81NM	OR070	-	-	-8.5	10.1	L	-	-	-	1.0
004	TF	OR071	-	163 (154.6)	-8.5	2.2	-	1700	-	-	1.0
005	TF	OR052	-	163 (154.6)	-8.5	1.4	-	1268	-	-3.00	0.10 0.30
006	RF Center: ORRF4 r=2.00NM	OR053	-	-	-8.5	2.1	L	593	-	-3.00	0.10 0.30
007	TF	RW10	Y	102 (093.8)	-8.5	1.6	-	83	-	-3.00/54	0.10 0.30
008	FA	-	-	102 (093.8)	-8.5	-	-	+500	-	-	1.0
009	DF	OR054	Y	-	-8.5	-	L	-	-	-	1.0
010	DF	TRE	-	-	-8.5	-	L	6000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	TRE	329 (321.0)	-8.5	1.0 (-14000) 1.5 (+14001)	L	6000	-	-230(-14000) -240(+14001)	1.0

Waypoint Coordinates


Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
TRE	353138.28N / 1340953.59E	ORRF5	353730.33N / 1340628.72E
OR450	353729.37N / 1340956.14E	ORRF4	353356.61N / 1340726.83E
OR070	353617.39N / 1340321.54E		
OR071	353418.50N / 1340431.03E		
OR052	353304.86N / 1340514.03E		
OR053	353156.66N / 1340716.98E		
RW10	353150.32N / 1340914.57E		
OR054	354013.71N / 1341418.65E		

CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJOR / TOTTORI


RNP X RWY10



INSTRUMENT APPROACH CHART

RJOR / TOTTORI

RNP Z RWY28(AR)



INSTRUMENT APPROACH CHART

RJOR / TOTTORI

RNP Z RWY28(AR)

Coding Table

Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	KANNA	-	-	-8.5	-	-	+7000	-	-	-
002	TF	ISASA	-	333 (324.6)	-8.5	13.4	-	+6000	-	-	1.0
003	TF	OR860	-	253 (245.0)	-8.5	12.2	-	2800	-165	-	1.0
004	TF	OR861	-	253 (244.9)	-8.5	1.4	-	2360	-	-3.00	0.10 0.30
005	RF Center: ORRF2 r=1.61NM	OR862	-	-	-8.5	1.6	L	1860	-	-3.00	0.10 0.30
006	TF	OR863	-	198 (189.2)	-8.5	0.6	-	1668	-	-3.00	0.10 0.30
007	RF Center: ORRF1 r=2.25NM	OR864	-	-	-8.5	3.3	R	603	-	-3.00	0.10 0.30
008	TF	RW28	Y	282 (273.8)	-8.5	1.5	-	115	-	-3.00/50	0.10 0.30
009	FA	-	-	282 (273.8)	-8.5	-	-	+700	-	-	1.0
010	DF	OR865	Y	-	-8.5	-	R	-	-	-	1.0
011	DF	TRE	-	-	-8.5	-	R	6000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	KANNA	312 (303.4)	-8.5	1.0 (-14000) 1.5 (+14001)	R	7000	-	-230(-14000) -240(+14001)	1.0
Hold	TRE	329 (321.0)	-8.5	1.0 (-14000) 1.5 (+14001)	L	6000	-	-230(-14000) -240(+14001)	1.0

Waypoint Coordinates


Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
KANNA	353011.27N / 1344121.95E	ORRF2	353353.44N / 1341726.73E
ISASA	354107.52N / 1343147.31E	ORRF1	353354.77N / 1341238.96E
OR860	353556.51N / 1341808.58E		
OR861	353521.38N / 1341636.47E		
OR862	353409.01N / 1341529.49E		
OR863	353333.13N / 1341522.36E		
OR864	353139.90N / 1341226.53E		
RW28	353146.03N / 1341033.79E		
OR865	353913.26N / 1340315.89E		
TRE	353138.28N / 1340953.59E		

CHANGE : PROC renamed. OR860, OR861, OR862, OR863, OR864, OR865 established. OR850, OR851, OR852, OR853, OR854 abolished. HLDG pattern added.

INSTRUMENT APPROACH CHART

RJOR / TOTTORI

RNP Y RWY28(AR)



CHANGE : New PROC.

INSTRUMENT APPROACH CHART

RJOR / TOTTORI

RNP Y RWY28(AR)

Coding Table											
Serial Number	Path Descriptor	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KIAS)	VPA/ RDH (°/FT)	RNP Value
001	IF	TRE	-	-	-8.5	-	-	+6000	-	-	-
002	TF	OR450	-	009 (000.3)	-8.5	5.9	-	+2100	-200	-	1.0
003	RF Center: ORRF3 r=2.51NM	OR858	-	-	-8.5	8.3	R	-	-	-	1.0
004	TF	OR859	-	198 (189.2)	-8.5	2.2	-	2100	-165	-	1.0
005	TF	OR863	-	198 (189.2)	-8.5	1.4	-	1668	-	-3.00	0.10 0.30
006	RF Center: ORRF1 r=2.25NM	OR864	-	-	-8.5	3.3	R	603	-	-3.00	0.10 0.30
007	TF	RW28	Y	282 (273.8)	-8.5	1.5	-	115	-	-3.00/50	0.10 0.30
008	FA	-	-	282 (273.8)	-8.5	-	-	+700	-	-	1.0
009	DF	OR865	Y	-	-8.5	-	R	-	-	-	1.0
010	DF	TRE	-	-	-8.5	-	R	6000	-	-	1.0

Path	Waypoint Identifier	Inbound Course °M(°T)	Magnetic Variation	Outbound Time (MIN)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FT)	Speed (KIAS)	RNP Value
Hold	TRE	329 (321.0)	-8.5	1.0 (-14000) 1.5 (+14001)	L	6000	-	-230(-14000) -240(+14001)	1.0


Waypoint Coordinates

Waypoint Identifier	Coordinates	RF Arc Center Identifier	Coordinates
TRE	353138.28N / 1340953.59E	ORRF3	353728.44N / 1341301.43E
OR450	353729.37N / 1340956.14E	ORRF1	353354.77N / 1341238.96E
OR858	353704.21N / 1341604.33E		
OR859	353453.72N / 1341538.38E		
OR863	353333.13N / 1341522.36E		
OR864	353139.90N / 1341226.53E		
RW28	353146.03N / 1341033.79E		
OR865	353913.26N / 1340315.89E		

CHANGE : New PROC.

RJOR / TOTTORI


Visual REP



※図中に標高を示す数字がある場合、単位はメートル(m)である。The unit of measurement used to express elevation is meter(m).


CHANGE : Secondary FREQ abolished.

Call sign	BRG / DIST from ARP	Remarks
10NM NW	315°T / 10.0NM	海上 Over the sea
浜坂 Hamasaka	069°T / 15.1NM	駅 Station
駟馳山 Shichiyama	069°T / 6.2NM	山 Mountain
長尾鼻 Nagaobana	273°T / 7.7NM	岬 Cape
鳥取駅 Tottori eki	126°T / 3.7NM	駅 Station
東郷 Togo	257°T / 13.7NM	池 Pond
郡家 Koge	149°T / 8.2NM	駅 Station
若桜 Wakasa	134°T / 15.9NM	駅 Station



RJOR / TOTTORI

Minimum Vectoring Altitude CHART



INTENTIONALLY LEFT BLANK