

Laboratorium **Programowanie w języku Python 2**
Wydział Elektrotechniki Automatyki I Informatyki
Politechnika Świętokrzyska

Studia: Stacjonarne I stopnia	Kierunek: Informatyka
Data wykonania: 03.06.2021	Grupa: 3ID16B
Imię i nazwisko: Arkadiusz Więclaw	Temat ćwiczenia: Gry, multimedia

Zad 1:

```
# Import the pygame module
import pygame

# Import pygame.locals for easier access to key coordinates
# Updated to conform to flake8 and black standards
from pygame.locals import (

    K_UP,

    K_DOWN,

    K_LEFT,

    K_RIGHT,

    K_ESCAPE,

    KEYDOWN,

    QUIT,

)

# Define constants for the screen width and height
SCREEN_WIDTH = 800
SCREEN_HEIGHT = 600

# Define a player object by extending pygame.sprite.Sprite
# The surface drawn on the screen is now an attribute of 'player'
class Player(pygame.sprite.Sprite):

    def __init__(self):

        super(Player, self).__init__()

        self.surf = pygame.Surface((95, 75))

        self.surf.fill((255, 255, 255))
```

```

        self.rect = self.surf.get_rect()

# Move the sprite based on user keypresses
def update(self, pressed_keys):

    if pressed_keys[K_UP]:
        self.rect.move_ip(0, -5)

    if pressed_keys[K_DOWN]:
        self.rect.move_ip(0, 5)

    if pressed_keys[K_LEFT]:
        self.rect.move_ip(-5, 0)

    if pressed_keys[K_RIGHT]:
        self.rect.move_ip(5, 0)

# Initialize pygame
pygame.init()

# Create the screen object
# The size is determined by the constant SCREEN_WIDTH and
SCREEN_HEIGHT
screen = pygame.display.set_mode((SCREEN_WIDTH, SCREEN_HEIGHT))

# Instantiate player. Right now, this is just a rectangle.
player = Player()

# Variable to keep the main loop running
running = True

# Main loop
while running:

    # for loop through the event queue
    for event in pygame.event.get():

        # Check for KEYDOWN event
        if event.type == KEYDOWN:

            # If the Esc key is pressed, then exit the main loop

```

```

    if event.key == K_ESCAPE:

        running = False

# Check for QUIT event. If QUIT, then set running to false.
elif event.type == QUIT:

    running = False

# Get all the keys currently pressed
pressed_keys = pygame.key.get_pressed()

# Update the player sprite based on user keypresses
player.update(pressed_keys)

# Fill the screen with black
screen.fill((0, 0, 0))

# Draw the player on the screen
screen.blit(player.surf, (SCREEN_WIDTH/2, SCREEN_HEIGHT/2))

# Update the display
pygame.display.flip()

```

Wynik:



Zad 2:

```

from math import pi, sin, cos

```

```

from direct.showbase.ShowBase import ShowBase
from direct.task import Task
from direct.actor.Actor import Actor
from direct.interval.IntervalGlobal import Sequence
from panda3d.core import Point3

"""
Przykład demonstrujące działanie panda3d za przykładzie chodzącej
pandy.
"""
class MyApp(ShowBase):
    def __init__(self):
        ShowBase.__init__(self)

        # Disable the camera trackball controls.
        self.disableMouse()

        # Load the environment model.
        self.scene = self.loader.loadModel("models/environment")
        # Reparent the model to render.
        self.scene.reparentTo(self.render)
        # Apply scale and position transforms on the model.
        self.scene.setScale(0.75, 0.35, 0.85)
        self.scene.setPos(-8, 43, -12)

        # Add the spinCameraTask procedure to the task manager.
        self.taskMgr.add(self.spinCameraTask, "SpinCameraTask")

        # Load and transform the panda actor.
        self.pandaActor = Actor("models/panda-model",
                                {"walk": "models/panda-walk4"})
        self.pandaActor.setScale(0.005, 0.005, 0.005)
        self.pandaActor.reparentTo(self.render)
        # Loop its animation.
        self.pandaActor.loop("walk")

        # Create the four lerp intervals needed for the panda to
        # walk back and forth.
        posInterval1 = self.pandaActor.posInterval(13,
                                                    Point3(0, -10, 0),
                                                    startPos=Point3(0,
10, 0))
        posInterval2 = self.pandaActor.posInterval(13,

```

```

Point3(0, 10, 0),
startPos=Point3(0,
-10, 0))
    hprInterval1 = self.pandaActor.hprInterval(3,
Point3(180, 0, 0),
startHpr=Point3(0,
0, 0))
    hprInterval2 = self.pandaActor.hprInterval(3,
Point3(0, 0, 0),
startHpr=Point3(180, 0, 0))


    # Create and play the sequence that coordinates the intervals.
    self.pandaPace = Sequence(posInterval1, hprInterval1,
                              posInterval2, hprInterval2,
                              name="pandaPace")
    self.pandaPace.loop()

    # Define a procedure to move the camera.
    def spinCameraTask(self, task):
        angleDegrees = task.time * 6.0
        angleRadians = angleDegrees * (pi / 180.0)
        self.camera.setPos(20 * sin(angleRadians), -20 *
cos(angleRadians), 3)
        self.camera.setHpr(angleDegrees, 0, 0)
        return Task.cont

app = MyApp()
app.run()

```

Wynik:



Zad 3:

```
'''
```

Ten przykład ćwiczy rysowanie okręgu (elipsy). Suwaki na górze ekranu z logo Kivy pod nim. Suwaki kontrolują początek i koniec kąta oraz skalę wysokości i szerokości. Jest przycisk aby zresetować suwaki. Logo użyte do obrazu tła koła to z katalogu kivy/data. Cały przykład jest zakodowany w kv opis języka.

```
'''
```

```
from kivy.app import App
from kivy.lang import Builder
```

```
kv = '''
```

```
BoxLayout:
    orientation: 'vertical'
    BoxLayout:
        size_hint_y: None
        height: sp(100)
        BoxLayout:
            orientation: 'vertical'
            Slider:
                id: e1
                min: -360.
                max: 360.
            Label:
```

```

        text: 'angle_start = {}'.format(e1.value)
BoxLayout:
    orientation: 'vertical'
    Slider:
        id: e2
        min: -180.
        max: 180.
        value: 180
    Label:
        text: 'angle_end = {}'.format(e2.value)

BoxLayout:
    size_hint_y: None
    height: sp(100)
    BoxLayout:
        orientation: 'vertical'
        Slider:
            id: wm
            min: 0
            max: 2
            value: 1
        Label:
            text: 'Width mult. = {}'.format(wm.value)
    BoxLayout:
        orientation: 'vertical'
        Slider:
            id: hm
            min: 0
            max: 2
            value: 1
        Label:
            text: 'Height mult. = {}'.format(hm.value)
    Button:
        text: 'Reset ratios'
        on_press: wm.value = 1; hm.value = 1

FloatLayout:
    canvas:
        Color:
            rgb: 1, 1, 1
        Ellipse:
            pos: 100, 100

```



```
size: 200 * wm.value, 201 * hm.value
source: 'data/logo/kivy-icon-512.png'
angle_start: e1.value
angle_end: e2.value
```

```
'''
```

```
class CircleApp(App):
    def build(self):
        return Builder.load_string(kv)
```

```
CircleApp().run()
```

Wynik:

