




#### but first...

# CoitHub



**Review Time!** 

#### What We'll Cover

- Responsive Web Design with Media Queries
- Support Queries
- Pseudo Elements

# Responsive Web Design

#### **Objectives**

- Describe Responsive Web Design
- Use media-queries to create an adaptive design
- Explain why the viewport meta tag is important
- Use flexible images
- Add media-queries to your grid to adjust for small format screens

#### Responsive Web Design



**Responsive designs** respond to changes in browser width or orientation by adjusting placement of content to fit in the available space.

# Hallmarks of Responsive Web Design

- A Fluid Layout
- Media Queries
- Flexible Images


# Fluid Layout

#### Fluid Layout

Fluid layouts can be accomplished with floats, flexbox and grid. They are built with relative units of measure so that the page can adapt easily to different screen sizes.

#### Fluid Floats Example

```
header {
  width: 100%;
main {
  width: 75%;
  float: left;
aside {
  width: 25%;
  float: left;
footer {
  width: 100%;
```



#### Media Queries

#### Media Queries

Media Queries allow us to write CSS rules that are applied for specific screen sizes or orientation.

When the conditions of the query are satisified the styles within are applied.

Media Queries can also be used for adapting to other conditions, such as print and speech.

# Media Query Example

```
div {
 width: 100%;
 background-color: blue;
   Media queries need to follow the base styles
    to be applied correctly */
@media (min-width: 768px) {
 div {
   width: 75%; /* Cascades and overrides the width: 100% rule */
```

#### Media Features

Media features allow us to selectively apply styles based on a feature of the device or browser in use. They include: width and height, the orientation of the device, the aspect-ratio or resolution of the device.

```
@media (orientation: landscape) {
   /* orientation is a media feature */
}

@media (max-width: 768px) {
   /* max-width is a media feature */
}
```

#### Media Types

We can also target the delivery mode with media types.

There are: screen, speech, print, and only.

```
/* Exclusively used when the page is printed */
@media only print {
    ...
}
```

## Logical Operators

Media features and types can be combined using operators:


```
and, or, not.
```

```
/* All of our extra small, small and medium devices in landscape mode *
@media (orientation: landscape) and (min-width: 767.98px) {
   body {
     flex-direction: row;
   }
}
/* Some of our small, all medium and some large devices */
@media (max-width: 950px) and (min-width: 600px) {...}
```

# Combining Media Types and Media Features

```
/* On devices under 768px */
.col-left, .col-center, .col-right {
   width: 100%;
}

@media only screen and (min-width: 768px) {
     [class*="col-"] {
       width: calc(100%/3);
       float: left;
   }
}
```




**Media Queries** 

#### Mobile First

#### Mobile First Concept

Generally, we build for the smallest devices, then add media queries for common breakpoints.




#### Why Mobile First?

It's simple: Mobile devices are our **primary devices for viewing web content** today.

## A Mobile First Approach

```
/* Extra small devices (portrait phones, less than 576px)
   are the default (Mobile First) */
/* Small devices (landscape phones, 576px and up) */
@media (min-width: 576px) { ... }
/* Medium devices (tablets, 768px and up) */
@media (min-width: 768px) { ... }
/* Large devices (desktops, 992px and up) */
@media (min-width: 992px) { ... }
/* Extra large devices (large desktops, 1200px and up) */
@media (min-width: 1200px) { ... }
```



Adding Media Queries to Matchmaker

# Viewport Tag

## Viewport Meta Tag

- Without instructions, mobile devices render pages at typical desktop screen widths, and then scale the pages to fit the mobile viewport
- If you don't set the viewport meta tag, your media queries don't fire
- Thank you Apple!

#### Scaled vs. Responsive




# Viewport Meta Tag

- width=device-width: sets the width of the viewport to the width of the device
- <u>initial-scale=1</u>: sets the initial zoom level when visiting the page
- shrink-to-fit=no : tells the device browser to reflow content instead of shrinking it



Adding Our Viewport Tag



**Experiment with Media Queries** 

#### Support Queries

#### CSS @supports

Support queries let us check if a feature is available and apply styles accordingly! **> (\*)** 

#### Use @supports

```
@supports(prop:value) {
    /* more styles */
}

/* Check for flexbox */
@supports (display: flex) {
    div { display: flex; }
}
```

# Logicals Operators Also Work

#### A Real Life Example

```
section {
  float: left;
@supports (display: -webkit-flex) or
          (display: -moz-flex) or
          (display: flex) {
    section {
      display: -webkit-flex;
      display: -moz-flex;
      display: flex;
      float: none;
```



Change our Floats to Grid

#### Pseudo Elements

#### It's Kind of an Element

- Pseudo element is a keyword added to a selector that lets you style a specific part of the selected element(s).
- Keeps your HMTL semantic
- Careful about accessibility

#### You'll Use These


::before

::after


Inserted as the first child—Inserted as the last child

```
/* Add hearts before links */
a::before {
  content: "♥";
 padding-right: 10px;
```


```
/* Add copyright to the footer */
footer::after {
  content: "\0000A9 2018 Acme Corp.
```



Pseudo Elements in the Real World



Add a Copyright to Matchmaker



Finish Making Matchmaker Responsive

## Go Build Awesome Things!