Emulation and Benchmarking of C Code

Kian S Frassek[†] and Cameron F Clark[‡]
EEE3096S Class of 2023
University of Cape Town
South Africa
[†]FRSKIA001 [‡]CLRCAM007

Abstract—**This report details the emulation and benchmarking of C code with various compiler optimisation. Python was using as our Golden Measure, and C code with 8 threads, floats, -Os and unrolled loops being the fastest**

I. Introduction

This report covers an investigation into the topics of emulation, benchmarking, and optimisation in embedded systems development. The aim is to uncover the impact of the chosen high-level language, compiler flags, bit widths, and multi-threading on a program's performance.

Emulation is a useful tool that allows the simulation of hardware and software simultaneously, and benchmarking is used to give a reference frame for all the tests. Python is chosen as our Golden Measure for these tests for its simplicity while the C code is optimised to increase the speed of the program.

Optimizations are tools used during the compiling process that are designed to improve program performance in one or more key aspects. These optimizations include changing the number of bits that the variables are stored in, adding various optimisation flags and the use of multi-threading.

II. Methodology

A. Hardware

The hardware used for this practical was a macOS laptop running Virtual Box with 4 CPU cores and 8 Gb of RAM. The Virtual Box was running Ubuntu image, which was in turn simulating a Raspberry Pi emulator. The Raspberry Pi emulator was used for the tests.

B. Implementation

Also mention the implementation source code:

```
nano makefile
make
for i in {1..5}; do make run; done
```

```
nano makefile
make
for i in {1..5}; do make run; done
```

```
nano makefile
make
for i in {1..5}; do make run; done
```

```
nano makefile
make
for i in {1..5}; do make run; done
```

```
nano makefile
make
for i in {1..5}; do make run; done
```

or you could turn it into a float: see listing 1. Floats are tables, figures and listings that appear at a different place than in the source code. This template is set up to put floats at the top of the next column, as prescribed by the IEEE article specification.

Only list what is relevant. Don't give too much detail - just enough to show what you've done. This template supports the following languages:

- Matlab (Octave)
- GLSL
- OpenCL
- Verilog
- C++ (use the name "Cpp")

C. Experiment Procedure

Furthermore, include detail relating to the experiment itself: what did you do, in what order was this done, why was this done, etc. What are you trying to prove / disprove?

III. Results

The results section is for presenting and discussing your findings. You can split it into subsections if the experiment has multiple sections or stages.

A. Figures

Include good quality graphs. These were produced by the Octave code presented in listings 2 and 3. You can play around with the `PaperSize` and `PaperPosition` variables to change the aspect ratio. An easy way to obtain more space on a paper is to use wide, flat figures, such as Fig.

Always remember to include axes text, units and a meaningful caption in your graphs. When typing units, a μ sign has a tail! The letter "u" is not a valid unit prefix. When typing resistor values, use the Ω symbol.

B. Tables

Tables are often a convenient means by which to specify lists of parameters. An example table is presented in table I. You can use Tablesgenerator to make your LaTeXtables.

```
__kernel void Multiply(
  __global float* A, // Global input buffer
  __global float* B, // Global input buffer
  __global float* Y, // Global output buffer
    const  int    N  // Global uniform
){
  const int i = get_global_id(0); // 1st dimension index
  const int j = get_global_id(1); // 2nd dimension index

  // Private variables
  int   k;
  float f = 0.0;

  // Kernel body
  for(k = 0; k < N; k++) f += A[i*N + k] * B[k*N + j];
  Y[i*N + j] = f;
}
```

Listing 1. OpenCL kernel to perform matrix multiplication

```
function FormatFig(X, Y, File);
  set(gcf, 'PaperUnits'    , 'inches');
  set(gcf, 'PaperOrientation', 'landscape');
  set(gcf, 'PaperSize'     ,      [8, 4]);
  set(gcf, 'PaperPosition'  , [0, 0, 8, 4]);

  set(gca, 'FontName', 'Times New Roman');
  set(gca, 'Position', [0.1 0.2 0.85 0.75]);

  xlabel(["\n" X]);
  ylabel([Y "\n\n"]);

  setenv("GSC", "GSC"); # Eliminates stupid warning
  print(...
    [File '.pdf'],...
    '-dpdf'...
  );
end
```

Listing 2. Octave function to format a figure and save it to a high quality PDF graph

```
figure;                            # Create a new figure
# Some code to calculate the various variables to plot...
plot(N, r, 'k', 'linewidth', 4); grid on; # Plot the data
xlim([0 360]);                     # Limit the x range
ylim([-1 1]);                      # Limit the y range
set(gca, 'xtick', [0 90 180 270 360]);   # Set the x labels

FormatFig(...                      # Call the function with:
  'Phase shift [\circ]',...              # The x title
  'Correlation coefficient',...          # The y title
  ['r_vs_N;_f=' num2str(f) ';_P=' num2str(P)]... # Format the file name
);
close all;                         # Close all open figures
```

Listing 3. Example of how to use the FormatFig function

TABLE I
MY INFORMATIVE TABLE

Heading 1	Heading 2	Heading 3
Data	123	321
Data	456	654
Data	789	987

C. Pictures and Screen-shots

When you include screen-shots, pdfLATEX supports JPG and PNG file formats. PNG is preferred for screen-shots, as it is a loss-less format. JPG is preferred for photos, as it results in a smaller file size. It's generally a good idea to resize photos (not screen-shots) to be no more that 300 dpi, in order to reduce file size. For 2-column article format papers, this translates to a maximum width of 1024. **Never change the aspect ratio of screen-shots and pictures!**

The source used to import a picture in an exact spot, with a caption and labels

Fig. 1: An example image

D. Maths

LATEX has a very sophisticated maths rendering engine, as illustrated by equation 1. When talking about approximate answers, never use ± 54 V, as this implies "positive or negative 54 V". Use ≈ 54 V or ~ 54 V instead.

$$y = \int_0^\infty e^{x^2} \mathrm{d}x \qquad (1)$$

IV. CONCLUSION

The conclusion should provide a summary of your findings. Many people only read the introduction and conclusion of a paper. They sometimes scan the tables and figures. If the conclusion hints at interesting findings, only then will they bother to read the whole paper.

You can also include work that you intend to do in future, such as ideas for further improvements, or to make the solution more accessible to the general user-base, etc.

Publishers often charge "overlength article charges" [1], so keep within the page limit. In EEE4084F we will simulate overlength fees by means of a mark reduction at 10% per page. Late submissions will be charged at 10% per day, or part thereof.

REFERENCES

[1] "Voluntary Page and Overlength Article Charges," http://www.ieee.org/advertisement/2012vpcopc.pdf, 2014.