# Emulation and Benchmarking of C Code

Kian S Frassek<sup>†</sup> and Cameron F Clark<sup>‡</sup>
EEE3096S Class of 2023
University of Cape Town
South Africa

<sup>†</sup>FRSKIA001 <sup>‡</sup>CLRCAM007

Abstract—This report details the emulation and benchmarking of C code with various compiler optimisation. Python was using as our Golden Measure, and C code with 8 threads, floats, -Os and unrolled loops being the fastest

#### I. Introduction

This report covers an investigation into the topics of emulation, benchmarking, and optimisation in embedded systems development. The aim is to uncover the impact of the chosen high-level language, compiler flags, bit widths, and multi-threading on a program's performance.

Emulation is a useful tool that allows the simulation of hardware and software simultaneously, and benchmarking is used to give a reference frame for all the tests. Python is chosen as our Golden Measure for these tests for its simplicity while the C code is optimised to increase the speed of the program.

Optimizations are tools used during the compiling process that are designed to improve program performance in one or more key aspects. These optimizations include changing the number of bits that the variables are stored in, adding various optimisation flags and the use of multi-threading.

#### II. METHODOLOGY

## A. Hardware

The hardware used for this practical was a macOS laptop running Virtual Box with 4 CPU cores and 8 Gb of RAM. The Virtual Box was running Ubuntu image, which was in turn simulating a Raspberry Pi emulator. The Raspberry Pi emulator was used for the tests.

# B. Implementation

The following code is the sudo code format of the two files: the python code which was used as the benchmark for the C code tests and the non-threaded C code. The third file that was used in this test was a multi-threaded version of the C code file. The 'data' and 'carrier' arrays are predefined arrays found in another tile

```
# Load data arrays from external file
Load data from external file

# Define values
c = carrier array
d = data array
result = empty array

# Main function
function main():
Display "There are " + length of c + " samples"
Display "Waing type " + type of first element in data array
Call Timing.startlog()
for i from 0 to length of c - 1:
Append c[i] * d[i] to result array
Call Timing.endlog()
```

# C. Experiment Procedure

The experiment start by benchmarking in Python using the following code. All tests were run 5 times and then an average was taken.

```
cd Python
for i in {1..5}; do python3 PythonHeterodyning.py; done
```

The C code was tested next starting with the non-threaded version using the following code.

```
cd ../C
make
for i in {1..5}; do make run; done
```

The threaded version of the C code was tested next, where each test changed the defined number of threaded in the CHeterodyning  $_threaded.hfile.Thenanocommand was using to edit the free constant of the contract of the co$ 

```
nano src/CHeterodyning_threaded.h
for i in {1..5}; do make run; done
```

where the thread count was changed in the following line to the values 1, 2, 4, 8, 16, and 32 in turn.

```
#define Thread_Count 1
```

The threaded C code was executed for each change of thread count using the following code

```
make threaded
for i in {1..5}; do make run_threaded; done
```

#### III. RESULTS

The results section is for presenting and discussing your findings. You can split it into subsections if the experiment has multiple sections or stages.

### A. Figures

Include good quality graphs. These were produced by the Octave code presented in listings 1 and 2. You can play around with the PaperSize and PaperPosition variables to change the aspect ratio. An easy way to obtain more space on a paper is to use wide, flat figures, such as Fig.

Listing 1. Octave function to format a figure and save it to a high quality PDF graph

```
figure;  # Create a new figure
# Some code to calculate the various variables to plot...
plot(N, r, 'k', 'linewidth', 4); grid on; # Plot the data
xlim([0 360]);  # Limit the x range
ylim([-1 1]);  # Limit the y range
set(gca, 'xtick', [0 90 180 270 360]); # Set the x labels

FormatFig(...  # Call the function with:
'Phase shift [\circ]'...  # The x title
'Correlation coefficient',...  # The y title
['r_vs_N;_f=' num2str(f) ';_P=' num2str(P)]... # Format the file name
);
close all; # Close all open figures
```

Listing 2. Example of how to use the FormatFig function

Always remember to include axes text, units and a meaningful caption in your graphs. When typing units, a  $\mu$  sign has a tail! The letter "u" is not a valid unit prefix. When typing resistor values, use the  $\Omega$  symbol.

## B. Tables

Tables are often a convenient means by which to specify lists of parameters. An example table is presented in table I. You can use Tablesgenerator to make your LATEX tables.

# C. Pictures and Screen-shots

When you include screen-shots, pdfIfTeX supports JPG and PNG file formats. PNG is preferred for screen-shots, as it is a loss-less format. JPG is preferred for photos, as it results in a smaller file size. It's generally a good idea to resize photos (not screen-shots) to be no more that 300 dpi, in order to reduce file size. For 2-column article format papers, this translates to a maximum width of 1024. Never change the aspect ratio of screen-shots and pictures!

The source used to import a picture in an exact spot, with a caption and labels

TABLE I
MY INFORMATIVE TABLE

Heading 1	Heading 2	Heading 3
Data	123	321
Data	456	654
Data	789	987



Fig. 1: An example image

#### D. Maths

LATEX has a very sophisticated maths rendering engine, as illustrated by equation 1. When talking about approximate answers, never use  $\pm 54$  V, as this implies "positive or negative 54 V". Use  $\approx 54$  V or  $\sim 54$  V instead.

$$y = \int_0^\infty e^{x^2} \mathrm{dx} \tag{1}$$

### IV. CONCLUSION

The conclusion should provide a summary of your findings. Many people only read the introduction and conclusion of a paper. They sometimes scan the tables and figures. If the conclusion hints at interesting findings, only then will they bother to read the whole paper.

You can also include work that you intend to do in future, such as ideas for further improvements, or to make the solution more accessible to the general user-base, etc.

Publishers often charge "overlength article charges" [1], so keep within the page limit. In EEE4084F we will simulate overlength fees by means of a mark reduction at 10% per page. Late submissions will be charged at 10% per day, or part thereof.

## REFERENCES

 "Voluntary Page and Overlength Article Charges," http://www.ieee.org/advertisement/2012vpcopc.pdf, 2014.