

Project Name: RFID BASED DOOR ACCESS SYSTEM

1. Router (R1) Network Configuration

Router par IP address aur DHCP pool set karne ki commands:

```
enable
configure terminal
hostname R1
```

```
interface gigabitEthernet 0/0
ip address 192.168.1.1 255.255.255.0
no shutdown
exit
```

```
ip dhcp pool iot
network 192.168.1.0 255.255.255.0
```

2. IoT Server Configuration Details

IoT Registration Server ki networking aur login details:

- **Server IP Address:** 192.168.1.51
- **Default Gateway:** 192.168.1.1
- **Username:** admin
- **Password:** admin

3. IoT Monitor Rules (Automation Logic)

Server ke IoT Monitor mein door access control ke liye 4 rules ki configuration:

Rule 1: Sahi Card Ki Pehchaan

- **Name:** rfid valid

- **If:** IoT1 | Card ID | == | 1001
- **Then set:** IoT1 | Status | to | Valid

Rule 2: Ghalat Card Ya Bina Card

- **Name:** rfid invalid
- **If:** IoT1 | Card ID | != | 1001
- **Then set:** IoT1 | Status | to | Invalid

Rule 3: Door Ko Unlock Karna

- **Name:** door unlock
- **If:** IoT1 | Status | is | Valid
- **Then set:** IoT0 | Lock | to | Unlock

Rule 4: Door Ko Lock Karna

- **Name:** door lock
- **If:** IoT1 | Status | is | Invalid
- **Then set:** IoT0 | Lock | to | Lock