

INDEX

Note: Page numbers followed by *f* indicate figures, and *t* indicate tables.

A

- Active debris removal (ADR)
 - description, 1
 - manipulator, 2–7
 - multi-space tethers, 10–13
 - single space tether, 8–10
 - tentacles, 2
- Adaptive and robust target capture controller (ARTC)
 - capture component, 258
 - error function, 257
 - Lyapunov function, 259
 - NN, 257
 - system parameters, 256
 - tracking errors, 256
 - trajectory tracking, 262, 263*f*
- Aerospace Dual-Arm Manipulator (ADAM), 7
- Algebraic Riccati equation, 215
- Approach control
 - actuator assignment, 169*t*
 - actuator configuration, 167–168, 168*f*
 - attitude controller, 177–178
 - attitude model, 168–169
 - bead model, 166, 166*f*
 - close-loop adaptive controller, 175–177
 - noncooperative target detection and tracking, 165–166
 - numerical simulation, 178–181
 - open-loop optimal trajectory, 172–175
 - rendezvous control, 165–166, 167*f*
 - scheme, 172, 173*f*
 - trajectory model, 170–171
- Approach trajectory model, 172
- ASTRO, 5
- Attitude controller. *See also* Coordinated orbit and attitude control method
 - approach stage, 177–178
 - design, 131–134
 - stability, 134–136
- Attitude control model, 168–169

- Attitude coordinated controller design, 223–226
- Attitude dynamic model, 188–189, 219–220, 278–279
 - design of mechanism, 217–219
 - task description, 222–223
- Autonomous rendezvous and docking (ARVD), 75
- Aviospace, 2
- Azimuth angles, calculation theory, 105–106

B

- Bead model, 27
 - anchor point motion, 32
 - bead mass, 32
 - configuration, 29*f*
 - C–W equations, 29–31
 - Hook's law, 30–31
 - mass point motion, 30–31
 - platform coordinate system, 29–30, 30–31*f*
 - tether deployment, 31
- Bias momentum approach, 245–246
- Body frame, 148
- Boundary control, 215

C

- Camera coordinate system (CCS), 105, 106*f*
- Capstan, 45–46, 46*f*, 61–62
- Carnot energy loss term (CELT), 61–64
- Chebyshev polynomial, 183–184
- Circular object detection method
 - arc support region, 102–104
 - circle equation and parameters, 104–105
- Classical string theory, 148–149
- Closed-loop control law, 158–159
- Closed-loop control system, 158–159
 - tracking errors, 162–163, 162*f*
- Close-loop adaptive controller, 175–177
- Close-range detectors, 77
- Continuum model, 146

Control force
 optimal approaching trajectory, 234*f*
 in tether coordinate frame, 211*f*
 thrusters, 211–213*f*, 237*f*

Controller. *See* Coordinated controller

Optimal coordinated controller

Control torque
 releasing motor, 210*f*
 tethers, 242*f*
 thrusters, 242*f*

Coordinated controller
 attitude control fuel consumption, 243*f*
 attitude coordinated, 223–226
 block diagram of, 232*f*, 288, 288*f*
 configuration of mechanism, 234*t*
 coordinated tracking, 226–232
 fuel consumption, 294–296, 296*f*
 numerical simulation, 233–243
 orbit control fuel consumption, 238*f*
 parameter identification, 283–284
 parameter optimization, 287–288
 switching conditions, 287
 tether tension, 284–285
 thruster controller design, 285–287
 tracking control of position, 235*f*
 tracking errors of position, 235*f*

Coordinated control mechanism, 217–218
 gripper, 218*f*
 tether reel mechanism, 218*f*

Coordinated coupling control strategy, 193
 attitude control torque, 208*f*
 control diagram, 198*f*
 operation robot, thrusters layout of, 197
 optimal trajectory planning, 193–197

Coordinated orbit and attitude control
 method
 attitude control torque, 143*f*
 control diagram, 127, 127*f*
 Fuzzy PD control force, 140, 141*f*
 orbit control force, 128–131
 PD controller, 131
 process steps, 127–128
 reaction wheels angular velocity, 143*f*
 relative attitude angle, 142*f*
 thruster force comparison, 138–140, 139–140*f*

Coordinated tracking controller design, 226–232

Coupling dynamics modeling
 attitude model, 188–189
 body frame, 148
 Hamiltonian theory, 149–152
 inertial frame, 147
 mathematical discretization, 152–157
 orbital frame, 148
 releasing model, 184–187
 6-DOF model, 192–193
 TSR system, 147, 148*f*

C–W equations, 29–31

D

Deutsche Orbital Servicing Mission (DEOS), 6–7
 sensor arrangements, 75

Dynamics model, 193–194.
 See also Coupling dynamics modeling
 of target, 252
 of TSR, 248–252

Dynamic template strategy, 111

E

Energy optimal performance index, 126

Engineering Test Satellite VII (ETS-VII), 3–5, 5*f*

Euler angle, 279
 Oxyz, 249
 of target attitude during capture, 272*f*
 of three-axis attitude, 292, 292*f*

F

Far-range detectors, 77

Fault-tolerant nonlinear control design, 215–216

FREND, 5–6

Fuzzy decision-making method, 183

Fuzzy PD controller, 131

G

Gauss numerical integration method, 71

Gauss pseudospectral method, 122, 125, 131, 174–175

German ROTEX, 3, 4*f*

Global polynomial, 121, 174–175, 183–184
Greedy Snake algorithm, 82, 88, 94, 96, 101

Gripper

approach stage, 179–181, 180*f*
control torque, 241*f*
coordinated control mechanism, 218*f*
Euler attitude tracking result, 239*f*
Hertz model, 253–254
initial parameters, 234*t*
optimal approaching trajectory, 233*f*
orbit dynamics model, 226
PBIC for, 254, 256*f*
tether tension, 223
trajectory planning, 232–233
TSR, 252–253, 253*f*
velocity, 236*f*

H

Hamiltonian method, 28
deployment motion equation, 64–65
deployment/retrieval mechanism, 61–62, 62*f*
dynamics modeling, 149–152
Gauss numerical integration, 71
implicit differential equations, 72
integration range, 68*f*
interpolation function, 69, 69*f*
iteration equations, 73
Kelvin–Voigt expression, 62
kinetic energy, 63
matrix assembly process, 71, 72*f*
motion equation, 64
nondimensional variable, 68
potential energy, 63
retrieval motion equation, 66
stress–strain equation, 62–63
system configuration, 60–61, 61*f*
TSRS motion, 67
Hertz model, 253–254
Hessian matrix, 80, 83
Hill equation, 221
orbit dynamic model, 280
trajectory model, 171
Hook's law
bead model, 30–31
hybrid unit method, 37–38
Ritz method, 33*f*

Hp-adaptive pseudospectral method, 146–147, 158

Hybrid unit method

deployment point, 36–37
disadvantages, 36
Hook's law, 37–38
hybrid point, 38
motion equations, 37
stress boundary condition, 37

I

Image sensor's imaging model, 106*f*
Impact forces, 262–270, 268–270*f*
Inertial frame, 147
Inline angle, 79, 79*f*
Interferential torque, 128, 130, 141*f*

J

Japanese ETS-VII, 3–5, 5*f*
Japanese Space Research Centre, 189–190
Japan's Aerospace Dual-Arm Manipulator (ADAM), 7

K

Kelvin–Voigt expression, 62
Kevlar tether, 277
KLT algorithm, 81, 86–87

L

Lagrange's equations, 251
Least square integrated predictor, 109–111
Legendre polynomial, 183–184
Line-support region, 102
Long-distance optimal trajectory planning, 183–184
Lumped mass model, 146
Lyapunov function, 201, 224, 259, 286
Lyapunov stability theory, 201

M

Mobile tether attachment points
attitude dynamics model, 216–223
boundary control, 215
coordinated controller, 223–232
numerical simulation, 232–243
off-set control strategy, 215
orbit dynamic model, 217–219, 221

- Mobile tether attachment points (*Continued*)
 - position of, 240*f*
 - trajectory of, 240*f*
- Modified Rodrigues parameter (MRP), 219, 222–223
- Monocular real-time robust feature tracking (MRRFT)
 - adaptive features updating strategy, 89–91
 - detector-descriptor scheme, 80
 - DOF motion platform, 92–93, 93*f*
 - feature extraction, 82–86
 - feature matching algorithm, 86–88
 - object precise location, 88–89
 - performance, 95, 95*f*
 - point detectors and descriptors, 80–81
 - qualitative analysis, 99–101
 - quantitative comparisons, 95–99
 - satellite model, 92, 92*f*
 - SIFT *vs.* SURF, 79–80
 - target precise location, 94, 94*f*
 - tracking sequences, 94–95, 94*f*
 - tracking types, 80
- Multiple impedance control (MIC)
 - algorithm, 246–247
- Multi-space tethers
 - attitude control, 12
 - description, 10–11
 - dynamics and control, 11–12
 - structure and configuration, 12–13

N

- Newton-Euler method, 28
 - capstan, 45–46, 46*f*
 - deployment and retrieval equations, 45, 47
 - deployment and retrieval mechanisms, 44–45, 45*f*
 - discretization of mathematical model, 58–59
 - flexible tether, 40–41
 - ill-conditioned characteristic, 49
 - infinitesimal segment, force analysis, 41–42, 41*f*
 - integration equation, 50–51
 - linear interpolation, 51, 51*f*
 - mathematical model, 41–44
 - node insertion, 59, 59*f*
 - node deletion, 60*f*
 - orbit coordinate system, 39–40*f*
 - STRS discretization, 53–55
 - terminal device, force analysis, 42, 42*f*
 - tether motion, 48–49, 48*f*
 - tether segments, 56–57, 56*f*
 - trapezoid formula, 51
 - Nonlinear programming (NLP), 194–195, 227–229
 - Normalized SAD (NSAD), 107
- ## O
- OctArm, 2
 - Off-set control strategy, 14–16, 215, 245
 - On-orbit service (OOS), 2–3, 145, 183
 - Open-loop optimal trajectory
 - control inputs, 179*f*
 - gripper attitude, 172
 - objectives, 174
 - optimal control problem, 174–175
 - pseudospectral method, 174–175
 - TSR approach trajectory, 172
 - Operation robot, 183
 - angular velocity, 209*f*
 - angular velocity vector, 131–132
 - attitude angle, 207*f*
 - attitude angular velocity, 208*f*
 - attitude dynamic equation, 132
 - in-plane angle, 204*f*
 - optimization parameters, 137*t*
 - out-of-plane angle, 205*f*
 - relative attitude quaternion kinematics equation, 131–132
 - relative trajectory, 204*f*
 - releasing trajectory, 203*f*
 - thrusters layout, 197, 197*f*
 - trajectory comparison, 138*f*
 - Optimal approaching trajectory, 193–197
 - control force, 234*f*
 - TSR, 183–184, 227–228, 233
 - Optimal coordinated controller
 - classical methods, 146
 - closed-loop controller, 158–159
 - hp-adaptive pseudospectral method, 158
 - minimum-fuel problem, 157
 - numerical simulation, 159–163

Optimal trajectory tracking. *See* Trajectory optimization method

Orbital frame, 148

Orbit control method. *See* Coordinated orbit and attitude control method

Orbit coordinate system, 39–40*f*

Orbit dynamic model, 221
design of mechanism, 217–219
postcapture attitude control, 280

OXYZ, 40, 247–248
Euler angle, 249

P

Phoenix program, 6

P-KLT algorithm, 87–88

Position-based impedance control (PBIC), 254–255, 256*f*

Postcapture attitude control
attitude dynamics model, 278–279
coordinated controllers, block diagram of, 288, 288*f*
dynamic analysis, 280–281
numerical simulation, 289–298
orbit dynamic model, 280
parameter identification, 283–284
parameter optimization, 287–288
switching conditions, 287
tether tension, 284–285
thruster controller design, 285–287

Potential energy, 63, 250

Pseudospectral method, 121, 125, 183–184, 233. *See also* Gauss pseudospectral method
control law, 161*f*
open-loop optimal trajectory, 174–175

R

Reel
motor mechanism, 189–190
rotating angle, 206*f*
rotating angular velocity, 207*f*

Releasing dynamic model, 184–187

Retinal coordinate system (RCS), 105–106

Ritz method
differential equations, 34–35
element acceleration, 32–33, 33*f*
Hook's law, 33*f*

motion equations, 33–34
numerical integration, 35
tension force projection, 33

Robotic sensing system
inline angle, 79, 79*f*
measurement information, 78*t*
sensor types, 76
task flow, visual perception system, 78–79, 79*f*
vision-based measurements, 76
visual perception system construction, 77, 77*f*

Robot Technology Experiment (ROTEX), 3, 4*f*

Rod model, 146

S

Scale-invariant feature transform (SIFT), 80, 83, 84*f*

SEDS project, 189–190

Servoing control system
design, 113
experimental set-up, 113
qualitative analysis, 113–114
quantitative comparisons, 114–117

SIFT. *See* Scale-invariant feature transform (SIFT)

Single space tether
artificial gravity, 8
attitude stabilization, 9–10
space transportation, 8–9

6-DOF coupled dynamics model, 192, 198

Sliding mode controller, 286

Sliding mode control method, 224, 230

SNOPT optimization algorithm, 196–197, 229

Spacecraft for the Universal Modification of Orbits (SUMO), 5–6, 6*f*

Space debris micro-remover (SDMR), 7

Space free-flying robots (SFFR), 246–247

Space manipulator, 2–7

Space tentacles, 2

Space tether
control force, 138*f*
endpoint, 28
interferential torque, 141*f*
kinetic energy of, 250

Space tether (*Continued*)

- PD controller, 201
- releasing length, 205*f*
- releasing mechanism, 190*f*
- tension force, 209*f*
- velocity comparison, 206*f*

SUMO. *See* Spacecraft for the Universal Modification of Orbits (SUMO)

- SURF, 80
- comparative diagram, 83, 84*f*
 - description, 83–85
 - modified, 85–86

- Switching conditions, 287
- optimal values of, 289, 290*t*

T

Tait-Bryan angle derivation, 169

Target attitude, 271, 272*f*

Target capture control

- adaptive and robust control law, 257
- attitude of TSR, 262, 264*f*
- capture component, 253, 253*f*
- dynamic collision process, 246–247
- dynamic modeling, 247–254, 248*f*
- error function, 262, 267*f*
- Euler angle, 271, 272*f*
- impact forces, 262–270, 268–270*f*
- impact torques, 270–271, 270*f*
- impedance control, 254–255
- numerical simulation, 261–272
- parameters, 261, 262*t*
- position change of target, 271, 273*f*
- space tether, 262, 265–266*f*
- target attitude, 271, 272*f*
- TC *vs.* ARTC, 262, 263*f*
- tracking errors, 262, 264–266*f*
- TSR's gripper, 252–253, 253*f*

Target Collaborativize (TAKO), 2

Target tracking system. *See also* Monocular real-time robust feature tracking

(MRRFT)

- flow diagram, 91*f*

Taylor's expansion formula, 250

Template matching, 107–109

Tentacles, 2

Tethered space robot (TSR), 13–14, 14*f*

- angular velocity, 239*f*

- capture and post-capture phase, 17
- coordinate frame, 185*f*
- coupled dynamics model, 198
- deorbiting phase, 17
- MRP attitude tracking, 238*f*
- operational robot, 18–19, 18*f*
- optimal approaching trajectory, 227–228, 233

- optimal trajectory planning, 183–184
- orbit design, 19–21
- release and retrieval phase, 14–17
- releasing dynamic model, 184–185
- 6-DOF coupled dynamics model, 192
- target approaching phase, 217*f*
- target capture, 276–277, 277*f*

Tethered space satellite system (TSS), 165–166

Tethered subsystem, 184

Tether force, 237*f*

Tether reeling model, 130–131

Tether releasing mechanism

- coordinated coupling control strategy, 193–201
- coupling dynamic models, 184–193
- model of, 189–192
- numerical simulation, 201–212
- operation robot, 183

Tethers

- attitude interference torque, 210*f*
- control torque, 242*f*
- lengths of, 241*f*
- multi-space, 10–13
- single space, 8–10

Tether tension, 223, 226, 280, 296*f*

- coordinated controller, 282, 284–285
- linear velocity changes, 296–298, 297*f*
- pitch and yaw angles, 284–285
- position changes, 296–298, 297*f*
- torques of, 294, 295*f*

Tether vector, 281

Three-axis angular velocity, 292, 293*f*

Three-axis attitude, 290–292, 291–292*f*

Thruster, 233

- control commands, for coordinated control, 294, 294*f*
- control force, 237*f*
- controller design, 285–287

control torque, 242*f*
 Tracking errors, 262, 264*f*
 Trajectory model, approach stage, 170–171
 Trajectory optimization method, 183
 description, 121
 energy optimal performance index, 126
 fuel saving, 122–123
 Gauss quadrature, 125–126
 Lagrange interpolation, 125
 numerical simulation, 136–143
 path constraints, 124
 performance index, 124
 PID, 122–123
 reference frames, 123–124, 123*f*

relative dynamics, 126
 thruster force comparison, 138–140,
 139–140*f*
 Transformation matrix, 278–279, 281
 TSR. *See* Tethered space robot (TSR)

V

Visual servoing controller, 112–113

W

World coordinate system (WCS), 105–106

Y

YES2 project, 189–190