

 Online Flex Compiler IDE

Stop Execution

Download

Search

Login

New Project

1

%{

2

#include<stdio.h>

3

%}

4

5

%%

6

7

[a-zA-Z]+ { printf("WORD : %s\n", yytext); }

8

[0-9]+ { printf("NUMBER : %s\n", yytext); }

9

\n { }

10

. { printf("SPECIAL CHARACTER : %s\n", yytext); }

11

12

%%

13

14

int yywrap()

15

{

16

return 1;

17

}

18

19

int main()

20

{

21

printf("Enter Input:\n");

22

yylex();

23

return 0;

24

}

Want me to explain code logic?

Explain code

Not Now

Input/Output

API

Language version: 2.6.4

Interactive Mode

Input arguments

Output

Generated files

Enter Input:

1

NUMBER : 1

|

 Online Flex Compiler IDE

Stop Execution

Groovy

Login

New Project

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

```
%{
#include<stdio.h>
%}

%%

[0-9]{10}  { printf("Valid Mobile Number\n"); }
.*        { printf("Invalid Mobile Number\n"); }

%%

int yywrap()
{
    return 1;
}

int main()
{
    printf("Enter Mobile Number: ");
    yylex();
    return 0;
}
```

Want me to explain code logic?

Explain code

Not Now

Input/Output

API

Language version:

2.5.4

Interactive Mode

Input arguments

Output

Generated files

Enter Mobile Number: 0987654321

Valid Mobile Number

|



New Project

flex Online Flex Compiler IDE

Stop Execution

PARI/GP

Login

```
1  %{
2  #include<stdio.h>
3  %{
4
5  %%
6
7  "int"|"float"|"char"|"double"|"void" { printf("Keyword : %s\n",yytext); }
8  [a-zA-Z_][a-zA-Z0-9_]* { printf("Identifier : %s\n",yytext); }
9  [0-9]+ { printf("Number : %s\n",yytext); }
10 [{}();,+=/*-~] { printf("Symbol : %s\n",yytext); }
11 [ \t\n] ;
12 . { printf("Unknown : %s\n",yytext); }
13
14 %%
15
16 int yywrap()
17 {
18     return 1;
19 }
20
21 int main()
22 {
23     printf("Enter Program:\n");
24     yylex();
25     return 0;
26 }
```

Input/Output

API

Language version: 26.4

Interactive Mode

Input arguments

Output

Generated files

Enter Program:
qwert
Identifier : qwert
|

 New Project

flex Online Flex Compiler IDE

Stop Execution

 Clojure



 Login

```
1  %{
2  #include<stdio.h>
3  %}
4
5  %%
6
7  [a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z][a-zA-Z]+
8  {
9      printf("Valid Email\n");
10 }
11
12 .*
13 {
14     printf("Invalid Email\n");
15 }
16
17 %%
18
19 int yywrap()
20 {
21     return 1;
22 }
23
24 int main()
25 {
26     printf("Enter Email: ");
27     yylex();
28     return 0;
29 }
```

 Input/Output



API

Language version: 2.6.4



Interactive Mode



Input arguments

Output

Generated files

Enter Email: abc@gmail.com

valid email

Debugging



[flex](#) Online Flex Compiler IDE

Stop Execution

```

1  %{
2  #include <stdio.h>
3  %}
4
5  %%
6
7  https?:\\\/\\\/[a-zA-Z0-9-._\\-]+    { printf("Valid URL\n"); }
8
9  .*                                  { printf("Invalid URL\n"); }
10
11  %%
12
13  int yywrap()
14  {
15      return 1;
16  }
17
18  int main()
19  {
20      printf("Enter URL: ");
21      yylex();
22      return 0;
23  }

```

Want me to explain code logic?

Explain code Not Now

Input/Output

Language version: 2.6.4

Interactive Mode

Input arguments

Output Generated files

```
Enter URL: abc.com
Invalid URL
```

⋮ New Project ⋮

flex Online Flex Compiler IDE

Stop Execution ⚙

🔥 Elixir



👤 Login

```
1 %{
2 #include <stdio.h>
3 %{
4
5 %%
6
7 http:\\\\[a-zA-Z0-9.-]+ { printf("Valid URL\n"); }
8 https:\\\\[a-zA-Z0-9.-]+ { printf("Valid URL\n"); }
9
10 .* { printf("Invalid URL\n"); }
11
12 %%
13
14 int yywrap()
15 {
16     return 1;
17 }
18
19 int main()
20 {
21     printf("Enter URL: ");
22     yylex();
23     return 0;
24 }
```

Want me to explain code logic?

Explain code

[Not Now](#)

🖥 Input/Output



⬆ API

Language version:

2.6.4



Interactive Mode ⓘ



Input arguments

Output

Generated files

Enter URL: www.asdf.com
Invalid URL