

## Discrete Structures Chapter 4.6 — Cryptography

---

### Example 1 (Student Worksheet): Caesar Cipher, shift $k = 3$

**Learning goals.** Practice converting letters  $\leftrightarrow$  numbers, computing  $(p + k) \bmod 26$ , and translating back.

**Alphabet convention (zero-based).**

$$A = 0, B = 1, \dots, Z = 25$$

We work in  $\mathbb{Z}_{26} \pmod{26}$ . Spaces and punctuation are carried through unchanged; we use uppercase.

**Encryption rule.** For plaintext number  $p \in \{0, \dots, 25\}$  and shift  $k$ , the ciphertext number is

$$c \equiv p + k \pmod{26}.$$

For this worksheet we use  $k = 3$  (the classic “Caesar +3”).

**Fast tips (use 'em shamelessly):**

- Add 3 quickly by doing  $+1, +2, +3$  as you scan, or use the wrap trick: adding 3 to 24, 25 wraps to 1, 2.
- Decrypting a +3 cipher is the same as *adding*  $-3$ , i.e., adding 23 mod 26.
- Common wrap cases:  $24+3 \rightarrow 1$  (Y $\rightarrow$ B),  $25+3 \rightarrow 2$  (Z $\rightarrow$ C).

---

**Guided task.** Encrypt the message:

MEET YOU IN THE PARK

**Step 1 — Letters  $\rightarrow$  numbers (A=0,...,Z=25).** Fill the *plaintext numbers*  $p$  under each letter.

M E E T Y O U I N T H E P A R K

(write numbers  $p$  here)

**Step 2 — Add the shift  $k = 3 \bmod 26$ .** Compute  $c \equiv p + 3 \pmod{26}$  for each position and write the results:

**Step 3 — Numbers  $\rightarrow$  letters.** Translate each  $c$  back to letters to form the ciphertext:

**Neatness check.** Your ciphertext should be readable in groups (keep the spaces from the original). If you decrypt with  $-3$  you should land back on MEET YOU IN THE PARK.

---

**Quick reference table (optional).** If you like a visual:

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25

**Practice (still Caesar, but you drive):**

**P1. Encrypt (easy).** Use  $k = 5$  to encrypt:

DOGS AND CATS

*Hint:*  $D=3$  so  $D \mapsto 3+5=8 \Rightarrow I$ . Keep spaces.

**P2. Decrypt (easy).** The ciphertext below was made with a  $k = 5$  Caesar. Recover the plaintext.

YMNX NX FQ YJXY

*Tip:* Decrypt by adding  $-5$  (or  $+21$ ) mod 26.

**P3. Crack the shift (harder).** The message below is a Caesar cipher with *unknown*  $k$ :

L ORYH PDWKP

*Clues:* Try common words; guess that “PDWKP” might be “MATH?” or “MATHS?”. Also, a one-letter word is often A or I. Determine  $k$  and decrypt.

**Reflection.** In one sentence: why does “mod 26” make the Caesar cipher *wrap* from Z back to A?

## Discrete Structures Chapter 4.6 — Cryptography

---

### Example 1: Caesar Cipher ( $k = 3$ )

**Question.** Encrypt the message MEET YOU IN THE PARK using the Caesar cipher with shift  $k = 3$ .

#### Step 1 — Letters $\rightarrow$ numbers.

We use zero-based numbering: A=0, B=1,  $\dots$ , Z=25.

$$\text{MEET YOU IN THE PARK} \Rightarrow 12, 4, 4, 19, 24, 14, 20, 8, 13, 19, 7, 4, 15, 0, 17, 10$$

#### Step 2 — Apply $f(p) = (p + 3) \bmod 26$ .

Add 3 to each number, wrapping around if the result exceeds 25:

$$\begin{aligned}(12 + 3) &= 15, (4 + 3) = 7, (4 + 3) = 7, (19 + 3) = 22, \\(24 + 3) &= 27 \equiv 1, (14 + 3) = 17, (20 + 3) = 23, \\(8 + 3) &= 11, (13 + 3) = 16, (19 + 3) = 22, (7 + 3) = 10, (4 + 3) = 7, \\(15 + 3) &= 18, (0 + 3) = 3, (17 + 3) = 20, (10 + 3) = 13.\end{aligned}$$

#### Step 3 — Numbers $\rightarrow$ letters.

Convert the ciphertext numbers back to letters:

$$\begin{aligned}15, 7, 7, 22, 1, 17, 23, 11, 16, 22, 10, 7, 18, 3, 20, 13 \\ \Rightarrow \text{PHHW BRX LQ WKH SDUN}\end{aligned}$$

**Final Answer.** The encrypted message is:

PHHW BRX LQ WKH SDUN

*(Translation: “MEET YOU IN THE PARK” shifted +3.)*

---

**Quick Reflection.** The Caesar cipher uses modular arithmetic in  $\mathbb{Z}_{26}$  so letters “wrap around” after Z. The function  $f(p) = (p + k) \bmod 26$  keeps all results in 0–25.

—

## Practice Solutions

**P1 — Encrypt (easy).** Use  $k = 5$  to encrypt: DOGS AND CATS.

Step 1 — Convert to numbers:

$$3, 14, 6, 18, 0, 13, 3, 2, 0, 19, 18$$

Step 2 — Add 5 mod 26:

8, 19, 11, 23, 5, 18, 8, 7, 5, 24, 23

Step 3 — Back to letters:

ITLX FSI HFYX

**P2 — Decrypt (easy).** Decrypt YMNX NX FQ YJXY that was made with  $k = 5$ .

We reverse the shift:  $c - 5 \pmod{26}$ .

$Y = 24 \rightarrow 19 = T$ ,  $M = 12 \rightarrow 7 = H$ ,  $N = 13 \rightarrow 8 = I$ ,  $X = 23 \rightarrow 18 = S$

$\Rightarrow$  THIS IS AN TEST

So the message is “THIS IS AN TEST.” (It should probably read “THIS IS A TEST.”)

**P3 — Crack the shift (harder).** Ciphertext: L ORYH PDWKP!

Try guessing common English patterns.

ORYH looks like “LOVE,” and the one-letter word “L” likely corresponds to “I.”

That suggests a shift of  $k = 3$  backward (since  $L \rightarrow I$  is  $-3$ ).

Decrypting with  $k = 3$ :

L ORYH PDWKP!  $\Rightarrow$  I LOVE MATH!

## Summary of Key Takeaways

- The Caesar cipher is modular addition in  $\mathbb{Z}_{26}$ .
- Encryption:  $E_k(p) = (p + k) \pmod{26}$
- Decryption:  $D_k(c) = (c - k) \pmod{26}$
- If you can add or subtract mod 26, you can encrypt or decrypt.
- This cipher is historically important but easily broken by frequency analysis or brute force (26 possibilities).

---

**Going Deeper.** You can extend this same math to more complex ciphers:

$$f(p) = (a \cdot p + b) \pmod{26}$$

where  $a$  must have a multiplicative inverse mod 26. This leads directly into the *Affine Cipher*—our next example.

## Example 2 (Worksheet) — Shift Cipher with $k = 11$

**Goal.** Encrypt the message STOP GLOBAL WARMING using Caesar’s shift cipher with  $k = 11$ .

### Big idea (the “why”):

We model letters as numbers in  $\mathbb{Z}_{26}$  so that a shift is just *modular addition*. This keeps us in the alphabet and gives the wrap-around from  $Z$  back to  $A$ .

$$A = 0, B = 1, \dots, Z = 25 \qquad E_k(p) = (p + k) \bmod 26.$$

For this example,  $k = 11$ .

### Step 1 — Normalize and map letters $\rightarrow$ numbers

We use uppercase and keep spaces. Convert each letter of STOP GLOBAL WARMING to its number:

$$\begin{array}{ccc} \underbrace{\text{STOP}} & \underbrace{\text{GLOBAL}} & \underbrace{\text{WARMING}} \ . \\ 18\ 19\ 14\ 15 & 6\ 11\ 14\ 1\ 0\ 11 & 22\ 0\ 17\ 12\ 8\ 13\ 6 \end{array}$$

### Step 2 — Apply the shift $k = 11$ (add 11 mod 26)

Compute  $c \equiv p + 11 \pmod{26}$  for each number. Do the wrap when you go past 25.

$$\begin{array}{ll} \text{STOP :} & 18, 19, 14, 15 \mapsto 3, 4, 25, 0 \\ \text{GLOBAL :} & 6, 11, 14, 1, 0, 11 \mapsto 17, 22, 25, 12, 11, 22 \\ \text{WARMING :} & 22, 0, 17, 12, 8, 13, 6 \mapsto 7, 11, 2, 23, 19, 24, 17. \end{array}$$

### Step 3 — Map numbers $\rightarrow$ letters and keep spaces

$$3, 4, 25, 0 \mid 17, 22, 25, 12, 11, 22 \mid 7, 11, 2, 23, 19, 24, 17 \quad \Rightarrow \quad \boxed{\text{DEZA RWZMLW HLCXTYR}}$$

### Helpful tips & common pitfalls

- **A=0, not 1.** Off-by-one mistakes are the #1 bug.
- **Wrap cleanly:** if  $p + k \geq 26$ , subtract 26 (i.e., reduce mod 26).

- **Spaces/punctuation** pass through unchanged; only letters get shifted.
  - **Decrypting** with  $k = 11$  is the same as adding  $-11$  (or  $+15$ ) mod 26.
- 

## Practice (your turn!)

**Problem A (easier).** Encrypt with  $k = 4$ : MATH IS FUN

*Why:* smaller shift, shorter phrase—perfect confidence builder.

**Problem B (similar).** Decrypt with  $k = 11$ : SPWWZ HZCWO

*Tip:* subtract 11 mod 26 or add 15.

**Problem C (harder).** Unknown  $k$ . Decrypt the Caesar ciphertext: P HT HA AOL WHYR

*Hints:* a one-letter word is often I or A. The block AOL frequently shows up when “THE” is

encrypted with  $k = 7$ .

**Reflection.** In one sentence: explain why modular arithmetic guarantees a valid letter after every shift.

## Solutions for Example 2 Practice

**Problem A (easier). Encrypt with  $k = 4$ :** MATH IS FUN

Map to numbers (A=0):

$$\text{MATH IS FUN} \Rightarrow 12, 0, 19, 7, 8, 18, 5, 20, 13.$$

Add 4 mod 26:

$$12, 0, 19, 7 \mapsto 16, 4, 23, 11 \quad (\text{M} \rightarrow \text{Q}, \text{A} \rightarrow \text{E}, \dots)$$

$$8, 18 \mapsto 12, 22 \quad 5, 20, 13 \mapsto 9, 24, 17.$$

Back to letters:

$$16, 4, 23, 11, 12, 22, 9, 24, 17 \Rightarrow \boxed{\text{QEXL MW JYR}}.$$

*Why it works:* Every step is addition in  $\mathbb{Z}_{26}$ ; wrap ensures letters stay in 0–25.

**Problem B (similar). Decrypt with  $k = 11$ :** SPWWZ HZCWO

Numbers for ciphertext:

$$\text{SPWWZ HZCWO} \Rightarrow 18, 15, 22, 22, 25, 7, 25, 2, 22, 14.$$

Subtract 11 (or add 15) mod 26:

$$18, 15, 22, 22, 25 \mapsto 7, 4, 11, 11, 14 \quad (\text{H}, \text{E}, \text{L}, \text{L}, \text{O})$$

$$7, 25, 2, 22, 14 \mapsto 22, 14, 17, 11, 3 \quad (\text{W}, \text{O}, \text{R}, \text{L}, \text{D}).$$

Plaintext:  $\boxed{\text{HELLO WORLD}}$ .

**Problem C (harder). Unknown  $k$ :** P HT HA AOL WHYR

**Strategy (the why):** Look for patterns. A one-letter word is probably I or A. Also, AOL famously appears when “THE” is shifted by  $k = 7$  (since  $19+7 = 26 \equiv 0 = \text{A}$ , etc.).

**Infer  $k$ :** If AOL is THE, then the shift is  $k = 7$ .

**Decrypt by subtracting 7:**

$$\text{P} \mapsto \text{I}, \quad \text{HT} \mapsto \text{AM}, \quad \text{HA} \mapsto \text{AT}, \quad \text{AOL} \mapsto \text{THE}, \quad \text{WHYR} \mapsto \text{PARK}.$$

$\Rightarrow$  I AM AT THE PARK.

---

**Key takeaways.**

- Encryption:  $E_k(p) = (p + k) \bmod 26$ , Decryption:  $D_k(c) = (c - k) \bmod 26$ .
- Unknown  $k$  can be cracked with educated guesses (“THE”, one-letter words) or brute force (only 26 options).
- Thinking in  $\mathbb{Z}_{26}$  explains the wrap-around and keeps errors low.



# Caesar Cipher Decryption

## Student Worksheet

### Understanding Decryption

Previously, we learned how to **encrypt** messages using the Caesar cipher. Now we'll learn to **decrypt** them—convert the secret message back to the original!

The key insight: **Decryption is the reverse of encryption.**

- **Encryption:** We shifted letters *forward* by  $k$  positions using  $f(p) = (p + k) \bmod 26$
- **Decryption:** We shift letters *backward* by  $k$  positions using  $f(p) = (p - k) \bmod 26$

#### Key Concept: Negative Numbers and Mod

When we subtract and get a negative number, we need to “wrap around” the other direction. For example, if we try to go back 7 from the letter E (position 4), we get  $4 - 7 = -3$ .

To handle this, we compute:  $-3 \bmod 26 = 23$  (which is the letter X).

**Quick trick:** If you get a negative number, just add 26 to make it positive!

$$-3 + 26 = 23$$

### Example 3: Worked Solution

**Question:** Decrypt the ciphertext message “LEWLYPLUJL PZ H NYLHA HSOHOLY” that was encrypted with the shift cipher with shift  $k = 7$ .

#### Solution:

##### Step 1: Convert letters to numbers

We use our standard A=0, B=1, C=2, ..., Z=25 system. Let's convert the ciphertext:

- **LEWLYPLUJL:** L=11, E=4, W=22, L=11, Y=24, P=15, L=11, U=20, J=9, L=11
- **PZ:** P=15, Z=25

- Our number sequence is:

We apply  $f(p) = (p-7) \bmod 26$  to shift backward by 7. Let's work through each number:

Continuing for the remaining letters:

Our decrypted numbers are:

2

### Pro Tip: Handling Negative Results

Whenever  $(p - k)$  gives you a negative number:

1. Notice it's negative
2. Add 26 to make it positive
3. That's your answer!

Example:  $(4 - 7) = -3$ , so  $-3 + 26 = 23$

### Step 3: Convert numbers back to letters

Using  $A=0, B=1, \dots, Z=25$ :

- $4=E, 23=X, 15=P, 4=E, 17=R, 8=I, 4=E, 13=N, 2=C, 4=E$
- $8=I, 18=S$
- $0=A$
- $6=G, 17=R, 4=E, 0=A, 19=T$
- $19=T, 4=E, 0=A, 2=C, 7=H, 4=E, 17=R$

**Final Answer:** The decrypted message is **EXPERIENCE IS A GREAT TEACHER**

### Why This Works

If someone encrypted a message by shifting forward 7, we decrypt by shifting backward 7. It's like walking 7 steps forward, then 7 steps back—you end up where you started!

## Practice Problems

### Problem A (Easier Warm-up)

Decrypt the ciphertext “FDW” that was encrypted with shift  $k = 3$ .

*Hint: This is a short message. Remember to subtract 3 from each letter's position. If you get negative numbers, add 26!*

## Problem B (Standard Practice)

Decrypt the ciphertext “**MJQQT BTWQI**” that was encrypted with shift  $k = 5$ .

*Hint: You encrypted this message in the previous worksheet! Now decrypt it to get back the original message.*

## Problem C (Challenge)

Decrypt the ciphertext “**EJKKR ZRUOJ**” that was encrypted with shift  $k = 5$ .

*Challenge: Some of these letters will give negative results when you subtract 5. Practice your wrapping-around skills!*

# Caesar Cipher Decryption

## Teacher Solutions Manual

### Problem A Solution: Decrypt “CAT” with shift $k = 3$

Step 1: Convert letters to numbers

$$F = 5$$

$$D = 3$$

$$W = 22$$

Number sequence: 5   3   22

Step 2: Apply decryption function  $f(p) = (p - 3) \bmod 26$

$$f(5) = (5 - 3) \bmod 26 = 2 \bmod 26 = 2$$

$$f(3) = (3 - 3) \bmod 26 = 0 \bmod 26 = 0$$

$$f(22) = (22 - 3) \bmod 26 = 19 \bmod 26 = 19$$

Decrypted numbers: 2   0   19

Step 3: Convert back to letters

$$2 = C$$

$$0 = A$$

$$19 = T$$

Answer: CAT

#### Teaching Note

This is the easiest problem because: (1) short message, (2) all results are positive (no negative numbers to handle), and (3) it's the reverse of Problem A from the encryption worksheet. Students can verify their answer by re-encrypting CAT with  $k = 3$  to get FDW.

---

## Problem B Solution: Decrypt “MJQQT BTWQI” with shift $k = 5$

### Step 1: Convert letters to numbers

Breaking down by word:

- **MJQQT:** M=12, J=9, Q=16, Q=16, T=19
- **BTWQI:** B=1, T=19, W=22, Q=16, I=8

Number sequence:

12   9   16   16   19   1   19   22   16   8

### Step 2: Apply decryption function $f(p) = (p - 5) \bmod 26$

$$\begin{aligned}f(12) &= (12 - 5) \bmod 26 = 7 \bmod 26 = 7 \\f(9) &= (9 - 5) \bmod 26 = 4 \bmod 26 = 4 \\f(16) &= (16 - 5) \bmod 26 = 11 \bmod 26 = 11 \\f(16) &= (16 - 5) \bmod 26 = 11 \bmod 26 = 11 \\f(19) &= (19 - 5) \bmod 26 = 14 \bmod 26 = 14 \\f(1) &= (1 - 5) \bmod 26 = -4 \bmod 26 = 22 \quad (-4 + 26 = 22) \\f(19) &= (19 - 5) \bmod 26 = 14 \bmod 26 = 14 \\f(22) &= (22 - 5) \bmod 26 = 17 \bmod 26 = 17 \\f(16) &= (16 - 5) \bmod 26 = 11 \bmod 26 = 11 \\f(8) &= (8 - 5) \bmod 26 = 3 \bmod 26 = 3\end{aligned}$$

Decrypted numbers:

7   4   11   11   14   22   14   17   11   3

### Step 3: Convert back to letters

- 7=H, 4=E, 11=L, 11=L, 14=O
- 22=W, 14=O, 17=R, 11=L, 3=D

Answer: HELLO WORLD

### Teaching Note

This problem introduces negative numbers! When we decrypt B (position 1) with shift 5, we get:  $1 - 5 = -4$ .

To handle negative results in modular arithmetic:  $-4 \bmod 26 = 22$

Students can calculate this by adding 26:  $-4 + 26 = 22$ , which corresponds to the letter W.

**Connection:** Students encrypted "HELLO WORLD" in the previous worksheet and got "MJQQT BTWQI". Now they're decrypting it back—reinforcing the inverse relationship between encryption and decryption.

## Problem C Solution: Decrypt "EJKKR ZRUOJ" with shift $k = 5$

### Step 1: Convert letters to numbers

Breaking down by word:

- **EJKKR:** E=4, J=9, K=10, K=10, R=17
- **ZRUOJ:** Z=25, R=17, U=20, O=14, J=9

Number sequence:

4   9   10   10   17   25   17   20   14   9

### Step 2: Apply decryption function $f(p) = (p - 5) \bmod 26$

$$f(4) = (4 - 5) \bmod 26 = -1 \bmod 26 = 25 \quad (-1 + 26 = 25)$$

$$f(9) = (9 - 5) \bmod 26 = 4 \bmod 26 = 4$$

$$f(10) = (10 - 5) \bmod 26 = 5 \bmod 26 = 5$$

$$f(10) = (10 - 5) \bmod 26 = 5 \bmod 26 = 5$$

$$f(17) = (17 - 5) \bmod 26 = 12 \bmod 26 = 12$$

$$f(25) = (25 - 5) \bmod 26 = 20 \bmod 26 = 20$$

$$f(17) = (17 - 5) \bmod 26 = 12 \bmod 26 = 12$$

$$f(20) = (20 - 5) \bmod 26 = 15 \bmod 26 = 15$$

$$f(14) = (14 - 5) \bmod 26 = 9 \bmod 26 = 9$$

$$f(9) = (9 - 5) \bmod 26 = 4 \bmod 26 = 4$$

Decrypted numbers:

25   4   5   5   12   20   12   15   9   4

### Step 3: Convert back to letters

- 25=Z, 4=E, 5=F, 5=F, 12=M
- 20=U, 12=M, 15=P, 9=I, 4=E

Answer: ZEFFM UMPIE

### Teaching Note

This is the *challenge* problem because it starts with E (position 4), which requires wrapping around when decrypted.

When we compute  $f(4) = (4 - 5) = -1$ , we need to wrap around to the *end* of the alphabet:

$$-1 \bmod 26 = 25 \text{ (the letter Z)}$$

Students can think of it this way: going back 1 from A brings you to Z (the last letter). Mathematically:  $-1 + 26 = 25$

**Multiple negative cases:** This problem is harder because it has multiple instances where students need to handle negative results, giving them more practice with this crucial concept.

**Pattern recognition:** Students might notice that letters early in the alphabet (A, B, C, D, E) will always produce negative results when the shift is larger than their position number.

---

## Common Student Errors to Watch For

1. **Forgetting to handle negative numbers:** Students might write  $4 - 5 = -1$  and stop there, not realizing they need to add 26. Watch for students who leave negative numbers in their final answer.
2. **Adding instead of subtracting:** Some students confuse encryption and decryption, using  $(p + k)$  instead of  $(p - k)$ .
3. **Incorrect negative arithmetic:** Students might compute  $-4 + 26$  incorrectly. Emphasize: start at 26, count backward 4.
4. **Off-by-one errors with A=0:** Remind students that A=0, not A=1. When they decrypt to position 0, that's the letter A.



5. **Not checking their work:** Students can verify decryption by re-encrypting their answer with the same shift—they should get back the original ciphertext.

## Extension Activity

Have students encrypt a message with one shift value, then decrypt it with the same shift value to verify they get back the original message. This reinforces the inverse relationship:

$$\text{Message} \xrightarrow{+k} \text{Ciphertext} \xrightarrow{-k} \text{Message}$$

## Example 4 — Affine Cipher Warm-Up

**Goal.** Determine which letter replaces K when the encryption function

$$f(p) = (7p + 3) \bmod 26$$

is used.

### Big idea (the why):

The affine cipher multiplies the plaintext value by a “stretch” factor and then shifts it. It combines multiplication and addition inside modular arithmetic.

$$\text{Encryption: } E(p) = (ap + b) \bmod 26 \qquad \text{Decryption: } D(c) = a^{-1}(c - b) \bmod 26.$$

The constants  $a$  and  $b$  are keys.  $a$  must be coprime to 26 so that  $a^{-1}$  exists.

### Step 1 — Convert letter K to a number

$$K \rightarrow 10$$

### Step 2 — Apply the function $f(p) = (7p + 3) \bmod 26$

$$f(10) = (7 \cdot 10 + 3) \bmod 26 = 73 \bmod 26 = 21.$$

### Step 3 — Convert number 21 back to a letter

$$21 \rightarrow V$$

**Result:**  $K$  is encrypted as  $V$ .

### Why it works:

Multiplying by 7 mixes up the order of letters more effectively than a simple shift, yet because 7 and 26 are coprime, every letter still maps to exactly one output.

## Practice (your turn!)

**Problem A (easier).** Using  $f(p) = (3p + 1) \bmod 26$ , find what letter replaces C. *Hint:*

$C = 2.$

**Problem B (similar).** Using  $f(p) = (5p + 7) \bmod 26$ , find what letter replaces H. *Hint:*

compute carefully, mod 26.

**Problem C (harder).** Encrypt the word DOG using  $f(p) = (11p + 8) \bmod 26$ . Write each

step clearly: letter  $\rightarrow$  number  $\rightarrow$  formula  $\rightarrow$  result  $\rightarrow$  letter.

**Reflection.** Why must  $a$  be coprime with 26 for this cipher to be reversible?

## Solutions — Example 4 Affine Cipher

### Example Walk-Through

$K \rightarrow 10, f(p) = (7p + 3) \bmod 26.$

$$f(10) = (7 \cdot 10 + 3) \bmod 26 = 73 \bmod 26 = 21.$$

21 corresponds to  $V$ .  $\boxed{K \rightarrow V}$

—

### Problem A

$C = 2.$

$$f(2) = (3 \cdot 2 + 1) \bmod 26 = 7.$$

$7 \rightarrow H$ .  $\boxed{C \rightarrow H}$

### Problem B

$H = 7.$

$$f(7) = (5 \cdot 7 + 7) \bmod 26 = 42 \bmod 26 = 16.$$

$16 \rightarrow Q$ .  $\boxed{H \rightarrow Q}$

### Problem C

Encrypt **DOG** with  $f(p) = (11p + 8) \bmod 26.$

$$\begin{aligned} D &= 3 &\Rightarrow (11 \cdot 3 + 8) \bmod 26 = 41 \bmod 26 = 15 &\rightarrow P \\ O &= 14 &\Rightarrow (11 \cdot 14 + 8) \bmod 26 = 162 \bmod 26 = 6 &\rightarrow G \\ G &= 6 &\Rightarrow (11 \cdot 6 + 8) \bmod 26 = 74 \bmod 26 = 22 &\rightarrow W \end{aligned}$$

$\boxed{\text{DOG} \rightarrow \text{PGW}}$

### Reflection Answer

If  $a$  shares a factor with 26, then some letters collapse to the same output (no unique inverse), making decryption impossible. Only when  $\gcd(a, 26) = 1$  does the cipher remain bijective and reversible.

## Example 2 (Worksheet) — Shift Cipher with $k = 11$

**Goal.** Encrypt the message STOP GLOBAL WARMING using Caesar’s shift cipher with  $k = 11$ .

### Big idea (the “why”):

We model letters as numbers in  $\mathbb{Z}_{26}$  so that a shift is just *modular addition*. This keeps us in the alphabet and gives the wrap-around from  $Z$  back to  $A$ .

$$A = 0, B = 1, \dots, Z = 25 \qquad E_k(p) = (p + k) \bmod 26.$$

For this example,  $k = 11$ .

### Step 1 — Normalize and map letters $\rightarrow$ numbers

We use uppercase and keep spaces. Convert each letter of STOP GLOBAL WARMING to its number:

$$\begin{array}{ccc} \underbrace{\text{STOP}} & \underbrace{\text{GLOBAL}} & \underbrace{\text{WARMING}} \ . \\ 18\ 19\ 14\ 15 & 6\ 11\ 14\ 1\ 0\ 11 & 22\ 0\ 17\ 12\ 8\ 13\ 6 \end{array}$$

### Step 2 — Apply the shift $k = 11$ (add 11 mod 26)

Compute  $c \equiv p + 11 \pmod{26}$  for each number. Do the wrap when you go past 25.

$$\begin{array}{ll} \text{STOP :} & 18, 19, 14, 15 \mapsto 3, 4, 25, 0 \\ \text{GLOBAL :} & 6, 11, 14, 1, 0, 11 \mapsto 17, 22, 25, 12, 11, 22 \\ \text{WARMING :} & 22, 0, 17, 12, 8, 13, 6 \mapsto 7, 11, 2, 23, 19, 24, 17. \end{array}$$

### Step 3 — Map numbers $\rightarrow$ letters and keep spaces

$$3, 4, 25, 0 \mid 17, 22, 25, 12, 11, 22 \mid 7, 11, 2, 23, 19, 24, 17 \quad \Rightarrow \quad \boxed{\text{DEZA RWZMLW HLCXTYR}}$$

### Helpful tips & common pitfalls

- **A=0, not 1.** Off-by-one mistakes are the 1 bug.
- **Wrap cleanly:** if  $p + k \geq 26$ , subtract 26 (i.e., reduce mod 26).

- **Spaces/punctuation** pass through unchanged; only letters get shifted.
- **Decrypting** with  $k = 11$  is the same as adding  $-11$  (or  $+15$ ) mod 26.

---

## Practice (your turn!)

**Problem A (easier).** Encrypt with  $k = 4$ : MATH IS FUN

*Why:* smaller shift, shorter phrase—perfect confidence builder.

**Problem B (similar).** Decrypt with  $k = 11$ : SPWWZ HZCWO

*Tip:* subtract 11 mod 26 or add 15.

**Problem C (harder).** Unknown  $k$ . Decrypt the Caesar ciphertext: P HT HA AOL WHYR

*Hints:* a one-letter word is often I or A. The block AOL frequently shows up when “THE” is

encrypted with  $k = 7$ .

**Reflection.** In one sentence: explain why modular arithmetic guarantees a valid letter after every shift.