


SLIDE SWITCH MSS(6)(14) SERIES

Miniature Travel & SMT Type (2P2T, 1P4T)



FEATURES

- ※ 1.4mm height
- ※ 2P2T, 1P4T models
- ※ Stroke 1.5mm

APPLICATION

- ※ Remote control
- ※ Consumer electronics
- ※ Instrumentations


SPECIFICATION

Contact Rating	25mA , 24V DC	
Contact Resistance	70mΩ max	
Insulation Resistance	100MΩ min. 100V DC	
Dielectric Strength	100V AC/1 minute	
Operating Force	200±150gf (1.96N±1.47N)	MSS6
	A→B 150±100gf (1.47N±0.98N)	MSS14
	D→C 150±100gf (1.47N±0.98N)	
	B→C 200±150gf (1.96N±1.47N)	
	C→D 200±150gf (1.96N±1.47N)	
	C→B 200±150gf (1.96N±1.47N)	
	B→A 200±150gf (1.96N±1.47N)	
Travel	1.5mm	
Operating Life	10, 000 cycles	
Operating Temp.	-20°C ~ +70°C	
Storage Temp.	-40°C ~ +85°C	

HOW TO ORDER

M S S - - -
 Package:
 T/R=Tape & Reel
 V=RoHS & Lead Free Solderable
 Q=Halogen Free
 Poles-Positions:
 6=2P2T
 14=1P4T

CIRCUIT





PACKAGE



<Tape & Reel>

MSS6: 1400 pcs
 MSS14: 2500 pcs

MSS6



MSS14



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Diptronics:

[MSS6-V-T/R](#) [MSS14-V-T/R](#)