



Innovative Data Solutions

NCIS-Alias™

XML Service Documentation

Version 3.0

Table of Contents

Table of Contents	Error! Bookmark not defined.
1. Overview	5
1.1 IDS WS Requirements	5
1.2 IDS WS URLs	5
1.21 SOAP URL	5
1.22 POST URLs	5
1.3 Testing IDS WS	6
1.4 Sending IDS Requests	6
1.5 Infinity Screening™ Receiver Page	6
1.6 Change Notification	7
1.7 “No Change” Notification	7
2. Products	8
2.1.1 NCIS™ Alias™	8
2.1.2 NCIS™ Alias™ Parameters	8
2.1.3 Infinity Screening™	8
2.1.4 Infininty Screening™ Parameters	8
3. Service Methods	9
3.1.1 GetStatus	9
3.1.2 GetStatus Parameters	9
3.1.3 GetResults	9
3.1.4 GetResults Parameters	9
3.1.5 PlaceOrder	9
3.1.6 PlaceOrder Parameters	9
3.2.1 inputXML Document	9
3.2.2 Subject Parameters Summary	9
3.3 ISUnEnrollBySearchToken	10
3.3.1 ISUnEnrollBySearchToken Parameters	10
3.4 ISEnrollBySearchToken	10
3.4.1 ISEnrollBySearchToken Parameters	10
3.5 ISGetList	10

3.5.1	ISGetList Request Parameters.....	10
3.5.2	ISGetList Response	11
3.6	ISGetScreeningResults	11
3.6.1	ISGetScreeningResults Request Parameters.....	11
3.6.2	ISGetScreeningResults Response	11
3.7	ISGetLastComparison Request Parameters	11
3.8	ISResendErrorPostBacks	Error! Bookmark not defined.
3.8.1	ISResendErrorPostBack Parameters	Error! Bookmark not defined.
4.	ieirequest Schema.....	12
5.	ieiresponse Schema	41
5.1	requestinformation.....	41
5.2	criminal information	45
5.3	addressinformation.....	45
5.4	criminal information	60
6.	Errors.....	79
6.1	Codes and Code Messages.....	79

Date	Description	Author	Version
05/16/18	Change to Non-Conviction Custom Year Filter default value	Jason Wilborn	2.1
09/12/18	Added GroupAddresses Setting	Lee Sheene	2.2
11/05/18	Update IS billing options	Jason Wilborn	2.3
09/04/19	Addition of new error codes	Jason Wilborn	2.4
10/09/19	Addition of new ICE filter setting	Jason Wilborn	2.5
01/13/21	Addition of new error code	Jason Wilborn	2.6
06/21/21	Added ISResendErroredPostBacks method description	Jason Wilborn	2.7
09/09/21	Removed fuzzy SSN filter	Jason Wilborn	2.8
04/01/22	Update to error code text	Jason Wilborn	2.9
01/05/23	Add error code 218	Karan Dilawar	3.0

1. Overview

The Innovative Data Solutions XML Web Service 2.0 ("IDS WS 2.0") allows for the exchange of informational product requests and results between Innovative Data Solutions and its clients over the Internet.

1.1 IDS WS Requirements

In order to use this service, you will need the following:

- Have a valid Innovative Enterprises User ID and Password.
- Have this service enabled for your account. Contact your Account Representative at Innovative Enterprises for more information.
- Develop a solution that will send requests and process IEI response results as defined in this document.

Infinity Screening™ API users that wish to have changes posted to their server must create a receiving page that will accept posts from our server. More information about the receiving page is included in this document.

1.2 IDS WS URLs

1.21 SOAP URL

<https://xml.innovatedatasolutions.com/NatCrimWs/Search.asmx>

1.22 POST URLs

<https://xml.innovatedatasolutions.com/NatCrimWs/Search.asmx/PlaceOrder>

Place an order for an IDS product.

<https://xml.innovatedatasolutions.com/NatCrimWs/Search.asmx/GetStatus>

Retrieve status of an offline order.

<https://xml.innovatedatasolutions.com/NatCrimWs/Search.asmx/GetResults>

Retrieve results of an offline order.

<https://xml.innovatedatasolutions.com/NatCrimWs/Search.asmx/RemoveOrders>

Unenroll subjects from Infinity Screening™.

<https://xml.innovatedatasolutions.com/NatCrimWs/Search.asmx/ISEnrollBySearchToken>

Enroll subjects in Infinity Screening™ with a search-token from a prior search.

<https://xml.innovatedatasolutions.com/NatCrimWs/Search.asmx/ISUnEnrollBySearchToken>

Unenroll subjects from Infinity Screening with a search-token from a prior search.

<https://xml.innovatedatasolutions.com/NatCrimWs/Search.asmx/ISGetList>

Retrieve a list of subjects enrolled in Infinity Screening™.

<https://xml.innovatedatasolutions.com/NatCrimWs/Search.asmx/ISGetScreeningResults>

Retrieve the latest screening results for an Infinity Screening™ subject.

<https://xml.innovatedatasolutions.com/NatCrimWs/Search.aspx/ISGetLastComparison>

Retrieve the latest comparison markup from the last screening.

<https://xml.innovatedatasolutions.com/NatCrimWs/Search.aspx/ISResendErroredPostBacks>

Resend any errored post backs that exist for the Account ID.

1.3 Testing IDS WS

Contact your sales rep when ready to test so they can setup an account.

1.4 Sending IDS Requests

Request

To send search requests, you will need to do the following:

- Create a PlaceOrder XML document with the required elements and attributes for the desired product. (Section 5.1.1).
- Post the XML document along with username and password to the PlaceOrder method (Section 1.2.1)

Response

You will immediately receive an IDS response document (Section 3.2) as a server response. Instant products will return completed results immediately.

Offline products will return a Pending status and can be picked up later using the GetStatus and/or GetResults methods or may be posted to a receiver URL hosted on your server (for select products only).

NOTE: All XML nodes may contain invalid XML characters returned as entities, e.g. "<" will be returned as "<".

1.5 Infinity Screening™ Receiver Page

An Infinity Screening™ receiver page will need to be hosted on your server when you choose to have Infinity Screening™ results posted to you. Five parameters will be posted to your receiver page:

1. Username (string) – this is your IDS XML username
2. Password (string) – this is your IDS XML password
3. Token (string) – the token for the enrolled search
4. IsChanged (boolean) – a “1” or “0” – This will be “1” when a change is detected and “0” when no change is detected.
5. ieiresponse XML document (string) – the ieiresponse document that contains the changes, additions and deletions information.

The receiver page must be secured with at least TLS1.1. Please contact us if you need to use different security protocols.

Alternatively, if you cannot host a receiver page on your server, you can use the `ISGetScreeningResults` to retrieve the latest screening results for a particular enrolled subject.

Please send us the full URL of your receiver page when you are ready to receive notifications.

1.6 Change Notification

When a change is detected after a screening, we will post a change notification to your receiver page. A change notification will contain an `ieiresponse` document that has been modified with an attribute named `isType` that identifies the type of change in the new screening. There are three possible values for the `isType` attribute: `isAdd`, `isChange`, `isDelete`. Any of the XML nodes in the `ieiresponse` document might have an `isType` attribute, but only if it was changed, or if it is new or if it was removed. For example, when a new record appears in the most recent screening, the change notification will contain a record node like `<record id="1234567890XYZ" isType="isAdd">`. Similarly, if a disposition node has changed you may see `<disposition isType="isChange">`. Please refer to the sample change notification `ieiresponse` document *IS Change Notification.xml* as a full example.

1.7 “No Change” Notification

You may opt to receive “No Change” notifications, for your Infinity Screenings. A “No Change” notification can be posted to your receiver page when no changes are found after a screening.

“Send ‘No Change’ notifications” setting – this is an option we can set on your behalf so that you can choose whether or not you want to receive notifications of “No Change”. When disabled, you will not receive notifications of “No Change” after a screening is performed and you will only receive notifications when changes are detected. When enabled, you will receive notifications at your receiver page that no change has been found after a screening was performed in addition to notifications when changes are detected.

2. Products

2.1.1 NCISTM AliasTM

NCISTM AliasTM is a powerful, multi-faceted search that delivers a more complete criminal background examination than a traditional database search alone. NCISTM AliasTM uncovers names, addresses and dates of birth as well as known aliases including maiden names as revealed by our FACTTM search, with complete findings returned in a single, comprehensive report.

2.1.2 NCISTM AliasTM Parameters

To perform a NCISTM AliasTM search you must provide a valid login and password. The “subject” section of your XML document must contain, at minimum, “first name”, “last name”, “ssn”, “dob” fields. The product section of your XML document must contain an “NCISTM AliasTM” element.

2.1.3 Infinity ScreeningTM

The Infinity ScreeningTM product may optionally be requested with the following products: NCISTM, NCISTM AliasTM, SentinelTM, SafeGuardTM, SafeGuard-ProTM, NCISTM Statewide, OffenderScanTM, FirstAAAlertTM, NCISTM FirstAAAlertTM, I-MEDTM, I-MEDTM AliasTM. When requested, the subject will be enrolled in the Infinity ScreeningTM product and will be periodically rescreened. If there is a change in the returned records for a subject, you can receive a notification email indicating that FACT by configuring your email settings under the Admin section. Currently, you must log into the website to view the changes to the report.

2.1.4 Infinity ScreeningTM Parameters

To request Infinity ScreeningTM enrollment for a search, you must add an <enrollis>1</enrollis> element to the XML request under the <order> element. If the subject is already enrolled in Infinity ScreeningTM for the particular product, you will receive back a return code indicating that FACT. The search will not be performed in this case. Otherwise, the return XML will contain the results of the initial screening upon which the next rescreen will be based upon.

3. Service Methods

3.1.1 GetStatus

3.1.2 GetStatus Parameters

Name	Data Type	Max Length	Description
Login	Int	20	Your Innovative Account ID
Password	String	20	You Innovative Account password
referenceId	String	100	The reference ID you submitted for the original search

3.1.3 GetResults

3.1.4 GetResults Parameters

Name	Data Type	Max Length	Description
Login	Int	20	Your Innovative Account ID
Password	String	20	You Innovative Account password
referenceId	String	100	The reference ID you submitted for the original search

3.1.5 PlaceOrder

3.1.6 PlaceOrder Parameters

Name	Data Type	Max Length	Description
Login	Int	20	Your Innovative Account ID
Password	String	20	You Innovative Account password
inputXML	String	N/A	Input XML Document

3.2.1 inputXML Document

The inputXML document is a string formatted to the ieirequest schema (refer to Section 4). Sample XML request and response documents should be provided along with this document.

3.2.2 Subject Parameters Summary

Name	Data Type	Max Length	Description	NCIS™
First name	String	50	First name of person being searched	X
Middle name	String	50	Middle name of person	O

Name	Data Type	Max Length	Description	NCIS™
			being searched	
Last name	String	65	Last name of person being searched	X
ssn	String	11	SSN being searched for in the format XXX-XX-XXXX	X
dob	String	10	Date of Birth for person being searched for in the format MM/DD/YYYY	X
state	String	2	State to search in. If left blank, a nationwide search will be performed	O
				X = REQUIRED O = OPTIONAL

3.3 ISUnEnrollBySearchToken

3.3.1 ISUnEnrollBySearchToken Parameters

Name	Data Type	Max Length	Description
Login	Int	20	Your Innovative Account ID
Password	String	20	You Innovative Account password
searchToken	String	100	The searchToken value from a previous search that was enrolled in Infinity Screening™

3.4 ISEnrollBySearchToken

3.4.1 ISEnrollBySearchToken Parameters

Name	Data Type	Max Length	Description
Login	Int	20	Your Innovative Account ID
Password	String	20	You Innovative Account password
searchToken	String	100	The searchToken value from a previous search
billingOption	String	"Annual", "Monthly", "Weekly", "Quarterly" or "Biennial"	The billing option for Infinity Screening. Default is annual if empty.

3.5 ISGetList

3.5.1 ISGetList Request Parameters

Name	Data Type	Max Length	Description
------	-----------	------------	-------------

Login	Int	20	Your Innovative Account ID
Password	String	20	You Innovative Account password
pageNumber	Int		Start with page 1. Increment to subsequent pages if the nextPageNumber node is returned.

3.5.2 ISGetList Response

See ISGetList ieireponse.xml sample file

3.6 ISGetScreeningResults

3.6.1 ISGetScreeningResults Request Parameters

Name	Data Type	Max Length	Description
Login	Int	20	Your Innovative Account ID
Password	String	20	You Innovative Account password
searchToken	String	100	The searchToken value from a previous search

3.6.2 ISGetScreeningResults Response

See ISGetScreeningResults ieireponse.xml sample file

3.6.3 ISGetLastComparison Request Parameters

Name	Data Type	Max Length	Description
Login	Int	20	Your Innovative Account ID
Password	String	20	You Innovative Account password
searchToken	String	100	The searchToken value from a previous search

3.7 ISGetLastComparison Request Parameters

Name	Data Type	Max Length	Description
Login	Int	20	Your Innovative Account ID
Password	String	20	You Innovative Account password
searchToken	String	100	The searchToken value from a previous search

3.8 ISResendErroredPostbacks

3.8.1 ISResendErroredPostbacks Parameters

Name	Data Type	Max Length	Description
Login	Int	20	Your Innovative Account ID
Password	String	20	You Innovative Account password

4. ieirequest Schema

ieirequest

Elements and Attributes	Description
ieirequest	The root element for the PlaceOrder XML document
ieirequest/ order	A container for the order within the ieirequest.

order

Elements and Attributes	Description
ieirequest/ order	The root element of the order.
ieirequest/ order/ quoteback	Your reference string for this order. Max 40 characters
ieirequest/ order/ profilename	The profile name to use for this order. If no element is provided, the default profile will be used.
ieirequest/ order/ subject	A container for subject data.
ieirequest/ order/ product	Container for product specific data.
ieirequest/ order/ options	Specific options for medical suite orders.
ieirequest/ order/ enrollis	Flag to indicate that the subject should be enrolled in Infinity Screening™.

subject

Elements and Attributes	Description	Data Type	Usage	Frequency
ieirequest/ order/ subject	Root element for all input data	Complex	Required	1
ieirequest/ order/ subject/ firstname	First name sent in the request	string	Required	1
ieirequest/ order/ subject/ middlename	Middle name sent in the request	string	Optional	0 – 1
ieirequest/ order/ subject/ lastname	Last name sent in the request	string	Required	1
ieirequest/ order/ subject/ ssn	SSN sent in the request	string	Required	1
ieirequest/ order/ subject/ dob	DOB sent in the request. The dob node contains the data in month, day and year attributes.	string	Required	1
ieirequest/ order/ subject/ state	State to narrow search results (for criminal searches). Address state of subject (for medical products and BPS product)	string	Optional	0 – 1

product

Elements and Attributes	Description	Data Type	Usage	Frequency
ieirequest/ order/ product	Root element of order.	Complex	Required	1
ieirequest/ order/ product/ ncis-alias	NCIS™ Alias™ product type	Complex	Optional	0 – 1

settings

Some products have settings that can be overridden by using the following XML parameters. Settings are able to control different aspects of the search to give a more detailed or less detailed report.

ieirequest/ order/ <productname>/ settings	Root element of settings.	Complex	Optional	0-1
ieirequest/ order/ <productname>/ settings/ probability	Setting for how close the found name must be to the name that was searched for.	string	Optional Options include: "MostStrict", "MoreStrict", "Default", "LessStrict", "LeastStrict"	0-1
ieirequest/ order/ <productname>/ settings/ exactnamematch only	Flag to only return results that match the exact first and last name searched. This will still match results that have the name as an alias.	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ exactdobmatch only	Flag to only return results that match the exact date of birth searched	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ partialdob	Flag to return results that match the exact date of birth and partial date of birth searched	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ alternatedoboption	Flag to use Alternate Date of Birth options.	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ alternatedobmm	Alternate Date of Birth Option: Month 0 equals exact Default value is 0	String	Optional 0-12	0-1
ieirequest/ order/ <productname>/ settings/ alternatedobdd	Alternate Date of Birth Option: Day 0 equals exact Default value is 0	String	Optional 0-31	0-1
ieirequest/ order/ <productname>/ settings/ alternatedobyy	Alternate Date of Birth Option: Year 0 equals exact Default value is 0	String	Optional 0-10	0-1
ieirequest/ order/ <productname>/ settings/ enableadditionalname	This flag will enable additional name searches.	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includejurisdictionsearched	Flag to include a node in the criminal information section that contains a list of jurisdictions that were searched	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ includenulldob	Flag to include jurisdictions in the search that contain NULL date of birth	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ showonlynulldob address	Flag to show only offenders in the search if offenders contain NULL date of birth with an address	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includesexoffend erdata	Flag to include sex offender results in the search. Default value is 1 unless specified otherwise.	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includesexoffend ernulldobs	Flag to include sex offender records with Null DOBs Default value is 1 unless specified otherwise. Include Sex Offender Data must be true for this option.	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ showonlynulldob addresssexoffen der	Flag to show only offenders in the search if offenders contain NULL date of birth with an address	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ sexoffenderaltern atedoboption	Flag to use Sex Offender Alternate Date of Birth options.	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ sexoffenderaltern atedobmm	Sex Offender Alternate Date of Birth Option: Month 0 equals exact Default value is 0	String	Optional 0-12	0-1
ieirequest/ order/ <productname>/ settings/ sexoffenderaltern atedobdd	Sex Offender Alternate Date of Birth Option: Day 0 equals exact Default value is 0	String	Optional 0-31	0-1
ieirequest/ order/ <productname>/ settings/ sexoffenderaltern atedobyy	Sex Offender Alternate Date of Birth Option: Year 0 equals exact Default value is 0	String	Optional 0-10	0-1
ieirequest/ order/ <productname>/ settings/ sexoffenderexact dobmatch	Flag to only return Sex Offender results that match the exact date of birth searched	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ sexoffenderpartialdob	Flag to return Sex Offender results that match the exact date of birth and partial date of birth searched	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ sexoffenderconsidermiddlenamexml	Default value is 0	String	1 = Consider Middle Name 0 = Ignore Middle Name	0-1
ieirequest/ order/ <productname>/ settings/ excludearrestrecords	Flag to exclude arrest records from criminal search results. Default value is 0 unless specified otherwise.	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
order/ <productname>/ settings/ includewarrant	Include warrant records from criminal search results. Default value is 1 unless specified otherwise.		Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	
ieirequest/ order/ <productname>/ settings/ includecountyfipscode	Flag to include cleansed county and fips code to records from criminal search results. Default value is 0 unless specified otherwise.	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ enableadditionalname	Flag to perform searches with additional common nicknames. Default value is 0/False unless specified otherwise.	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ apply7yearlimit	Flag to filter criminal records to within the last 7 years. See sub-options to filter sex offender or sentinel records. Default value is 0/False unless specified otherwise.	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ apply7yearfilteroverride	Overrides the seven year filter with inputted year between 1 and 30. Default value is 7.	String	Optional Requires apply7yearlimit to be enabled. A number from 1 to 30.	0-1
ieirequest/ order/ <productname>/ settings/ apply7yearlimitsexoffender	Flag to filter sex offender records to within the last 7 years. Default value is 0/False unless specified otherwise.	string	Optional Requires apply7yearlimit to be enabled. Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ apply7yearlimitse ntinel	Flag to filter sentinel records to within the last 7 years. Default value is 0/False unless specified otherwise.	string	Optional Requires apply7yearlimit to be enabled. Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ exclude7yeardate	Flag to exclude records with no ending date. Default value is 0/False unless specified otherwise.	string	Optional Requires apply 7 year limit to be enabled. Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includesentineldata	Flag to include Sentinel™ data. Default value is 1/True unless specified otherwise.	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includesentinelnulldob	Flag to include Sentinel™ Null DOBs. Default value is 1/True unless specified otherwise.	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ showonlynulldob addresssentinel	Flag to show only offenders in the search if offenders contain NULL date of birth with an address	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ sentinelexactdob	Flag to include Sentinel Exact DOB. Default value is 0/False unless specified otherwise.	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ sentinelpartialdob	Flag to return results that match the exact date of birth and partial date of birth searched. Default value is 0/False unless specified otherwise.	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ sentinelexcludes ourcetypes	Excludes sources that have the specified jurisdiction type.	string	Optional pipe- delimited field.	Text
ieirequest/ order/ <productname>/ settings/ ssnmasking	Determines SSN Masking Default value is 0 Applies to all products.	String	Optional SSN is required or Optional Options include: 0 = first five 1 = last four 2 = All 3 = None	0,1,2,3

ieirequest/ order/ <productname>/ settings/ enablecommonnameprofile	Enables use of Common Name Profile when max hits is encountered on searches Default value is 0	String	Optional Options include: 0 = Disabled 1 = Enabled	0-1
ieirequest/ order/ <productname>/ settings/ considermiddle nameXML	Default value is 1	String	1 = Consider Middle Name 0 = Ignore Middle Name	0-1
ieirequest/ order/ <productname>/ settings/ includecasetypefelony	Default value is 1	String	1 = Include Felony Case Types 0 =Exclude Felony Case Types	0-1
ieirequest/ order/ <productname>/ settings/ includecasetype misdemeanor	Default value is 1	String	1 = Include Misdemeanor Case Types 0 =Exclude Misdemeanor Case Types	0-1
ieirequest/ order/ <productname>/ settings/ includecasetype traffic	Default value is 1	String	1 = Include Traffic Case Types 0 =Exclude Traffic Case Types	0-1
ieirequest/ order/ <productname>/ settings/ includecasetype criminaltraffic	Default value is 1	String	1 = Include Criminal Traffic Case Types 0 =Exclude Criminal Traffic Case Types	0-1

ieirequest/ order/ <productname>/ settings/ includecasetypeinfrac	Default value is 1	String	1 = Include Infraction Case Types 0 =Exclude Infraction Case Types	0-1
ieirequest/ order/ <productname>/ settings/ includecasetypeunknown	Default value is 1	String	1 = Include Unknown Case Types 0 =Exclude Unknown Case Types	0-1
ieirequest/ order/ <productname>/ settings/ considerhyphenatednamecombination	Considers the first and second part of a hyphenated last name separately and together. Default value is 0	String	Optional “0”, “1”, “yes”, “no”, “y”, “n”, “true”, “false” 1 = Include Consider Hyphenated Name Combination 0 =Exclude Consider Hyphenated Name Combination	0-1
ieirequest/ order/ <productname>/ settings/ isbillingoption	InfinityScreening™ Billing Option Default value is 1	String	Optional 1 = Annual 2 = Monthly 3 = Weekly 4 = Quarterly 5 = Biennial	0-1

ieirequest/ order/ <productname>/ settings/ agepostfilter	Filters out records that do not have an age value. Default value is 0	String	Optional “0”, “1”, “yes”, “no”, “y”, “n”, “true”, “false” 1 = Include Age Post Filter 0 =Exclude Age Post Filter	0-1
ieirequest/ order/ <productname>/ settings/ enablecustomdobformat	Enables custom DOB formatting options. Default value is 0	String	Optional “0”, “1”, “yes”, “no”, “y”, “n”, “true”, “false” 1 = Enable Custom DOB Format 0 = Disbale Custom DOB Format	0-1
ieirequest/ order/ <productname>/ settings/ defaultcustomdobformat	Selects the custom DOB format. Default value is 1	String	Optional “0”, “1” 1 = Use MM/DD/YYYY default format 0 = Use YYYY/MM/DD format	0-1
ieirequest/ order/ <productname>/ settings/ defaultcustomdobplaceholder	Selects the custom DOB placeholder for partial dates. Default value is 1	String	Optional “0”, “1” 1 = Use “X” default placeholder 0 = Use “0” placeholder	0-1

ieirequest/ order/ <productname>/ settings/ ncoffensedescription	Overrides the default of "Offense description not provided by source" for NC offenses	string	Optional	Text
ieirequest/ order/ <productname>/ settings/ offensedescription	Overrides the default of "Not provided by source" for non-NC offenses	string	Optional	Text
ieirequest/ order/ <productname>/ settings/ docsourcesonlyfilter	Only includes records with Department Of Corrections sources Default value is 0	String	Optional "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ icesourcesfilter	Includes records from ICE source Default value is 1	String	Optional "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ ncissexoffenderyobsread	Setting for +/- number of years from submitted Year in the DOB Default value is 1	String	Optional 0-10	0-1
ieirequest/ order/ <productname>/ settings/ includedispositionconviction	Include Conviction criminal records Default value is 1	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/	Include Non-Conviction criminal	String	Optional Options include:	0-1

<productname>/ settings/ includedispositio nnonconviction	records Default value is 1		"0", "1", "yes", "no", "y", "n", "true", "false"	
--	-----------------------------------	--	---	--

ieirequest/ order/ <productname>/ settings/ nonconvictioncustomyearfilter	Apply Non-Conviction custom year filter to criminal records Default value is 1 New accounts require a signed addendum to change this setting.	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ nonconvictionapplyyearfilteroverride	Apply Non-Conviction custom year filter override to criminal records Default value is 7	Int	Optional Options include: 1-30	0-1
ieirequest/ order/ <productname>/ settings/ nonconvictionexcludeyearnode	Exclude Non-Conviction no year date to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includedispositionpending	Include Pending criminal records Default value is 1	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includedispositiondeferred	Include Deferred criminal records Default value is 1	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ includedispositio nother	Include Other criminal records Default value is 1	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includecriminalda ta	Include Criminal records Default value is 1	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ filterfactfirstname	This flag will remove FACT™-based records that have a single letter for the first name.	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ defaultaddressda tes	Date Option for handling addresses with blank dates Default value is 1	string	Optional Options include: 0 = Address with blank date 1 = Custom Address date (01/1901) 2 = Remove address record from report	0,1,2
ieirequest/ order/ <productname>/ settings/ defaultaddressm onth	Month Option for handling addresses with blank dates Default value is 01	string	Optional Options include: 01-12	01-12

ieirequest/ order/ <productname>/ settings/ defaultaddressyear	Year Option for handling addresses with blank dates Default value is 1901	string	Optional Options include: 1901-Current Year	1901-Current Year
ieirequest/ order/ <productname>/ settings/ ignorefirstlastxml	Ignore First and Last name from XML Default value is 0	String	Optional Options include: 0 = Do Not Ignore First and Last Name from XML 1 = Ignore First and Last Name from XML	0-1
ieirequest/ order/ <productname>/ settings/ ignorefirstxml	Ignore First and Last name from XML Default value is 0	String	Optional Options include: 0 = Do Not Ignore First Name from XML 1 = Ignore First Name from XML	0-1
ieirequest/ order/ <productname>/ settings/ ignorelastxml	Ignore First and Last name from XML Default value is 0	String	Optional Options include: 0 = Do Not Ignore Last Name from XML 1 = Ignore Last Name from XML	0-1

ieirequest/ order/ <productname>/ settings/ disablefuzzynam ematch	Turns off fuzzy and nickname matching on the first name Default value is 0 Applies to FACT™, NCIS™ Alias™, SafeGuard™, SafeGuard-Pro™	String	Optional Options include: 0 = Apply fuzzy and nickname matching 1 = Disables fuzzy and nickname matching	0-1
ieirequest/ order/ <productname>/ settings/ factlastcharoff	Flag used to apply filter for matching records when the last name is off by X number of characters. Default value is 0 unless specified otherwise.	string	Optional Options include: “0”, “1”, “yes”, “no”, “y”, “n”, “true”, “false”	0-1

ieirequest/ order/ <productname>/ settings/ factlastcharoffnum	Setting to determine how many characters from the last name can be off when matching records. Default value is 0 unless specified otherwise.	string	Optional, but robotic Last Char Off must be enabled (true) for use. Options include: 0-50	0-1
ieirequest/ order/ <productname>/ settings/ factfirstcharoff	Flag used to apply filter for matching records when the first name is off by X number of characters. Default value is 0 unless specified otherwise.	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ groupaddresses	Flag used to apply address grouping to records when the setting is turned on. Default value is 0 unless specified otherwise.	string	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ enablefactfilteryear	Filters address records based on year. Default value is 0	String	Optional “0”, “1”, “yes”, “no”, “y”, “n”, “true”, “false” 0 = Ignore FACT™ Year Filter option 1 = Filter FACT™ results by year NOTE: FACT™ filter year setting is required when the value of this option is set to 1	0-1
ieirequest/ order/ <productname>/ settings/ factfilteryear	Applies to FACT™ based products	String	Optional 1-30 NOTE: enable FACT™filter year setting must be enabled	0-1
ieirequest/ order/ <productname>/ settings/ factremovepartial dob	Removes partial DOB from record. Default value is 0	String	Optional “0”, “1”, “yes”, “no”, “y”, “n”, “true”, “false” 0 = Keep FACT™ partial DOB 1 = Remove FACT™ partial DOB	0-1

ieirequest/ order/ <productname>/ settings/ factremoverecord partialdob	Removes record if it contains a partial DOB. Default value is 0	String	Optional "0", "1", "yes", "no", "y", "n", "true", "false" 0 = Keep FACT™ record with a partial DOB 1 = Remove FACT™ record with a partial DOB	0-1
ieirequest/ order/ <productname>/ settings/ factremoverecord nodob	Removes record if it contains no DOB. Default value is 0	String	Optional "0", "1", "yes", "no", "y", "n", "true", "false" 0 = Keep FACT™ record with no DOB 1 = Remove FACT™ record with no DOB	0-1

ieirequest/ order/ <productname>/ settings/ customssnrando mizationmessage	FACT™ Custom SSN Randomization Message Option Default Value is “UNABLE TO VALIDATE SSN”	String	Optional	Text
ieirequest/ order/ <productname>/ settings/ factexactfirstnam e	Flag to only return FACT™ results that match the exact first name searched.	string	Optional Options include: “0”, “1”, “yes”, “no”, “y”, “n”, “true”, “false”	0-1
ieirequest/ order/ <productname>/ settings/ factexactlastnam e	Flag to only return FACT™ results that match the exact last name searched.	string	Optional Options include: “0”, “1”, “yes”, “no”, “y”, “n”, “true”, “false”	0-1
ieirequest/ order/ <productname>/ settings/ factincludealiasn ameparts	Flag to return FACT™ alias name parts when available.	string	Optional Options include: “0”, “1”, “yes”, “no”, “y”, “n”, “true”, “false”	0-1
ieirequest/ order/ <productname>/ settings/ factenablecustom dobformat	Enables custom DOB formatting options. Default value is 0	String	Optional “0”, “1”, “yes”, “no”, “y”, “n”, “true”, “false” 1 = Enable Custom DOB Format 0 = Disbale Custom DOB Format	0-1

ieirequest/ order/ <productname>/ settings/ factdefaultcustomdobformat	Selects the custom DOB format. Default value is 1	String	Optional “0”, “1” 1 = Use MM/DD/YYYY default format 0 = Use YYYY/MM/DD format	0-1
ieirequest/ order/ <productname>/ settings/ factdefaultcustomdobplaceholder	Selects the custom DOB placeholder for partial dates. Default value is 0	String	Optional “0”, “1” 1 = Use “X” placeholder 0 = Use “0” default placeholder	0-1

ieirequest/ order/ <productname>/ settings/ factfirstcharoffnum	Setting to determine how many characters from the first name can be off when matching records. Default value is 0 unless specified otherwise.	string	Optional, but robotic First Char Off must be enabled (true) for use. Options include: 0-50	0-1
ieirequest/ order/ <productname>/ settings/ dobsummary	Enable use of DOB Summary in response and website reports Default value is 0	String	Optional Options include: 0 = Default 1 = Enabled	0-1
ieirequest/ order/ <productname>/ settings/ includedispositionconviction	Include Conviction criminal records Default value is 1	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includedispositionnonconviction	Include Non-Conviction criminal records Default value is 1	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ nonconvictioncustomyearfilter	Apply Non-Conviction custom year filter to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ nonconvictionap plyyearfilteroverri de	Apply Non- Conviction custom year filter override to criminal records Default value is 7	Int	Optional Options include: 1-30	0-1
ieirequest/ order/ <productname>/ settings/ nonconvictionexc ludeyearnode	Exclude Non- Conviction no year date to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includedispositio npending	Include Pending criminal records Default value is 1	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includedispositio ndeferred	Include Deferred criminal records Default value is 1	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ includedispositio nother	Include Other criminal records Default value is 1	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ includecriminaldata	Include Criminal records Default value is 1	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ applyfelonycustomyearfilter	Apply Felony Custom Year filter to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ felonycustomyearfilter	Apply Felony Custom Year filter number of years to criminal records Default value is 7	Int	Optional Options include: 1-30	0-1
ieirequest/ order/ <productname>/ settings/ excludefelonyrecordswithnoenddate	Exclude Felony records with no year date to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ applymisdemeanorcustomyearfilter	Apply Misdemeanor Custom Year filter to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ misdemeanorcus	Apply Misdemeanor Custom Year filter number of years to criminal records	Int	Optional Options include: 1-30	0-1

toyearfilter	Default value is 7			
ieirequest/ order/ <productname>/ settings/ excludemisdemeanorrecordswithnoendingdate	Exclude Misdemeanor records with no year date to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ applycriminaltrafficcustomyearfilter	Apply Criminal Traffic Custom Year filter to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ criminaltrafficcustomyearfilter	Apply Criminal Traffic Custom Year filter number of years to criminal records Default value is 7	Int	Optional Options include: 1-30	0-1
ieirequest/ order/ <productname>/ settings/ excludecriminaltrafficrecordswithnoendingdate	Exclude Criminal Traffic records with no year date to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ applyinfractioncustomyearfilter	Apply Felony Custom Year filter to criminal records Default value is 0 New accounts require a signed addendum to change this setting.	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

ieirequest/ order/ <productname>/ settings/ infractioncustom yearfilter	Apply Infraction Custom Year filter number of years to criminal records Default value is 7 New accounts require a signed addendum to change this setting.	Int	Optional Options include: 1-30	0-1
ieirequest/ order/ <productname>/ settings/ excludeinfraction recordswithnoen dingdate	Exclude Infraction records with no year date to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ applyunknowncu stomyearfilter	Apply Unknown Custom Year filter to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1
ieirequest/ order/ <productname>/ settings/ unknowncustomy earfilter	Apply Unknown Custom Year filter number of years to criminal records Default value is 7	Int	Optional Options include: 1-30	0-1
ieirequest/ order/ <productname>/ settings/ excludeunknownr ecordswithnoend ingdate	Exclude Unknown records with no year date to criminal records Default value is 0	String	Optional Options include: "0", "1", "yes", "no", "y", "n", "true", "false"	0-1

5. ieiresponse Schema

ieiresponse

Elements and Attributes	Description
ieiresponse	Root element
ieiresponse/ requestinformation	The data items that were sent in the request or any errors that occurred. See section 5.1
ieiresponse/ addressinformation	Container element for all of the records containing address information. See section 5.2
ieiresponse/ criminalinformation	Container element for all of the records containing criminal information. See section 5.3
ieiresponse/ enrollmentinformation	Container element for Infinity Screening™ enrollment information. See section 5.8
ieiresponse/ quoteback	The quoteback value will be reported back here.
ieiresponse/ disclaimer_link	The IEI criminal records disclaimer. Will appear in all responses on 01/12/15 and thereafter. Contains general disclaimer text and includes a link to an external disclaimer URL.

5.1 requestinformation

Elements and Attributes	Description
ieiresponse/ requestinformation	Root element
ieiresponse/ requestinformation/ @code	Response code
ieiresponse/ requestinformation/ code message	Message to go along with the Response Code
ieiresponse/ requestinformation/ inputs	Container for input data

inputs

Elements and Attributes	Description	Data Type	Usage	Frequency
ieireponse/ requestinformatio n/ inputs	Root element	Complex	Required	1
ieireponse/ requestinformatio n/ inputs/ firstname	First name sent in the request	String	Optional (required for AssuredTenant™)	0 – 1
ieireponse/ requestinformatio n/ inputs/ middlename	Middle name sent in the request	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ lastname	Last name sent in the request	String	Optional (required for AssuredTenant™)	0 – 1
ieireponse/ requestinformatio n/ inputs/ ssn	SSN sent in the request	String	Optional (required for AssuredTenant™)	0 – 1
ieireponse/ requestinformatio n/ inputs/ dob	DOB sent in the request. The dob node contains the data in year, month, and day attributes.	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ state	State sent in the request	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ product	Product sent in the request	String	Required	1

ieireponse/ requestinformatio n/ inputs/ quoteback	Quoteback value sent in the request	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ includenulldob	Includenulldob value sent in the request	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ showonlynulldo baddress	ShowOnlyNullDob Address value sent in the request	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ includesexoffen derdata	Include Sex Offender values sent in the request	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ exactdobmatcho nly	Exact dob match only values sent in the request	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ partialdob	Exact dob match and partial dob values sent in the request	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ exactnamematch only	Exact name match only values sent in the request	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ probability	probability values sent in the request	String	Optional	0 – 1

ieireponse/ requestinformatio n/ inputs/ includejurisdicti onssearched	Include jurisdictions searched values sent in the request	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ apply7yearlimit	Apply 7 year limit value used by the request		Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ apply7yearlimits exoffender	Apply 7 year limit sex offender value used by the request		Optional	0 - 1
ieireponse/ requestinformatio n/ inputs/ apply7yearlimits entinel	Apply 7 year limit Sentinel™ value used by the request		Optional	0 - 1
ieireponse/ requestinformatio n/ inputs/ exclude7yearnod ate	Exclude 7 year no date value used by the request		Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ includesentineld ata	Include Sentinel™ data in the results	String	Optional	0 – 1
ieireponse/ requestinformatio n/ inputs/ timestamp	Auto generated timestamp	String	Required	1
ieireponse/ requestinformatio n/ inputs/ resultmessage	Auto generated message	String	Optional	0-1

ieireponse/inputs / searchtoken	A unique alphanumeric ID for the search. Only included when status code is 100 or 101.	String	Optional	
--	--	--------	----------	--

5.2 criminal information

Elements and Attributes	Description	Data Type	Usage	Frequency
ieireponse/ criminalinformation	Root element	Complex	Optional	0 - 1
ieireponse/ criminalinformation/ records	Element for records	Complex	Required if criminal information node exists	1
ieireponse/ criminalinformation/ jurisdictionsearched	List of jurisdictions that were searched	String	Optional	0 – 1

5.3 addressinformation

Elements and Attributes	Description	Data Type	Usage	Frequency
ieireponse/ addressinformation	Root element	Complex	Optional	0 - 1
ieireponse/ addressinformation/ message	Message returned about the SSN searched	String	Optional	0 – 1
ieireponse/ addressinformation/ year	Year(s) that the SSN could have been issued in	String	Optional	0 – 1

ieireponse/ addressinformatio n/ records	Element for records	Complex	Required if addressinformatio n node exists	1
ieireponse/ addressinformatio n/ summaryinforma tion	Element for summary information	Complex	Optional	0 - 1

summary information

Elements and Attributes	Description	Data Type	Usage	Frequency
ieireponse/ addressinformatio n/ summaryinforma tion	Root element	Complex	Optional	1
ieireponse/ addressinformatio n/ summaryinformati on/ uniquedobs	Element for dob records	Complex	Required if summary information node exists	1
ieireponse/ addressinformatio n/ summaryinformati on/ uniquedobs/ @count	Number of dob nodes returned	Integer	Required if unique dobs node exists	1
ieireponse/ addressinformatio n/ summaryinformati on/ uniquedobs/ dob	dob	String	Required if unique dobs node exists	
ieireponse/ addressinformatio n/ summaryinformati on/ uniquenames	Element for full name records	Complex	Required if summary information node exists	1

ieireponse/ addressinformatio n/ summaryinformati on/ uniquenames/ @count	Number of fullname nodes returned	Integer	Required if unique names node exists	1
ieireponse/ addressinformatio n/ summaryinformati on/ uniquenames/ fullname	fullname	String	Required if unique names node exists	
ieireponse/ addressinformatio n/ summaryinformati on/ uniquecounties	Element for county records	Complex	Required if summary information node exists	1
ieireponse/ addressinformatio n/ summaryinformati on/ uniquecountiess/ @count	Number of county nodes returned	Integer	Required if unique counties node exists	1
ieireponse/ addressinformatio n/ summaryinformati on/ uniquecounties/ county	County	String	Required if unique counties exists	
ieireponse/ addressinformatio n/ summaryinformati on/ distinctaddressc ount	Number of distinct addresses found	Integer	Required if summary information node exists	1

records

Elements and Attributes	Description	Data Type	Usage	Frequency
ieireponse/ addressinformatio n/ records	Root element	Complex	Required if address information node exists	1
ieireponse/ addressinformatio n/ records/ @count	Number of record nodes returned	Integer	Required if records node exists	1
ieireponse/ addressinformatio n/ records/ record	Element for address record	Complex	Required if records node exists	1 - 1000

record

Elements and Attributes	Description	Data Type	Usage	Frequency
ieireponse/ addressinformatio n/ records/ record/ fullname	The full name returned on the record	String	Optional	0 - 1
ieireponse/ addressinformatio n/ records/ record/ firstname	The first name retuned on the record	String	Optional	0 - 1
ieireponse/ addressinformatio n/ records/ record/ middlename	The middle name returned on the record	String	Optional	0 - 1

ieiresponse/ addressinformatio n/ records/ record/ lastname	The last name returned on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ suffix	The suffix returned on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ nameparts/ firstname	The first name retuned on the record for ACE™ Searches only	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ nameparts/ middlename	The middle name retuned on the record for ACE™ Searches only	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ nameparts/ lastname	The last name retuned on the record for ACE™ Searches only	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ nameparts/ suffix	The suffix retuned on the record for ACE™ Searches only	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ fulldob	The full date of birth returned on the record	String	Optional	0 - 1

ieiresponse/ addressinformatio n/ records/ record/ dob	The date of birth returned on the record. The dob node contains the data in year, month, and day attributes.	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ ssn	The SSN returned on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ age	The age returned on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ age-at-death	The age at death returned on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ death-verification- code	The death verification code returned on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ aliases	Element for aliases	Complex	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses	Element for addresses	Complex	Optional	0 - 1

ieiresponse/ addressinformatio n/ records/ record/ phonenumbers	Element for phonenumbers	Complex	Optional	0 - 1
---	-----------------------------	---------	----------	-------

aliases

Elements and Attributes	Description	Data Type	Usage	Frequency
ieiresponse/ addressinformatio n/ records/ record/ aliases	Root element	Complex	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ aliases/ @count	Number of alias nodes	Integer	Required if aliases node exists	1
ieiresponse/ addressinformatio n/ records/ record/ aliases/ alias	Element for alias	Complex	Required if aliases node exists	1 - ∞

alias

Elements and Attributes	Description	Data Type	Usage	Frequency
ieiresponse/ addressinformatio n/ records/ record/ aliases/ alias	Root element	Complex	Required if aliases node exists	1 - ∞

ieireponse/ addressinformatio n/ records/ record/ aliases/ alias/ fullname	Full alias name	String	Optional	0 – 1
ieireponse/ addressinformatio n/ records/ record/ aliases/ alias/ firstname	Alias first name	String	Optional	0 – 1
ieireponse/ addressinformatio n/ records/ record/ aliases/ alias/ middlename	Alias middle name	String	Optional	0 – 1
ieireponse/ addressinformatio n/ records/ record/ aliases/ alias/ lastname	Alias last name	String	Optional	0 – 1
ieireponse/ addressinformatio n/ records/ record/ aliases/ alias/ suffix	Alias suffix	String	Optional	0 – 1

ieireponse/ addressinformatio n/ records/ record/ aliases/ alias/ fulldob	Full alias date of birth	String	Optional	0 – 1
ieireponse/ addressinformatio n/ records/ record/ aliases/ alias/ dob	Alias date of birth. Dob node contains the data in year, month, and day attributes	String	Optional	0 - 1

addresses

Elements and Attributes	Description	Data Type	Usage	Frequency
ieireponse/ addressinformatio n/ records/ record/ addresses	Root element	Complex	Optional	0 - 1
ieireponse/ addressinformatio n/ records/ record/ addresses/ @count	The number of address nodes	Integer	Required if addresses node exists	1
ieireponse/ addressinformatio n/ records/ record/ addresses/ address	Element for address	Complex	Required if addresses node exists	1 - ∞

address

Elements and Attributes	Description	Data Type	Usage	Frequency
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address	Root element	Complex	Required if addresses node exists	1 - ∞
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ fullstreet	The entire street line of the address record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ street-number	The street number of the address record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ street-pre- direction	The pre direction of the street for the address record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ street-name	The street name of the address record	String	Optional	0 - 1

ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ street-post- direction	The post direction of the street for the address record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ street-suffix	The suffix of the street name of the address record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ unit-number	The unit number of the address record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ city	The city of the address record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ state	The state of the address record	String	Optional	0 - 1

ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ zip	The zip code of the address record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ zip4	The four digit postfix of the zip code of the address record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ county	The county of the address record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ verified	Whether or not the address has been verified	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ from-date	The first reported date the offender lived in this address. The data is returned in year, month, and day attributes.	String	Optional	0 - 1

ieiresponse/ addressinformatio n/ records/ record/ addresses/ address/ to-date	The last reported date the offender lived in this address. The data is returned in year, month, and day attributes.	String	Optional	0 - 1
--	---	--------	----------	-------

phonenumbers

Elements and Attributes	Description	Data Type	Usage	Frequency
ieiresponse/ addressinformatio n/ records/ record/ phonenumbers	Root element	Complex	Optional	0 – 1
ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ @count	Number of phone number elements	Integer	Required if phone numbers node exists	1
ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ phonenum	Element for phone number	Complex	Required if phone numbers node exists	1 - ∞

phonenum

Elements and Attributes	Description	Data Type	Usage	Frequency
ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ phonenum	Root element	Complex	Required if phone numbers node exists	1 - ∞

ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ phonenumbers/ fullnumber	The full phone number on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ phonenumbers/ areacode	The area code on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ phonenumbers/ listed	Whether or not the phone number is listed	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ phonenumbers/ firstname	The first name for the phone number on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ phonenumbers/ middlename	The middle name for the phone number on the record	String	Optional	0 - 1

ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ phonenumbers/ lastname	The last name for the phone number on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ phonenumbers/ namesuffix	The suffix for the phone number on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ phonenumbers/ dualname	The dual listed name of the phone number on the record	String	Optional	0 - 1
ieiresponse/ addressinformatio n/ records/ record/ phonenumbers/ phonenumbers/ companyname	The company name for the phone number on the record	String	Optional	0 - 1

5.4 criminal information

records

Elements and Attributes	Description	Data Type	Usage	Frequency
ieiresponse/ criminalinformatio n/ records	Root element	Complex	Required if criminal information node exists	1
ieiresponse/ criminalinformatio n/ records/ @count	Number of record nodes returned	Integer	Required if records node exists	1
ieiresponse/ criminalinformatio n/ records/ record	Element for record	Complex	Required if records node exists	1 - 1000

record

Elements and Attributes	Description	Data Type	Usage	Frequency
ieiresponse/ criminalinformatio n/ records/ record	Root element	Complex	Required if records node exists	1 - 1000
ieiresponse/ criminalinformatio n/ records/ record/ @id	Unique ID for the record.	String	Required	1
ieiresponse/ criminalinformatio n/ records/ record/ category	Category of the record	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ sourceorjurisdict ion	The source or jurisdiction for this record	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ countycle ansed	The county of the jurisdiction for this record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ fipscode	The Federal Information Processing Standard Code for this record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ state	The state for this record	String	Optional	0 – 1

ieiresponse/ criminalinformatio n/ records/ record/ fullname	The full name returned on the record	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ firstname	The first name retuned on the record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ middlename	The middle name returned on the record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ last name	The last name returned on the record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ suffix	The suffix returned on the record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ fulldob	The full date of birth returned on the record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ dob	The date of birth returned on the record. The dob node contains the data in year, month, and day attributes.	String	Optional	0 - 1

ieireponse/ criminalinformatio n/ records/ record/ birthstate	The birth state returned on the record	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ ssn	The SSN returned on the record	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ sex	The sex returned on the record	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ race	The race returned on the record	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ haircolor	The hair color returned on the record	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ eyecolor	The eye color returned on the record	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ weight	The weight returned on the record	String	Optional	0 - 1

ieiresponse/ criminalinformatio n/ records/ record/ height	The height returned on the record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ scarsmarks	The scars and marks returned on the record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ skintone	The skin tone returned on the record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ militaryservice	The military service returned on the record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ age	The age returned on the record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ age-at-death	The age at death returned on the record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ dlnumber	The drivers license number returned on the record	String	Optional	0 – 1

ieireponse/ criminalinformatio n/ records/ record/ death- verification-code	The death verification code returned on the record	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ casenumber	The case number of the offense on this record	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ countyorjurisdict ion	The county or jurisdiction that was returned on this record	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ photoname	The URL to a photo of the offender returned on the record	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ status	The status of the offender returned on this record	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ comments	Any additional information that pertains to this record	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ aliases	Element for aliases	Complex	Optional	0 - 1

ieiresponse/ criminalinformatio n/ records/ record/ addresses	Element for addresses	Complex	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses	Element for offenses	Complex	Optional	0 - 1

aliases

Elements and Attributes	Description	Data Type	Usage	Frequency
ieiresponse/ criminalinformatio n/ records/ record/ aliases	Root element	Complex	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ aliases/ @count	Number of alias nodes	Integer	Required if aliases node exists	1
ieiresponse/ criminalinformatio n/ records/ record/ aliases/ alias	Element for alias	Complex	Required if aliases node exists	1 - ∞

alias

Elements and Attributes	Description	Data Type	Usage	Frequency
ieireponse/ criminalinformatio n/ records/ record/ aliases/ alias	Root element	Complex	Required if aliases node exists	1 - ∞
ieireponse/ criminalinformatio n/ records/ record/ aliases/ alias/ fullname	Full alias name	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ aliases/ alias/ fulldob	Full alias date of birth	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ aliases/ alias/ dob	Alias date of birth. Dob node contains the data in year, month, and day attributes	String	Optional	0 - 1

addresses

Elements and Attributes	Description	Data Type	Usage	Frequency
ieireponse/ criminalinformatio n/ records/ record/ addresses	Root element	Complex	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ addresses/ @count	The number of address nodes	Integer	Required if addresses node exists	1
ieireponse/ criminalinformatio n/ records/ record/ addresses/ address	Element for address	Complex	Required if addresses node exists	1 - ∞

address

Elements and Attributes	Description	Data Type	Usage	Frequency
ieireponse/ criminalinformatio n/ records/ record/ addresses/ address	Root element	Complex	Required if addresses node exists	1 - ∞
ieireponse/ criminalinformatio n/ records/ record/ addresses/ address/ address1	The first street line of the address record	String	Optional	0 - 1

ieiresponse/ criminalinformatio n/ records/ record/ addresses/ address/ address2	The second street line of the address record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ addresses/ address/ city	The city of the address record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ addresses/ address/ state	The state of the address record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ addresses/ address/ zip	The zip code of the address record	String	Optional	0 - 1

offenses

Elements and Attributes	Description	Data Type	Usage	Frequency
ieiresponse/ criminalinformatio n/ records/ record/ offenses	Root element	Complex	Optional	0 - 1

ieireponse/ criminalinformatio n/ records/ record/ offenses/ @count	Number of offense nodes	Integer	Required if offenses node exists	1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense	Element for offense	Complex	Required if offenses node exists	1 - ∞

offense

Elements and Attributes	Description	Data Type	Usage	Frequency
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense	Root element	Complex	Required if offenses node exists	1 - ∞
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ offensedescripti on	The description of the offense on record	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ arrestdate	The date of arrest of the offense on record	String	Optional	0 – 1

ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ counts	The counts of the offense on record	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ statute	The statute of the offense on record	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ casetype	The type of case of the offense on record	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ sentencelength	The length of the sentence for the offense on record. Data is returned in year, month, and day attributes	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ suspendedsenten ce	The length of the sentence that has been suspended of the offense on record	String	Optional	0 – 1

ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ arrestingagency	The arresting agency of the offense on record	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ chargefilingdate	The date the charges were filed for the offense on record	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ disposition	The disposition of the offense on record	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ dispositiondate	The date of the disposition of the offense on record	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ convictiondate	The date of the conviction for the offense on record	String	Optional	0 – 1

ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ convictionlocati on	The location of the conviction for the offense on record	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ offensedate	The date of the offense on record	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ offensecode	The code of the offense on record	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ nciccode	The NCIC code of the offense on record	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ nciccodedescrip tion	The NCIC code description of the offense on record	String	Optional	0 – 1

ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ probationsenten celength	The length of the probation sentence of the offense on record. Data is returned in year, month, and day attributes	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ amendeddisposi tion	If the final disposition is different than the original disposition, it will appear here	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ amendeddisposi tiondate	If the final disposition date is different than the original disposition date, it will appear here	String	Optional	
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ court	The court for the offense on record	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ plea	The plea that was entered for the case on record	String	Optional	0 – 1

ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ courtcosts	The court costs that were ordered for the offense on record	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ finest	The fines that were ordered for the offense on record	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ warrantdate	The warrant date for this offense	String	Optional	0 – 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ warrantcounty	The county the warrant was issued in for this offense	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ warrantstate	The state the warrant was issued in for this offense	String	Optional	0 - 1

ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ supervisioncoun ty	The county that supervision was ordered for this offense	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ supervisionstate	The state that supervision was ordered for this offense	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ supervisiondate	The date that supervision was ordered for this offense	String	Optional	0 – 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ commitmentloca tion	The location where the offender was committed for this offense	String	Optional	0 - 1
ieireponse/ criminalinformatio n/ records/ record/ offenses/ offense/ commitmentcou nty	The county where the offender was committed for this offense	String	Optional	0 - 1

ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ commitmentstate	The state where the offender was committed for this offense	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ commitmentdate	The date the offender was committed for this offense	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ releasedate	The date the offender was released for this offense	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ fbnumber	The FBI identification number for the offender for this offense	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ bookingnumber	The booking number for this offenses	String	Optional	0 - 1

ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ restitution	The amount that the offender was ordered to pay in restitution for this offense	String	Optional	0 - 1
ieiresponse/ criminalinformatio n/ records/ record/ offenses/ offense/ comments	Comments about the offense on record	String	Optional	0 – 1

6. Errors

In case of an error, the system will send back an error code and message wrapped in an IEI response node.

6.1 Codes and Code Messages

Code	Code Message
100	Records Found
101	No Records Found
102	Pending
200	Invalid username and/or password
201	Product does not exist or you do not have access to the product
203	First name must exist
204	Last name must exist
205	Invalid month
206	Invalid day
207	Invalid year
208	Invalid state
209	Invalid SSN
209	Last 4 of SSN is only valid with a last name
210	Invalid DOB
211	This service is not enabled, please try again later
212	This method is not enabled, please try again later
213	Your account is not enabled for this service
214okay	Service cannot be found
215	More than 1000 records were found.
216	DOB is required
217	Already Enrolled in Infinity Screening™
218	Invalid SSN-Unable to process 4 digit SSN
219	Invalid Permissible Purpose
220	SSN must exist
221	Building Number must exist
222	City must exist
223	State must exist
224	Zip must exist
225	Number of addresses must be between 1 and 3
226	Building number exceeds the maximum length of 20
227	Street name exceeds the maximum length of 40
228	City exceeds the maximum length of 40

229	State exceeds the maximum length of 2
230	Zip exceeds the maximum length of 5
231	Address, City, and State must exist
232	Invalid XML character
233	This applicant cannot be conducted through the automated system at this time.
234	Invalid Zip
235	Invalid Building Number
236	Invalid City
237	Invalid Character
238	Excessive results expected
239	Your original search returned a 'too many records error' from the source. Additional identifiers were used to generate the results for this report.
240	Your original search is older than the 60 day limit allowed for enrollment in Infinity Screening™
241	Invalid Billing Option
242	Your search is not Enrolled in Infinity Screening™
243	Invalid Search Token
244	Invalid Page Number
245	No subjects currently enrolled in Infinity Screening™
246	Infinity Screening™ is unavailable for the product
247	Entity name is required
248	Level is required
249	Additional state is required
250	Search type is required
251	Level must be 1, 2 or 3
252	Additional Addresses value must be between 1 and 30
253	Street name must exist
300	General Program Exception or Blocked Due to Excessive Usage
310	General PACERPlus™ Search Program Exception
311	PACERPlus™ time out error
312	PACERPlus™ exceeded max pages error
313	PACERPlus™ invalid region for the court type
314	PACERPlus™ PACER.gov Username or Password are invalid
315	PACERPlus™ PACER.gov Account is disabled
316	Unauthorized to access
317	Invalid JSON document

318	Unprocessable search criteria
319	Invalid age minimum
320	Invalid age maximum
321	Building number exceeds the maximum length of 20