

Jakub Bogdański

Geany

Geany to małe i bardzo szybkie środowisko programistyczne (IDE), które nie obciąża komputera. Twórcy zaprojektowali je tak, aby było maksymalnie niezależne, dzięki czemu nie wymaga instalacji dziesiątek dodatkowych pakietów w systemie. Program nie jest też przywiązany do żadnego konkretnego, dużego środowiska graficznego (jak KDE czy GNOME) – do odpalenia interfejsu wystarczy mu tylko podstawowe biblioteki GTK+.

Przebieg instalacji:

```
nakselano@DESKTOP-07LCCCH:~$ sudo apt update
[sudo] password for nakselano:
Sorry, try again.
[sudo] password for nakselano:
Sorry, try again.
[sudo] password for nakselano:
Hit:1 http://archive.ubuntu.com/ubuntu noble InRelease
Hit:2 http://security.ubuntu.com/ubuntu noble-security InRelease
Hit:3 http://archive.ubuntu.com/ubuntu noble-updates InRelease
Hit:4 http://archive.ubuntu.com/ubuntu noble-backports InRelease
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
146 packages can be upgraded. Run 'apt list --upgradable' to see them.
nakselano@DESKTOP-07LCCCH:~$
```

Pierwszym krokiem jaki należało wykonać była aktualizacja systemu

```
nakselano@DESKTOP-07LCCCH:~$ wget https://download.geany.org/geany-2.0.tar.gz
--2026-06-13 17:28:36-- https://download.geany.org/geany-2.0.tar.gz
Resolving download.geany.org (download.geany.org)... 194.36.144.33, 2a03:4000:4d:a0::1
Connecting to download.geany.org (download.geany.org)|194.36.144.33|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 9236525 (8.8M) [application/octet-stream]
Saving to: 'geany-2.0.tar.gz'

geany-2.0.tar.gz          6%[==>                ] 623.69K  74.7KB/s   eta 1m 43s |
```

Następnie pobieram Geany z oficjalnej strony przy użyciu wget

```
nakselano@DESKTOP-07LCCCH:~$ tar -zxvf geany-2.0.tar.gz |
```

Po pobraniu rozpakowuje pakiet przy użyciu polecenia tar z flagą -zxvf

```
nakselano@DESKTOP-07LCCCH:~/geany-2.0$ ls
ABOUT-NLS      HACKING      README      aclocal.m4   configure.ac  geany.exe.manifest  m4      src
AUTHORS         INSTALL     README.I18N  autogen.sh   ctags        geany.nsi.in       plugins  tests
COPYING         Makefile.am README.Packagers  build-aux    data         geany.pc.in        po
ChangeLog       Makefile.in THANKS       config.h.in  doc         geany_private.rc   scintilla
ChangeLog.pre-1-22 NEWS      TODO       configure    geany.desktop.in  icons          scripts
nakselano@DESKTOP-07LCCCH:~/geany-2.0$ ./configure |
```

Sprawdzam zawartość rozpakowanego folderu i podejmuję próbę wykonania ./configure

```

nakselano@DESKTOP-07LCCCH:~/geany-2.0$ ./configure
checking for a BSD-compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking for a race-free mkdir -p... /usr/bin/mkdir -p
checking for gawk... gawk
checking whether make sets $(MAKE)... no
checking whether make supports nested variables... no
checking whether make supports the include directive... no
checking for gcc... no
checking for cc... no
checking for cl.exe... no
checking for clang... no
configure: error: in `/home/nakselano/geany-2.0':
configure: error: no acceptable C compiler found in $PATH
See `config.log' for more details
nakselano@DESKTOP-07LCCCH:~/geany-2.0$ |

```

Po wykonaniu widzę, że mój system WSL nie ma kompilatora C

```

nakselano@DESKTOP-07LCCCH:~/geany-2.0$ sudo apt install build-essential

```

Aby to naprawić instaluje build-essential, która zawiera w sobie kompilator C (gcc)

```

nakselano@DESKTOP-07LCCCH:~/geany-2.0$ ./configure
checking for a BSD-compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking for a race-free mkdir -p... /usr/bin/mkdir -p
checking for gawk... gawk
checking whether make sets $(MAKE)... yes
checking whether make supports nested variables... yes
checking whether make supports the include directive... yes (GNU style)
checking for gcc... gcc
checking whether the C compiler works... yes
checking for C compiler default output file name... a.out

```

Po instalacji pakietu, ponownie wykonuje skrypt ./configure

```

configure: error: The pkg-config script could not be found or is too old.  Make sure it
is in your PATH or set the PKG_CONFIG environment variable to the full
path to pkg-config.

Alternatively, you may set the environment variables GTK_CFLAGS
and GTK_LIBS to avoid the need to call pkg-config.
See the pkg-config man page for more details.

To get pkg-config, see <http://pkg-config.freedesktop.org/>.
See `config.log' for more details
nakselano@DESKTOP-07LCCCH:~/geany-2.0$ |

```

Tym razem dowiaduje się o braku pkg-config.

```

nakselano@DESKTOP-07LCCCH:~/geany-2.0$ sudo apt install pkg-config -y
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  libpkgconf3 pkgconf pkgconf-bin
The following NEW packages will be installed:
  libpkgconf3 pkg-config pkgconf pkgconf-bin
0 upgraded, 4 newly installed, 0 to remove and 145 not upgraded.
Need to get 75.4 kB of archives.
After this operation, 283 kB of additional disk space will be used.
Get:1 http://archive.ubuntu.com/ubuntu noble/main amd64 libpkgconf3 amd64 1.8.1-2build1 [30.7 kB]
Get:2 http://archive.ubuntu.com/ubuntu noble/main amd64 pkgconf-bin amd64 1.8.1-2build1 [20.7 kB]
Get:3 http://archive.ubuntu.com/ubuntu noble/main amd64 pkgconf amd64 1.8.1-2build1 [16.8 kB]
Get:4 http://archive.ubuntu.com/ubuntu noble/main amd64 pkg-config amd64 1.8.1-2build1 [7264 B]
Fetched 75.4 kB in 0s (609 kB/s)
Selecting previously unselected package libpkgconf3:amd64.
(Reading database ... 46782 files and directories currently installed.)
Preparing to unpack .../libpkgconf3_1.8.1-2build1_amd64.deb ...
Unpacking libpkgconf3:amd64 (1.8.1-2build1) ...
Selecting previously unselected package pkgconf-bin.
Preparing to unpack .../pkgconf-bin_1.8.1-2build1_amd64.deb ...
Unpacking pkgconf-bin (1.8.1-2build1) ...
Selecting previously unselected package pkgconf:amd64.
Preparing to unpack .../pkgconf_1.8.1-2build1_amd64.deb ...
Unpacking pkgconf:amd64 (1.8.1-2build1) ...
Selecting previously unselected package pkg-config:amd64.
Preparing to unpack .../pkg-config_1.8.1-2build1_amd64.deb ...
Unpacking pkg-config:amd64 (1.8.1-2build1) ...
Setting up libpkgconf3:amd64 (1.8.1-2build1) ...

```

Instaluje brakujący pakiet i ponawiam próbę konfiguracji

```

configure: error: Package requirements (gtk+-3.0 >= 3.24 glib-2.0 >= 2.32 gio-2.0 >= 2.32 gmodule-no-export-2.0 gthread-2.0) were not met:

Package 'gtk+-3.0', required by 'virtual:world', not found
Package 'glib-2.0', required by 'virtual:world', not found
Package 'gio-2.0', required by 'virtual:world', not found
Package 'gmodule-no-export-2.0', required by 'virtual:world', not found
Package 'gthread-2.0', required by 'virtual:world', not found

```

Po ponownym wykonaniu ./configure, widzę kolejne brakujące pakiety

```

nakselano@DESKTOP-07LCCCH:~/geany-2.0$ sudo apt install libgtk-3-dev -y
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done

```

Pełen nadziei, po raz kolejny używam ./configure

```

-----
Install Geany in                               : /usr/local
Using GTK version                             : 3.24.41
Enable binary relocation                      : no
Build with plugin support                     : yes
Use (UNIX domain) socket support              : yes
Use virtual terminal support (VTE)            : yes
Build HTML documentation                     : no
Build PDF documentation                       : no
Build API documentation                       : no
Generate GtkDoc header                       : no

Configuration is done OK.

```

Tym razem próba się powiodła

```

nakselano@DESKTOP-07LCCCH:~/geany-2.0$ make
make all-recursive
make[1]: Entering directory '/home/nakselano/geany-2.0'
Making all in ctags
make[2]: Entering directory '/home/nakselano/geany-2.0/ctags'
  CC      dsl/optscript.lo
  CC      dsl/es.lo
  CC      libreadtags/readtags.lo

```

Następnym krokiem było wykonanie polecenia make

```

make[2]: Entering directory '/home/nakselano/geany-2.0'
  GEN      geany.desktop
make[2]: Leaving directory '/home/nakselano/geany-2.0'
make[1]: Leaving directory '/home/nakselano/geany-2.0'
nakselano@DESKTOP-07LCCCH:~/geany-2.0$

```

Make się powiódł

```

nakselano@DESKTOP-07LCCCH:~/geany-2.0$ sudo make install
[sudo] password for nakselano:
Making install in ctags
make[1]: Entering directory '/home/nakselano/geany-2.0/ctags'
make[2]: Entering directory '/home/nakselano/geany-2.0/ctags'
make[2]: Nothing to be done for 'install-exec-am'.

```

Ostatni pozostały krok to sudo make install

```

make[1]: Entering directory '/home/nakselano/geany-2.0'
  GEN      geany.desktop
make[2]: Entering directory '/home/nakselano/geany-2.0'
make[2]: Nothing to be done for 'install-exec-am'.
/bin/bash /home/nakselano/geany-2.0/build-aux/install-sh -d /usr/local/share/geany
/usr/bin/install -c -m 644 ./COPYING /usr/local/share/geany/GPL-2
  GEN      geany.desktop
/usr/bin/mkdir -p '/usr/local/share/applications'
/usr/bin/install -c -m 644 ./geany.desktop '/usr/local/share/applications'
/usr/bin/install: cannot stat './geany.desktop': No such file or directory
make[2]: *** [Makefile:543: install-desktopDATA] Error 1
make[2]: Leaving directory '/home/nakselano/geany-2.0'
make[1]: *** [Makefile:903: install-am] Error 2
make[1]: Leaving directory '/home/nakselano/geany-2.0'
make: *** [Makefile:591: install-recursive] Error 1
nakselano@DESKTOP-07LCCCH:~/geany-2.0$ |

```

Niestety, wyskoczył mi błąd. Po chwili researchu, udało się wstępnie ustalić że winowajcą tego błędu może być WSL sam w sobie, a konkretnie brak aktualizacji

```

C:\Users\Nakselano>wsl --update
Sprawdzanie dostępności aktualizacji.
Aktualizowanie Podsystem Windows dla systemu Linux do wersji: 2.7.8.
[===== 32,5% ]

```

W tej sytuacji wyłączyłem WSL i zabrałem się do aktualizacji.

```

nakselano@DESKTOP-07LCCCH:~/geany-2.0$ sudo make install
[sudo] password for nakselano:
Making install in ctags
make[1]: Entering directory '/home/nakselano/geany-2.0/ctags'
make[2]: Entering directory '/home/nakselano/geany-2.0/ctags'
make[2]: Nothing to be done for 'install-exec-am'.
make[2]: Nothing to be done for 'install-data-am'.
make[2]: Leaving directory '/home/nakselano/geany-2.0/ctags'
make[1]: Leaving directory '/home/nakselano/geany-2.0/ctags'
Making install in scintilla
make[1]: Entering directory '/home/nakselano/geany-2.0/scintilla'
make[2]: Entering directory '/home/nakselano/geany-2.0/scintilla'

```

Po zaktualizowaniu WSL ponawiam próbę instalacji.

```

/bin/bash /home/nakselano/geany-2.0/build-aux/install-sh -d /usr/local/share/geany
/usr/bin/install -c -m 644 ./COPYING /usr/local/share/geany/GPL-2
GEN      geany.desktop
/usr/bin/mkdir -p '/usr/local/share/applications'
/usr/bin/install -c -m 644 ./geany.desktop '/usr/local/share/applications'
/usr/bin/install: cannot stat './geany.desktop': No such file or directory
make[2]: *** [Makefile:543: install-desktopDATA] Error 1
make[2]: Leaving directory '/home/nakselano/geany-2.0'
make[1]: *** [Makefile:903: install-am] Error 2
make[1]: Leaving directory '/home/nakselano/geany-2.0'
make: *** [Makefile:591: install-recursive] Error 1
nakselano@DESKTOP-07LCCCH:~/geany-2.0$ |

```

Niestety, i tym razem pojawił się ten sam błąd. Po kolejnych kilkunastu minutach researchu, dowiaduje się że pliki .desktop w starszych aplikacjach (używających Autotools) potrzebują pomocy pakietu intltool w celu poprawnego utworzenia takiego pliku.

```

nakselano@DESKTOP-07LCCCH:~/geany-2.0$ sudo apt install intltool
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following packages were automatically installed and are no longer required:
  libdrm-nouveau2 libdrm-radeon1 libgll-amber-dri libglapi-mesa libllvm17t64 libxcb-dri2-0
Use 'sudo apt autoremove' to remove them.
The following additional packages will be installed:
  autoconf automake autotools-dev libauthn-sasl-perl libclone-perl libdata-dump-perl libencode-locale-perl
  libfile-listing-perl libfont-afm-perl libhtml-form-perl libhtml-format-perl libhtml-parser-perl libhtml-tagset-perl
  libhtml-tree-perl libhttp-cookies-perl libhttp-daemon-perl libhttp-date-perl libhttp-message-perl
  libhttp-negotiate-perl libio-html-perl libio-socket-ssl-perl liblwp-mediatypes-perl liblwp-protocol-https-perl
  libmailtools-perl libnet-http-perl libnet-smtp-ssl-perl libnet-ssleay-perl libtimedate-perl libtiny-perl
  liburi-perl libwww-perl libwww-robotrules-perl libxml-parser-perl m4 perl-openssl-defaults
Suggested packages:
  autoconf-archive gnu-stardiff autoconf-doc libtool libdigest-hmac-perl libgssapi-perl libio-compress-brotli-perl
  libcrypt-ssleay-perl libsub-name-perl libbusiness-isbn-perl libregexp-ipv6-perl libauthn-ntlm-perl m4-doc debhelper
The following NEW packages will be installed:
  autoconf automake autotools-dev intltool libauthn-sasl-perl libclone-perl libdata-dump-perl libencode-locale-perl
  libfile-listing-perl libfont-afm-perl libhtml-form-perl libhtml-format-perl libhtml-parser-perl libhtml-tagset-perl
  libhtml-tree-perl libhttp-cookies-perl libhttp-daemon-perl libhttp-date-perl libhttp-message-perl
  libhttp-negotiate-perl libio-html-perl libio-socket-ssl-perl liblwp-mediatypes-perl liblwp-protocol-https-perl
  libmailtools-perl libnet-http-perl libnet-smtp-ssl-perl libnet-ssleay-perl libtimedate-perl libtiny-perl
  liburi-perl libwww-perl libwww-robotrules-perl libxml-parser-perl m4 perl-openssl-defaults
0 upgraded, 36 newly installed, 0 to remove and 122 not upgraded.
Need to get 3024 kB of archives.
After this operation, 10.3 MB of additional disk space will be used.
Do you want to continue? [Y/n] |

```

Instaluje pakiet intltool


```

nakselano@DESKTOP-07LCCCH:~/geany-2.0$ make clean
Making clean in ctags
make[1]: Entering directory '/home/nakselano/geany-2.0/ctags'
rm -rf .libs _libs
rm -rf dsl/.libs dsl/_libs
rm -rf fnmatch/.libs fnmatch/_libs
rm -rf gnu_regex/.libs gnu_regex/_libs
rm -rf libreadtags/.libs libreadtags/_libs
rm -rf main/.libs main/_libs
rm -rf parsers/.libs parsers/_libs
rm -rf parsers/cxx/.libs parsers/cxx/_libs
test -z "libctags.la" || rm -f libctags.la
rm -f ./so_locations

```

Wykonuje make clean, w celu pozbycia się pozostałości po poprzedniej próbie instalacji

```

make[2]: Leaving directory '/home/nakselano/geany-2.0/tests'
make[1]: Leaving directory '/home/nakselano/geany-2.0/tests'
make[1]: Entering directory '/home/nakselano/geany-2.0'
rm -rf .libs _libs
rm -f *.lo
make[1]: Leaving directory '/home/nakselano/geany-2.0'
nakselano@DESKTOP-07LCCCH:~/geany-2.0$

```

Make clean się powiódł

```

make[1]: Leaving directory '/home/nakselano/geany-2.0'
nakselano@DESKTOP-07LCCCH:~/geany-2.0$ ./configure
checking for a BSD-compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking for a race-free mkdir -p... /usr/bin/mkdir -p
checking for gawk... gawk
checking whether make sets $(MAKE)... yes
checking whether make supports nested variables... yes
checking whether make supports the include directive... yes (GNU style)
checking for gcc... gcc
checking whether the C compiler works... yes
checking for C compiler default output file name... a.out
checking for suffix of executables...
checking whether we are cross compiling... no
checking for suffix of object files... o
checking whether the compiler supports GNU C... yes
checking whether gcc accepts -g... yes
checking for gcc option to enable C11 features... none needed

```

Jeszcze raz wykonuje ./configure

```
-----
Install Geany in           : /usr/local
Using GTK version          : 3.24.41
Enable binary relocation   : no
Build with plugin support  : yes
Use (UNIX domain) socket support : yes
Use virtual terminal support (VTE) : yes
Build HTML documentation   : no
Build PDF documentation    : no
Build API documentation    : no
Generate GtkDoc header     : no
```

Configuration is done OK.

```
nakselano@DESKTOP-07LCCCH:~/geany-2.0$ |
```

Znow się powiódł, ale tym razem jeszcze nie świętuje, bo wiem, że problem jest na późniejszym etapie

```
nakselano@DESKTOP-07LCCCH:~/geany-2.0$ make
make all-recursive
make[1]: Entering directory '/home/nakselano/geany-2.0'
Making all in ctags
make[2]: Entering directory '/home/nakselano/geany-2.0/ctags'
  CC      dsl/optscript.lo
  CC      dsl/es.lo
  CC      libreadtags/readtags.lo
  CC      main/args.lo
  CC      main/colprint.lo
  CC      main/CommonPrelude.lo
```

Ponownie wykonuje make

```
make[3]: Entering directory '/home/nakselano/geany-2.0/tests'
make[3]: Nothing to be done for 'all-am'.
make[3]: Leaving directory '/home/nakselano/geany-2.0/tests'
make[2]: Leaving directory '/home/nakselano/geany-2.0/tests'
make[2]: Entering directory '/home/nakselano/geany-2.0'
  GEN      geany.desktop
make[2]: Leaving directory '/home/nakselano/geany-2.0'
make[1]: Leaving directory '/home/nakselano/geany-2.0'
nakselano@DESKTOP-07LCCCH:~/geany-2.0$ |
```

make się powiódł, więc próbujemy wykonać sudo make install

```
make[1]: Leaving directory '/home/nakselano/geany-2.0'
nakselano@DESKTOP-07LCCCH:~/geany-2.0$ sudo make install |
```

