

МИНИСТЕРСТВО ОБРАЗОВАНИЯ И НАУКИ РОССИЙСКОЙ
ФЕДЕРАЦИИ МОСКОВСКИЙ АВИАЦИОННЫЙ ИНСТИТУТ
(НАЦИОНАЛЬНЫЙ ИССЛЕДОВАТЕЛЬСКИЙ УНИВЕРСИТЕТ)

ЛАБОРАТОРНАЯ РАБОТА №7
по курсу объектно-ориентированное программирование I семестр, 2021/22
уч. год

Студент Ханнанов Руслан Маратович, группа М8О-208Б-20

Преподаватель Дорохов Евгений Павлович

Условие

Задание: Вариант 22: N-дерево. Используя структуру данных, разработанную для лабораторной работы №4, спроектировать и разработать итератор для динамической структуры данных.

Итератор должен быть разработан в виде шаблона и должен позволять работать с любыми типами фигур, согласно варианту задания.

Итератор должен позволять использовать структуру данных в операторах типа `for`. Например:

1. Требования к классу фигуры аналогичны требованиям из лабораторной работы №1.
2. Требования к классу фигуры аналогичны требованиям из лабораторной работы №2.
3. Шаблон класса-контейнера должен содержать объекты используя `std::shared_ptr<...>`.

Нельзя использовать:

1. Стандартные контейнеры `std`.

Программа должна позволять:

1. Вводить произвольное количество фигур и добавлять их в контейнер.
2. Распечатывать содержимое контейнера.
3. Удалять фигуры из контейнера.

Описание программы

Исходный код лежит в 11 файлах:

1. `src/main.cpp`: основная программа, взаимодействие с пользователем посредством команд из меню
2. `include/figure.h`: описание абстрактного класса фигур
3. `include/point.h`: описание класса точки
4. `include/node.h`: описание класса ноды дерева
5. `include/pentagon.h`: описание класса пятиугольника, наследующегося от `figures`
6. `include/tnary_tree.h`: описание класса N-дерева
7. `include/iterator`: описание класса итератора

8. include/point.cpp: реализация класса точки
9. include/pentagon.cpp: реализация класса пятиугольника, наследующегося от figures
10. include/node.cpp: реализация класса ноды дерева
11. include/tnary_tree.cpp: реализация класса N-дерева

Протокол работы

7: [7.5: [10], 8, 9]

Iterator work:

Pentagon: (0, 0) (0, 2) (1, 3) (2, 3) (3, 0)

Pentagon: (0, 0) (0, 3) (1, 3) (2, 3) (3, 0)

Pentagon: (0, 0) (0, 4) (1, 3) (2, 3) (3, 0)

Iterator1 != Iterator2

Iterator1 == Iterator2

Дневник отладки

Недочёты

Недочетов не заметил

Выводы

В процессе выполнения данной лабораторной работы я познакомился с итераторами и реализовал класс итератора по N-дереву. Мне кажется часто итераторы очень удобны для перемещения по контейнеру.

Исходный код:

iterator.h

```
#ifndef LAB5__ITERATOR_H_
#define LAB5__ITERATOR_H_

#endif //LAB5__ITERATOR_H_

#include <iostream>
#include <memory>

template <class item, class T>
class TIterator {
public:
    TIterator(std::shared_ptr<item> n){
        node_ptr = n;
    }

    T operator*() {
        return *(node_ptr->key);
    }

    void to_son(){
        if (node_ptr->son == nullptr){
            std::cout << "Node does not exist" << std::endl;
        } else {
            node_ptr = node_ptr->son;
        }
    }

    void to_brother(){
        if (node_ptr->brother == nullptr){
            std::cout << "Node does not exist" << std::endl;
        } else {
            node_ptr = node_ptr->brother;
        }
    }

    bool operator==(TIterator const& i) {
        return node_ptr == i.node_ptr;
    }

    bool operator!=(TIterator const& i) {
```

```

        return *this != i;
    }

private:
    std::shared_ptr<item> node_ptr;
};

```

figure.h

```

#ifndef LAB4__FIGURE_H_
#define LAB4__FIGURE_H_
#include <memory>
#include "point.h"

class Figure {
private:
    virtual void Print(std::ostream& os) = 0;
    virtual double Area() = 0;
    virtual size_t VertexesNumber() = 0;
};
#endif //LAB4__FIGURE_H_

```

point.h

```

//
// Created by Руслан on 31.10.2021.
//

#ifndef LAB4__POINT_H_
#define LAB4__POINT_H_
#include <istream>

class Point {
public:
    Point();
    Point(std::istream &is);
    Point(double x, double y);

    double dist(Point& other);
    friend double getx(Point& p);
    friend double gety(Point& p);

    friend std::istream& operator>>(std::istream& is, Point& p);

```

```

    friend std::ostream& operator<<(std::ostream& os, const Point& p);

private:
    double x_;
    double y_;

};
#endif //LAB4__POINT_H_

point.cpp

//
// Created by Руслан on 31.10.2021.
//

#include "point.h"

#include <cmath>

Point::Point() : x_(0.0), y_(0.0) {}

Point::Point(double x, double y) : x_(x), y_(y) {}

Point::Point(std::istream &is) {
    is >> x_ >> y_;
}

double Point::dist(Point& other) {
    double dx = (other.x_ - x_);
    double dy = (other.y_ - y_);
    return std::sqrt(dx*dx + dy*dy);
}

std::istream& operator>>(std::istream& is, Point& p) {
    is >> p.x_ >> p.y_;
    return is;
}

std::ostream& operator<<(std::ostream& os, const Point& p) {
    os << "(" << p.x_ << ", " << p.y_ << ") ";
    return os;
}

```

```
double getx(Point& p) {
    return p.x_;
}
```

```
double gety(Point& p) {
    return p.y_;
}
```

pentagon.h

```
//
// Created by Руслан on 31.10.2021.
//
```

```
#ifndef LAB4__PENTAGON_H_
#define LAB4__PENTAGON_H_
#include "figure.h"
#include "point.h"
#include <iostream>
```

```
class Pentagon : public Figure {
public:
    Pentagon();
    Pentagon(Point v1,Point v2,Point v3,Point v4,Point v5);
    explicit Pentagon(std::istream &is);
    Pentagon(Pentagon &other);

    void Print(std::ostream& os) override;
    double Area() override;
    size_t VertexesNumber() override;

    friend std::ostream &operator<<(std::ostream &os, const Pentagon &figure);

    ~Pentagon();
private:
    Point v1,v2,v3,v4,v5;
};
#endif //LAB4__PENTAGON_H_
```

pentagon.cpp

```
//
// Created by Руслан on 31.10.2021.
//
```

```

#include "pentagon.h"
#include <cmath>

Pentagon::Pentagon(): v1(0,0),v2(0,0),v3(0,0),v4(0,0),v5(0,0){
    //std::cout << "Default pentagon created" << std::endl;
}

Pentagon::Pentagon(Point v_1,Point v_2, Point v_3, Point v_4, Point v_5):
    v1(v_1), v2(v_2), v3(v_3), v4(v_4), v5(v_5)
{
    //std::cout << "Pentagon created" << std::endl;
}

Pentagon::Pentagon(Pentagon& other):
    Pentagon(other.v1,other.v2,other.v3,other.v4,other.v5)
{
    //std::cout << "Made copy of pentagon";
}

Pentagon::Pentagon(std::istream &is) {
    is >> v1 >> v2 >> v3 >> v4 >> v5;
    //std::cout << "Pentagon created via istream" << std::endl;
}

void Pentagon::Print(std::ostream& os) {
    os << "Pentagon:" << v1 << v2 << v3 << v4 << v5 << "\n";
}

Pentagon::~Pentagon() {
    //std::cout << "Object Pentagon ";
    //Print(std::cout);
    //std::cout << "deleted" << std::endl;
}

double Pentagon::Area() {
    Point ar[5];
    ar[0] = v1;
    ar[1] = v2;
    ar[2] = v3;
    ar[3] = v4;
    ar[4] = v5;
}

```



```

    double res = 0;
    for (unsigned i = 0; i < 5; i++) {
        Point p = i ? ar[i-1] : ar[4];
        Point q = ar[i];
        res += (getx(p) - getx(q)) * (gety(p) + gety(q));
    }
    return fabs(res) / 2;
}

size_t Pentagon::VertexesNumber() {
    return 5;
}

std::ostream &operator<<(std::ostream &os, const Pentagon &figure)
{
    os << "Pentagon: " << figure.v1 << " " << figure.v2 << " " << figure.v3 << " " << figure.v4 << " " << figure.v5;
    return os;
}

```

node.h

```

//
// Created by Руслан on 31.10.2021.
//

#ifndef LAB4__NODE_H_
#define LAB4__NODE_H_
#include <iostream>
#include <memory>
#include "pentagon.h"
template <class T>

class Node {
public:

    Node(const std::shared_ptr<T> &k);
    Node(const Node &other);

    std::shared_ptr<Node<T>> last_son();

    template<class A>
    friend std::ostream &operator<<(std::ostream & os, const Node<A> &obj);
}

```

```

    std::shared_ptr<Node<T>> son;
    std::shared_ptr<Node<T>> brother;
    std::shared_ptr<T> key;
};
#endif //LAB4__NODE_H_

```

node.cpp

```

#include "node.h"

template <class T>
Node<T>::Node(const std::shared_ptr<T> &k) {
    key = k;
    son = nullptr;
    brother = nullptr;
}

template <class T>
Node<T>::Node(const Node &other) {
    this->son = other.son;
    this->brother = other.brother;
    this->key = other.key;
}

template <class T>
std::shared_ptr<Node<T>> Node<T>::last_son() {
    std::shared_ptr<Node<T>> ls = son;
    int number_of_sons = 0;
    while (ls->brother != nullptr) {
        ls = ls->brother;
        ++number_of_sons;
    }
    return ls;
}

template<class T>
std::ostream &operator<<(std::ostream & os, const Node<T> &obj) {
    os << "Item: " << *obj.key << std::endl;
    return os;
}

#include "pentagon.h"
template class Node<Pentagon>;

```

```
template std::ostream& operator<<(std::ostream& os, const Node<Pentagon>& obj);
```

tnary_tree.h

```
#ifndef LAB4__TNARY_TREE_H_
#define LAB4__TNARY_TREE_H_
#include "node.h"
#include "iterator.h"
template <class T>
class TNaryTree {
public:
    TNaryTree();
    TNaryTree(int n);
    TNaryTree(const TNaryTree<T> &other);

    void Update(std::shared_ptr<T> k, const std::string &&tree_path = "");
    void RemoveSubTree(const std::string &&tree_path);
    bool Empty();

    template<class A>
    friend std::ostream &operator<<(std::ostream &os, const TNaryTree<A> &tree);

    std::shared_ptr<Node<T>> getroot();

    const std::shared_ptr<T> &GetItem(const std::string &&tree_path = "");
    virtual ~TNaryTree();

private:
    int N;
    std::shared_ptr<Node<T>> root;

    void sub_copy(std::shared_ptr<Node<T>> &cur, std::shared_ptr<Node<T>> cp);
    void set_root(std::shared_ptr<T> &k);
    void sub_remove(std::shared_ptr<Node<T>> cur);
    void sub_print_operator(std::shared_ptr<Node<T>> cur, std::ostream &os) const;
};
#endif //LAB4__TNARY_TREE_H_
```

tnary_tree.cpp

```
#include "tnary_tree.h"

template <class T>
```

```

TNaryTree<T>::TNaryTree(int n) {
    N = n;
    root = nullptr;
}

template <class T>
TNaryTree<T>::TNaryTree() {
    N = 3;
    root = nullptr;
}

template <class T>
void TNaryTree<T>::Update(std::shared_ptr<T> k, const std::string &&tree_path) {
    if (tree_path == "") {
        if (root == nullptr) {
            set_root(k);
        } else root->key = k;
    } else {
        std::shared_ptr<Node<T>> cur = root;
        int degree = 1;
        for (int i = 0; i < tree_path.size() - 1; ++i) {

            if (tree_path[i] == 'c') {

                degree = 1;
                cur = cur->son;
                if (cur == nullptr) {
                    throw std::invalid_argument("The node doesn't exist");
                }

            }
            if (tree_path[i] == 'b') {

                ++degree;
                cur = cur->brother;
                if (cur == nullptr) {
                    throw std::invalid_argument("The node doesn't exist");
                }

            }

        }
    }
}

```

```

        if (tree_path[tree_path.size() - 1] == 'c') {
            if (cur->son == nullptr) {
                std::shared_ptr<Node<T>> item(new Node(k));
                cur->son = item;
            } else cur->son->key = k;
        }
        if (tree_path[tree_path.size() - 1] == 'b') {
            ++degree;
            if (degree > N) {
                throw std::out_of_range("Node cannot be added due to overflow");
            }
            if (cur->brother == nullptr) {
                std::shared_ptr<Node<T>> item(new Node(k));
                cur->brother = item;
            } else cur->brother->key = k;
        }
    }
}

template <class T>
void TNaryTree<T>::set_root(std::shared_ptr<T> &k) {
    std::shared_ptr<Node<T>> cur(new Node(k));
    root = cur;
}

template <class T>
bool TNaryTree<T>::Empty() {
    if (root == nullptr)
        return true;
    else return false;
}

template <class T>
void TNaryTree<T>::RemoveSubTree(const std::string &&tree_path) {
    std::shared_ptr<Node<T>> cur;
    if (tree_path == "") {
        sub_remove(root);
    } else {
        cur = root;
        for (int i = 0; i < tree_path.size() - 1; ++i) {

            if (tree_path[i] == 'c') {

```

```

        cur = cur->son;

    }
    if (tree_path[i] == 'b') {

        cur = cur->brother;

    }

}

if (tree_path[tree_path.size() - 1] == 'c') {
    std::shared_ptr<Node<T>> cur_d = cur->son;
    cur->son = nullptr;
    sub_remove(cur_d);
}
if (tree_path[tree_path.size() - 1] == 'b') {
    std::shared_ptr<Node<T>> cur_d = cur->brother;
    cur->brother = nullptr;
    sub_remove(cur_d);
}
}
}

template <class T>
void TNaryTree<T>::sub_remove(std::shared_ptr<Node<T>> cur) {
    if (cur->son != nullptr) {
        std::shared_ptr<Node<T>> it = cur->son;
        cur->son = nullptr;
        sub_remove(it);
    }
    if (cur->brother != nullptr) {
        std::shared_ptr<Node<T>> it = cur->brother;
        cur->brother = nullptr;
        sub_remove(it);
    }
    cur.reset();
    return;
}

template <class T>
TNaryTree<T>::~TNaryTree() {

```

```

    if (root == nullptr) {
        return;
    }
    sub_remove(root);
}

template <class T>
TNaryTree<T>::TNaryTree(const TNaryTree &other) {
    N = other.N;
    std::shared_ptr<Node<T>> cp = other.root;
    std::shared_ptr<Node<T>> item(new Node(cp->key));
    root = item;
    std::shared_ptr<Node<T>> cur = root;
    if (cp->son != nullptr) {
        sub_copy(cur->son, cp->son);
    }
    if (cp->brother != nullptr) {
        sub_copy(cur->brother, cp->brother);
    }
}

template <class T>
void TNaryTree<T>::sub_copy(std::shared_ptr<Node<T>> &cur, std::shared_ptr<Node<T>> cp)
{
    std::shared_ptr<Node<T>> item(new Node(cp->key));
    cur = item;
    if (cp->son != nullptr) {
        sub_copy(cur->son, cp->son);
    }
    if (cp->brother != nullptr) {
        sub_copy(cur->brother, cp->brother);
    }
    return;
}

template <class T>
std::ostream &operator<<(std::ostream &os, const TNaryTree<T> &tree) {
    std::shared_ptr<Node<T>> cur = tree.root;
    tree.sub_print_operator(cur, os);
    return os;
}

template <class T>

```

```

void TNaryTree<T>::sub_print_operator(std::shared_ptr<Node<T>> cur, std::ostream &os) co
    T k = *(cur->key);
    os << k.Area();
    if (cur->son != nullptr) {
        os << ": [";
        sub_print_operator(cur->son, os);
        os << "];"
    }
    if (cur->brother != nullptr) {
        os << ", ";
        sub_print_operator(cur->brother, os);
        //os << "];"
    }
    return;
}

template <class T>
const std::shared_ptr<T> &TNaryTree<T>::GetItem(const std::string &&tree_path) {
    std::shared_ptr<Node<T>> cur;
    if (tree_path == "") {
        return root->key;
    } else {
        cur = root;
        for (int i = 0; i < tree_path.size() - 1; ++i) {

            if (tree_path[i] == 'c') {

                cur = cur->son;

            }
            if (tree_path[i] == 'b') {

                cur = cur->brother;

            }

        }
        if (tree_path[tree_path.size() - 1] == 'c') {
            return cur->son->key;
        }
        if (tree_path[tree_path.size() - 1] == 'b') {
            return cur->brother->key;
        }
    }
}

```



```

    }
}
}

template <class T>
std::shared_ptr<Node<T>> TNaryTree<T>::getroot(){
    return root;
};

template class TNaryTree<Pentagon>;
template std::ostream &operator<<(std::ostream &os, const TNaryTree<Pentagon> &tree);

```

main.cpp

```

#include <iostream>
#include "pentagon.h"
#include "tnary_tree.h"
int main() {
    TNaryTree<Pentagon> t(3);

    std::shared_ptr<Pentagon> p1(new Pentagon({0, 0}, {0, 2}, {1, 3}, {2, 3}, {3, 0}));
    std::shared_ptr<Pentagon> p2(new Pentagon({0, 0}, {0, 3}, {1, 3}, {2, 3}, {3, 0}));
    std::shared_ptr<Pentagon> p3(new Pentagon({0, 0}, {0, 4}, {1, 3}, {2, 3}, {3, 0}));
    std::shared_ptr<Pentagon> p4(new Pentagon({0, 0}, {0, 6}, {1, 3}, {2, 3}, {3, 0}));
    std::shared_ptr<Pentagon> p5(new Pentagon({0, 0}, {0, 8}, {1, 3}, {2, 3}, {3, 0}));
    std::shared_ptr<Pentagon> p6(new Pentagon({0, 0}, {0, 0}, {0, 0}, {0, 0}, {0, 0}));

    t.Update(p1, "");
    t.Update(p2, "c");
    t.Update(p3, "cb");
    t.Update(p4, "cbb");
    t.Update(p5, "cc");
    std::cout << t << std::endl;

    std::shared_ptr<Node<Pentagon>> r = t.getroot();
    //r->key->Print(std::cout);

    TIterator<Node<Pentagon>, Pentagon> iter1(r);

    std::cout << "Iterator work:" << std::endl;
    std::cout << *iter1 << std::endl;
    iter1.to_son();
    std::cout << *iter1 << std::endl;
}

```

```

iter1.to_brother();
std::cout << *iter1 << std::endl;

TIterator<Node<Pentagon>, Pentagon> iter2(r);
iter2.to_son();

if (iter1 == iter2) {
    std::cout << "Iterator1 == Iterator2" << std::endl;
} else {
    std::cout << "Iterator1 != Iterator2" << std::endl;
}

iter2.to_brother();

if (iter1 == iter2) {
    std::cout << "Iterator1 == Iterator2" << std::endl;
} else {
    std::cout << "Iterator1 != Iterator2" << std::endl;
}

return 0;
}

```