



Class has been archived by your teacher. You can't add or edit anything.

ICE 12.1



Aman Gupta • Apr 11, 2025 (Edited Apr 27, 2025)

8/8

1. (2 marks) When tunnel mode is used across routers connecting two LANs to the Internet, a new IP header is added to the original IP packet as part of encapsulation. Is the “Time-to-Live” parameter the same in the new and original IP headers?

- Yes
- **No (correct)**
- Cannot say

2. (2 marks) Refer to question 1 above, how about the “header checksum” field in the outer IP header?

- Yes
- **No (correct)**
- Cannot say

3. (2 marks) In IPSEC, let the current window be [120 ... 529], both inclusive. Indicate as to what is the receiver's response if the next received packet is numbered 440?

- Simply reject packet
- **Simply accept packet (correct)**
- Accept packet and move window 1 place to right
- None of the above

4. (2 marks) Refer to Question 3 above. What if the received packet is numbered 531?

- Simply reject packet
- Simply accept packet
- Accept packet and move window one place to right
- **Accept packet and move window 2 places to right (correct)**
- None of the above

[ICE 12.1](#)

Google Forms



Your work

Graded

Class has been archived by your teacher. You can't add or edit anything.

 Private comments

[Add comment to Aman Gupta](#)

 Class comments

 [Add comment](#)

