

# Map-Reduce Matrix Multiplication

\* Indicates required question

---

1. Email \*

---

2. Roll number \*

---

3. Password \*

---

## Untitled Section

Using the matrix-matrix multiplication with Map-Reduce one phase algorithm:

M=

|    |    |    |    |
|----|----|----|----|
| 1  | 2  | 3  | 4  |
| 5  | 6  | 7  | 8  |
| 9  | 10 | 11 | 12 |
| 13 | 14 | 15 | 16 |

N =

|    |    |    |    |
|----|----|----|----|
| 1  | 2  | 3  | 4  |
| 5  | 6  | 7  | 8  |
| 9  | 10 | 11 | 12 |
| 13 | 14 | 15 | 16 |

When we apply the Map function, identify the correct key-value pairs that are input to a Reducer as well as correct statements in the context of Map-reduce algorithm. .

4.

1 point

*Check all that apply.*

- ☐ Reducer with K= (2,2) shall have V = [(M,1,5), (M,2,6), (M,3,7), (M,4,8), (N,1,2), (N,2,6), (N,3,10), (N,4,14)]
- ☐ Reducer with K= (2,3), shall have V = [(M,1,5), (M,2,6), (M,3,7), (M,4,8), (N,1,3), (N,2,7), (N,3,11), (N,4,15)]
- ☐ Reducer with K = (1,2), shall have V = [(M,1,1), (M,2,6), (M,3,7), (M,4,8), (N,1,2), (N,2,6), (N,3,10), (N,4,14)]
- ☐ All reducers size are of same size, i.e., each reduce would have 8 objects in its value.
- ☐ Reducer with key (3,4) would produce the highest value at the output

---

This content is neither created nor endorsed by Google.

Google Forms