

Creating a RESTful API using express.js and creating a database and index in MongoDB.


Name : Nalla Kishor

Email : nallakishor10@gmail.com

College: Visakha institute of engineering and technology

source code :

index.js file :



The screenshot shows a Visual Studio Code editor with a project named 'crud'. The Explorer sidebar on the left shows the file structure: 'api' folder containing 'controllers', 'db', 'model', 'routes', and 'index.js'. The 'index.js' file is selected and its code is displayed in the main editor. The code is a Node.js script using Express.js to serve static files and handle GET requests. The terminal at the bottom shows the command 'nodemon api/index.js' and its output, indicating that the server is running on port 5000 and connected to MongoDB.


```
api > JS index.js > ...
1 import path from 'path';
2 import express from 'express';
3 import {config} from 'dotenv';
4 import { connectToDB } from './db/connectToDB.js';
5 config();
6 import userRoute from './routes/user.routes.js'
7
8
9 const __dirname = path.resolve();
10 const app = express();
11
12 app.use(express.json());
13
14 app.use("/api/user",userRoute);
15
16 app.use(express.static(path.join(__dirname,"/client/dist")));
17
18 app.get("*",(req,res)=>{
19     res.sendFile(path.join(__dirname,"client","dist","index.html"))
20 })
21
22 const PORT = process.env.PORT || 5000
23 app.listen(PORT,()=>{
24     connectToDB();
25     console.log("Server is running on PORT : ",PORT)
26 })
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
> node + v ...
> nodemon api/index.js

[nodemon] 3.1.0
[nodemon] to restart at any time, enter 'rs'
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting 'node api/index.js'
Server is running on PORT : 5000
DB connected successfully
```

MONGODB CONNECTION :




The screenshot shows the VS Code editor with the Explorer sidebar on the left. The file explorer shows a project structure with folders like 'api', 'controllers', 'db', 'model', 'routers', 'index.js', 'client', 'node_modules', '.env', '.gitignore', 'package-lock.json', and 'package.json'. The file 'connectToDB.js' is selected in the Explorer. The main editor shows the code for 'connectToDB.js'.

```
1 import mongoose from 'mongoose';
2
3 export function connectToDB(){
4   mongoose.connect(process.env.CONN_STR)
5   .then(()=>{
6     console.log("DB connected successfully")
7   })
8   .catch((err)=>{
9     console.log("Error while connecting to DB : ",err.message);
10  })
11 }
```

The terminal at the bottom shows the command 'nodemon api/index.js' and the output:

```
[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

MODEL :




The screenshot shows the VS Code editor with the Explorer sidebar on the left. The file explorer shows a project structure with folders like 'api', 'controllers', 'db', 'model', 'routers', 'index.js', 'client', 'node_modules', '.env', '.gitignore', 'package-lock.json', and 'package.json'. The file 'emp.model.js' is selected in the Explorer. The main editor shows the code for 'emp.model.js'.

```
1 import mongoose from 'mongoose';
2
3 const userSchema = new mongoose.Schema({
4   username:{
5     type:String,
6     unique:true,
7     required:true
8   },
9   empname:{
10    type:String,
11    required:true
12  },
13   email:{
14    type:String,
15    required:true
16  },
17   role:{
18    type:String,
19    required:true
20  },
21   salary:{
22    type: Number,
23    required: true,
24  }
25 },{timestamps:true})
26
27 const Emp = mongoose.model("User",userSchema);
28
29 export default Emp;
```

The terminal at the bottom shows the command 'nodemon api/index.js' and the output:

```
[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

ROUTES:



The screenshot shows the VS Code editor with the file explorer on the left. The file explorer shows a project structure with a 'crud' folder containing 'api', 'controllers', 'db', 'model', 'routes', and 'index.js'. The 'api' folder is expanded, showing 'user.routes.js'. The 'user.routes.js' file is open in the editor, showing the following code:


```
1 import express from 'express'
2 import { create, readAll, read, remove, update, } from '../controllers/emp.controller.js';
3
4 const router = express.Router();
5
6 router.post('/create', create);
7 router.get('/readall', readAll);
8 router.get('/read/:id', read);
9 router.put('/update/:id', update);
10 router.delete('/remove/:id', remove);
11
12 export default router;
```

The terminal at the bottom shows the output of running 'nodemon api/index.js'. The output is:

```
[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

CONTROLLERS :


CREATE :



The screenshot shows the VS Code editor with the file explorer on the left. The file explorer shows a project structure with a 'crud' folder containing 'api', 'controllers', 'db', 'model', 'routes', and 'index.js'. The 'controllers' folder is expanded, showing 'emp.controller.js'. The 'emp.controller.js' file is open in the editor, showing the following code:

```
1 import Emp from '../model/emp.model.js';
2
3 export async function create(req,res){
4   try {
5     const {username,empname,email,role,salary} = req.body;
6
7     console.log(req.body);
8     const emp = await Emp.findOne({username});
9
10    if(emp) return res.status(400).json({error:"username is already exists"});
11
12    const newEmp = new Emp({
13      username,
14      empname,
15      email,
16      role,
17      salary
18    });
19
20    if(newEmp){
21      await newEmp.save();
22
23      res.status(201).json({
24        _id : newEmp._id,
25        username : newEmp.username,
26        empname : newEmp.empname,
27        email : newEmp.email,
28        role : newEmp.role,
29        salary : newEmp.salary
30      });
31    }
32  } else {
33    res.status(400).json({error:"Invalid emp data"});
34  }
35
36  } catch (error) {
37    console.log("Error in create controller : ",error.message);
38    res.status(500).json({message : error.message});
39  }
40
41 }
```


READALL:



The screenshot shows the VS Code editor with the file explorer on the left and the code editor in the center. The file explorer shows the project structure with folders like api, controllers, db, model, routers, and client. The code editor displays the file `emp.controller.js` with the following code:

```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){ ...
40 }
41
42 > export async function read(req,res){ ...
58 }
59
60 export async function readAll(req,res){
61   try {
62     const emps = await Emp.find();
63
64     if(!emps || !emps.length ) return res.status(404).json({error:" no emp data found!"});
65
66     res.status(201).json({
67       emps
68     })
69   } catch (error) {
70     console.log("Error in create controller : ",error.message);
71     res.status(500).json({error:"Internal server Error"})
72   }
73 }
74
75
76
77 > export async function update(req,res){ ...
94 }
95
96 > export async function remove(req,res){ ...
110 }
```


READONE :



The screenshot shows the VS Code editor with the file explorer on the left and the code editor in the center. The file explorer shows the project structure with folders like api, controllers, db, model, routers, and client. The code editor displays the file `emp.controller.js` with the following code:

```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){ ...
40 }
41
42 export async function read(req,res){
43   try {
44     const {id} = req.params;
45
46     const emp = await Emp.findById({_id:id});
47
48     if(!emp) return res.status(404).json({error:"emp not found!"});
49
50     res.status(201).json({
51       emp
52     })
53   } catch (error) {
54     console.log("Error in create controller : ",error.message);
55     res.status(500).json({error:"Internal server Error"})
56   }
57 }
58
59
60 > export async function readAll(req,res){ ...
75 }
76
77 > export async function update(req,res){ ...
94 }
95
96 > export async function remove(req,res){ ...
110 }
```


UPDATE :



The screenshot shows the Visual Studio Code editor with the file explorer on the left and the code editor in the center. The file explorer shows a project structure with folders like 'api', 'controllers', 'db', 'model', 'routers', and 'user.routes.js'. The file 'emp.controller.js' is selected in the 'controllers' folder. The code editor shows the following JavaScript code:

```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){ ...
40 }
41
42 > export async function read(req,res){ ...
58 }
59
60 > export async function readAll(req,res){ ...
75 }
76
77 export async function update(req,res){
78   try {
79     const {id} = req.params;
80
81     const emp = await Emp.findById(_id:id);
82
83     if(!emp) return res.status(404).json({error:"emp not found!"});
84
85     const newEmp = await Emp.findByIdAndUpdate(_id:id,{...req.body},{new:true});
86
87     res.status(201).json({
88       newEmp
89     });
90   } catch (error) {
91     console.log("Error in create controller : ",error.message);
92     res.status(500).json({error:"Internal server Error"});
93   }
94 }
95
96 > export async function remove(req,res){ ...
110 }
```

DELETE :



The screenshot shows the Visual Studio Code editor with the file explorer on the left and the code editor in the center. The file explorer shows a project structure with folders like 'api', 'controllers', 'db', 'model', 'routers', and 'user.routes.js'. The file 'emp.controller.js' is selected in the 'controllers' folder. The code editor shows the following JavaScript code:

```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){ ...
40 }
41
42 > export async function read(req,res){ ...
58 }
59
60 > export async function readAll(req,res){ ...
75 }
76
77 > export async function update(req,res){ ...
94 }
95
96 export async function remove(req,res){
97   try {
98     const {id} = req.params;
99
100     await Emp.findByIdAndDelete(_id:id);
101
102     res.status(201).json({
103       id,
104       message : 'deleted successfully..',
105     });
106   } catch (error) {
107     console.log("Error in create controller : ",error.message);
108     res.status(500).json({error:"Internal server Error"});
109   }
110 }
```


HOW TO RUN ON LOCALLY :

1. Create a folder as any name.
2. Open that folder in any code editor (vs code).
3. Open terminal (ctrl + ~) on code editor.
4. Type this code to get code locally.
git clone <https://github.com/4727yesuraju/crud.git>
5. Now move to crud folder (cd crud in terminal)
6. Ignore client folder.
7. Here crud is root folder.
8. In root folder create a .env file and create a PORT and

CONN_STR variables and assign value.

ex : PORT = 3000 (commonly any number between 3000 - 8080).

CONN_STR = your mongodb_connection_string.



--- trouble in above process ? :

simply paste this code in .env file .

PORT = 5000

CONN_STR=mongodb+srv://4727yesuraju:rough@cluster0.wbclvtg.mongodb.net
/?retryWrites=true&w=majority&appName=Cluster0

9. After in terminal (in crud folder as root folder) type this command to run server.

npm i (installing all dependencies)

npm run dev (to run server)

10. if you get below message in terminal then your server will running successfully.

```
PS C:\Users\4727y\OneDrive\Desktop\internshala\crud> npm run dev

> crud@1.0.0 dev
> nodemon api/index.js

[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
█
```

route and its functionality :

For this use any API using tools like Postman or Thunder Client.

i use THUNDER CLIENT.

CREATE ROUTE :

- 1. This route is used to create a new employee in database with a below fields.**

username, empname, email, role, salary

- 2. in thunder client click on new request and select this options
method as post**

url as `http://localhost:5000/api/user/create`

pass this json data as a body as your required value.

```
{  
  
  "username": "jack",  
  
  "empname": "jack rider",  
  
  "email": "jack@gmail.com",  
  
  "role": "Front End Developer",  
  
  "salary": 60000  
}
```

- 3. finally press send to insert data in mongodb data base and get a
inserted**

data as a response.

- 4. If user is already in db it will return User is already exist as
response.**

for more details visit below output images...

READONE :

1. This route is used to read specific user info by passing that user id as a param.

method as get

url as

http://localhost:5000/api/user/read/65ed7b3d76e1dcc9a51654ca

2. After sending you will get that specific user details as response.

READALL :

- 1 . Read all route is used to get all the user data existing in the mongodb data base .

method as get

url as http://localhost:5000/api/user/readall

- 2 . After sending you will get that all user details as response.

UPDATE :

1. This route is used to update specific user by passing that user id as a param.

method as put

url as

http://localhost:5000/api/user/update/65ed7b3d76e1dcc9a51654ca

2. After sending you will get updated user details as response.

DELETE :

1. This route is used to delete specific user by passing that user id as a param.

method as delete


url as

<http://localhost:5000/api/user/delete/65ed7b3d76e1dcc9a51654ca>


2. After sending you will deleted successfully as response.

OUTPUT :


CREATE A NEW USER :



CREATING USER WITH EXISTING USERNAEM :



READONE :



READ ALL :

Thunder Client interface showing a GET request to `http://localhost:5000/api/user/readall`. The response is a JSON array of two employee objects. The terminal shows the output of the response.

```
GET http://localhost:5000/api/user/readall
```

Status: 201 Created Size: 468 Bytes Time: 130 ms

Response

```
1 {
2   "emps": [
3     {
4       "_id": "65ed7a9d76e1dcc9a51654c6",
5       "username": "rose",
6       "empname": "rose143",
7       "email": "rose@gmail.com",
8       "role": "software developer",
9       "salary": 90000,
10      "createdAt": "2024-03-10T09:17:17.904Z",
11      "updatedAt": "2024-03-10T09:17:17.904Z",
12      "__v": 0
13    },
14    {
15      "_id": "65ed7b3d76e1dcc9a51654ca",
16      "username": "jack",
17      "empname": "jack rider",
18      "email": "jack@gmail.com",
19      "role": "Front End Developer",
20      "salary": 60000,
21      "createdAt": "2024-03-10T09:19:57.171Z",
22      "updatedAt": "2024-03-10T09:19:57.171Z",
23      "__v": 0
24    }
25  ]
26 }
```

Terminal Output:

```
username: 'jack',
empname: 'jack rider',
email: 'jack@gmail.com',
role: 'Front End Developer',
salary: 60000
}
```

UPDATE :

Thunder Client interface showing a PUT request to `http://localhost:5000/api/user/update/65ed7b3d76e1dcc9a51654ca`. The response is a JSON object with a new employee object. The terminal shows the output of the response and an error message.

```
PUT http://localhost:5000/api/user/update/65ed7b3d76e1dcc9a51654ca
```

Status: 201 Created Size: 246 Bytes Time: 213 ms

Response

```
1 {
2   "newEmp": {
3     "_id": "65ed7b3d76e1dcc9a51654ca",
4     "username": "jack",
5     "empname": "jack rider",
6     "email": "jack123@gmail.com",
7     "role": "MERN STACK Developer",
8     "salary": 100000,
9     "createdAt": "2024-03-10T09:19:57.171Z",
10    "updatedAt": "2024-03-10T09:22:55.106Z",
11    "__v": 0
12  }
13 }
```

Terminal Output:

```
empname: 'jack rider',
email: 'jack@gmail.com',
role: 'Front End Developer',
salary: 60000
}
Error in create controller : Cast to ObjectId failed for value "{ _id: '65ed625bbd510e515f6767d' }" (type Object) at path "_id" for model "User"
```

DELETE :

The screenshot displays the Thunder Client interface with a DELETE request configured and executed. The request is sent to `http://localhost:5000/api/user/remove/65ed7b3d76e1dcc9a51654ca`. The response is a 201 Created status with a JSON body containing an ID and a success message.

Request Details:

- Method: DELETE
- URL: `http://localhost:5000/api/user/remove/65ed7b3d76e1dcc9a51654ca`
- Send button: Send

Response Details:

- Status: 201 Created
- Size: 68 Bytes
- Time: 111 ms
- Response Body:

```
1 {
2   "id": "65ed7b3d76e1dcc9a51654ca",
3   "message": "deleted successfully.."
4 }
```

Terminal Output:

```
Node.js v20.11.0
[nodemon] app crashed - waiting for file changes before starting...
[nodemon] restarting due to changes...
[nodemon] starting 'node api/index.js'
Server is running on PORT : 5000
DB connected successfully
```